

(12) **United States Patent**  
**Craig et al.**

(10) **Patent No.: US 11,679,930 B1**  
(45) **Date of Patent: Jun. 20, 2023**

(54) **TANK CONTAINER**

(71) Applicant: **Quality Carriers, Inc.**, Tampa, FL (US)  
(72) Inventors: **Steven Craig**, Jasper, GA (US); **Stephan Strydom**, Uitenhage/Kariega (ZA); **Timothy Neil McLaren**, Port Elizabeth (ZA)  
(73) Assignee: **QUALITY CARRIERS, INC.**, Tampa, FL (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/580,515**  
(22) Filed: **Jan. 20, 2022**

(51) **Int. Cl.**  
**B65D 88/12** (2006.01)  
**B65D 88/54** (2006.01)  
**B65D 90/00** (2006.01)  
**B65D 90/24** (2006.01)  
**B65D 90/30** (2006.01)  
(52) **U.S. Cl.**  
CPC ..... **B65D 88/128** (2013.01); **B65D 88/54** (2013.01); **B65D 90/0033** (2013.01); **B65D 90/24** (2013.01); **B65D 90/30** (2013.01); **B65D 2588/54** (2013.01); **B65D 2588/74** (2013.01); **B65D 2590/24** (2013.01)  
(58) **Field of Classification Search**  
CPC ..... B65D 90/12; B65D 90/02; B65D 88/129; B65D 88/128; B65D 88/28; B65D 19/44; B65D 2588/54  
USPC ..... 220/1.5  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS			
6,244,288 B1 *	6/2001	Pettesch	F16K 27/07 137/267
6,834,689 B1	12/2004	Peters	
10,060,101 B2 *	8/2018	Plummer	F16K 17/363
2010/0187192 A1 *	7/2010	Ness	B65D 88/10 211/71.01
2013/0333897 A1 *	12/2013	Wells	E21B 41/0021 166/93.1
2018/0291578 A1 *	10/2018	Webster	E01H 5/102
2020/0140190 A1 *	5/2020	Van Laarhoven	B65D 88/06

**OTHER PUBLICATIONS**

Girard Equipment USA, 45 Deg TTMA Bottom and Top Valves Owners Manual; Feb. 20, 2018 (Year: 2018).\*  
“Girard Equipment USA 45 Deg TTMA Bottom and Top Valves Owner’s Manual GQ81300 and GQ81350.” <https://girardequip.com/wp-content/uploads/2019/07/QF-830-009-45-Degree-TTMA-Bottom-and-Top-Valves-Owners-Manual-Rev-A-1.pdf> published Feb. 20, 2018, (21 pages).


(Continued)

*Primary Examiner* — Anthony D Stashick  
*Assistant Examiner* — Raven Collins  
(74) *Attorney, Agent, or Firm* — Quarles & Brady LLP

(57) **ABSTRACT**

A tank container includes a frame having a front end opposite a rear end that defines a rear plane, a vessel extending between the front end and the rear end of the frame, and a discharge valve assembly. The discharge valve assembly comprises an internal bottom valve, an adaptor, and a discharge valve. The internal bottom valve is positioned within an interior volume of the vessel and the discharge valve is positioned entirely within the frame and offset at least one inch from the rear plane. The adaptor curves downwardly between the internal bottom valve and the discharge valve.

**20 Claims, 15 Drawing Sheets**



(56)

**References Cited**

## OTHER PUBLICATIONS

“Girard Equipment, Inc. GE Hydraulic Hand Pump Gen 2 Assembly”—<https://girardequip.com/product/ge-hydraulic-hand-pump-gen2-assembly/> published Aug. 9, 2021 (5 pages).

“Girard Equipment, Inc. GE GVRA Y-tube Assembly”—<https://girardequip.com/product/ge-gvra-y-tube-assembly/>, published May 5, 2020 (4 pages).

“Girard Equipment, Inc. GVRAB2”—<https://girardequip.com/product/gvrab2/> published Oct. 29, 2020 (7 pages).

Girard Main Catalog 2019—[https://girardequip.com/wp-content/uploads/2019/09/Main-Catalog\\_2019.pdf](https://girardequip.com/wp-content/uploads/2019/09/Main-Catalog_2019.pdf), published Sep. 2019 (50 pages).

“Girard Equipment, Inc. HydraFlo RDV Steam Jacketed”—<https://girardequip.com/product/gh50002/>, published Nov. 6, 2020 (6 pages).

“Girard Equipment, Inc. 702004 EZ-Clean Compression TEF Ferrule”—<https://girardequip.com/product/702004/>, published May 18, 2020 (4 pages).

“Girard Equipment, Inc. HydraFlo Valve Sheet”—<http://girardequip.com/wp-content/uploads/2019/06/HydraFlo-Solution-Sheet-Final-1.pdf>, published Jun. 2019 (2 pages).

“Girard Equipment, Inc. GE Chemovation Internal “Top Hat” Assembly”—<https://girardequip.com/product/gq87000/> published Aug. 2019 (6 pages).

“Girard Equipment, Inc. GE 4 “X2” TTMA Sump Mounting Pad, Machined”—<https://girardequip.com/product/gp40110/>, published Mar. 2019 (5 pages).

“21000 liters T7 Tank Container”—<https://www.tankcon.com/EN/21000-liters-T7-tank-container-TCSU-100502-1>, published Nov. 7, 2019 (14 pages).

\* cited by examiner






FIG. 1






FIG. 2





FIG. 3



**FIG. 4**




FIG. 5






FIG. 6




FIG. 7






FIG. 8




FIG. 9




FIG. 10




FIG. 11






FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16






FIG. 17




FIG. 18




FIG. 19






FIG. 20




FIG. 21






FIG. 22




FIG. 23






FIG. 24

## 1

## TANK CONTAINER

## RELATED APPLICATIONS

N/A

## BACKGROUND

## Field of the Disclosure

This disclosure relates generally to tank containers for transporting, storing, and dispensing contents, e.g., liquids.

## Description of the Background of the Disclosure

Tank containers are used for transporting, storing, and dispensing contents, e.g., liquids, across various distances by various means. Tank containers are designed and constructed of various sizes, shapes, materials, and with various features. Further, tank containers are subject to certain regulations, standards, and codes relating to their sizes, capacities, strengths, etc.

## SUMMARY

Various aspects are described in connection with the illustrative implementations of a tank container disclosed herein.

In one aspect, a tank container includes a frame having a front end opposite a rear end that defines a rear plane, a vessel extending between the front end and the rear end of the frame, and a discharge valve assembly that is located at the rear end of the frame and coupled to the vessel. The discharge valve assembly further comprises an internal bottom valve, an adaptor, and a discharge valve that has an outlet. The internal bottom valve is at least partially positioned within an interior volume of the vessel and the discharge valve is positioned entirely within the frame and offset from the rear plane. The adaptor curves downwardly between the internal bottom valve and the discharge valve.

In some embodiments, the adaptor is configured to position the discharge valve below the internal bottom valve. The adaptor includes an inner flange and an outer flange. Further, the inner flange can be disposed at about a 45 degree angle relative to the outer flange. The adaptor includes a curved body that narrows in diameter between the inner flange and the outer flange. Additionally, the outer flange of the adaptor includes a plurality of apertures spaced radially and a plurality of tabs arranged on a first side of the outer flange. Further, each of the apertures of the outer flange of the adaptor are configured to receive a fastener therethrough and a head of the fastener is configured to be received between two of the tabs. In another embodiment, the outer flange of the adaptor includes a plurality of apertures and a plurality of slots arranged on a first side of the outer flange. Further, each of the apertures of the outer flange of the adaptor are configured to receive a fastener therethrough and a head of the fastener is configured to be received within one of the slots. The discharge valve is operably connected to a heating system.

In another aspect, a tank container includes a vessel having a front dished end opposite a rear dished end and a shell extending between the front dished end and the rear dished end. The tank container further includes a frame that at least partially surrounds the vessel and defines a front end, a rear end, a curb side, and a street side. Further, the tank container includes a discharge valve that is located adjacent

## 2

the rear dished end and has an internal bottom valve mounted to the shell. Additionally, the tank container includes a spill box that is located on a top end of the shell of the vessel. The spill box including a street side wall and a curb side wall. A drain is connected to the street side wall of the spill box and a drain pan extends approximately half of a distance between the street side wall and the curb side wall within the spill box.

In some embodiments, the drain pan is sloped downwardly from the curb side wall to the shell. A plurality of appurtenances is arranged on the shell proximate the street side wall of the spill box. Further, the appurtenances are spaced apart from the drain pan. A lid is positioned on the shell within the spill box and intersected by a longitudinal axis that bisects the tank container. The drain pan extends between the longitudinal axis and the curb side wall of the spill box, and the longitudinal axis intersects the lid. The longitudinal axis is positioned between the drain pan and the drain.

In still another aspect, a tank container includes a vessel having an interior volume, a frame that is connected to the vessel at a front end and a rear end, a vapor recovery system, and a discharge valve assembly. The discharge valve assembly and the vapor recovery system are both operably connected to a hydraulic pumping system.

In some embodiments, the hydraulic pumping system includes a hand pump that is mounted to a lower side rail of the frame at a curb side of the tank container. The vapor recovery system includes a hydraulic pipeline that has a first branch and a second branch, the first branch being coupled to a vapor recovery adaptor that is located at a top end of the tank container, and the second branch being coupled to an internal bottom valve of the discharge valve assembly. Further, the discharge valve assembly includes a discharge valve that is operably coupled to a steam heating system.

In still another aspect, a tank container includes a vessel having an interior volume, a frame that is connected to the vessel at a front end by a front ring mounting assembly and at a rear end by a rear ring mounting assembly. The front ring mounting assembly comprises a front reinforcement flange that connects the front end of the frame to a front dished end of the vessel. The rear ring mounting assembly comprises a rear reinforcement flange that connects the rear end of the frame to a rear dished end of the vessel. The vessel is offset longitudinally toward the front end of the frame to allow a longitudinal space for housing a bottom discharge assembly extending from the rear dished end toward the rear end within the frame. The front and rear ring mounting assemblies are configured to accommodate the vessel being offset longitudinally toward the front end.

In some embodiments the rear ring mounting assembly has a side reinforcing end that varies in thickness to accommodate a shell thickness.

## DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a top, right, and rear side of a tank container according to an embodiment of the present disclosure;

FIG. 2 is a rear elevational view of the tank container of FIG. 1;

FIG. 3 is a front elevational view of the tank container of FIG. 1;

FIG. 4 is a right side elevational view of the tank container of FIG. 1;

FIG. 5 is a left side elevational view of the tank container of FIG. 1;



3

FIG. 6 is a perspective view of a bottom, right, and front side of the tank container of FIG. 1;

FIG. 7 is a cross-sectional view of the tank container taken along line 7-7 of FIG. 1;

FIG. 8 is a partial, top plan view of a spill box of the tank container of FIG. 1;

FIG. 9 is a partial, top plan view of a portion of a vapor recovery system of the tank container of FIG. 1;

FIG. 10 is a partial, top plan view of another portion of the vapor recovery system of the tank container of FIG. 1;

FIG. 11 is a partial, front elevational view of the portion of the vapor recovery system of FIG. 10;

FIG. 12 is a partial, top plan view of a portion of an air inlet assembly of the tank container of FIG. 1;

FIG. 13 is a partial, front elevational view of the portion of the air inlet assembly of FIG. 12;

FIG. 14 is a partial, top plan view of a portion of a relief valve assembly of the tank container of FIG. 1;

FIG. 15 is a partial, rear elevational view of the portion of the relief valve assembly of FIG. 14;

FIG. 16 is a cross-sectional view of a lid of the tank container taken along lines 16-16 of FIG. 6;

FIG. 17 is a partial, perspective view of a bottom and left side of the tank container of FIG. 1;

FIG. 18 is a partial, perspective view of a bottom and rear side of the tank container;

FIG. 19 is a left side elevational view of an embodiment of a bottom discharge valve assembly;

FIG. 20 is an exploded, perspective view of a left and rear side of the bottom discharge valve assembly of FIG. 19;

FIG. 21 is a perspective view of a left and front side of an adaptor of the bottom discharge valve assembly of FIG. 20;

FIG. 22 is a perspective view of a right and rear side of another embodiment of an adaptor;

FIG. 23 is a sectional view of the adaptor of FIG. 22; and

FIG. 24 is a schematic representation of a sectional view of another embodiment of a tank container.

#### DETAILED DESCRIPTION

Before any embodiments are explained in detail, it is to be understood that the embodiments disclosed herein are not limited to the details of construction and the arrangement of components set forth in the following description or illustrated in the following drawings. The embodiments of the present disclosure are capable of being practiced or of being carried out in various ways. Also, it is to be understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of “including,” “comprising,” or “having” and variations thereof herein is meant to encompass the items listed thereafter and equivalents thereof as well as additional items. Unless specified or limited otherwise, the terms “mounted,” “connected,” “supported,” and “coupled” and variations thereof are used broadly and encompass both direct and indirect mountings, connections, supports, and couplings. Further, “connected” and “coupled” are not restricted to physical or mechanical connections or couplings.

The term “about,” as used herein, refers to variations in the numerical quantity that may occur, for example, through typical measuring and manufacturing procedures used for a tank container with a frame and appurtenances or other articles of manufacture that may include embodiments of the disclosure herein; through inadvertent error in these procedures; through differences in the manufacture, source, or purity of the ingredients used to make the compositions or

4

mixtures or carry out the methods; and the like. Throughout the disclosure, the terms “about” and “approximately” refer to a range of values  $\pm 5\%$  of the numeric value that the term precedes.

FIG. 1 illustrates an embodiment of a tank container 100 including a vessel 104 that is mounted to a frame 108. The tank container 100 includes a front end 112 opposite a rear end 116, a curb side 120 opposite a street side 124, and a top end opposite a bottom end 132. It will be appreciated that the front end 112, rear end 116, curb side 120, street side 124, top end 128, and bottom end 132 are regions of the tank container 100 which may be referenced with respect to one or more components, e.g., the vessel 104 or the frame 108, of the tank container 100 for reference. Further, it will be appreciated that the curb side 120 corresponds to the right-hand side of the tank container 100 and the street side 124 corresponds to the left-hand side of the tank container 100 when viewed from a vantage point facing the rear end 116, as in FIG. 1. Thus, the terms right, right-hand, and curb side are synonymous for purposes of the present disclosure. In a similar fashion, the terms left, left-hand, and street side are synonymous for purposes of the present disclosure.

The tank container 100 of the present disclosure is configured for road transportation, e.g., conveyance on a commercial vehicle along roads and highways, as well as for rail transportation, e.g., conveyance along railroads, which collectively may be referred to as ground transportation. Further, the tank container 100 is designed for international and domestic travel by way of ground transportation, but not for water transportation, e.g., conveyance on a vessel across oceans and waterways. Thus, for purposes of the present disclosure, it will be understood that the tank container 100 is designed for ground-only transportation, i.e., suited only for ground transportation and not for water transportation. As such, the tank container 100 and, specifically, the vessel 104 are designed in compliance with the American Society of Mechanism Engineers (ASME) VIII Division 1 standards and also with various U.S. Department of Transportation (USDOT) regulations, e.g., U.S. 49 C.F.R. § 180.407 (“USDOT 407”). In addition, unlike ground-only transport tank containers that are compliant with USDOT regulations, the frame 108 is fashioned in compliance with the International Organization for Standardization (ISO) Standard 1496/3, the International Convention for Safe Container (CSC), and the Convention on International Transport of Goods Under Cover of TIR Carnets (TIR). Further, the frame 108 is designed to be Transport Canada (TC) Impact Approved. Accordingly, the tank container 100 of the present disclosure combines a frame that is designed and constructed for compliance with ISO standards and international regulations with a vessel that is designed and constructed for domestic standards and regulations.

Referring to FIG. 1, the tank container 100 defines a longitudinal axis 136 that intersects the rear end 116 and the front end 112 to bisect the tank container 100, such that the curb side 120 is located opposite the street side 124 relative to the longitudinal axis 136. Accordingly, the longitudinal axis 136 extends in a longitudinal direction, i.e., in a front-to-rear or rear-to-front direction, and also in a vertical direction, i.e., top-to-bottom or bottom-to-top direction. The tank container 100 defines a rear plane 140 at the rear end 116 and, in particular, the frame 108 defines the rear plane 140 at the rear end 116. The rear plane 140 is disposed orthogonally relative to the longitudinal axis 136, such that the rear plane 140 extends in the vertical direction and in a lateral direction, i.e., curb side-to-street side or street side-to-curb side. The tank container 100 also defines a front



## 5

plane 142 at the front end 112 and, in particular, the frame 108 defines the front plane 142 at the front end 112. The front plane 142 is disposed orthogonally relative to the longitudinal axis 136, such that the front plane 142 extends in the vertical direction and in a lateral direction, i.e., curb side-to-street side or street side-to-curb side. The front plane 142 and the rear plane 140 extend parallel with one another and the vessel 104 is positioned closer to the front plane 142 at the front end 112 than to the rear plane 140 at the rear end 116, such that the vessel 104 is offset toward the front end 112 within the frame 108.

With reference to FIGS. 1-3, the frame 108 is a generally rectangular prism-shaped structure including a pair of rear vertical members 150, 154 at the rear end 116 and a pair of front vertical members 158, 162 at the front end 112. The rear vertical members 150, 154 are generally parallel and coextensive with each other, and the front vertical members 158, 162 are generally parallel and coextensive with each other. Upper side rails 166, 170 extend between the rear vertical members 150, 154 and the front vertical members 158, 162, and the upper side rails 166, 170 are located at the top end 128 of the tank container 100. The upper side rails 166, 170 are generally parallel and coextensive with each other. Further, lower side rails 174, 178 extend between the rear vertical members 150, 154 and the front vertical members 158, 162 at the bottom end 132 of the tank container 100. The lower side rails 174, 178 are generally parallel and coextensive with each other and also extend substantially parallel with the upper side rails 166, 170.

With reference to FIGS. 1-3, the frame 108 comprises a rear upper cross-member 182 that extends between the rear vertical members 150, 154 and the upper side rails 166, 170 at the rear end 116 and the top end 128. Further, a rear bottom cross-member 186 extends between the rear vertical members 150, 154 and the lower side rails 174, 178 at the rear end 116 and the bottom end 132. Also, a front upper cross-member 190 extends between the front vertical members 158, 162 and the upper side rails 166, 170 at the front end 112 and the top end 128, while a front bottom cross-member 194 (see FIG. 3) extends between the front vertical members 158, 162 and the lower side rails 174, 178 at the front end 112 and the bottom end 132. A plurality of corners 198 are formed at intersections among the aforementioned members of the frame 108. Each corner 198 includes features for rigging, i.e., lifting holes or eyes 202, that are formed on or through the corners 198 of the frame 108. In addition, feet 206 extend from the corners 198 at the bottom end 132 of the frame 108 for supporting the tank container 100 on ground surfaces and/or for engagement with a vehicle chassis and/or securing mounts. The frame 108 is also configured to be stacked on top of or underneath other tank containers. To that end, stacking plates 210 are provided in the form of metal plates at each corner 198 of the top end 128 (see FIG. 1) and reinforcement plates 212 are located each corner 198 of the bottom end 132 (see FIG. 6) of the frame 108. In the illustrated embodiment, the stacking plates 210 extend between the upper side rails 166, 170 and respective front and rear upper cross-members 182, 190. The stacking plates 210 promote stacking of other vessels or assemblies, which may be differently sized or shaped, upon the tank container 100 and further allow for guidance into a proper alignment to prevent mis-stacking and damage of the tank container 100.

With reference to FIGS. 1-8, the vessel 104 includes a generally cylindrical shell 214 that defines an internal volume 218 and that is surrounded by a plurality of cladding panels 222 (see FIG. 7). Further, the cladding panels 222 are

## 6

attached to one another and to the shell 214 to form a spacing 226 between the shell 214 and the cladding 222. The shell 214 is insulated with polyurethane panels having a thickness of about 75 mm (about 3 inches), although other configurations are possible. Further, the cladding panels 222 are provided in the form of high impact panels having a thickness of about 1.6 mm (about 0.0625 inch) that are painted with a glass fiber reinforced plastic and/or resin. All joints and/or seams of the cladding panels 222 are sealed with silicone. In some embodiments, a stainless steel retaining belt (not shown) is provided on the cladding panels 222 near the dished ends 230, 274.

In this particular embodiment, the vessel 104 is configured for the storage and transportation of various forms of liquids, including viscous and non-viscous liquids, with a nominal capacity of 21,200 L (about 5,600 gals). Accordingly, the shell 214 has a wall thickness of at least about 4.2 mm (about 0.17 inch). Further, the wall thickness of the shell 214 is designed to accommodate a corrosion tolerance or allowance of about 0.2 mm (about 0.0079 inch). The shell 214 is manufactured of stainless steel material, e.g., 316L, in compliance with ASTM SA 316, or SANS 50028-7 Type 1.4402 or Type 1.4404, or equivalents. In some embodiments, the shell 214 has a surface finish in the form of a 2B that is achieved by cold rolling, in compliance with the standard specification ASTM A480 or equivalents, although other processes and surface finishes are contemplated. The shell 214 is constructed to be resilient and durable, such that the shell 214 achieves a joint coefficient of 0.85 measured by non-destructive testing methods in accordance with ASME VIII.

As illustrated in FIGS. 1 and 2, the rear end 116 of the vessel 104 includes a rear dished end 230 that is connected to the frame 108. In the illustrated embodiment, the rear dished end 230 of the vessel 104 is connected to the rear vertical members 150, 154 by side reinforcing ends or members 232, 233, respectively, which have a thickness that can vary based on the wall thickness of the shell 214 and the position of the vessel 104 relative to the frame 108, e.g., thicker side reinforcing ends 232, 233 accommodate the vessel 104 being offset toward the front end 112 of the frame 108. Further, the rear dished end 230 is attached to the rear upper cross-member 182 of the frame 108 by a rear reinforcing flange 234 extending therebetween. That is, the vessel 104 is attached to the rear upper cross-member 182 by the reinforcing flange 234, which may be attached by welding, fastening, or the like. Further, rear skirts 238 are provided between portions of the rear dished end 230 and the rear bottom cross-member 186. The rear reinforcing flange 234, rear reinforcing skirts 238, and side reinforcing members 232, 233 comprise a rear ring mounting assembly 239 that secures the rear dished end 230 of the vessel 104 to the frame 108 at the rear end 116. As illustrated in FIG. 2, the rear skirts 238 also extend laterally to connect to respective panel sides 242 that are positioned on an underside 246 of the vessel 104. The panel sides 242 extend generally longitudinally between the rear bottom cross-member 186 and an angled shield 250 disposed on the underside 246 of the vessel 104. Ladder mount brackets 254 are provided at corresponding locations on the rear bottom cross-member 186 and the rear upper cross-member 182 of the frame 108 for attaching a ladder (not shown) to the rear end 116. The rear bottom cross-member 186 is angled or sloped as it extends from the respective rear vertical members 150, 154 toward a central region 258, which is a relatively thin section of the rear bottom cross-member 186. To that end, a gap or opening 262 is formed between the rear dished end 230 of



the vessel 104 and the central region 258 of the rear bottom cross-member 186, as illustrated in FIGS. 1 and 2. In addition, the gap is 262 extends laterally between the rear skirts 238. A pair of rear support blocks 266 extend downwardly from the rear bottom cross-member 186 to further support the frame 108 when mounted on a vehicle, a rail car, or another tank container.

With reference to FIG. 2, the tank container 100 is provided with connection lugs 270 for grounding the tank container 100 to prevent electrical damage. In the illustrated embodiment, the lugs 270 include two off-brass connection lugs on the rear end 116 of the frame 108. Further, a thermometer 272 is provided on the rear dished end 230 with a dual scale (Celsius and Fahrenheit), in the form of a gas filled capillary type thermometer with shock resistant glass. A contact probe (not shown) of the thermometer 272 is secured to the rear dished end 230 at a location corresponding with a 19% fill level, although other configurations are possible. On the whole, the tank container 100 and all appurtenances thereof are designed for a minimum design operating temperature of about -40 degrees C. (-40 degrees F.), which represents the low limit of the metallurgical design temperature for the vessel 104. The high limit of the metallurgical design temperature for the vessel 104 is about 150 degrees C. (about 302 degrees F.).

Turning briefly to FIG. 3, the front end 112 of the vessel 104 includes a front dished end 274 that is connected to the frame 108. In the illustrated embodiment, the front dished end 274 is connected to the front vertical members 158, 162 by side reinforcing ends or members 276, 277, respectively, which have a thickness that can vary based on wall thickness of the shell 214 and the position of vessel 104 relative to the frame 108, e.g., thinner side reinforcing ends 276, 277 accommodate the vessel 104 being offset toward the front end 112 of the frame 108. Further, the front dished end 274 is attached to the front upper cross-member 190 by a front reinforcing flange 278 extending therebetween. That is, the vessel 104 is attached to the front upper cross-member 190 of the frame 108 by the front reinforcing flange 278, which may be attached by welding, fastening, or the like. Further, a front skirt 280 is provided between the front dished end 274 of the vessel 104 and the front bottom cross-member 194. The front reinforcing flange 278, the front skirt 280, and side reinforcing ends 276, 277 comprise a front ring mounting assembly 281 that secures the front dished end 274 of the vessel 104 to the frame 108 at the front end 112. The front bottom cross-member 194 is angled or sloped as it extends from the front vertical members 158, 162 to a lowest point that is intersected the longitudinal axis 136. A pair of front support blocks 282 extend downwardly from the front bottom cross-member 194 to further support the frame 108 when mounted on a vehicle, rail car, or another tank container. In this particular embodiment, the frame 108 is constructed of steel or steel alloys, such as, e.g., S355J2, SJ275J0, or equivalents. In addition, the corners 198 are constructed of metals or metal alloys, such that the corners 198 are provided to be in compliance with ISO Standard 1161. Further, the rear and front dished ends 230, 274 are insulated with pre-molded polyurethane foam panels, although other configurations are possible.

With reference to FIGS. 4-6, the frame 108 further includes a set of rear braces 286 and a set of front braces 290 disposed at the bottom end 132. The rear braces 286 extend at an angle between the rear bottom cross-member 186 and the respective lower side rails 174, 178. In a similar fashion, the set of front braces 290 extend at an angle between the front bottom cross-member 194 and the respective lower

side rails 174, 178. In particular, the set of rear braces 286 connect to the rear support blocks 266, and the set of front braces 290 connect to the front support blocks 282. Further, as illustrated in FIG. 7, a casing 292 is attached to shell 214 at the underside 246 of the vessel 104 and positioned within the spacing 226 formed between the cladding panels 222 and the shell 214. In some embodiments, the casing 292 collects moisture, e.g., condensation, from the shell 214 for removal through a drain line 294 near the rear end 116 of the tank container 100.

Referring back to FIGS. 1-3, the rear dished end 230 and the front dished end 274 of the vessel 104 are connected by the shell 214, and each of the dished ends 230, 274 is made of stainless steel material, such as, e.g., 316L, in compliance with ASTM 216, or SANS 50028-7 Type 1.4402 or Type 1.4404, or equivalents. In some embodiments, the dished ends 230, 274 have a surface finish that is polished smooth to have an arithmetic average of roughness (Ra) measured in accordance with ASME B46.1, although other surface finishes are contemplated. Further, the dished ends 230, 274 are configured to have a wall thickness of at least about 4.3 mm (about 0.17 inch) and to accommodate a corrosion allowance of about 0.2 mm (about 0.0079 inch). The dished ends 230, 274 are constructed to be resilient and durable, such that the dished ends 230, 274 have a joint coefficient of 0.85 measured by non-destructive testing methods in accordance with ASME VIII.

In general, the vessel 104 is designed for an operating temperature of about 150 degrees C. (302 degrees F.) and a maximum allowable working pressure of about 2.67 bar (about 38.7 psi). In one embodiment, the tank container 100 has a length of about 6.1 m (about 20 ft) as measured in the longitudinal direction, a width of about 2.4 m (about 8 ft) as measured in the lateral direction, and a height of about 2.6 m (about 8.5 ft) as measured in the vertical direction. However, it will be understood that the tank container 100 of the present disclosure shall not be limited to the foregoing dimensions and that embodiments of tank containers having different dimensions is within the scope of this disclosure. Further, the tank container 100 is configured for a maximum gross weight capacity of about 30,500 kg (about 67,000 lbs.) and a tare weight of about 3,200 kg (about 7,100 lbs.). However, it also will be understood that the tank container 100 of the present disclosure shall not be limited to the foregoing weights/capacities and that embodiments of tank containers having different weights/capacities are within the scope of this disclosure.

Referring back to FIGS. 1-3, a heating system 300 is provided on the tank container 100. The heating system 300 can be operated with both steam and glycol mediums depending upon when the heating system 300 is operated, i.e., while in transit or while stationary. To that end, the heating system 300 includes a steam inlet or supply connection 308 located at the rear end 116 of the tank container 100. The heating system 300 further includes a bottom discharge valve steam supply 314 located adjacent the steam supply 308 at the rear end 116 of the tank container 100. Further, a steam trap and a ball valve are provided in connection with a steam return line 322 that is in fluid communication with a common outlet or return connection 324 that is located at the front end 112 of the tank container 100. The heating system 300 also includes a glycol inlet 328 at the front end 112 of the tank container 100. Additionally, the common outlet connection 324 is coupled to a bypass 332 in the form of a ball valve that is in communication with a glycol line 334. Accordingly, the bypass 332 is configured for isolating the portion of the heating system 300 that is not



in use, i.e., the glycol supply **328** or the steam supply **308** and **314**. In the illustrated embodiment, the heating system **300** is configured for use with steam when the tank container **100** is stationary, i.e., not during transit, and for operation with glycol when the tank container **100** is conveyed, i.e., in transit. In operation, the heating system **300** is configured for a saturated steam working pressure of about 10.0 bar (about 145.0 psi and a saturated steam test pressure of about 15.0 bar (about 218 psi).

With reference again to FIG. 1, the tank container **100** includes walkways **336** attached to the frame **108** for providing access to a valve arrangement **340** within a spill box **344** located at the top end **128**. In the illustrated embodiment, the walkways **336** include several sections, with longitudinal sections extending the longitudinal direction and lateral sections extending the lateral direction. In particular, the walkways **336** surround the spill box **344** and provide a pathway from the rear end **116** to the spill box **344**, although other configurations are possible. The walkways **336** may be attached to the upper side rails **166**, **170** of the frame **108** and the to the spill box **344** by fasteners, brackets, welding, or the like, such as by U-shaped or L-shaped brackets extending between sides of or undersides of the walkway **336** and the frame **108**, such that the surface of the walkways are flush or even with the top end **128** of the frame **108**. In this way, the walkways **336** allow for stacking of tank containers on the top end **128**. The walkways **336** may be formed as non-slip, self-draining patterns of a durable material, such as a marine-resistant aluminum, in compliance with ASTM B209 M86 or 5052H32, or equivalents.

As illustrated in FIGS. 1 and 8, the spill box **344** is positioned on the vessel **104** at the top end **128** of the tank container **100** in the form of a generally rectangular box having opposing front and rear walls **352**, **356**, opposing curb side and street side walls **360**, **364**, and an unbounded top opening **368**. In some embodiments, a cover (not shown) can be provided to bound or close the top opening **368**, such as by extending across the spill box **344** and removably attached to one or more of the walls **352**, **356**, **360**, **364**. Additionally, a distance **W** is defined between the curb side wall **360** and the street side wall **364** of the spill box **344**, in the lateral direction. The distance **W** is substantially uniform across the spill box **344** between the front wall **352** and the rear wall **356**, such that the spill box **344** can be divided into equal longitudinal sections, i.e., a street side half and a curb side half, along the longitudinal axis **136**, although other configurations are possible.

Referring to FIGS. 7 and 8, the spill box **344** is configured to facilitate drainage of liquids, such as, e.g., precipitation, condensation, or fluids used for cleaning. To that end, the spill box **344** is provided with a drain outlet **372** and a drain line **376** on the street side wall **364** of the spill box **344** and near the rear wall **356**. Further, the spill box **344** includes a drain pan **380** that is positioned on the curb side half of the spill box **344** and is disposed at a downward angle between the curb side wall **360** of the spill box **344** and the shell **214** to direct liquids toward the drain **372** and out of the spill box **344**. In the illustrated embodiment, drain pan **380** extends approximately half of the distance **W** and occupies the curb side half of the spill box **344** while each of the aforementioned valves and fittings are arranged on the street side half of the spill box **344**. In some embodiments, the drain pan **380** may be disposed at an angle in the longitudinal direction, e.g., sloping downwardly from the front wall **352** to the rear wall **356**, to direct liquids toward the drain **372** and out of the spill box **344**. Further, the drain line **376** is arranged to extend longitudinally toward the rear end **116** and with a

downward slope. As illustrated in FIG. 7, a portion of the drain line **376** extends through the cladding panel **222** and into the spacing **226** before connecting to the drain **372** at the spill box **344**. In some embodiments, the drain line **376** is formed of polyvinyl chloride (PVC), or other suitable materials.

With reference to FIGS. 8-11, a vapor recovery system **390** is provided on the tank container **100**. The vapor recovery system **390** includes a pump **394** (see FIGS. 4, 6, and 7), in the form of a hydraulic hand-operated pump, that is attached to the lower side rail **174** on the curb side **120** of the frame **108**, within the outer periphery of the frame **108** so as not to protrude outwardly thereof. The pump **394** is connected to a pipeline **398** that has a first branch **402** that runs vertically upwards on the vessel **104**, within the spacing **226** between the shell **214** and the cladding panels **222**, to the spill box **344**, as shown in FIGS. 1, 2, and 4. The pipeline **398** further includes a second branch **406** that runs underneath the rear dished end **230** of the vessel **104** and into the gap **262** for operative connection to a valve assembly, as will be described below. Further, the pipeline **398** has a third branch **410** that runs laterally across the rear end **116** to the street side **124** and then longitudinally along the street side **124** to the front end **112** of the frame **108**. The pipeline **398** is configured to be serviceable and/or accessible at various locations, e.g., along the second branch **406** at the rear end **116** and along the third branch **410** at the front end **112**.

In the illustrated embodiment, the pipeline **398** is provided as a hydraulic pipeline to be compatible with the hydraulic hand-operated pump **394** for remote operation of the vapor recovery system **390**. To that end, with reference to FIG. 8 where a top plan view of the spill box **344** is provided, the first branch **402** of the pipeline **398** extends into the spill box **344** and is coupled to a vapor recovery adaptor **414** via a flexible hose **418**. The vapor recovery adaptor **414** is configured to be cleaned in-place and is configured for both top and bottom vapor recovery. The vapor recovery adaptor **414** is coupled to the shell **214** of the vessel **104** at the top end **128** and further coupled to a Y-joint **422** that is also connected to an upper vapor return (VR) or air inlet valve **426**, which can be operated as a VR valve in some applications and an air inlet valve in other applications. For purposes of clarity, this disclosure will refer to the upper VR valve or air inlet valve **426** as simply the upper VR valve **426**. The upper VR valve **426** is a ball valve that includes a locking handle **430** and a gauge **434** and, preferably, the upper VR valve **426** is made of stainless steel or stainless steel alloys. Further, the Y-joint **422** couples the upper VR valve **426** and the vapor recovery adaptor **414** to vapor recovery piping **438**. In some embodiments, the vapor recovery system **390** includes a clamp **442**, such as, e.g., a 3-off 2" TRI clamp, with TRI ferrules and gaskets (not shown) to facilitate removal and cleaning, and is provided with anti-tampering features, such as, e.g., TIR seal points, in compliance with relevant standards and regulations.

With reference to FIGS. 1, 2, 4, 8, and 9, the vapor recovery piping **438** extends along the vessel **104** to the rear end **116** and down to connect with a manifold **444** on the curb side **120** of the tank container **100**. The manifold **444** has various fittings, such as check valves, filters, T-joints, and other suitable fittings to provide proper functionality and operation, and also includes a rear connection **446** and a curb side connection **448**. In some embodiments, the rear connection **446** is provided with a quick coupling fitting and a camlock. Further, the curb side connection **448** can be configured as a quick coupling fitting with a ball valve, and the manifold **444** can include a filter, a manometer, and a



## 11

drainage pipe, among other components. Accordingly, the vapor recovery system 390 is configured to be accessible at the top end 128, at the rear end 116, and on the curb side 120 of the tank container 100, while also being operated remotely, i.e., at a distance from the upper VR valve 426 and/or the rear end 116 of the tank container 100, by actuation of the pump 394 at the bottom end 132 and curb side 120 of the tank container 100.

Turning to FIGS. 8 and 12-13, an air inlet assembly 450, which is also known in the tank container industry as a vacuum breaker assembly, is provided in the spill box 344 at the top end 128 of the vessel 104 and proximate the street side wall 364 of the spill box 344. In the illustrated embodiment, the air inlet assembly 450 includes an air inlet valve 454 in the form of a weld-in nozzle configuration with NPT threading, although other configurations are possible. In some embodiments, the air inlet valve 454 is a 4 inch valve provided with several accessories for proper operation, such as an elbow ball valve with male and female couplings, as well as a manometer 456.

With reference to FIGS. 8 and 14-15, a safety relief valve assembly 460 is provided in the spill box 344 at the top end 128 of the vessel 104. In the illustrated embodiment, the safety relief valve assembly 460 includes a safety relief valve 464 in the form of a weld-in nozzle configuration with NPT thread, although other configurations are possible. In particular, the safety relief valve 464 is configured for operation with a set pressure of about 3.33 bar (about 48 psi), although other configurations are possible. In some embodiments, the safety relief valve 464 is a 4" pressure only, high flow relief valve with a minimum flow rate of about 2.8761 Nm<sup>3</sup>/s, although other configurations are possible.

With reference to FIGS. 8 and 16, a lid assembly 480 is provided in the spill box 344 at the top end 128 of the vessel 104. The lid assembly 480 includes a lid 484 extending from the vessel 104 having latches 488 radially spaced about the lid 484 and a hinge 492 that allows for movement, e.g., rotation, of the lid 484 from an open configuration to a closed configuration. In the illustrated embodiment, the lid 484 includes a handle 494 (see FIG. 8) located diametrically opposite the hinge 492, and six latches 488 are provided on the lid 484, although greater or fewer latches 488 may be provided without departing from the scope of this disclosure. Further, the hinge 492 may be provided with a biasing mechanism (not shown), such as, e.g., a coil spring, to assist with movement of the lid 484 between the open and closed configurations. In addition, the lid 484 has a nozzle 496 with a cap 500 for cleaning. In some embodiments, the nozzle 496 is a 76.2 mm (3 inch) nozzle located centrally on the lid 484, but other configurations are possible. An access hole 504 is covered by the lid 484 when in the closed configuration and accessible when the lid 484 is moved to the open configuration. In some embodiments, the lid 484 has a diameter of about 506 mm (about 20 inch) and made of stainless steel or stainless steel alloys, such as, e.g., 316. The lid assembly 480 is provided with a gasket (not shown), such as, e.g., a gasket made of chlorosulfonated polyethylene synthetic rubber (CSM) or equivalents.

Referring to FIGS. 1, 2, 6, 7, 17, and 18, a bottom discharge assembly 520 is provided in the gap 262 between the rear skirts 238 and adjacent the central region 258 of the rear bottom cross-member 186. As shown in FIG. 7, the bottom discharge assembly 520 includes an internal bottom valve or sump 524 attached to the underside 246 of the vessel 104. The internal bottom valve 524 includes a mounting flange 528 and an internal top hat assembly (not shown)

## 12

that is configured to be in fluid communication with the internal volume 218 of the vessel 104. To that end, the internal bottom valve 524 is located in the knuckle area of the dished end 230 on the underside 246 of the vessel 104. The mounting flange 528 is welded to the rear dished end 230 and located in the gap 262 formed below the rear dished end 230. The internal bottom valve 524 is attached to the mounting flange 528 and thereby to the vessel 104 by fasteners 536, e.g., bolts, (see FIG. 17) threaded through the mounting flange 528, although other configurations are possible. Further, a discharge valve 540 is connected to the internal bottom valve 524 and the vessel 104 by an adaptor 544, as shown in FIGS. 6 and 17-18. With reference to FIGS. 1-6, the vessel 104 is arranged within the frame 108 to also accommodate the bottom discharge assembly 520 within the frame 108. To that end, the vessel 104 is offset longitudinally toward the front end 112 and, in particular, the front dished end 274 is located a shorter front distance from the front end plane 142 than a rear distance between the rear dished end 230 and the rear plane 140. Accordingly, the front and rear ring mounting assemblies 281, 239 are configured to accommodate the vessel 104 being offset longitudinally toward the front end 112. In this way, the tank container 100 is configured to allow ample longitudinal space for housing the bottom discharge assembly 520 extending from the rear dished end 230 toward the rear end 116 within the frame 108.

In some embodiments, the rear distance between the rear dished end 230 of the vessel 104 and the rear end 116 and/or rear plane 140 on the frame 108 can be between about 100 mm and about 500 mm and, preferably, the rear distance is between about 150 mm and about 400 mm. More preferably, the rear distance is between about 200 mm and about 300 mm. In one embodiment, the rear distance is about 220 mm between the rear dished end 230 of the vessel 104 and the rear end 116 of the frame 108.

In some embodiments, the front distance between the front dished end 274 of the vessel 104 and the front end 112 and/or front plane 142 on the frame 108 can be between about 5 mm and about 75 mm and, preferably, the front distance is between about 10 mm and about 50 mm. More preferably, the front distance is between about 15 mm and about 40 mm. In one embodiment, the front distance is about 30 mm between the front dished end 274 of the vessel 104 and the front end 112 of the frame 108. Accordingly, the front distance is between about 5% and about 50% of the rear distance and, preferably, the front distance is between about 10% and about 25% of the rear distance. In one embodiment, the front distance is about 12% of the rear distance.

Additionally, the vessel 104 is arranged within the frame 108 between the top end 128 and the bottom end 132. In some embodiments, the vessel 104 is offset toward the top end 128 of the frame 108 to accommodate the bottom discharge assembly 520 within the frame 108, such that the vessel 104 is positioned a top distance that is shorter than a bottom distance between the vessel 104 and the bottom end 132 of the frame 108. In other embodiments, the vessel 104 is positioned offset toward the bottom end 132 of the frame 108 to accommodate the spill box 344 within the frame 108. It is contemplated that the top distance and the bottom distance each can be between about 10 mm to about 500 mm. In one embodiment, the top distance is between about 200 mm and about 300 mm, and the bottom distance is between about 100 mm and about 200 mm.

In the illustrated embodiment, the discharge valve 540 includes a discharge outlet 546 that curves laterally and



rearwardly adjacent a hand wheel **548** that is provided for manually opening and closing the discharge valve **540**. The adaptor **544** extends substantially linearly in the longitudinal direction from the internal bottom valve **524** to the discharge valve **540**, although other configurations are possible. Further, the top hat assembly (not shown) of the internal bottom valve **524** is configured to be hydraulically operated by the hydraulic pump **394** via connection to the second branch **406** of the pipeline **398**. The discharge valve **540** has a steam inlet connection **550** that is operably connected to the heating system **300** through a heating hose **552** for steam heating of the discharge valve **540**, and the discharge valve **540** also includes a drain line **556** to direct moisture, e.g., condensation, away from the bottom discharge valve assembly **520**.

When the tank container **100** is in a filled state, the internal volume of the vessel **104** is at least 80% occupied by liquid and/or contents while the remaining volume is occupied by gas, e.g., vapors, inert gases, compressed air, etc. In some instances, chemical reactions, ambient temperatures, and/or agitation due to motion related to transportation can increase an internal pressure of the internal volume **218** of the vessel **104**. Thus, the safety relief valve assembly **460** operates to maintain the internal pressure of the internal volume **218** within a desired pressure range. Further, when liquid in the internal volume **218** is discharged from the vessel **104** to an external system or source, the internal pressure within the internal volume **218** may be increased by actuating the hydraulic hand pump **394** to facilitate evacuation of the liquid and/or gas from the vessel **104**. The vessel **104** is preferably evacuated down to an empty state at which 20% or less of the internal volume **218** is occupied by liquid and/or gas. The tank container **100** allows for remote operation of the vapor recovery system **390** and the internal bottom valve **524** of the discharge assembly **520** from the hand pump **394**. To that end, the pipeline **398** is operably connected to the internal bottom valve **524** and vapor recovery adaptor **414**, while the vapor recovery piping **438** is accessible from the top end at the upper VR valve **426** and also from ground level at the rear connection **446** at the rear end **116** and the curb side connection **448** near the manifold **444**. For example, instead of climbing to the top end **128** of the tank container **100** to open and close the upper VR valve **426** before and after performing a liquid discharge operation, an operator can connect and disconnect an external air line (not shown) to the curb side connection **448**. Accordingly, the tank container **100** allows users to perform various operations, e.g., vapor recovery and liquid discharge/transfer, from a substantially centralized location at ground level near the hand pump **394**, which reduces the time and number of operators required to operate the tank container **100**.

FIGS. 19-21 depict another embodiment of a bottom discharge assembly **560** that is configured to be used with the tank container **100** of FIG. 1. The bottom discharge assembly **560** is similar to the bottom discharge assembly **520** of FIG. 18 and, thus, like reference numerals will be used to indicate like components. As illustrated in FIGS. 19 and 20, the bottom discharge valve assembly **560** includes the internal bottom valve **524** coupled to the discharge valve **540** by an adaptor **570**. The adaptor **570** has an interior **572** that extends from an inner flange **574** to an outer flange **578** for discharging the liquid from the internal volume **218** of the vessel **104**. Accordingly, the inner flange **574** is attached to the vessel **104**, and preferably to the mounting flange **528**. Further, the outer flange **578** is attached to the discharge valve **540**. As illustrated in FIG. 19, the outer flange **578** defines a vertical axis V and the adaptor **570** is provided with

a curved body **582** between the inner flange **574** and the outer flange **578**. It will be appreciated that the vessel **104** can be offset longitudinally toward the front end **112** to accommodate the bottom discharge assembly **560** extending from the rear dished end **230** at the rear end **116** within the frame **108**. In the illustrated embodiment, the inner flange **574** is disposed at about a 45 deg angle relative to the vertical axis V of the outer flange **578**. To that end, the curved body **582** bends, i.e., curves convexly downwardly and outwardly, to connect to the outer flange **578**. Further, the discharge valve **540** defines a central axis CA that extends centrally through the hand wheel **548**, and the discharge outlet **546** defines an outlet axis OA that is parallel with and offset downwardly from the central axis CA of the discharge valve **540**. To that end, the discharge outlet **546** extends downwardly from the discharge valve **540** below the central axis CA. When viewed from a rear elevational view, the outlet axis OA of the discharge outlet **546** is radially offset about 5 degrees from a horizontal plane defined by the central axis CA.

When the bottom discharge assembly **560** is mounted to the tank container **100**, the shape and size of the adaptor **570** allows the discharge valve **540** to be positioned entirely within the frame **108** and offset inwardly from the rear plane **140** at the rear end **116** of the tank container **100**. In some embodiments, the adaptor **570** is provided to be about 203 mm (8 inches) long in the longitudinal direction, i.e., perpendicular to the V axis, and about 152 mm (6 inches) tall in the vertical direction, i.e., parallel with the V axis. Accordingly, the discharge valve **540** is spaced a sufficient distance, e.g., between about one (1) inch and about ten (10) inches, from the rear plane **140** of the frame **108** to be in compliance with pertinent regulations or standards, e.g., USDOT regulations. This inward position of the outer flange **578** also allows for a sufficient distance, e.g., at least six (6) inches, from a bumper (not shown) of a truck or vehicle when the container **100** is mounted on a flatbed of the truck, in compliance with USDOT regulations, e.g., 49 C.F.R. § 180.405(1). Accordingly, the outer flange **578** of the adaptor **570** is positioned within the frame **108** at a position for connection with the discharge valve **540** to help minimize damage to the discharge valve **540**, the discharge outlet **546**, and the hand wheel **548**, such as when mounted on a vehicle, e.g., a flatbed truck, for transport.

In the illustrated embodiment, the adaptor **570** is a curved pipe section through which fluid/contents stored within the internal volume **218** of the vessel **104** can be discharged. As illustrated in FIG. 19, a curved body **582** of the adaptor **570** extends both downwardly and longitudinally rearwardly from the internal bottom valve **524** and/or the vessel **104**. In this way, the adaptor **570** is configured to position the discharge valve **540** at least partially below the internal bottom valve **524**, which allows gravity to assist during discharge of liquid from the tank container **100**. In addition, when the adaptor **570** is installed as part of the bottom discharge assembly **560**, the inner flange **574** is configured to be elevated vertically above the outer flange **578** to provide a downward-sloping elevation difference, unlike conventional adaptors or discharge assemblies that have an opposite or inverted elevation difference. Accordingly, the uppermost point of the interior **572** at the inner flange **574** of the adaptor **570** is elevated above the uppermost point of the interior **572** at the outer flange **578**.

Further, the adaptor **570** is configured to allow ample room for access and connection to the vessel **104** while being spaced from the bottom end **132** of the frame **108**, thereby providing clearance with the ground or when



## 15

stacked. In addition, the curved body **582** narrows from the inner flange **574** toward the outer flange **578**, such that the interior **572** also narrows in diameter, e.g., from about 101 mm (4 inches) to about 76 mm (3 inches), between the inner flange **574** and the outer flange **578**, thereby increasing a velocity of the liquid and/or contents discharged from the vessel **104**. This is contrary to conventional adaptors and/or discharge assemblies that may expand or increase in diameter from the inner flange to the outer flange. It will also be appreciated that the curved body **582** of the adaptor **570** is configured to avoid forming sharp edges within the interior **572**, unlike conventional adaptors. In this way, the adaptor **570** may reduce the risk of trapping or collecting liquid, particles, debris, and any other undesirable buildup of matter inside the adaptor **570**. Further, a mating surface **586** of the inner flange **574** is provided with serration in compliance with ASME B16.5 for engagement with the internal bottom valve **524**. The adaptor **570** may be made of stainless steel or stainless steel alloys, e.g., CF8M austenitic stainless steel, although other materials are contemplated.

Referring to FIGS. **19**, **20**, and **21** the inner flange **574** is coupled to the internal bottom valve **524** and the outer flange **578** is coupled to the discharge valve **540**. In the illustrated embodiment, the outer flange **578** has a plurality of apertures **598** spaced radially and a plurality of tabs **602** disposed on a back side **590** that is opposite a mating surface **594** configured for engagement with the discharge valve **540**. In the illustrated embodiment, the tabs **602** are provided in pairs on opposing sides of each aperture **598** on the outer flange **578** where a fastener **604**, e.g., a bolt, can be inserted to secure the outer flange **578** to the discharge valve **540**. Each fastener **604** includes a head **606**, such as a hex head, that is configured to be captured between the paired tabs **602** when the fastener **604** is inserted through the aperture **598** of the outer flange **578**. In this way, the tabs **602** are configured to receive and capture the head **606** of each of the fasteners **604** to facilitate mounting and assembly of the adaptor **570** to the discharge valve **540** by preventing rotation of the head when a nut at an opposite end of the fastener is tightened. In another embodiment, the direction of the fastener may be reversed so that the bolt may be captured between the tabs **602** to prevent its rotation when the head of the fastener is rotated. Accordingly, assembly and/or disassembly of the bottom discharge assembly **560** can be performed by a single technician using fewer tools, e.g., one wrench, thereby minimizing downtime and labor costs.

Referring to FIGS. **22** and **23**, another embodiment of an adaptor **610** that is configured for use with the tank container **100** is shown. In the illustrated embodiment, the adaptor **610** includes a plurality of slots **614** formed on the back side **590** of the outer flange **578**. The slots **614** are spaced radially about the outer flange **578** and correspond with the apertures **598**, such that each aperture **598** is positioned within one of the slots **614**. When the adaptor **610** is assembled with the discharge valve **540**, the head **606** of the fastener **604** or, alternatively, a bolt, is received within the slot **614** to become captured after the fastener **604** is threaded through the aperture **598**. Thus, in this additional way, a single technician can use fewer tools, e.g., one wrench, for assembling and/or disassembling the adaptor **610** and the discharge valve **540**, thereby minimizing downtime and labor costs.

Referring to FIG. **23**, the curved body **582** of the adaptor **610** is convexly curved between the inner flange **574** and the outer flange **578** along a longer side of the body **582** and concavely curved between the inner flange **574** and the outer flange **578** along a shorter side of the body. Accordingly,

## 16

when the adaptor **610** is assembled with the discharge valve **540** and the internal bottom valve **524** on the vessel **104** to form the bottom discharge valve assembly **560**, the curvature and compact sizing of the adaptor **610** allows for the discharge valve **540** to be positioned within the frame **108** and offset inwardly from the rear plane **140** of the rear end **116**. In addition, an inside diameter ID of the interior **572** and an outside diameter OD of the curved body **582** narrow from the inner flange **574** to the outer flange **578**. In some embodiments, the ID is about 102 mm (4 inches) proximate the inner flange **574** and about 76 mm (3 inches) proximate the outer flange **578**. In this way, the liquid discharged from the internal volume **218** of the vessel **104** travels with increased velocity through the adaptor **610** and out of the discharge valve **540** during operation.

FIG. **24** depicts a schematic representation of another embodiment of a tank container **700**. The tank container **700** share similarities with the tank container **100** of FIGS. **1-18** and, thus, like reference numerals will be used to indicate like components. It will be appreciated that the vessel **104** is compatible with the bottom discharge assembly **560** of FIG. **19** and also with the bottom discharge assembly **520** of FIG. **18**. Further, it will be appreciated that the top end **128** defines a top plane and the bottom end **132** defines a bottom plane that is parallel with the top plane; accordingly, the top plane is referenced as the top end **128** and the bottom plane **132** is referenced as the bottom end **132**, for purposes of clarity. In addition, the vessel **104** is illustrated defining a central axis C that is disposed centrally between the front dished end **274** and the rear dished end **230**.

As illustrated in FIG. **24**, the vessel **104** is arranged within the frame **108** to accommodate the bottom discharge assembly **520** within the frame **108**. To that end, the vessel **104** is offset longitudinally toward the front end **112** and, in particular, the front dished end **274** is located a shorter front distance **704** from the front end plane **142** than a rear distance **708** between the rear dished end **230** and the rear plane **140**. Accordingly, the front and rear ring mounting assemblies **281**, **239** are configured to accommodate the vessel **104** being offset longitudinally toward the front end **112**. In this way, the tank container **100** is configured to allow ample longitudinal space for housing the bottom discharge assembly **520** extending from the rear dished end **230** toward the rear end **116** within the frame **108**.

In some embodiments, the rear distance **708** between the rear dished end **230** of the vessel **104** and the rear end **116** and/or rear plane **140** on the frame **108** can be between about 100 mm and about 500 mm and, preferably, the distance **708** is between about 150 mm and about 400 mm. More preferably, the distance **708** is between about 200 mm and about 300 mm. In one embodiment, the rear distance **708** is about 220 mm between the rear dished end **230** of the vessel **104** and the rear end **116** of the frame **108**.

In some embodiments, the front distance **704** between the front dished end **274** of the vessel **104** and the front end **112** and/or front plane **142** on the frame **108** can be between about 5 mm and about 75 mm and, preferably, the distance **704** is between about 10 mm and about 50 mm. More preferably, the distance **704** is between about 15 mm and about 40 mm. In one embodiment, the front distance **704** is about 30 mm between the front dished end **274** of the vessel **104** and the front end **112** of the frame **108**. Accordingly, the front distance **704** is between about 5% and about 50% of the rear distance **708** and, preferably, the front distance **704** is between about 10% and about 25% of the rear distance **708**. In one embodiment, the front distance **704** is about 12% of the rear distance **708**.



17

Additionally, the vessel 104 is arranged with in the frame 108 between the top end 128 and the bottom end 132. In some embodiments, the vessel 104 is offset toward the top end 128 of the frame 108 to accommodate the bottom discharge assembly 520 within the frame 108, such that the vessel 104 is positioned a top distance 712 that is shorter than a bottom distance 716 between the vessel 104 and the bottom end 132 of the frame 108. In the embodiment of FIG. 24, the vessel 104 is positioned offset toward the bottom end 132 of the frame 108 to accommodate the spill box 344 within the frame 108. In some embodiments, the top distance 712 is between about 100 mm and about 500 mm and, preferably the top distance 712 is between about 150 mm and about 400 mm. More preferably, the top distance 712 is between about 200 mm and about 300 mm. In the illustrated embodiment, the top distance 712 is about 220 mm. Further, the bottom distance 716 can be between about 50 mm and about 300 mm and, preferably the bottom distance 716 is between about 75 mm and about 250 mm. In the illustrated embodiment, the bottom distance 716 is about 130 mm. Accordingly, when the vessel 104 is offset vertically toward the top end 128 of the frame 108, as illustrated in FIG. 24, the bottom distance 716 is 60% of the top distance 712.

Although various aspects are herein disclosed in the context of certain preferred embodiments, implementations, and examples, it will be understood by those skilled in the art that the present invention extends beyond the specifically disclosed embodiments to other alternative embodiments and/or uses of the inventive aspects and obvious modifications and equivalents thereof. In addition, while a number of variations of the aspects have been noted, other modifications, which are within their scope, will be readily apparent to those of skill in the art based upon this disclosure. It should be also understood that the scope of this disclosure includes the various combinations or sub-combinations of the specific features and aspects of the embodiments disclosed herein, such that the various features, modes of implementation and operation, and aspects of the disclosed subject matter may be combined with or substituted for one another. Thus, it is intended that the scope of the present invention herein disclosed should not be limited by the particular disclosed embodiments or implementations described above but should be determined only by a fair reading of the claims.

Similarly, this method of disclosure, is not to be interpreted as reflecting an intention that any claim require more features than are expressly recited in that claim. Rather, as the following claims reflect, inventive aspects lie in a combination of fewer than all features of any single foregoing disclosed embodiment. Thus, the claims following the Detailed Description are hereby expressly incorporated into this Detailed Description, with each claim standing on its own as a separate embodiment.

#### INDUSTRIAL APPLICABILITY

Numerous modifications to the present invention will be apparent to those skilled in the art in view of the foregoing description. Accordingly, this description is to be construed as illustrative only and is presented for the purpose of enabling those skilled in the art to make and use the invention. The exclusive rights to all modifications which come within the scope of the appended claims are reserved.

The invention claimed is:

1. A tank container, comprising:
  - a frame having a front end opposite a rear end that defines a rear plane;

18

- a vessel extending between the front end and the rear end of the frame; and
- a discharge valve assembly that is located at the rear end of the frame and coupled to the vessel, the discharge valve assembly further comprising:
  - an internal bottom valve;
  - a discharge valve having an outlet; and
  - an adaptor that curves downwardly between the internal bottom valve and the discharge valve, wherein the internal bottom valve is at least partially positioned within an interior volume of the vessel,
 wherein the adaptor includes an inner flange and an outer flange, the inner flange being disposed at an acute angle relative to the outer flange, and
- wherein the discharge valve is positioned entirely within the frame and offset at least one inch inward from the rear plane.

2. The tank container of claim 1, wherein the adaptor is configured to position the discharge valve below the internal bottom valve.

3. The tank container of claim 1, wherein the inner flange is disposed at about a 45 degree angle relative to the outer flange.

4. The tank container of claim 3, wherein the adaptor includes a curved body that narrows in diameter between the inner flange and the outer flange.

5. The tank container of claim 4, wherein the outer flange of the adaptor includes a plurality of apertures spaced radially and a plurality of tabs arranged on a first side of the outer flange.

6. The tank container of claim 4, wherein the outer flange of the adaptor includes a plurality of apertures spaced radially and a plurality of slots arranged on a first side of the outer flange.

7. The tank container of claim 5, wherein each of the apertures of the outer flange of the adaptor are configured to receive a fastener therethrough and a head of the fastener is configured to be received between two of the tabs.

8. The tank container of claim 6, wherein each of the apertures of the outer flange of the adaptor are configured to receive a fastener therethrough and a head of the fastener is configured to be received within one of the slots.

9. The tank container of claim 1, wherein the discharge valve is operably connected to a heating system.

10. A tank container, comprising:

- a frame having a front end opposite a rear end that defines a rear plane;
- a vessel extending between the front end and the rear end of the frame; and
- a discharge valve assembly that is located at the rear end of the frame and coupled to the vessel, the discharge valve assembly further comprising:
  - an internal bottom valve;
  - a discharge valve having an outlet; and
  - an adaptor that curves downwardly between the internal bottom valve and the discharge valve, wherein the internal bottom valve is at least partially positioned within an interior volume of the vessel,
 wherein the adaptor includes an outer flange having a mating surface that is opposite a back surface, the mating surface being configured to engage the discharge valve,
- wherein a plurality of tabs are disposed on the back surface of the outer flange, and
- wherein the discharge valve is positioned entirely within the frame and offset at least one inch inward from the rear plane.



## 19

11. The tank container of claim 10, wherein the outer flange includes a plurality of apertures that are spaced radially on the outer flange and extend through the back surface and the mating surface.

12. The tank container of claim 11, wherein the plurality of tabs are spaced radially on the outer flange and provided in pairs on opposing sides of at least one aperture of the plurality of apertures.

13. The tank container of claim 11, wherein at least one aperture of the plurality of apertures is configured to receive a fastener therethrough and a head of the fastener is configured to be received between one pair of the plurality of tabs.

14. The tank container of claim 10, wherein the adaptor includes a curved body that narrows in diameter between an inner flange and the outer flange.

15. The tank container of claim 14, wherein the inner flange is disposed at an acute angle relative to the outer flange.

16. A tank container, comprising:

a frame having a front end opposite a rear end that defines a rear plane;

a vessel extending between the front end and the rear end of the frame; and

a discharge valve assembly that is located at the rear end of the frame and coupled to the vessel, the discharge valve assembly further comprising:

an internal bottom valve;

a discharge valve having an outlet; and

## 20

an adaptor that curves downwardly between the internal bottom valve and the discharge valve, wherein the internal bottom valve is at least partially positioned within an interior volume of the vessel,

wherein the adaptor includes an outer flange having a mating surface that is opposite a back surface, the mating surface being configured to engage the discharge valve,

wherein a plurality of slots are formed on the back surface of the outer flange, and

wherein the discharge valve is positioned entirely within the frame and offset at least one inch inward from the rear plane.

17. The tank container of claim 16, wherein the outer flange includes a plurality of apertures that are spaced radially on the outer flange and extend through the back surface and the mating surface.

18. The tank container of claim 17, wherein the plurality of slots are spaced radially about the outer flange and at least one slot of the plurality of slots corresponds with at least one aperture of the plurality of apertures.

19. The tank container of claim 17, wherein at least one aperture of the plurality of apertures is configured to receive a fastener therethrough and a head of the fastener is configured to be received within one of the slots.

20. The tank container of claim 16, wherein an inner flange of the adaptor is disposed at an acute angle relative to the outer flange.

\* \* \* \* \*