

(12) **United States Patent**
Beyhs

(10) **Patent No.:** **US 11,906,937 B2**
(45) **Date of Patent:** ***Feb. 20, 2024**

(54) **CROWN FOR AN ELECTRONIC WATCH**

(71) Applicant: **Apple Inc.**, Cupertino, CA (US)

(72) Inventor: **Michael J. Beyhs**, San Francisco, CA (US)

(73) Assignee: **Apple Inc.**, Cupertino, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/094,930**

(22) Filed: **Jan. 9, 2023**

(65) **Prior Publication Data**

US 2023/0161299 A1 May 25, 2023

Related U.S. Application Data

(63) Continuation of application No. 16/191,349, filed on Nov. 14, 2018, now Pat. No. 11,561,515.

(60) Provisional application No. 62/713,745, filed on Aug. 2, 2018.

(51) **Int. Cl.**
G04G 21/08 (2010.01)
G04G 9/00 (2006.01)
G06F 3/042 (2006.01)

(52) **U.S. Cl.**
CPC **G04G 21/08** (2013.01); **G04G 9/007** (2013.01); **G06F 3/0425** (2013.01)

(58) **Field of Classification Search**
CPC G01D 5/30; G04G 17/08; G04G 21/025; G04G 21/08; G04G 9/007; G04B 37/10; G04B 27/002; H01H 3/122; H01H 9/16;

H01H 25/008; H01H 2215/006; H01H 2221/01; H01H 25/06; H01H 2209/006; H01H 2223/002; G04C 3/002; G06F 3/0425

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,237,860 A 4/1941 Bolle
2,288,215 A 6/1942 Taubert et al.
2,497,935 A 2/1950 Feurer

(Continued)

FOREIGN PATENT DOCUMENTS

CH 1888928 1/1937
CN 1302740 9/2001

(Continued)

OTHER PUBLICATIONS

Author Unknown, "Desirable Android Wear smartwatch from LG," Gulf News, Dubai, 3 pages, Jan. 30, 2015.

(Continued)



Primary Examiner — Edwin A. Leon

(74) *Attorney, Agent, or Firm* — Brownstein Hyatt Farber Schreck LLP

(57) **ABSTRACT**

An electronic watch includes a housing defining a side surface of the electronic watch, a transparent cover coupled to the housing and defining a front surface of the electronic watch, an image-sensing element, and a crown extending from the side of the housing and defining an imaging surface. The crown may include a light-directing feature configured to direct, onto the image-sensing element, an image of an object in contact with the imaging surface.

20 Claims, 13 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,771,734 A	11/1956	Morf	5,960,366 A	9/1999	Duwaer et al.
2,788,236 A	4/1957	Kafowi	5,963,332 A	10/1999	Feldman et al.
2,797,592 A	7/1957	Marrapese	5,999,168 A	12/1999	Rosenberg et al.
3,040,514 A	6/1962	Dinstman	6,069,567 A	5/2000	Zawilski
3,056,030 A	9/1962	Kelchner	6,128,006 A	10/2000	Rosenberg et al.
3,130,539 A	4/1964	Davis	6,134,189 A	10/2000	Carrard
3,355,873 A	12/1967	Morf	6,154,201 A	11/2000	Levin et al.
3,362,154 A	1/1968	Perret	6,175,679 B1	1/2001	Veligdan et al.
3,410,247 A	11/1968	Dronberger	6,203,190 B1	3/2001	Stotz
3,495,398 A	2/1970	Widmer et al.	6,241,684 B1	6/2001	Amano
3,577,876 A	5/1971	Spadini	6,246,050 B1	6/2001	Tullis et al.
3,621,649 A	11/1971	Vulcan et al.	6,252,825 B1	6/2001	Perotto
3,662,618 A	5/1972	Kroll et al.	6,304,247 B1	10/2001	Black
3,733,803 A	5/1973	Hiraga	6,355,891 B1	3/2002	Ikunami
3,937,002 A	2/1976	Van Haften	6,361,502 B1	3/2002	Puolakanaho et al.
4,007,347 A	2/1977	Haber	6,377,239 B1	4/2002	Isikawa
4,031,341 A	6/1977	Wuthrich et al.	6,392,640 B1	5/2002	Will
4,037,068 A	7/1977	Gaynor	6,396,006 B1	5/2002	Yokoji et al.
4,051,665 A	10/1977	Arn	6,422,740 B1	7/2002	Leuenberger
4,077,200 A	3/1978	Schneider	6,477,117 B1	11/2002	Narayanaswami et al.
4,133,404 A	1/1979	Griffin	6,502,982 B1	1/2003	Bach et al.
4,170,104 A	10/1979	Yamagata	6,525,278 B2	2/2003	Villain et al.
4,258,096 A	3/1981	LaMarche	6,556,222 B1	4/2003	Narayanaswami
4,274,152 A	6/1981	Ikegami	6,575,618 B1	6/2003	Inoue et al.
4,287,400 A	9/1981	Kitik	6,587,400 B1	7/2003	Line
4,289,400 A	9/1981	Kubola et al.	6,636,197 B1	10/2003	Goldenberg et al.
4,311,026 A	1/1982	Ochoa	6,646,635 B2	11/2003	Pogatetz et al.
4,311,990 A	1/1982	Burke	6,661,438 B1	11/2003	Shiraishi et al.
4,324,956 A	4/1982	Sakakino et al.	6,672,758 B2	1/2004	Ehrsam et al.
4,345,119 A	8/1982	Latasiewicz	6,794,992 B1	9/2004	Rogers
4,364,674 A	12/1982	Tesch	6,809,275 B1	10/2004	Cheng et al.
4,379,642 A	4/1983	Meyrat	6,834,430 B2	12/2004	Worrell
4,395,134 A	7/1983	Luce	6,846,998 B2	1/2005	Hasumi et al.
4,396,298 A	8/1983	Ripley	6,882,596 B2	4/2005	Guanter
4,417,824 A	11/1983	Paterson et al.	6,888,076 B2	5/2005	Hetherington
4,448,199 A	5/1984	Schmid	6,896,403 B1	5/2005	Gau
4,520,306 A	5/1985	Kirby	6,909,378 B1	6/2005	Lambrechts et al.
4,581,509 A	4/1986	Sanford et al.	6,914,551 B2	7/2005	Vidal
4,600,316 A	7/1986	Besson	6,950,695 B2	9/2005	Chen
4,617,461 A	10/1986	Subbarao et al.	6,961,099 B2	11/2005	Takano et al.
4,634,861 A	1/1987	Ching et al.	6,963,039 B1	11/2005	Weng et al.
4,641,026 A	2/1987	Garcia, Jr.	6,967,903 B2	11/2005	Guanter
4,670,737 A	6/1987	Rilling	6,977,868 B2	12/2005	Brewer et al.
4,766,642 A	8/1988	Gaffney et al.	6,982,930 B1	1/2006	Hung
4,783,772 A	11/1988	Umemoto et al.	6,985,107 B2	1/2006	Anson
4,884,073 A	11/1989	Souloumiac	6,987,568 B2	1/2006	Dana
4,914,831 A	4/1990	Kanezashi et al.	6,998,553 B2	2/2006	Hisamune et al.
4,922,070 A	5/1990	Dorkinski	7,009,915 B2	3/2006	Brewer et al.
4,931,794 A	6/1990	Haag	7,016,263 B2	3/2006	Gueissaz et al.
4,952,799 A	8/1990	Loewen	7,021,442 B2	4/2006	Borgerson
4,980,685 A	12/1990	Souloumiac et al.	7,031,228 B2	4/2006	Born et al.
4,987,299 A	1/1991	Kobayashi et al.	7,034,237 B2	4/2006	Ferri et al.
5,034,602 A	7/1991	Garcia et al.	7,081,905 B1	7/2006	Raghunath et al.
5,177,355 A	1/1993	Branan	7,102,626 B2	9/2006	Denny, III
5,214,278 A	5/1993	Banda	7,111,365 B1	9/2006	Howie, Jr.
5,258,592 A	11/1993	Nishikawa et al.	7,113,450 B2	9/2006	Plancon et al.
5,288,993 A	2/1994	Bidiville et al.	7,119,289 B2	10/2006	Lacroix
5,347,123 A	9/1994	Jackson et al.	7,135,673 B2	11/2006	Saint Clair
5,383,166 A	1/1995	Gallay	7,167,083 B2	1/2007	Giles
5,471,054 A	11/1995	Watanabe	7,187,359 B2	3/2007	Numata
5,477,508 A	12/1995	Will	7,244,927 B2	7/2007	Huynh
5,509,174 A	4/1996	Worrell	7,255,473 B2	8/2007	Hiranuma et al.
5,559,761 A	9/1996	Frenkel et al.	7,265,336 B2	9/2007	Hataguchi et al.
5,572,314 A	11/1996	Hyman et al.	7,274,303 B2	9/2007	Dresti et al.
5,583,560 A	12/1996	Florin et al.	7,285,738 B2	10/2007	Lavigne et al.
5,631,881 A	5/1997	Pessey et al.	7,286,063 B2	10/2007	Gauthey
5,726,645 A	3/1998	Kamon et al.	7,292,741 B2	11/2007	Ishiyama et al.
5,738,104 A	4/1998	Lo	7,358,481 B2	4/2008	Yeoh et al.
5,748,111 A	5/1998	Bates	7,369,308 B2	5/2008	Tsuruta et al.
5,825,353 A	10/1998	Will	7,371,745 B2	5/2008	Ebright et al.
5,841,050 A	11/1998	Clift et al.	7,385,874 B2	6/2008	Vuilleumier
5,847,335 A	12/1998	Sugahara et al.	7,404,667 B2	7/2008	Born et al.
5,867,082 A	2/1999	Van Zeeland	7,465,917 B2	12/2008	Chin et al.
5,943,233 A	8/1999	Ebina	7,468,036 B1	12/2008	Rulkov et al.
5,953,001 A	9/1999	Challener et al.	7,506,269 B2	3/2009	Lang et al.
			7,520,664 B2	4/2009	Wai
			7,528,824 B2	5/2009	Kong
			7,545,367 B2	6/2009	Sunda et al.
			7,591,582 B2	9/2009	Hiranuma et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,593,755 B2	9/2009	Colando et al.	8,860,674 B2	10/2014	Lee et al.
7,605,846 B2	10/2009	Watanabe	8,863,219 B2	10/2014	Brown et al.
7,634,263 B2	12/2009	Louch et al.	D717,679 S	11/2014	Anderssen
7,646,677 B2	1/2010	Nakamura	8,878,657 B2	11/2014	Periquet et al.
7,655,874 B2	2/2010	Akieda	8,885,856 B2	11/2014	Sacha
7,682,070 B2	3/2010	Burton	8,895,911 B2	11/2014	Takahashi
7,708,457 B2	5/2010	Girardin	8,905,631 B2	12/2014	Sakurazawa et al.
7,710,456 B2	5/2010	Koshiha et al.	8,908,477 B2	12/2014	Peters
7,732,724 B2	6/2010	Otani et al.	8,920,022 B2	12/2014	Ishida et al.
7,761,246 B2	7/2010	Matsui	8,922,399 B2	12/2014	Bajaj et al.
7,763,819 B2	7/2010	Ieda et al.	8,928,452 B2	1/2015	Kim et al.
7,772,507 B2	8/2010	Orr	8,948,832 B2	2/2015	Hong et al.
7,778,115 B2	8/2010	Ruchonnet	8,954,135 B2	2/2015	Yuen et al.
7,781,726 B2	8/2010	Matsui et al.	8,975,543 B2	3/2015	Hakemeyer
RE41,637 E	9/2010	O'Hara et al.	8,994,827 B2	3/2015	Mistry et al.
7,791,587 B2	9/2010	Kosugi	9,001,625 B2	4/2015	Essery et al.
7,791,588 B2	9/2010	Tierling et al.	9,024,733 B2	5/2015	Wouters
7,791,597 B2	9/2010	Silverstein et al.	9,028,134 B2	5/2015	Koshoji et al.
7,822,469 B2	10/2010	Lo	9,030,446 B2	5/2015	Mistry et al.
7,856,255 B2	12/2010	Tsuchiya et al.	9,034,666 B2	5/2015	Vaganov et al.
7,858,583 B2	12/2010	Schmidt et al.	9,039,614 B2	5/2015	Yuen et al.
7,865,324 B2	1/2011	Lindberg	9,041,663 B2	5/2015	Westerman
7,894,957 B2	2/2011	Carlson	9,042,971 B2	5/2015	Brumback et al.
7,946,758 B2	5/2011	Mooring	9,049,998 B2	6/2015	Brumback et al.
8,063,892 B2	11/2011	Shahoian et al.	9,052,696 B2	6/2015	Breuillet et al.
8,138,488 B2	3/2012	Grot	9,086,717 B2	7/2015	Meerovitsch
8,143,981 B2	3/2012	Washizu et al.	9,086,738 B2	7/2015	Leung et al.
8,167,126 B2	5/2012	Stiehl	9,091,309 B2	7/2015	Battlogg
8,169,402 B2	5/2012	Shahoian et al.	9,100,493 B1	8/2015	Zhou
8,188,989 B2	5/2012	Levin et al.	9,101,184 B2	8/2015	Wilson
8,195,313 B1	6/2012	Fadell et al.	9,105,413 B2	8/2015	Hiranuma et al.
8,229,535 B2	7/2012	Mensing et al.	9,123,483 B2	9/2015	Ferri et al.
8,248,815 B2	8/2012	Yang et al.	9,134,807 B2	9/2015	Shaw et al.
8,263,886 B2	9/2012	Lin et al.	9,141,087 B2	9/2015	Brown et al.
8,263,889 B2	9/2012	Takahashi et al.	9,176,577 B2	11/2015	Jangaard et al.
8,275,327 B2	9/2012	Yi et al.	9,176,598 B2	11/2015	Sweetser et al.
8,294,670 B2	10/2012	Griffin et al.	9,202,372 B2	12/2015	Reams et al.
8,312,495 B2	11/2012	Vanderhoff	9,213,409 B2	12/2015	Redelsheimer et al.
8,318,340 B2	11/2012	Stimits	9,223,296 B2	12/2015	Yang et al.
8,368,677 B2	2/2013	Yamamoto	9,241,635 B2	1/2016	Yuen et al.
8,371,745 B2	2/2013	Manni	9,244,438 B2	1/2016	Hoover et al.
8,373,661 B2	2/2013	Lan et al.	9,256,209 B2	2/2016	Yang et al.
8,405,618 B2	3/2013	Colgate	9,277,156 B2	3/2016	Bennett et al.
8,410,971 B2	4/2013	Friedlander	9,350,850 B2	5/2016	Pope et al.
8,432,368 B2	4/2013	Momeyer et al.	9,367,146 B2	6/2016	Piot
8,439,559 B2	5/2013	Luk et al.	9,386,932 B2	7/2016	Chatterjee et al.
8,441,450 B2	5/2013	Degner et al.	9,426,275 B2	8/2016	Eim et al.
8,446,713 B2	5/2013	Lai	9,430,042 B2	8/2016	Levin
8,456,430 B2	6/2013	Oliver et al.	9,437,357 B2	9/2016	Furuki et al.
8,477,118 B2	7/2013	Lan et al.	9,449,770 B2	9/2016	Sanford et al.
8,493,190 B2	7/2013	Periquet et al.	9,501,044 B2	11/2016	Jackson et al.
8,508,511 B2	8/2013	Tanaka et al.	9,520,100 B2	12/2016	Houjou et al.
8,525,777 B2	9/2013	Stavely et al.	9,532,723 B2	1/2017	Kim
8,562,489 B2	10/2013	Burton et al.	9,542,016 B2	1/2017	Armstrong-Muntner
8,568,313 B2	10/2013	Sadhu	9,545,541 B2	1/2017	Aragones et al.
8,576,044 B2	11/2013	Chapman	9,552,023 B2	1/2017	Joo et al.
8,593,598 B2	11/2013	Chen et al.	9,599,964 B2	3/2017	Gracia
8,607,662 B2	12/2013	Huang	9,600,071 B2	3/2017	Rothkopf
8,614,881 B2	12/2013	Yoo	9,607,505 B2	3/2017	Rothkopf et al.
8,666,682 B2	3/2014	LaVigne et al.	9,620,312 B2	4/2017	Ely et al.
8,677,285 B2	3/2014	Tsern et al.	9,627,163 B2	4/2017	Ely
8,704,787 B2	4/2014	Yamamoto	9,632,318 B2	4/2017	Goto et al.
8,711,093 B2	4/2014	Ong et al.	9,632,537 B2	4/2017	Memering
8,717,151 B2	5/2014	Forutanpour et al.	9,638,587 B2	5/2017	Marquas et al.
8,724,087 B2	5/2014	Van De Kerkhof et al.	9,651,922 B2	5/2017	Hysek et al.
8,730,167 B2	5/2014	Ming et al.	9,659,482 B2	5/2017	Yang et al.
8,743,088 B2	6/2014	Watanabe	9,680,831 B2	6/2017	Jooste et al.
8,783,944 B2	7/2014	Doi	9,709,956 B1	7/2017	Ely et al.
8,797,153 B2	8/2014	Vanhelle et al.	9,753,436 B2	9/2017	Ely et al.
8,804,993 B2	8/2014	Shukla et al.	D800,172 S	10/2017	Akana
8,816,962 B2	8/2014	Obermeyer et al.	9,800,717 B2	10/2017	Ma et al.
8,824,245 B2	9/2014	Lau et al.	9,836,025 B2	12/2017	Ely et al.
8,847,741 B2	9/2014	Birnbaum et al.	9,873,711 B2	1/2018	Hoover et al.
8,851,372 B2	10/2014	Zhou	9,874,945 B2	1/2018	Fukumoto
8,859,971 B2	10/2014	Weber	9,886,006 B2	2/2018	Ely et al.
			9,891,590 B2	2/2018	Shim et al.
			9,891,651 B2	2/2018	Jackson et al.
			9,891,667 B2	2/2018	Jung et al.
			9,898,032 B2	2/2018	Hafez et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,913,591 B2	3/2018	Lapetina et al.	11,000,193 B2	5/2021	Tal et al.
9,921,548 B2	3/2018	Mitani	11,002,572 B2	5/2021	Boonsom et al.
9,927,902 B2	3/2018	Burr et al.	11,029,831 B2	6/2021	Block et al.
9,939,923 B2	4/2018	Sharma	11,036,318 B2	6/2021	Kuboyama
9,946,297 B2	4/2018	Nazzaro et al.	11,148,292 B2	10/2021	Bryner et al.
9,952,558 B2	4/2018	Ely	11,181,863 B2	11/2021	Ely et al.
9,952,682 B2	4/2018	Zhang et al.	11,194,298 B2	12/2021	Roach et al.
9,971,305 B2	5/2018	Ely et al.	11,194,299 B1	12/2021	Taylor et al.
9,971,405 B2	5/2018	Holenarsipur et al.	11,221,590 B2	1/2022	Rothkopf et al.
9,971,407 B2	5/2018	Holenarsipur et al.	11,347,189 B1	5/2022	Herrera et al.
9,979,426 B2	5/2018	Na et al.	11,347,351 B2	6/2022	Shedletsy et al.
10,001,817 B2	6/2018	Zambetti et al.	11,385,599 B2	7/2022	Ely et al.
10,012,550 B2	7/2018	Yang	11,474,483 B2	10/2022	Rothkopf
10,018,966 B2	7/2018	Ely et al.	11,513,613 B2	11/2022	Bushnell et al.
10,019,097 B2	7/2018	Ely et al.	11,531,306 B2	12/2022	Ely et al.
10,037,006 B2	7/2018	Ely	11,537,082 B2 *	12/2022	Ferri G04C 3/002
10,037,081 B2	7/2018	Grant	11,561,515 B2 *	1/2023	Beyhs G04G 9/007
10,048,802 B2	8/2018	Shedletsy	2002/0101457 A1	8/2002	Lang
10,057,470 B2	8/2018	Sangeun	2003/0174590 A1	9/2003	Arikawa et al.
10,061,399 B2	8/2018	Bushnell et al.	2004/0047244 A1	3/2004	Iino et al.
10,066,970 B2	9/2018	Gowreesunker et al.	2004/0082414 A1	4/2004	Knox
10,092,203 B2	10/2018	Mirov	2004/0130971 A1	7/2004	Ecoffet et al.
10,108,016 B2	10/2018	Bosveld	2004/0264301 A1	12/2004	Howard et al.
10,114,342 B2	10/2018	Kim et al.	2005/0075558 A1	4/2005	Vecerina et al.
10,145,711 B2	12/2018	Boonsom et al.	2005/0088417 A1	4/2005	Mulligan
10,175,652 B2	1/2019	Ely et al.	2006/0250377 A1	11/2006	Zadesky et al.
10,190,891 B1	1/2019	Rothkopf et al.	2007/0013775 A1	1/2007	Shin
10,203,662 B1	2/2019	Lin et al.	2007/0050054 A1	3/2007	Sambandam Guruparan et al.
10,209,148 B2	2/2019	Lyon et al.	2007/0182708 A1	8/2007	Poupyrev et al.
10,216,147 B2	2/2019	Ely et al.	2007/0211042 A1	9/2007	Kim et al.
10,222,755 B2	3/2019	Coakley et al.	2007/0222756 A1	9/2007	Wu et al.
10,222,756 B2	3/2019	Ely et al.	2007/0229671 A1	10/2007	Takeshita et al.
10,222,909 B2	3/2019	Shedletsy et al.	2007/0247421 A1	10/2007	Orsley et al.
10,234,828 B2	3/2019	Ely et al.	2008/0130914 A1	6/2008	Cho
10,241,593 B2	3/2019	Chen	2009/0051649 A1	2/2009	Rondel
10,274,905 B2 *	4/2019	Chung G04B 19/223	2009/0073119 A1	3/2009	Le et al.
10,296,125 B2	5/2019	Ely et al.	2009/0122656 A1	5/2009	Bonnet et al.
10,331,081 B2	6/2019	Ely et al.	2009/0146975 A1	6/2009	Chang
10,331,082 B2	6/2019	Ely et al.	2009/0152452 A1	6/2009	Lee et al.
10,332,111 B2	6/2019	Mokhasi et al.	2009/0217207 A1	8/2009	Kagermeier et al.
10,353,487 B2	7/2019	Chung et al.	2009/0285443 A1	11/2009	Camp et al.
10,379,629 B2	8/2019	Bushnell et al.	2009/0312051 A1	12/2009	Hansson et al.
10,386,940 B2	8/2019	Kim	2009/0312655 A1	12/2009	Lo
10,401,961 B2	9/2019	Cruz-Hernandez et al.	2010/0033430 A1	2/2010	Kakutani et al.
10,429,959 B2	10/2019	Battlogg	2010/0053468 A1	3/2010	Havrill
10,474,194 B1	11/2019	Ell et al.	2010/0081375 A1	4/2010	Rosenblatt et al.
10,503,258 B2	12/2019	Holenarsipur et al.	2010/0149099 A1	6/2010	Elias
10,509,486 B2	12/2019	Bushnell et al.	2011/0007468 A1	1/2011	Burton et al.
10,524,671 B2	1/2020	Lamego	2011/0090148 A1	4/2011	Li et al.
10,534,320 B2	1/2020	Ferri et al.	2011/0158057 A1	6/2011	Brewer et al.
10,534,900 B2	1/2020	Cheong et al.	2011/0242064 A1	10/2011	Ono et al.
10,551,798 B1	2/2020	Bushnell et al.	2011/0270358 A1	11/2011	Davis et al.
10,572,053 B2	2/2020	Ely et al.	2012/0067711 A1	3/2012	Yang
10,579,090 B2	3/2020	Jackson et al.	2012/0068857 A1	3/2012	Rothkopf et al.
10,593,617 B2	3/2020	Ashikaga et al.	2012/0075082 A1	3/2012	Rothkopf et al.
10,599,101 B2	3/2020	Rothkopf et al.	2012/0112859 A1	5/2012	Park et al.
10,610,157 B2	4/2020	Pandya et al.	2012/0113044 A1	5/2012	Strazisar et al.
10,613,685 B2	4/2020	Shedletsy	2012/0206248 A1	8/2012	Biggs
10,627,783 B2	4/2020	Rothkopf et al.	2012/0272784 A1	11/2012	Bailey et al.
10,655,988 B2	5/2020	Boonsom et al.	2013/0037396 A1	2/2013	Yu
10,664,074 B2	5/2020	Moussette et al.	2013/0087443 A1	4/2013	Kikuchi
10,732,571 B2	8/2020	Ely et al.	2013/0191220 A1	7/2013	Dent et al.
10,765,019 B2	9/2020	Werner	2013/0235704 A1	9/2013	Grinberg
10,845,764 B2	11/2020	Ely et al.	2013/0261405 A1	10/2013	Lee et al.
10,852,700 B2	12/2020	Abramov	2013/0335196 A1	12/2013	Zhang et al.
10,852,855 B2	12/2020	Niu	2014/0009397 A1	1/2014	Gillespie
10,871,385 B2	12/2020	Kok	2014/0045547 A1	2/2014	Singamsetty et al.
10,884,549 B2	1/2021	Shedletsy et al.	2014/0071098 A1	3/2014	You
10,936,071 B2	3/2021	Pandya et al.	2014/0073486 A1	3/2014	Ahmed et al.
10,942,491 B2	3/2021	Rothkopf	2014/0132516 A1	5/2014	Tsai et al.
10,948,880 B2	3/2021	Ely et al.	2014/0197936 A1	7/2014	Biggs et al.
10,955,937 B2	3/2021	Bushnell et al.	2014/0340318 A1	11/2014	Stringer et al.
10,962,930 B2	3/2021	Ely et al.	2014/0347289 A1	11/2014	Suh et al.
10,962,935 B1	3/2021	Ely et al.	2014/0368442 A1	12/2014	Vahtola
10,987,054 B2	4/2021	Pandya et al.	2014/0375579 A1	12/2014	Fujiwara
			2015/0049059 A1	2/2015	Zadesky et al.
			2015/0098309 A1	4/2015	Adams et al.
			2015/0124415 A1	5/2015	Goyal et al.
			2015/0186609 A1	7/2015	Utter, II

(56)

References Cited**U.S. PATENT DOCUMENTS**

2015/0221460 A1 8/2015 Teplitxky et al.
 2015/0293592 A1 10/2015 Cheong
 2015/0320346 A1 11/2015 Chen
 2015/0338642 A1 11/2015 Sanford
 2015/0341031 A1 11/2015 Marquas et al.
 2015/0366098 A1 12/2015 Lapetina et al.
 2016/0018846 A1 1/2016 Zenoff
 2016/0054813 A1 2/2016 Shediwy et al.
 2016/0058375 A1 3/2016 Rothkopf et al.
 2016/0061636 A1 3/2016 Gowreesunker et al.
 2016/0062623 A1 3/2016 Howard et al.
 2016/0069713 A1 3/2016 Ruh et al.
 2016/0109861 A1 4/2016 Kim et al.
 2016/0116306 A1 4/2016 Ferri et al.
 2016/0147432 A1 5/2016 Shi et al.
 2016/0170598 A1 6/2016 Zambetti et al.
 2016/0170608 A1 6/2016 Zambetti et al.
 2016/0170624 A1 6/2016 Zambetti et al.
 2016/0241688 A1 8/2016 Vossoughi
 2016/0253487 A1 9/2016 Sarkar et al.
 2016/0306446 A1 10/2016 Chung et al.
 2016/0320583 A1 11/2016 Hall, Jr.
 2016/0327911 A1 11/2016 Eim et al.
 2016/0338642 A1 11/2016 Parara et al.
 2016/0378069 A1 12/2016 Rothkopf et al.
 2016/0378070 A1 12/2016 Rothkopf et al.
 2016/0378071 A1 12/2016 Rothkopf et al.
 2017/0011210 A1 1/2017 Cheong et al.
 2017/0027461 A1 2/2017 Shin et al.
 2017/0031449 A1 2/2017 Karsten et al.
 2017/0045958 A1 2/2017 Battlogg et al.
 2017/0061863 A1 3/2017 Eguchi
 2017/0069443 A1 3/2017 Wang et al.
 2017/0069444 A1 3/2017 Wang et al.
 2017/0069447 A1 3/2017 Wang et al.
 2017/0090572 A1 3/2017 Holenarsipur
 2017/0090599 A1 3/2017 Kuboyama
 2017/0104902 A1 4/2017 Kim et al.
 2017/0139489 A1 5/2017 Chen et al.
 2017/0216519 A1 8/2017 Vouillamoz
 2017/0216668 A1 8/2017 Burton et al.
 2017/0238138 A1 8/2017 Aminzade
 2017/0251561 A1 8/2017 Fleck et al.
 2017/0269715 A1 9/2017 Kim et al.
 2017/0285404 A1 10/2017 Kubota et al.
 2017/0301314 A1 10/2017 Kim et al.
 2017/0307414 A1 10/2017 Ferri et al.
 2017/0331869 A1 11/2017 Bendahan et al.
 2017/0357465 A1 12/2017 Dzeryn et al.
 2018/0018026 A1 1/2018 Bushnell et al.
 2018/0059624 A1 3/2018 James
 2018/0136613 A1 5/2018 Ely et al.
 2018/0136686 A1 5/2018 Jackson et al.
 2018/0196517 A1 7/2018 Tan et al.
 2018/0225701 A1 8/2018 Han
 2018/0235491 A1 8/2018 Bayley et al.
 2018/0239306 A1 8/2018 Ely
 2018/0299834 A1 10/2018 Ely et al.
 2018/0307363 A1 10/2018 Ely et al.
 2018/0329368 A1 11/2018 Ely et al.
 2018/0335891 A1 11/2018 Shedletsy et al.
 2018/0337551 A1 11/2018 Park
 2018/0341342 A1 11/2018 Bushnell et al.
 2018/0364815 A1 12/2018 Moussette et al.
 2019/0017846 A1 1/2019 Boonsom et al.
 2019/0056700 A1 2/2019 Matsuno
 2019/0072902 A1 3/2019 Ely et al.
 2019/0072911 A1 3/2019 Ely et al.
 2019/0072912 A1 3/2019 Pandya et al.
 2019/0082547 A1 3/2019 Werner et al.
 2019/0088583 A1 3/2019 Ashikaga et al.
 2019/0146415 A1 5/2019 Ely et al.
 2019/0163324 A1 5/2019 Shedletsy
 2019/0250754 A1 8/2019 Ely et al.
 2019/0278232 A1 9/2019 Ely et al.

2019/0294117 A1 9/2019 Ely et al.
 2019/0302902 A1 10/2019 Bushnell et al.
 2019/0317454 A1 10/2019 Holenarsipur et al.
 2019/0391539 A1 12/2019 Perkins et al.
 2020/0041962 A1 2/2020 Beyhs
 2020/0064774 A1 2/2020 Ely et al.
 2020/0064779 A1 2/2020 Pandya et al.
 2020/0073339 A1 3/2020 Roach et al.
 2020/0110473 A1 4/2020 Bushnell et al.
 2020/0159172 A1 5/2020 Bushnell et al.
 2020/0233380 A1 7/2020 Rothkopf
 2020/0233529 A1 7/2020 Shedletsy et al.
 2020/0271483 A1 8/2020 Boonsom
 2020/0310609 A1 10/2020 Ham
 2020/0326659 A1 10/2020 Ely et al.
 2021/0055696 A1 2/2021 Ely
 2021/0060783 A1 3/2021 Bryner et al.
 2021/0096688 A1 4/2021 Shedletsy et al.
 2021/0181682 A1 6/2021 Ely et al.
 2021/0181688 A1 6/2021 Ely et al.
 2021/0181690 A1 6/2021 Rothkopf et al.
 2021/0181691 A1 6/2021 Rothkopf et al.
 2021/0181692 A1 6/2021 Rothkopf et al.
 2021/0181865 A1 6/2021 Bushnell et al.
 2021/0255590 A1 8/2021 Ely et al.
 2021/0303081 A1 9/2021 Kuboyama et al.
 2021/0373501 A1 12/2021 Pandya et al.
 2021/0405594 A1 12/2021 Holenarsipur et al.
 2022/0043397 A1 2/2022 Ely et al.
 2022/0043402 A1 2/2022 Roach et al.
 2022/0075328 A1 3/2022 Taylor
 2022/0171344 A1 6/2022 Rothkopf et al.
 2022/0261111 A1 8/2022 Shedletsy et al.
 2022/0299944 A1 9/2022 Ely
 2022/0326660 A1 10/2022 Perkins

FOREIGN PATENT DOCUMENTS

CN 1445627 10/2003
 CN 1504843 6/2004
 CN 1601408 3/2005
 CN 1624427 6/2005
 CN 1792295 6/2006
 CN 1825224 8/2006
 CN 101035148 9/2007
 CN 101201587 6/2008
 CN 201081979 7/2008
 CN 101404928 4/2009
 CN 201262741 6/2009
 CN 101750958 6/2010
 CN 201638168 11/2010
 CN 101923314 12/2010
 CN 102067070 5/2011
 CN 102216959 10/2011
 CN 202008579 10/2011
 CN 102590925 7/2012
 CN 102741772 10/2012
 CN 102890443 1/2013
 CN 202710937 1/2013
 CN 103177891 6/2013
 CN 103191557 7/2013
 CN 103253067 8/2013
 CN 103645804 3/2014
 CN 203564224 4/2014
 CN 103852090 6/2014
 CN 203630524 6/2014
 CN 103956006 7/2014
 CN 203693601 7/2014
 CN 203705837 7/2014
 CN 203732900 7/2014
 CN 103995456 8/2014
 CN 104020660 9/2014
 CN 203941395 11/2014
 CN 104777987 4/2015
 CN 104685794 6/2015
 CN 204479929 7/2015
 CN 204496177 7/2015
 CN 104880937 9/2015
 CN 104898406 9/2015

(56)	References Cited			JP	2004028979	11/2004
	FOREIGN PATENT DOCUMENTS			JP	2005017011	1/2005
				JP	2005063200	3/2005
				JP	2005099023	4/2005
				JP	2005108630	4/2005
				JP	2006101505	4/2006
				JP	2006164275	6/2006
				JP	3852854	12/2006
				JP	2007101380	4/2007
				JP	2007149620	6/2007
				JP	2007248176	9/2007
				JP	2007311153	11/2007
				JP	2008053980	3/2008
				JP	2008122124	5/2008
				JP	2008122377	5/2008
				JP	2008170436	7/2008
				JP	2008235226	10/2008
				JP	2009009382	1/2009
				JP	2009070657	4/2009
				JP	2009519737	5/2009
				JP	2009540399	11/2009
				JP	2010032545	2/2010
				JP	2010515153	5/2010
				JP	2010165001	7/2010
				JP	2010186572	8/2010
				JP	2010243344	10/2010
				JP	2010244797	10/2010
				JP	2011021929	2/2011
				JP	2011165468	8/2011
				JP	2011221659	11/2011
				JP	2012053801	3/2012
				JP	2013057516	3/2013
				JP	2013079961	5/2013
				JP	2013524189	6/2013
				JP	3190075	4/2014
				JP	5477393	4/2014
				JP	2014512556	5/2014
				JP	2014112222	6/2014
				JP	2014174031	9/2014
				JP	2018510451	4/2018
				KR	20010030477	4/2001
				KR	200278568	3/2002
				KR	WO2003/032538	4/2003
				KR	20070011685	1/2007
				KR	20070014247	2/2007
				KR	100754674	9/2007
				KR	20080028935	4/2008
				KR	20080045397	5/2008
				KR	2020100007563	7/2010
				KR	20110011393	2/2011
				KR	20110012784	2/2011
				KR	20110103761	9/2011
				KR	20110113368	10/2011
				KR	20130036038	4/2013
				KR	20130131873	12/2013
				KR	20140051391	4/2014
				KR	20140064689	5/2014
				KR	20140104388	8/2014
				KR	20160017070	2/2016
				KR	20160048967	5/2016
				KR	20170106395	9/2017
				NL	1040225	11/2014
				RO	129033	11/2013
				TW	200633681	10/2006
				WO	WO2001/022038	3/2001
				WO	WO2001/069567	9/2001
				WO	WO2010/058376	5/2010
				WO	WO2012/083380	6/2012
				WO	WO2012/094805	7/2012
				WO	WO2014/018118	1/2014
				WO	WO2014/200766	12/2014
				WO	WO2015/147756	10/2015
				WO	WO2016080669	5/2016
				WO	WO2016/104922	6/2016
				WO	WO2016/155761	10/2016
				WO	WO2016196171	12/2016
				WO	WO2016208835	12/2016
CN	204650147	9/2015				
CN	105022947	11/2015				
CN	105096979	11/2015				
CN	105339871	2/2016				
CN	105547146	5/2016				
CN	105556433	5/2016				
CN	105683876	6/2016				
CN	105760067	7/2016				
CN	105955519	9/2016				
CN	205645648	10/2016				
CN	205721636	11/2016				
CN	205750744	11/2016				
CN	106236051	12/2016				
CN	106557218	4/2017				
CN	206147524	5/2017				
CN	206209589	5/2017				
CN	107111342	8/2017				
CN	107122088	9/2017				
CN	107966895	4/2018				
CN	209560397	10/2019				
CN	209625187	11/2019				
CN	106125968	11/2022				
DE	3706194	9/1988				
DE	102008023651	11/2009				
DE	102016215087	3/2017				
EP	0165548	12/1985				
EP	0556155	8/1993				
EP	1345095	9/2003				
EP	1519452	3/2005				
EP	1669724	6/2006				
EP	1832969	9/2007				
EP	2375295	10/2011				
EP	2579186	4/2013				
EP	2720129	4/2014				
EP	2884239	6/2015				
FR	2030093	10/1970				
FR	2801402	5/2001				
GB	2433211	6/2007				
JP	S52151058	12/1977				
JP	S52164551	12/1977				
JP	S53093067	8/1978				
JP	S54087779	6/1979				
JP	S5708582	1/1982				
JP	S5734457	2/1982				
JP	S60103936	6/1985				
JP	S60103937	6/1985				
JP	H02285214	11/1990				
JP	H04093719	3/1992				
JP	H04157319	5/1992				
JP	H05203465	8/1993				
JP	H05312595	11/1993				
JP	H06050927	12/1994				
JP	H06331761	12/1994				
JP	H06347293	12/1994				
JP	H07116141	5/1995				
JP	H0914941	1/1997				
JP	H10161811	6/1998				
JP	H11121210	4/1999				
JP	H11191508	7/1999				
JP	2000258559	9/2000				
JP	2000316824	11/2000				
JP	2000337892	12/2000				
JP	2001084934	3/2001				
JP	2001167651	6/2001				
JP	2001202178	7/2001				
JP	2001215288	8/2001				
JP	2001524206	11/2001				
JP	2002071480	3/2002				
JP	2002165768	6/2002				
JP	2003050668	2/2003				
JP	2003151410	5/2003				
JP	2003331693	11/2003				
JP	2004184396	7/2004				

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO2017/013278	1/2017
WO	WO2020173085	9/2020

OTHER PUBLICATIONS

Author Unknown, "Fossil Q ups smartwatch game with handsome design and build," Business Mirror, Makati City, Philippines, 3 pages, Dec. 20, 2016.

Author Unknown, "How Vesag Helps Kids Women and Visitors," <http://www.sooperarticles.com/health-fitness-articles/children-health-articles/how-vesag-helps-kids-women-visitors-218542.html>, 2 pages, at least as early as May 20, 2015.

Author Unknown, "mHealth," <http://mhealth.vesag.com/?m=201012>, 7 pages, Dec. 23, 2010.

Author Unknown, "mHealth Summit 2010," <http://www.virtualpressoffice.com/eventsSubmenu.do?page=exhibitorPage&showId=1551&companyId=5394>, 5 pages, Nov. 18, 2010.

Author Unknown, "MyKronoz ZeTime: World's Most Funded Hybrid Smartwatch Raised over \$3M on Kickstarter, Running until Apr. 27th," Business Wire, New York, New York, 3 pages, Apr. 21, 2017.

Author Unknown, "RedEye mini Plug-in Universal Remote Adapter for iPhone, iPod touch and iPad," Amazon.com, 4 pages, date unknown.

Author Unknown, "Re iPhone Universal Remote Control—Infrared Remote Control Accessory for iPhone and iPod touch," <http://www.amazon.com/iPhone-Universal-Remote-Control-Accessory/dp/tech-data/B0038Z4...>, 2 pages, at least as early as Jul. 15, 2010.

Author Unknown, "Vesag Wrist Watch for Dementia Care from Vyzin," <http://vyasa-kaaranam-ketkadey.blogspot.com/2011/03/vesag-wrist-watch-for-dementia-care.html>, 2 pages, Mar. 31, 2011.

Author Unknown, "Vyzin Electronics Private Limited launches Vesag Watch," <http://www.virtualpressoffice.com/showJointPage.do?page=jp&showId=1544>, 5 pages, Jan. 6, 2011.

Author Unknown, "Vyzin Unveiled Personal Emergency Response System (PERS) with Remote Health Monitoring That Can Be Used for Entire Family," <http://www.24-7pressrelease.com/press-release/vyzin-unveiled-personal-emergency-response-system-pers-with-remote-health-monitoring-that-can-be-used-for-entire-family-219317.php>, 2 pages, Jun. 17, 2011.

Author Unknown, "DeskThorityNet, Optical Switch Keyboards," <http://deskthority.net/keyboards-f2/optical-switch-keyboards-t1474.html>, 22 pages, Jul. 11, 2015.

Epstein et al., "Economical, High-Performance Optical Encoders," Hewlett-Packard Journal, pp. 99-106, Oct. 1988. [text only version]. GreyB, "Google Watch: Convert your arm into a keyboard," <http://www.whatafuture.com/2014/02/28/google-smartwatch/#sthash.Yk35cDXK.dpbs>, 3 pages, Feb. 28, 2014.

IBM, "Additional Functionality Added to Cell Phone via "Learning" Function Button," www.ip.com, 2 pages, Feb. 21, 2007.

Kim, Joseph, "2010 mHealth Summit Emerges as Major One-Stop U.S. Venue for Mobile Health," <http://www.medicinandtechnology.com/2010/08/2010-mhealth-summit-emerges-as-major.html>, 3 pages, Aug. 26, 2010.

Krishnan et al., "A Miniature Surface Mount Reflective Optical Shaft Encoder," Hewlett-Packard Journal, Article 8, pp. 1-6, Dec. 1996.

Narayanaswami et al., "Challenges and considerations for the design and production of a purpose-optimized body-worn wrist-watch computer," Defense, Security, and Cockpit Displays, 2004. M.T. Raghunath et al., User Interfaces for Applications on a Wrist Watch, Personal and Ubiquitous Computing, vol. 6, No. 1, 2002, Springer.

Rick, "How Vesag Helps Health Conscious Citizens," <http://sensetekgroup.com/2010/11/29/wireless-health-monitoring-system/>, 2 pages, Nov. 29, 2010.

Sadhu, Rajendra, "How Vesag Helps People Who Want to 'Be There'," <http://ezinearticles.com/?How-Vesag-Helps-People-Who-Want-to-Be-There?&id=5423873>, 1 page, Nov. 22, 2010.

Sadhu, Rajendra, "Mobile Innovation Helps Dementia and Alzheimer's Patients," <http://www.itnewsafrika.com/2010/11/mobile-innovation-helps-dementia-andalzheimer%E2%80%99s-patients/>, 3 pages, Nov. 22, 2010.

Sherr, Sol, "Input Devices," p. 55, Mar. 1988.

Tran et al., "Universal Programmable Remote Control/Telephone," www.ip.com, 2 pages, May 1, 1992.

U.S. Appl. No. 17/377,482, filed Jul. 16, 2021, pending.

U.S. Appl. No. 17/840,222, filed Jun. 14, 2022, pending.

U.S. Appl. No. 17/899,498, filed Aug. 31, 2022, pending.

U.S. Appl. No. 17/951,020, filed Sep. 22, 2022, pending.

U.S. Appl. No. 17/951,973, filed Sep. 23, 2022, pending.

U.S. Appl. No. 17/989,057, filed Nov. 17, 2022, pending.

U.S. Appl. No. 18/074,358, filed Dec. 2, 2022, pending.

U.S. Appl. No. 18/075,253, filed Dec. 5, 2022, pending.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8




FIG. 9




FIG. 11A





FIG. 11B



CROWN FOR AN ELECTRONIC WATCH**CROSS-REFERENCE TO RELATED APPLICATION(S)**

This application is a continuation patent application of U.S. patent application Ser. No. 16/191,349, filed Nov. 14, 2018, and titled "Crown for an Electronic Watch" and claims the benefit of U.S. Provisional Patent Application No. 62/713,745, filed Aug. 2, 2018 and titled "Crown for an Electronic Watch," the disclosures of which are hereby incorporated herein by reference in their entirety.

FIELD

The described embodiments relate generally to electronic devices, and more particularly to a crown for a wearable electronic device.

BACKGROUND

Electronic devices frequently use physical input devices to facilitate user interaction. For example, buttons, keys, dials, and the like can be physically manipulated by users to control operations of the device. Physical input devices may use various types of sensing mechanisms to translate the physical manipulation to signals usable by the electronic device. For example, buttons and keys may use collapsible dome switches to detect presses, while dials and other rotating input devices may use encoders or resolvers to detect rotational movements.

SUMMARY

An electronic watch includes a housing defining a side surface of the electronic watch, a transparent cover coupled to the housing and defining a front surface of the electronic watch, an image-sensing element, and a crown extending from the side of the housing and defining an imaging surface. The crown may include a light-directing feature configured to direct, onto the image-sensing element, an image of an object in contact with the imaging surface.

The electronic watch may further include a display positioned at least partially within the housing, and a touch sensor positioned below the transparent cover and configured to detect touch inputs applied to the transparent cover. The crown may include a head having a light-transmissive portion defining the imaging surface, and a light-transmissive shaft configured to receive light from the light-directing feature. The light-transmissive portion of the head may be transparent to infrared radiation and opaque to visible light. The light-transmissive shaft may be configured to guide the light to the image-sensing element. The head and the light-transmissive shaft may be portions of a monolithic light-transmissive member.

The light-directing feature may include an interface between a first material and a second material, the interface configured to reflect incident light. The first material may be a light-transmissive solid, and the second material may be air. The interface between the first material and the second material may be at least partially defined by an angled surface, and the angled surface may cause the incident light to be reflected towards the image-sensing element.

A wearable electronic device may include a housing, a display positioned at least partially within the housing, a crown at least partially external to the housing and defining an imaging surface along a peripheral portion of the crown,

and an image-sensing element within the housing and configured to receive an image of an object in contact with the imaging surface. The imaging surface may be defined by a semi-transparent mirror coating.

The crown may include a light-transmissive member defining an angled surface configured to direct light from the imaging surface to the image-sensing element. The angled surface may have an angle configured to produce total internal reflection of the light. The wearable electronic device may further include a reflective material applied to the angled surface.

The light-transmissive member may at least partially define a head of the crown and a shaft of the crown. The wearable electronic device may further include a light source at least partially within the housing and configured to illuminate the object.

An electronic watch may include a housing, a display positioned at least partially within the housing, an image sensor at least partially within the housing and comprising an image-sensing element, and a crown. The crown may include a head portion defining an imaging surface external to the housing, a shaft portion extending at least partially into the housing, and a reflective feature directing light from the imaging surface through the shaft portion and towards the image-sensing element. The electronic watch may further include a transparent cover covering the display and a sensor configured to detect touch events applied to the transparent cover.

The reflective feature may include a curved surface configured to magnify an image of an object in contact with the imaging surface. The curved surface may define an interface between the head portion and air.

The crown may further include a cover member coupled to an end of the head portion. The head portion may define a cylindrical peripheral surface, and a peripheral surface of the cover member may be flush with the cylindrical peripheral surface of the head portion.

BRIEF DESCRIPTION OF THE DRAWINGS

The disclosure will be readily understood by the following detailed description in conjunction with the accompanying drawings, wherein like reference numerals designate like structural elements, and in which:

FIGS. 1A-1B depict an example wearable electronic device;

FIGS. 2A-2B depict an example wearable electronic device being used;

FIG. 3 is a partial cross-sectional view of an example wearable electronic device having a crown with a light-directing feature;

FIG. 4A depicts an example wearable electronic device in a state of use;

FIG. 4B depicts an example image-sensing element corresponding to the state of use in FIG. 4A;

FIG. 4C depicts an example wearable electronic device in another state of use;

FIG. 4D depicts an example image-sensing element corresponding to the state of use in FIG. 4C;

FIG. 5A depicts an example wearable electronic device in a state of use;

FIG. 5B depicts an example image-sensing element corresponding to the state of use in FIG. 5A;

FIG. 5C depicts an example wearable electronic device in another state of use;

FIG. 5D depicts an example image-sensing element corresponding to the state of use in FIG. 5C;

3

FIG. 6A is a partial cross-sectional view of an example wearable electronic device having a crown with a light-directing feature;

FIG. 6B depicts an example image-sensing element of the wearable electronic device of FIG. 6A;

FIG. 7 is a partial cross-sectional view of an example wearable electronic device having a crown with a curved light-directing feature;

FIG. 8 is a partial cross-sectional view of an example wearable electronic device having a crown that does not include a shaft;

FIG. 9 is a partial cross-sectional view of an example wearable electronic device having a crown with a cover member;

FIG. 10 is a partial cross-sectional view of an example wearable electronic device having a crown with a light-directing feature and a force sensor;

FIGS. 11A-11B are side views of example wearable electronic devices with crowns having imaging surfaces; and

FIG. 12 depicts example components of a wearable electronic device.

DETAILED DESCRIPTION

Reference will now be made in detail to representative embodiments illustrated in the accompanying drawings. It should be understood that the following description is not intended to limit the embodiments to one preferred embodiment. To the contrary, it is intended to cover alternatives, modifications, and equivalents as can be included within the spirit and scope of the described embodiments as defined by the appended claims.

The embodiments herein are generally directed to a crown of a wearable electronic device, such as an electronic watch (also referred to as a smart watch), and more particularly to a crown that includes an optical sensing system to detect user interactions with the crown. For example, users may interact with a crown by rotating the crown or, in the case of a crown that is rotationally constrained, sliding a finger over a surface of the crown. In order to sense the motion of the user's finger, a crown as described herein may include a window on the part of the crown that the user touches when interacting with the crown. The window may allow an image of the user's finger to be captured by an image sensor that is positioned within the housing. The image sensor, which may include an image-sensing element (e.g., a charge-coupled device (CCD)) in conjunction with associated processors and other components within the electronic watch, may determine how the user's finger has moved and control the operation of the electronic watch accordingly. For example, the watch may determine a speed and a direction of motion of the user's finger (or other suitable parameter), and cause a graphical output that is displayed on the watch's display to move at a speed and along a direction that is indicated by the detected motion.

As used herein, an image may refer to an optical representation of an object, which may be produced, transmitted, or propagated by lenses, mirrors, or the like. An image may be captured and stored, by an image sensor, as a multidimensional array having pixels that represent a small portion of the image formed on the image sensor. The multidimensional array may be stored as a single frame (e.g., a photograph) or a series of frames (e.g., a video). In order to detect motion using the image (e.g., the stored image), the image sensor may analyze multiple frames to determine, for example, a speed and direction of one or more features in the image. The features that are analyzed may include features

4

of a user's skin (e.g., fingerprints, hair follicles), or any other optically detectable feature, texture, surface irregularity, image, or the like, of any object. In this way, the device may be responsive to skin (e.g., the skin of a user's finger or hand), a stylus, a gloved finger, or any other suitable object with optically detectable features. As used herein, analysis of an image by an image sensor and/or other components of an electronic device may refer to an analysis of a stored image (e.g., the stored multidimensional array, which may be a digital photograph or a video).

To facilitate capturing an image of the user's finger (or other implement used to interact with the crown), the crown may include light-transmissive materials and light-directing features that direct light (corresponding to an image of the user's finger) through the crown and onto an image-sensing element of an image sensor. For example, a peripheral surface of the crown (e.g., the cylindrical peripheral surface that a user touches to rotate the crown) may be light-transmissive, and the crown may have a reflecting feature to direct light from the peripheral surface onto the image-sensing element. In one such example, the crown may include a monolithic light-transmissive member that defines both a head portion and a shaft portion of the crown, as well as an angled surface that causes light (e.g., the light corresponding to an image of the user's finger) to be reflected at an approximately 90 degree angle so that the light may be directed through the shaft and into an enclosure of the watch. More particularly, when a user places a finger on the peripheral surface of the head, the light corresponding to an image of the user's finger may be initially directed into the head along a radial direction (relative to the cylindrical peripheral surface of the head). However, an image-sensing element may be within the housing along an axial direction of the head. Accordingly, the head may have an angled surface formed into the material that effectively changes the direction of the light (e.g., reflects or otherwise redirects the light) so that the light is directed along the axis of the crown and into the watch. In this way, the image of the user's finger (or other implement or object) is directed onto an image-sensing element within the watch, allowing the watch to analyze the image and control the operation of the device accordingly.

The optical crown system described herein may be used with both freely rotatable crowns (e.g., crowns that can rotate about an axis an indefinite number of turns) as well as rotationally constrained crowns. As used herein, a "rotationally constrained" crown or component refers to a component that is not free to rotate more than a full revolution under normal use conditions (e.g., when manipulated by the hands of a person). Thus, rotationally constrained components include both rotationally fixed components and partially rotatable components.

In the case of a rotationally constrained crown, if a user attempts to rotate the crown to operate the device, the crown may not physically rotate. Instead, the user's fingers may slide along a surface of the crown while the crown remains stationary. As used herein, a finger or object "sliding" along a surface may refer to the finger (or other object) moving along the surface of the crown while the finger (or other object) is in contact with the surface. In the case of a rotating crown, as the user's finger moves forward to rotate the crown, the part of the user's finger that is touching the crown changes. In either case, as the user's finger moves, the image that is projected or incident on the image-sensing element may include a moving image of the surface of the user's finger. The image sensor may analyze the movement of the image to determine how to manipulate the graphical output

5

or other property of the watch. The image sensor may use features of the user's skin, such as the ridges of the user's skin (or any other texture or optically detectable feature), to determine the speed and direction of motion.

Advantageously, the crown described herein can detect inputs even under conditions when other types of touch sensors may fail. For example, some touch-sensing technologies use capacitive sensors to detect touch events or inputs. The effectiveness of capacitive sensors may be reduced, however, by gloves, clothing, overly wet or dry skin, lotions, or the like. By detecting motion via images, the optical sensing structures described herein may avoid such negative effects and may operate effectively over a broader range of conditions and may sense movement of objects other than bare skin.

FIGS. 1A-1B depict an electronic device **100**. The electronic device **100** is depicted as an electronic watch, though this is merely one example embodiment of an electronic device and the concepts discussed herein may apply equally or by analogy to other electronic devices, including mobile phones (e.g., smartphones), tablet computers, notebook computers, head-mounted displays, digital media players (e.g., mp3 players), or the like.

The electronic device **100** includes a housing **102** and a band **104** coupled to the housing. The band **104** may be configured to attach the electronic device **100** to a user, such as to the user's arm or wrist.

The electronic device **100** also includes a transparent cover **108** coupled to the housing **102**. The cover **108** may define a front face of the electronic device **100**. For example, in some cases, the cover **108** defines substantially the entire front face and/or front surface of the electronic device. The cover **108** may also define an input surface of the device **100**. For example, as described herein, the device **100** may include touch and/or force sensors that detect inputs applied to the cover **108**. The cover **108** may be formed from or include glass, sapphire, a polymer, a dielectric, or any other suitable material.

The cover **108** may cover at least part of a display **109** that is positioned at least partially within the housing **102**. The display **109** may define an output region in which graphical outputs are displayed. Graphical outputs may include graphical user interfaces, user interface elements (e.g., buttons, sliders, etc.), text, lists, photographs, videos, or the like. The display **109** may include a liquid-crystal display (LCD), organic light emitting diode display (OLED), or any other suitable components or display technology.

The display **109** may include or be associated with touch sensors and/or force sensors that extend along the output region of the display and which may use any suitable sensing elements and/or sensing techniques. Using touch sensors, the device **100** may detect touch inputs applied to the cover **108**, including detecting locations of touch inputs, motions of touch inputs (e.g., the speed, direction, or other parameters of a gesture applied to the cover **108**), or the like. Using force sensors, the device **100** may detect amounts or magnitudes of force associated with touch events applied to the cover **108**. The touch and/or force sensors may detect various types of user inputs to control or modify the operation of the device, including taps, swipes, multi-finger inputs, single- or multi-finger touch gestures, presses, and the like. Touch and/or force sensors usable with wearable electronic devices, such as the device **100**, are described herein with respect to FIG. 12.

The electronic device **100** also includes a crown **112** having a head, protruding portion, or component(s) or feature(s) positioned along a side surface of the housing **102**.

6

At least a portion of the crown **112** may protrude from the housing **102**, and may define a generally circular shape or a circular exterior surface. The exterior surface of the crown **112** may be textured, knurled, grooved, or may otherwise have features that may improve the tactile feel of the crown **112** and/or facilitate rotation sensing. The exterior surface of the crown **112** may also have one or more light-transmissive areas, such as a light-transmissive window, that define one or more imaging surfaces. An imaging surface may refer to a surface that allows an image to be captured of an object (e.g., a finger) that is touching that surface. For example, a light-transmissive window may allow an image to be captured, through the window, of a finger that is in contact with the window. Accordingly, the light-transmissive window may define an imaging surface.

The imaging surface or surfaces may enable the device **100** to capture an image of the user's finger while the finger is interacting with the crown **112** (e.g., in order to determine input parameters such as a speed and direction of an input, as described herein). The light-transmissive areas may be transparent to some wavelengths of light and substantially opaque to others. For example, if the device **100** uses infrared imaging to capture an image of the user's finger, the light-transmissive areas may be transparent to infrared wavelengths while being opaque to visible light.

The crown **112** may afford a variety of potential user interactions. For example, the crown **112** may be rotationally constrained (e.g., rotationally fixed or partially rotatable), and may include or be associated with sensors that detect when a user slides one or more fingers along a surface of the crown **112** in a movement that resembles rotating the crown **112** (or that would result in rotation of a freely rotating crown). More particularly, where the crown **112** is rotationally fixed or rotationally constrained, a user input that resembles a twisting or rotating motion may not actually result in any substantial physical rotation that can be detected for the purposes of registering an input. Rather, the user's fingers (or other object) will move in a manner that resembles twisting, turning, or rotating, but does not actually continuously rotate the crown **112**. As another example gesture that may be detected, a user attempting to rotate a rotationally fixed crown by applying a substantially tangential force to a surface of the crown **112** (as shown in FIGS. 2A-2B, for example) may also result in a sliding gesture along a surface of the crown **112**. Thus, in the case of a rotationally fixed or constrained crown **112**, an image sensor within the device **100** may detect inputs that result from a gesture that has the same motion as (and thus may feel and look the same as or similar to) rotating a rotatable crown.

In some cases, the crown **112** may be rotationally free or may include a rotationally free member that is free to rotate relative to the housing **102**. More particularly, the rotationally free member may have no rotational constraints, and thus may be capable of being rotated indefinitely (or a sufficiently large number of turns that a user does not typically reach a hard-stop under normal use conditions). Even where the crown **112** or a portion thereof can rotate, the crown **112** may be configured so that light reflected from the user's finger is directed from an imaging surface of the crown **112** onto an image-sensing element within the housing **102**.

Thus, both rotationally constrained and rotationally free crowns may detect gestures resembling a twisting, turning, or rotating motion, regardless of whether the crown rotates or not. As used herein, a twisting, turning, or rotating motion

applied to a crown may be referred to as a gesture input or a rotational input (even if the crown itself does not physically rotate).

In cases where the crown **112**, or a member or component of the crown **112**, is capable of some rotation, it may rotate about a rotation axis (e.g., it may rotate as indicated by arrow **103** in FIG. 1A). The crown **112**, or a member or component of the crown **112**, may also be translatable relative to the housing **102** to accept axial inputs. For example, the crown **112** may be movable or translatable along the rotation axis, towards and/or away from the housing **102** (as indicated by arrow **105** in FIG. 1A). The crown **112** may therefore be manipulated by pushing and/or pulling on the crown **112**.

The crown **112** may be able to translate any suitable distance. For example, a crown **112** may include a dome switch to register axial inputs, and the crown **112** may move a sufficient distance to facilitate physical actuation of the dome switch. In other cases, such as where a force sensor is used to detect axial inputs, the crown **112** may move a sufficient distance to facilitate force sensing. The distance that the crown **112** can translate or move may be any suitable distance, such as about 1 mm, 0.5 mm, 0.2 mm, 0.1 mm, 0.05 mm or any other suitable distance.

Alternatively, the crown **112** may be fixed or otherwise substantially non-translatable. In such cases, axial inputs applied to the crown **112** may be detected in other ways. For example, the crown **112** may include or be part of a contact sensor (described more fully below), such as a capacitive or resistive touch sensor, that determines when and optionally where a user's finger is in contact with the crown **112**. The crown **112** may also use an optical sensing scheme to detect axial inputs. For example, as noted above, the crown **112** or a portion of the crown may be light-transmissive to allow light (corresponding to an image of the user's finger) to be directed from a peripheral surface of a head onto an image-sensing element. To facilitate axial input sensing, the crown **112** may also define an optical path from an end **113** of the crown **112** to an image-sensing element so that the image sensor can determine when a user's finger (or other object) is in contact with the end **113** of the crown **112**.

The device **100** may include a force sensor to detect axial forces that are applied to the crown **112**. The force sensor may include or use any suitable force sensing components and may use any suitable technique for sensing force inputs. For example, a force sensor may include a strain sensor, capacitive gap sensor, or other force sensitive structure that is configured to produce an electrical response that corresponds to an amount of force (e.g., axial force) applied to the crown **112**. The electrical response may increase continuously as the amount of applied force increases, and as such may provide non-binary force sensing. Accordingly, the force sensor may determine, based on the electrical response of the force sensing components, one or more properties of the applied force associated with a touch input (e.g., a magnitude of the applied axial force).

As described herein, gesture inputs (e.g., rotational-style inputs applied to a rotationally free or rotationally constrained crown) and axial inputs (e.g., translations or axial forces) may control various operations and user interfaces of the electronic device **100**. In particular, inputs to the crown **112** may modify the graphical output of the display **109**. For example, a rotational movement of the crown **112** or a gesture applied to the crown **112** may zoom, scroll, or rotate a user interface or other object displayed on the display **109** (among other possible functions), while translational movements or axial inputs may select highlighted objects or icons,

cause a user interface to return to a previous menu or display, or activate or deactivate functions (among other possible functions).

The crown **112** may also be associated with or include a contact sensor that is configured to detect contact between a user and the crown **112** (e.g., touch inputs or touch events applied to the crown **112**). The contact sensor may detect even non-moving contacts between the user and the crown **112** (e.g., when the user touches the crown **112** but does not rotate the crown or apply a sliding gesture to the crown **112**). Contact sensing functionality may be provided by the same optical sensing system that also detects gestures (e.g., a finger sliding along a surface of a crown or the housing), or it may be provided by a separate sensor. The contact sensor may include or use any suitable type of sensor(s), including capacitive sensors, resistive sensors, magnetic sensors, inductive sensors, optical sensors, or the like. In some cases, the crown **112** itself, or components of the crown, may be conductive and may define a conductive path between the user (e.g., the user's finger) and a contact sensor. For example, the crown may be formed from or include metal, and may itself act as an electrode for conductively coupling a capacitive sensor to the user.

The device **100** may also include one or more haptic actuators that are configured to produce a tactile output through the crown **112**. For example, the haptic actuator may be coupled to the crown **112** and may be configured to impart a force to the crown **112**. The force may cause the crown **112** to move (e.g., to oscillate or vibrate translationally and/or rotationally, or to otherwise move to produce a tactile output), which may be detectable by a user when the user is contacting the crown **112**. The haptic actuator may produce tactile output by moving the crown **112** in any suitable way. For example, the crown **112** (or a component thereof) may be rotated (e.g., rotated in a single direction, rotationally oscillated, or the like), translated (e.g., moved along a single axis), or pivoted (e.g., rocked about a pivot point). In other cases, the haptic actuator may produce tactile outputs using other techniques, such as by imparting a force to the housing **102** (e.g., to produce an oscillation, vibration, impulse, or other motion), which may be perceptible to a user through the crown **112** and/or through other surfaces of the device **100**, such as the cover **108**, the housing **102**, or the like. Any suitable type of haptic actuator and/or technique for producing tactile output may be used to produce these or other types of tactile outputs, including electrostatics, piezoelectric actuators, oscillating or rotating masses, ultrasonic actuators, reluctance force actuators, voice coil motors, Lorentz force actuators, or the like. In some cases, haptic outputs may be produced by collapsible domes, springs, or other mechanical components.

Tactile outputs may be used for various purposes. For example, tactile outputs may be produced when a user presses the crown **112** (e.g., applies an axial force to the crown **112**) to indicate that the device **100** has registered the press as an input to the device **100**. As another example, tactile outputs may be used to provide feedback when the device **100** detects a rotation of the crown **112** or a gesture being applied to the crown **112**. For example, a tactile output may produce a repetitive "click" sensation as the user rotates the crown **112** or applies a gesture to the crown **112**. Tactile outputs may be used for other purposes as well.

The electronic device **100** may also include other inputs, switches, buttons, or the like. For example, the electronic device **100** includes a button **110**. The button **110** may be a movable button (as depicted) or a touch-sensitive region of the housing **102**. The button **110** may control various aspects

of the electronic device **100**. For example, the button **110** may be used to select icons, items, or other objects displayed on the display **109**, to activate or deactivate functions (e.g., to silence an alarm or alert), or the like.

FIGS. **2A-2B** show a front and side view, respectively, of a device **200** during one example use condition. The device **200** may be an embodiment of the device **100**, and may include the same or similar components and may provide the same or similar functions as the device **100**. Accordingly, details of the device **100** described above may apply to the device **200**, and for brevity will not be repeated here.

In the example shown in FIGS. **2A-2B**, the wearable device **200** includes a crown **212** that a user may contact to provide input through the crown **212**. The crown **212** may define an imaging surface **216** that is positioned in a location where a user is likely to touch the crown **212** when interacting with and/or providing input to the crown **212**. In some cases, the imaging surface **216** may extend around the entire peripheral portion or surface of the crown **212**. Thus, the crown **212** and an associated image sensor may detect inputs applied to any part of the periphery of the crown **212**. In other cases, the imaging surface **216** may extend along less than the entire periphery of the crown **212**.

The imaging surface **216**, which may be defined by a light-transmissive portion of the crown **212**, may in optical communication with an image-sensing element within the device **200** to facilitate the image sensor capturing and analyzing an image of whatever object is in contact with the imaging surface **216** (e.g., a bare finger, a gloved finger). For example, the crown **212** may include a light-directing feature, such as an angled surface that changes the direction of the light that corresponds to an image of the object so that it is incident on the image-sensing element. In some cases, the crown **212** includes a monolithic light-transmissive member that defines the imaging surface **216**, a shaft of the crown **212**, as well as a light-directing feature to redirect light down the shaft of the crown and towards the image-sensing element.

FIGS. **2A-2B** show a user interacting with the crown **212** to provide an input to the device **200**. In the case of a rotationally constrained crown, the crown will not continuously rotate in response to the force applied by the finger **201** moving along the direction indicated by arrow **217** (while the finger is in contact with the crown **212**). Rather, the finger **201** will slide along a surface of the crown **212**. In the case of a rotationally free crown, the force applied to the crown **212** by the user's finger **201** causes the crown **212** (or a head or other component of the crown **212**) to rotate relative to the housing **202**. In either case, an image of the user's finger **201** is projected or otherwise incident on the image-sensing element within the device **200**, and the image sensor detects the movement of the finger **201** sliding along the imaging surface **216** and causes the device **200** to take an action in response to the rotation. For example, as shown in FIG. **2A**, upon detection of the motion of the finger **201**, the device **200** may cause a graphical output **207** on a display **209** to move in accordance with the movement of the finger **201**. A movement of the finger **201** in the direction indicated by arrow **217** may result in the graphical output **207** moving in the direction indicated by arrow **215**. A movement of the finger **201** in the opposite direction may result in the graphical output **207** moving in the opposite direction. Rotating the crown **212** or sliding a finger along a surface of the crown **212** may change other operational properties of the device **200** in addition to or instead of scrolling a graphical output **207**. For example, sliding a finger along the surface of the crown **212** may change

parameters or settings of the device, control a zoom level of a graphical output, rotate a displayed graphical output, translate a displayed graphical output, change a brightness level of a graphical output, change a time setting, scroll a list of displayed items (e.g., numbers, letters, words, images, icons, or other graphical output), or the like.

In some cases, the graphical output **207** may also be responsive to inputs applied to a touch-sensitive display **208**. The touch-sensitive display **208** may include or be associated with one or more touch and/or force sensors that extend along an output region of a display and which may use any suitable sensing elements and/or sensing techniques to detect touch and/or force inputs applied to the touch-sensitive display **208**. The same or similar graphical output **207** manipulations that are produced in response to inputs applied to the crown **212** may also be produced in response to inputs applied to the touch-sensitive display **208**. For example, a swipe gesture applied to the touch-sensitive display **208** may cause the graphical output **207** to move along the direction indicated by the arrow **215** (FIG. **2A**). As another example, a tap gesture applied to the touch-sensitive display **208** may cause an affordance to be selected or activated. In this way, a user may have multiple different ways to interact with and control an electronic watch, and in particular the graphical output **207** of an electronic watch. Further, while the crown **212** may provide overlapping functionality with the touch-sensitive display **208**, using the crown allows for the graphical output of the display to be visible (without being blocked by the finger that is providing the touch input).

FIG. **3** is a partial cross section of an electronic device **400**, corresponding to a view along line A-A in FIG. **1B**. The device **300** may be an embodiment of the device **100**, and may include the same or similar components and may provide the same or similar functions as the device **100** (or any other wearable device described herein). Accordingly, details of the wearable device **100** described above may apply to the device **300**, and for brevity will not be repeated here.

The device **300** includes a crown **312** positioned along a side of a housing **302**. The crown **312** may include a head portion or head **313** and a shaft portion or shaft **315**. The head **313** and the shaft **315** may be a single monolithic component, as shown, or they may be separate components joined together (e.g., via adhesive, a threaded interface, fasteners, clips, rivets, fusion bonding, or the like). Where the head **313** and shaft **315** are separate components, index matching fluid or material may be used to occupy voids or gaps between the head **313** and shaft **315** (or between any other components of a crown **312**).

The head **313** and the shaft **315** may be formed of or include a light-transmissive material, which may define an imaging surface **316**. For example, head **313** and/or the shaft **315** may be formed from a light-transmissive solid such as an acrylic, glass, transparent ceramic, sapphire, polycarbonate, quartz, or another suitable material. The solid light-transmissive material may be optically transparent (e.g., clear and uncolored), or it may be transparent some wavelengths of light and opaque (or substantially opaque) to others. For example, if the device uses infrared imaging to capture an image of the user's finger, the light-transmissive areas may be transparent to infrared wavelengths while being opaque to visible light. In some cases, the light-transmissive material of the crown **312** may be coated or otherwise treated so that it is visually opaque. For example, a semi-transparent mirror coating may be applied to an otherwise transparent or light-transmissive material. This

11

may allow the crown **312** to appear, to the wearer, to be opaque and/or metallic, while still allowing light reflected by the portion of the user's finger **301** that is in contact with the crown **312** to enter the crown **312** through the imaging surface **316**. As another example, a visibly opaque but infrared-transparent paint, film, ink, or other coating or material may be applied to the crown **312** (and in particular the imaging surface **316**) to provide a visually opaque appearance while still facilitating optical imaging of the user's finger **301**. As used herein, light-transmissive may be used to refer to something that is transparent or otherwise allows light and/or images to propagate therethrough. In some cases, transparent or light-transmissive materials or components may introduce some diffusion, lensing effects, filtering effects (e.g., color filtering), distortions, attenuation, or the like (e.g., due to surface textures) while still allowing objects or images to be seen or transmitted through the materials or components, and such deviations are understood to be within the scope of the meaning of transparent or light-transmissive. Moreover, components such as a crown, shaft, or head that are formed of or include light-transmissive materials and that function as described herein may be referred to as, for example, a light-transmissive crown, a light-transmissive shaft, and a light-transmissive head.

The device **300** also includes an image-sensing element **324** within the housing **302** and positioned adjacent an end of the shaft **315**. An image of the user's finger **301** may be directed onto the image-sensing element **324** so that the image can be captured and analyzed to determine input parameters of an input gesture applied to the crown **312**. The image-sensing element **324** may be positioned on a support **322** as shown in FIG. 3, though other mounting and/or support structures are also contemplated.

The image-sensing element **324** is one example of an optical sensing element that may be used. In particular, the image-sensing element **324** may be an optical sensing element with multiple pixels or other sensing regions that capture individual portions of an image, and allow the image sensor (or other optical sensor) to detect and/or store photographs, videos, and the like. In other cases, however, one or more other optical sensing elements may be used, such as photodiodes, single-pixel sensors, photovoltaic cells, or the like. In such cases, the optical sensing element(s) may detect changes in light caused by the presence and/or motion of an object relative to the imaging surface **316** of the crown **312**, and may cause the device **300** to take actions based on the detected inputs (including but not limited to controlling any user interface animations or other device functions described herein).

As noted above, the imaging surface **316** is not directly in line with the image-sensing element **324**. Accordingly, the crown **312** may include a light-directing feature **326** that directs light corresponding to the image of the user's finger from the imaging surface onto the image-sensing element **324**. As shown in FIG. 3, the light-directing feature **326** includes an angled surface of the light-transmissive material of the crown **312**. The angled surface defines an interface between materials having different optical indices (e.g., the light-transmissive material and a different material, such as air). When the light corresponding to an image of the user's finger **301** is incident on the interface defined by the angled surface (as represented by arrow **319**), all or part of the light may be reflected at an angle (e.g., a 90 degree angle) towards the image-sensing element **324**. For example, the angled surface may direct the light (e.g., by causing the light to be reflected) through the shaft **315** of the crown, which may

12

also be light-transmissive. Thus, the shaft **315** guides the reflected light towards the image-sensing element **324** (as indicated by arrow **321**). In cases where the light-directing feature **326** reflects light towards the image-sensing element **324**, it may be referred to as a reflective feature.

The particular angle of the angled surface may be selected based on various factors, such as the optical properties of the light-transmissive material, the position of the image-sensing element **324** relative to the imaging surface **316**, the degree of reflectance desired, and the like. In some cases, the angle of the angled surface has an angle configured to produce total internal reflection of the light. For example, the angled surface may be configured so that the angle of incidence **327** of the light from the object on the imaging surface **316** is equal to or greater than the critical angle for the crown/air interface defined by the angled surface. This configuration may produce total internal reflection of the incident light. More particularly, all of the light reflected by the user's finger **301** towards the light-directing feature **326** may be reflected by the crown/air interface defined by the angled surface.

The angle and/or shape of the light-directing feature **326** that results in total internal reflection may depend, for example, on the geometry and material(s) of the crown **312**, the relative angles of the imaging surface **316** and the axis of the shaft **315**, and the material that is in contact with the angled surface (air, as shown in FIG. 3). In the case where the crown **312**, or the optically operative portions of the crown **312**, is acrylic, the critical angle may be about 41 degrees. Accordingly, the light-directing feature **326** may be configured so that the angle of incidence **327** is equal to or greater than about 41 degrees (e.g., about 41 degrees, about 45 degrees, about 50 degrees). In some cases, the angle of incidence on the light-directing feature **326** may be less than the critical angle, in which case some of the light that forms the image may be transmitted through the angled surface, rather than being reflected along the shaft **315**. This may be acceptable, as it may not be necessary to achieve total internal reflection. In particular, the light that is reflected by the light-directing feature **326** and incident on the image-sensing element **324** (even though it is less than all of the light being reflected by the user's finger) may be sufficient to allow the image sensor to analyze the image and ultimately detect the input.

In some cases, the exterior surface of the light-directing feature **326** includes a coating, film, or other material or treatment that increases the reflectivity of the imaging directing feature. For example, a mirror coating (or other reflective material) may be applied to the exterior surface of the light-directing feature **326**. In such cases, it may not be necessary for the angle of incidence to be at or greater than a critical angle, as the mirror coating may ensure that all or substantially all of the light forming the image is reflected along the shaft or otherwise towards an image-sensing element.

As described herein, the imaging surface **316** of the crown **312** may extend around the entire periphery of the head **313**. In such cases, the light-directing feature **326** may have a generally circular configuration so that the light-directing feature **326** directs the light corresponding to the image of the user's finger (or other object or implement) towards the image-sensing element **324** no matter where the finger contacts the periphery of the head **313**. For example, the light-directing feature **326** may resemble a conical recess in the end of the head **313**. Arrows **323** and **325** in FIG. 3 show an example light path for an object in contact with a bottom portion of the head **313**. Due to the radial symmetry of the

13

head **313** and the light-directing feature **326**, these arrows may be generally representative of a light path for an object in contact with any portion of the peripheral surface of the head **313**. In cases where the imaging surface **316** does not extend around the entire periphery of the head **313**, the light-directing feature **326** need not be circular, though it may still have the circular configuration.

Where the imaging surface **316** extends around the entire periphery of the head **313**, an image of a user's wrist (which may be proximate to the bottom portion of the peripheral surface of the head **313**) may be directed onto the image-sensing element **324** when the device is being worn. To avoid the image of the user's wrist causing false inputs to the device, the image sensor may ignore images received via the bottom surface of the head **313** under certain conditions. For example, if the only received or detected image is received via the bottom surface of the head **313**, the device **300** may ignore the image, as users are unlikely to turn the crown **312** by touching only the bottom surface (e.g., in the small area between the crown and the wearer's wrist). As another example, skin patterns or characteristics may differ between a wrist and a finger, and the device **300** may ignore any image that does not contain characteristics of the skin of a finger.

In order to illuminate the finger **301** while it is in contact with the imaging surface **316**, the device **300** may include a light source **330** within the housing **302**. The light source **330** may direct light through the shaft **315** towards the light-directing feature **326**, which in turn directs the light towards the imaging surface **316**, thereby illuminating the user's finger and allowing the image-sensing element **324** to capture an image of the user's finger **301**. The light source **330** may be configured to emit light of any suitable wavelength(s), based on the particular type of light and/or electromagnetic radiation that the image-sensing element **324** is configured to detect. For example, the light source **330** may emit infrared radiation. The light source **330** (or any other suitable light source) may be integrated with any of the crowns or devices described herein.

In some cases, the device **300** uses dark field illumination components and techniques for illuminating and imaging an object that is in contact with the imaging surface **316**. Such components may be integrated with the crown **312** or otherwise positioned within the crown **312** or the housing **302** as appropriate to provide suitable illumination and optical detection via the crown **312**.

As noted above, the crown **312** may be rotationally constrained or rotationally free, and may also be axially fixed, or it may be translatable along its axis to accept axial inputs. The crown **312** may also be coupled to or otherwise integrated with the housing **302** in any suitable way. For example, the shaft **315** may extend into the housing **302** through an opening **317**. A sealing member **320**, such as an elastomeric member or other material or component(s), may form a seal between the shaft **315** and the housing **302** to prevent ingress of liquids, debris, or other contaminants. The sealing member **320** may seal the opening **317** while also allowing the crown **312** to move relative to the housing **302**, if the crown **312** is configured to rotate and/or translate. In cases where the shaft **315** is rotationally constrained (e.g., rotationally fixed or partially rotatable), it may still be able to translate axially. As such, the sealing member **320** may seal the opening while allowing the shaft **315** to move axially within the opening **317**. In other cases, the shaft **315** may be fixed to the housing **302**, such as with adhesive, welds, fusion bonds, or the like. In such cases the sealing member **320** may be omitted.

14

As described with respect to FIG. 3, the crown **312** may be configured to redirect the light corresponding to an image of a user's finger from an imaging surface onto an image-sensing element that is offset or otherwise not in line with the imaging surface. FIGS. 4A-4D illustrate how the image of the wearer's finger may appear on an image-sensing element and how motion of the user's finger along an imaging surface may be detected by an image sensor.

FIG. 4A shows an example electronic device **400** receiving an input from a finger **401**. The device **400** may be an embodiment of the device **100**, and may include the same or similar components and may provide the same or similar functions as the device **100** (or any other wearable device described herein). Accordingly, details of the wearable device **100** described above may apply to the device **400**, and for brevity will not be repeated here. The device **400** may include a crown **412** (which may be an embodiment of the crown **312** or any other crown described herein). As shown in FIG. 4A, which is a side view of the device **400**, a portion **419** of the finger **401** is in contact with an imaging surface **416** of the crown **412**. FIG. 4B shows an example image-sensing element **424** (which may be an embodiment of the image-sensing element **324**, FIG. 3) with an image **426** of the portion **419** of the finger **401**. The image **426** (or light that corresponds to the image) may be directed onto the image-sensing element **424** by the crown **412** along a path as indicated by the arrows **319**, **321** in FIG. 3. As shown in FIGS. 4B and 4D (and elsewhere in the figures), the image-sensing element **424** is a square, though any other suitable shape may be used, including circular, rectangular, oval, or the like.

In the configuration shown in FIGS. 4A-4D, the crown **412** may have an imaging surface that extends around the entire periphery of the crown **412**. Accordingly, the image **426** is shown positioned along a top portion of the image-sensing element **424**, resulting from the fact that the user's finger **401** is in contact with a top-facing surface of the crown **412**. Were the user's finger **401** to be in contact with a bottom surface of the crown **412**, for example, the image may be incident on a bottom portion of the image-sensing element **424**.

FIGS. 4C and 4D show the electronic device **400** and image-sensing element **424**, respectively, after the finger **401** has moved forward (e.g., in the direction of arrow **417**). Notably, the portion **421** of the user's finger **401** that is in contact with the imaging surface **416** has changed, though the area of the image-sensing element **424** that receives the image **426** has not changed. However, because the user's finger **401** has moved, the features of the user's finger that are visible to the image-sensing element **424** (e.g., the ridges or other features of the skin of the finger **401**) have moved. For example, feature **430**, which may correspond to a ridge of a fingerprint, a texture of a fabric material of a glove, or the like, has moved along the image-sensing element **424**. A processor or other component of an image sensor may analyze the image **426** and use features such as the feature **430** to determine a speed and/or direction of motion of the user's finger, and the device **400** may use that information to change or control an operation of the device **400** (e.g., to move or scroll a graphical output on a display).

While FIGS. 4A-4D show a bare finger and a fingerprint, any other object or implement may be used in place of a bare finger. For example, if a gloved finger is used to provide a gesture input to the crown **412**, the image sensor may use a feature of the material of the glove to determine a speed and/or direction of motion. Indeed, the image sensor may

15

determine motion of any suitable object by analyzing a texture, surface irregularity, or some other optically detectable feature of the object.

A crown, and more particularly, a head of a crown, may also be shaped or configured to act as a lens to aid in the image sensing functionality of a device. FIGS. 5A-5D illustrate how a lensing feature on a crown may enable a device to reject or otherwise ignore images that do not correspond to a finger in contact with the crown. For example, a lensing feature may be configured so that only objects in direct contact with the crown are in sharp focus.

FIG. 5A, shows an example electronic device 500 receiving an input from a finger 501. The device 500 may be an embodiment of the device 100, and may include the same or similar components and may provide the same or similar functions as the device 100 (or any other wearable device described herein). Accordingly, details of the wearable device 100 described above may apply to the device 500, and for brevity will not be repeated here. The device 500 may include a crown 512 (which may be an embodiment of the crown 312 or any other crown described herein). As shown in FIG. 5A, which is a side view of the device 500, a portion of the finger 501 is in contact with an imaging surface 516 of the crown 512. FIG. 5B shows an example image-sensing element 524 (which may be an embodiment of the image-sensing element 324, FIG. 3) with an image 526 of the finger 501. Under these conditions, the image 526 is in focus so that the features of the user's finger 501 are clearly defined and the image sensor can easily analyze the motion (if any) of the finger 501.

FIG. 5C shows the electronic device 500 with the finger 501 elevated a distance off of the imaging surface 516 (e.g., moved in a direction indicated by the arrow 517). The crown 512 may have a shape or feature that acts as a lens so that objects that are not in direct contact with (or within a threshold distance of) the crown 512 are out of focus. The threshold distance may be about 0.1 mm, 0.5 mm, 1.0 mm, 2.0 mm, or any other suitable distance. FIG. 5D shows a representation of an out-of-focus image 526. The image sensor may be able to ignore the motion of images that are not in focus, thereby preventing images from the surrounding environment from triggering inputs to the device. In some cases, instead of or in addition to a lensing feature, the device 500 may use a contact sensor to determine when an object is in contact with the crown 512, and ignore image motion when there is nothing contacting the crown 512.

As noted above, in some cases an optical crown as described herein may be configured to detect axial inputs, such as a tap or press on an end surface of the crown. FIG. 6A illustrates an example electronic device 600 with an optical crown that incorporates both optical gesture sensing (as described above), as well as axial touch sensing.

The device 600 may be an embodiment of the device 100, and may include the same or similar components and may provide the same or similar functions as the device 100 (or any other wearable device described herein). Accordingly, details of the wearable device 100 described above may apply to the device 600, and for brevity will not be repeated here. The device 600 may include a crown 612 (which may be an embodiment of the crown 312 or any other crown described herein). The crown 612 may include a head 613 and a shaft 615. The crown 612 may include a light-directing feature 626, which operates substantially the same as the light-directing feature 626, and directs an image from an imaging surface 616 towards an image-sensing element 624. The device may include a sealing member 620 between the

16

shaft 615 and a housing 602, and the image-sensing element 624 may be positioned on a support 622.

The crown 612 also includes an axial imaging surface 628. The axial imaging surface 628 may be configured to allow light corresponding to an image of an object in contact with an end surface of the crown 612 to pass through the shaft 615 and onto the image-sensing element 624. The image sensor may be configured to determine, based on the image received on the image-sensing element 624, whether a user's finger (or other object) is in contact with the end surface of the head 613. In some cases, the axial imaging surface 628 may have a curvature or lensing feature that operates similar to that described with respect to FIGS. 5A-5D, so that only a finger or object that is actually in contact with the end surface of the head 613 cause the image sensor to positively identify an axial touch input.

FIG. 6B shows a representation of the image-sensing element 624, showing example images 632, 634 corresponding to a gesture applied to a peripheral surface of the crown (image 632), and an axial touch input (image 634). As shown, the image 634 is positioned on a center of the image-sensing element 624. Accordingly, the image sensor may be configured to analyze the center of the image-sensing element 624 to determine when an axial touch input has been applied (e.g., by detecting an in-focus image of a user's finger), and to analyze the peripheral portion of the image-sensing element 624 to detect a gesture input applied to the peripheral surface of the crown 612. The device 600 may take any suitable action in response to detecting an axial touch input, such as turning on or off the device (or a display of the device), selecting a user interface element being displayed on the display, activating or deactivating a device function, or the like.

In some cases, a light-directing feature may define a curved surface that not only directs light from an imaging surface onto an image-sensing element, but also adjusts, focuses, or otherwise modifies the image. FIG. 7 illustrates an example electronic device 700 with an optical crown having a light-directing feature with a curved surface to both redirect the light and modify the image of the user's finger.

The device 700 may be an embodiment of the device 100, and may include the same or similar components and may provide the same or similar functions as the device 100 (or any other wearable device described herein). Accordingly, details of the wearable device 100 described above may apply to the device 700, and for brevity will not be repeated here. The device 700 may include a crown 712 (which may be an embodiment of the crown 312 or any other crown described herein). The crown 712 may include a head 713 and a shaft 715. The crown 712 may include a light-directing feature 726 that directs light from an imaging surface 716 (e.g., reflected by a user's finger) to an image-sensing element 724, as described above. The device 700 may include a sealing member 720 between the shaft 715 and a housing 702, and the image-sensing element 724 may be positioned on a support 722.

The light-directing feature 726 includes a curved surface 728. The curved surface 728 may be configured so that an angle of incidence of the light from an object (e.g., a user's finger) is equal to or greater than a critical angle of the interface defined by the curved surface 728, thus producing total internal reflection of the light. Further, the curved surface 728 may be configured to magnify the image so that the image occupies a greater area of the image-sensing element 724. FIG. 7 illustrates the magnification of the image by showing the rays 730, 732, 734, and 736 diverging through the shaft 715.

17

As shown, the curved surface **728** is concave (e.g., as viewed from the exterior of the crown **712**), though the curved surface **728** may have other configurations and/or shapes, such as convex shapes, aspherical shapes, combination concave and convex shapes (e.g., having concave and convex regions), or the like. In some cases, the surface is not only curved, but has flat regions, stepped regions, or other complex geometries.

The crown **712** shown in FIG. 7 has an imaging surface along the entire periphery of the head **713**, and as such the curved surface **728** may be configured so that a magnified image does not extend past a midpoint of the image-sensing element **724**. In examples where the imaging surface extends along less than the entire periphery, the image may be magnified to a greater extent. Thus, for example, a finger applied to the top portion of the head **713** may result in an image that occupies the entire image-sensing element **724** (rather than less than half of the image-sensing element, which may occur with a full-periphery imaging surface).

The crowns shown in FIGS. 3-7 each have a shaft extending through an opening in a housing. In some cases, the shaft may be omitted, or the crown may otherwise have a different configuration and/or integration with the housing. FIG. 8 illustrates an example electronic device **800** with an optical crown **812** without a shaft. This configuration may have advantages such as easier or faster manufacturing, better environmental sealing, or the like.

The device **800** may be an embodiment of the device **100**, and may include the same or similar components and may provide the same or similar functions as the device **100** (or any other wearable device described herein). Accordingly, details of the wearable device **100** described above may apply to the device **800**, and for brevity will not be repeated here. The device **800** may include a crown **812** (which may be an embodiment of the crown **312** or any other crown described herein). The crown **812** may include a head **813**. The crown **812** may include a light-directing feature **826** that directs light from an imaging surface **816** to an image-sensing element **824**, as described above.

Instead of an internally mounted image-sensing element, the crown **812** includes an image-sensing element **824** mounted on or otherwise incorporated with the head **813**. For example, the image-sensing element **824** may be adhered to, encapsulated within, or mechanically fastened to the head **813**. In some cases, the image-sensing element **824** may be set into a recess in the head **813**. The light-directing feature **826** may still be configured to direct light from the imaging surface **816** onto the image-sensing element **824**, though the image will not need to pass through a shaft.

Conductors **821** (e.g., wires, a flex connector, a conductive trace, or another conductive component) may be coupled to the image-sensing element **824** and may extend through an opening **817** in the housing **802**, where they connect to a processor **820** or other component of an image sensor that analyzes the images received and/or detected by the image-sensing element **824**.

In the device **800**, both the head **813** and the image-sensing element **824** are positioned outside of the interior volume of the device housing **802**. This may simplify manufacture of the device **800**. For example, because there is no shaft, the need for precise optical alignment between the shaft and the image-sensing element may be eliminated. Moreover, the mating of the head **813** to the housing **802**, as well as the smaller opening **817** that need only accommodate the conductors **821** (rather than a crown shaft), may allow for better sealing against liquid or other debris.

18

The head **813** may be attached to the housing **802** using adhesive, welding, mechanical fasteners, or the like. Where the head **813** is configured to rotate and/or translate relative to the housing **802**, the head **813** may be attached to the housing **802** with bearings, bushings, guides, or other suitable components.

FIG. 9 illustrates an example electronic device **900** with an optical crown **912** with a cover member over an end surface of the crown. The device **900** may be an embodiment of the device **100**, and may include the same or similar components and may provide the same or similar functions as the device **100** (or any other wearable device described herein). Accordingly, details of the wearable device **100** described above may apply to the device **900**, and for brevity will not be repeated here. The device **900** may include a crown **912** (which may be an embodiment of the crown **312** or any other crown described herein). The crown **912** may include a head **913** and a shaft **915**. The crown **912** may include a light-directing feature **926** that directs light from an imaging surface **916** to an image-sensing element **924**, as described above. The device **900** may include a sealing member **920** between the shaft **915** and a housing **902**, and the image-sensing element **924** may be positioned on a support **922**.

In FIG. 9, the crown **912** also includes a cover member **928** attached to the end of the head **913**. The cover member **928**, which may also resemble and/or be referred to as a cap, may cover and protect the light-directing feature **926**, and may provide a cosmetic exterior surface to the crown **912**. The cover member **928** may be formed of any suitable material, such as plastic, sapphire, metal, gemstones, ceramic, or the like. In cases where the crown **912** includes an axial touch sensing system, as described above, the cover member **928** or a portion thereof may be light-transmissive to allow the axial touch sensing system to operate. The cover member **928** may be attached to the crown **912** in any suitable manner, including welding, adhesives, mechanical fasteners and/or interlocks, soldering, brazing, or the like. The cover member **928**, and more particularly a peripheral surface of the cover member **928**, may be substantially flush with the cylindrical peripheral surface of the head **913**.

FIG. 10 illustrates an example electronic device **1000** with an optical crown **1012**. The device **1000** may be an embodiment of the device **100**, and may include the same or similar components and may provide the same or similar functions as the device **100** (or any other wearable device described herein). Accordingly, details of the wearable device **100** described above may apply to the device **1000**, and for brevity will not be repeated here. The device **1000** may include a crown **1012** (which may be an embodiment of the crown **312** or any other crown described herein). The crown **1012** may include a head **1013** and a shaft **1015**. The crown **1012** may include a light-directing feature **1026** that directs light from an imaging surface **1016** to an image-sensing element **1024**, as described above. The device **1000** may include a sealing member **1020** between the shaft **1015** and a housing **1002**, and the image-sensing element **1024** may be positioned on a support **1022**.

The device **1000** also includes a force sensing component **1028**. The force sensing component **1028** may be configured to detect axial and/or translational inputs applied to the crown **1012**, as described above. As shown, the force sensing component **1028** is a dome switch, which may provide both an input detection and a tactile output function. For example, when an axial force exceeding a collapse threshold of the dome switch is applied to the crown **1012**, the dome switch may abruptly collapse, which both closes

19

an electrical contact (thereby allowing the device to register the input), and produces a tactile “click” or other tactile output that may be felt by the user. In other cases, the force sensing component **1028** may be a force sensor that is configured to produce an electrical response that corresponds to an amount of force (e.g., axial force) applied to the crown **1012**. The electrical response may increase continuously as the amount of applied force increases, and as such may provide non-binary force sensing.

As described above, an imaging surface may be defined along an entire peripheral surface of a crown, or along only a portion of a peripheral surface. FIGS. **11A** and **11B** illustrate example crowns in which the imaging surface extends along less than the entire peripheral surface. FIG. **11A**, for example, shows an example device **1100** (which may be an embodiment of the device **100**, and may include the same or similar components and may provide the same or similar functions as the device **100**) with a crown **1102**. An imaging surface **1104** may extend along less than the entire peripheral surface of the crown **1102**. As shown, the portion of the crown **1102** that faces or is nearest a user’s wrist when the device is being worn may not be part of the imaging surface **1104**. This may help prevent false inputs from being detected due to movement of the device **1100** relative to the user’s wrist (e.g., as may occur during jostling or other normal use conditions).

FIG. **11B** shows an example device **1110** (which may be an embodiment of the device **100**, and may include the same or similar components and may provide the same or similar functions as the device **100**) with a crown **1112**. The crown **1112** defines several imaging surfaces, which may also be described as an imaging surface having several discrete segments. For example, an imaging surface **1114** may extend along a top portion of the crown **1112**, while imaging surfaces **1114** and **1118** extend along side portions of the crown **1112**. The crown **1112** may not capture images in the areas between adjacent imaging surfaces.

In FIGS. **11A-11B**, the imaging surfaces may be defined by light-transmissive windows set into an otherwise opaque head. For example, windows of glass, plastic, ceramic, sapphire, or other materials may be inset into a head of metal, plastic, or other opaque material.

FIG. **12** depicts an example schematic diagram of an electronic device **1200**. By way of example, the device **1200** of FIG. **12** may correspond to the wearable electronic device **100** shown in FIGS. **1A-1B** (or any other wearable electronic device described herein). To the extent that multiple functionalities, operations, and structures are disclosed as being part of, incorporated into, or performed by the device **1200**, it should be understood that various embodiments may omit any or all such described functionalities, operations, and structures. Thus, different embodiments of the device **1200** may have some, none, or all of the various capabilities, apparatuses, physical features, modes, and operating parameters discussed herein.

As shown in FIG. **12**, a device **1200** includes a processing unit **1202** operatively connected to computer memory **1204** and/or computer-readable media **1206**. The processing unit **1202** may be operatively connected to the memory **1204** and computer-readable media **1206** components via an electronic bus or bridge. The processing unit **1202** may include one or more computer processors or microcontrollers that are configured to perform operations in response to computer-readable instructions. The processing unit **1202** may include the central processing unit (CPU) of the device. Additionally or alternatively, the processing unit **1202** may

20

include other processors within the device including application specific integrated chips (ASIC) and other microcontroller devices.

The memory **1204** may include a variety of types of non-transitory computer-readable storage media, including, for example, read access memory (RAM), read-only memory (ROM), erasable programmable memory (e.g., EPROM and EEPROM), or flash memory. The memory **1204** is configured to store computer-readable instructions, sensor values, and other persistent software elements. Computer-readable media **1206** also includes a variety of types of non-transitory computer-readable storage media including, for example, a hard-drive storage device, a solid-state storage device, a portable magnetic storage device, or other similar device. The computer-readable media **1206** may also be configured to store computer-readable instructions, sensor values, and other persistent software elements.

In this example, the processing unit **1202** is operable to read computer-readable instructions stored on the memory **1204** and/or computer-readable media **1206**. The computer-readable instructions may adapt the processing unit **1202** to perform the operations or functions described above with respect to FIGS. **1A-11B**. In particular, the processing unit **1202**, the memory **1204**, and/or the computer-readable media **1206** may be configured to cooperate with a sensor **1224** (e.g., an image sensor that detects input gestures applied to an imaging surface of a crown) to control the operation of a device in response to an input applied to a crown of a device (e.g., the crown **112**). The computer-readable instructions may be provided as a computer-program product, software application, or the like.

As shown in FIG. **12**, the device **1200** also includes a display **1208**. The display **1208** may include a liquid-crystal display (LCD), organic light emitting diode (OLED) display, light emitting diode (LED) display, or the like. If the display **1208** is an LCD, the display **1208** may also include a backlight component that can be controlled to provide variable levels of display brightness. If the display **1208** is an OLED or LED type display, the brightness of the display **1208** may be controlled by modifying the electrical signals that are provided to display elements. The display **1208** may correspond to any of the displays shown or described herein.

The device **1200** may also include a battery **1209** that is configured to provide electrical power to the components of the device **1200**. The battery **1209** may include one or more power storage cells that are linked together to provide an internal supply of electrical power. The battery **1209** may be operatively coupled to power management circuitry that is configured to provide appropriate voltage and power levels for individual components or groups of components within the device **1200**. The battery **1209**, via power management circuitry, may be configured to receive power from an external source, such as an AC power outlet. The battery **1209** may store received power so that the device **1200** may operate without connection to an external power source for an extended period of time, which may range from several hours to several days.

In some embodiments, the device **1200** includes one or more input devices **1210**. An input device **1210** is a device that is configured to receive user input. The one or more input devices **1210** may include, for example, a push button, a touch-activated button, a keyboard, a key pad, or the like (including any combination of these or other components). In some embodiments, the input device **1210** may provide a dedicated or primary function, including, for example, a power button, volume buttons, home buttons, scroll wheels, and camera buttons. Generally, a touch sensor or a force

sensor may also be classified as an input device. However, for purposes of this illustrative example, the touch sensor **1220** and a force sensor **1222** are depicted as distinct components within the device **1200**.

The device **1200** may also include a sensor **1224** that detects inputs provided by a user to a crown of the device (e.g., the crown **112**). As described above, the sensor **1224** may include sensing circuitry and other sensing elements that facilitate sensing of gesture inputs applied to an imaging surface of a crown, as well as other types of inputs applied to the crown (e.g., rotational inputs, translational or axial inputs, axial touches, or the like). The sensor **1224** may include an optical sensing element, such as a charge-coupled device (CCD), complementary metal-oxide-semiconductor (CMOS), or the like. The sensor **1224** may correspond to any sensors described herein or that may be used to provide the sensing functions described herein.

The device **1200** may also include a touch sensor **1220** that is configured to determine a location of a touch on a touch-sensitive surface of the device **1200** (e.g., an input surface defined by the portion of a cover **108** over a display **109**). The touch sensor **1220** may use or include capacitive sensors, resistive sensors, surface acoustic wave sensors, piezoelectric sensors, strain gauges, or the like. In some cases, the touch sensor **1220** associated with a touch-sensitive surface of the device **1200** may include a capacitive array of electrodes or nodes that operate in accordance with a mutual-capacitance or self-capacitance scheme. The touch sensor **1220** may be integrated with one or more layers of a display stack (e.g., the display **109**) to provide the touch-sensing functionality of a touchscreen. Moreover, the touch sensor **1220**, or a portion thereof, may be used to sense motion of a user's finger as it slides along a surface of a crown, as described herein.

The device **1200** may also include a force sensor **1222** that is configured to receive and/or detect force inputs applied to a user input surface of the device **1200** (e.g., the display **109**). The force sensor **1222** may use or include capacitive sensors, resistive sensors, surface acoustic wave sensors, piezoelectric sensors, strain gauges, or the like. In some cases, the force sensor **1222** may include or be coupled to capacitive sensing elements that facilitate the detection of changes in relative positions of the components of the force sensor (e.g., deflections caused by a force input). The force sensor **1222** may be integrated with one or more layers of a display stack (e.g., the display **109**) to provide force-sensing functionality of a touchscreen.

The device **1200** may also include a communication port **1228** that is configured to transmit and/or receive signals or electrical communication from an external or separate device. The communication port **1228** may be configured to couple to an external device via a cable, adaptor, or other type of electrical connector. In some embodiments, the communication port **1228** may be used to couple the device **1200** to an accessory, including a dock or case, a stylus or other input device, smart cover, smart stand, keyboard, or other device configured to send and/or receive electrical signals.

As described above, one aspect of the present technology is the gathering and use of data available from various sources to facilitate the detection of inputs to an electronic device. The present disclosure contemplates that in some instances, this gathered data may include personal information data that uniquely identifies or can be used to contact or locate a specific person. Such personal information data can include biometric data (e.g., fingerprints), demographic data, location-based data, telephone numbers, email addresses,

twitter ID's, home addresses, data or records relating to a user's health or level of fitness (e.g., vital signs measurements, medication information, exercise information), date of birth, or any other identifying or personal information.

The present disclosure contemplates that the entities responsible for the collection, analysis, disclosure, transfer, storage, or other use of such personal information data will comply with well-established privacy policies and/or privacy practices. In particular, such entities should implement and consistently use privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining personal information data private and secure. Such policies should be easily accessible by users, and should be updated as the collection and/or use of data changes. Personal information from users should be collected for legitimate and reasonable uses of the entity and not shared or sold outside of those legitimate uses. Further, such collection/sharing should occur after receiving the informed consent of the users. Additionally, such entities should consider taking any needed steps for safeguarding and securing access to such personal information data and ensuring that others with access to the personal information data adhere to their privacy policies and procedures. Further, such entities can subject themselves to evaluation by third parties to certify their adherence to widely accepted privacy policies and practices. In addition, policies and practices should be adapted for the particular types of personal information data being collected and/or accessed and adapted to applicable laws and standards, including jurisdiction-specific considerations. For instance, in the US, collection of or access to certain health data may be governed by federal and/or state laws, such as the Health Insurance Portability and Accountability Act (HIPAA); whereas health data in other countries may be subject to other regulations and policies and should be handled accordingly. Hence different privacy practices should be maintained for different personal data types in each country.

Despite the foregoing, the present disclosure also contemplates embodiments in which users selectively block the use of, or access to, personal information data. That is, the present disclosure contemplates that hardware and/or software elements can be provided to prevent or block access to such personal information data. For example, users can deactivate input detection using imaging techniques that may capture or use biometric information (e.g., fingerprints, skin features, etc.). In addition to providing "opt in" and "opt out" options, the present disclosure contemplates providing notifications relating to the access or use of personal information. For instance, a user may be notified upon downloading an app that their personal information data will be accessed and then reminded again just before personal information data is accessed by the app.

Moreover, it is the intent of the present disclosure that personal information data should be managed and handled in a way to minimize risks of unintentional or unauthorized access or use. Risk can be minimized by limiting the collection of data and deleting data once it is no longer needed. In addition, and when applicable, including in certain health related applications, data de-identification can be used to protect a user's privacy. De-identification may be facilitated, when appropriate, by removing specific identifiers (e.g., date of birth, etc.), controlling the amount or specificity of data stored (e.g., collecting location data a city level rather than at an address level), controlling how data is stored (e.g., aggregating data across users), and/or other methods.

23

Therefore, although the present disclosure broadly covers use of personal information data to implement one or more various disclosed embodiments, the present disclosure also contemplates that the various embodiments can also be implemented without the need for accessing such personal information data. That is, the various embodiments of the present technology are not rendered inoperable due to the lack of all or a portion of such personal information data. For example, gesture inputs applied to a crown with an object other than a finger, or with a gloved finger, may be operable to control the operation of an electronic device. Further, the functionality described herein may be provide without requiring any persistent storage of personal information. For example, images of a user's finger that are captured by an image sensor may be analyzed and then discarded immediately after the necessary motion information has been determined.

The foregoing description, for purposes of explanation, used specific nomenclature to provide a thorough understanding of the described embodiments. However, it will be apparent to one skilled in the art that the specific details are not required in order to practice the described embodiments. Thus, the foregoing descriptions of the specific embodiments described herein are presented for purposes of illustration and description. They are not targeted to be exhaustive or to limit the embodiments to the precise forms disclosed. It will be apparent to one of ordinary skill in the art that many modifications and variations are possible in view of the above teachings. Also, when used herein to refer to positions of components, the terms above and below, or their synonyms, do not necessarily refer to an absolute position relative to an external reference, but instead refer to the relative position of components with reference to the figures.

What is claimed is:

1. An electronic watch comprising:
a housing defining a side surface of the electronic watch;
a display positioned at least partially within the housing and configured to display a graphical output;
a transparent cover coupled to the housing and defining a front surface of the electronic watch;
an optical sensing element;
a crown extending from the side surface of the electronic watch and defining a peripheral surface along an exterior portion of the crown, wherein the electronic watch is configured to:
detect, using the optical sensing element, movement of an object along the peripheral surface of the crown; and
modify the graphical output in accordance with the movement of the object along the peripheral surface of the crown.
2. The electronic watch of claim 1, wherein:
the electronic watch further comprises a touch sensor positioned below the transparent cover and configured to detect touch inputs applied to the transparent cover; and
the crown comprises a light-directing feature configured to direct, onto the optical sensing element, an image of an object in contact with the peripheral surface of the crown.
3. The electronic watch of claim 2, wherein the light-directing feature comprises an interface between a first material and a second material, the interface configured to reflect incident light.
4. The electronic watch of claim 1, wherein the optical sensing element is positioned within the housing.

24

5. The electronic watch of claim 1, wherein the optical sensing element is positioned within the crown.

6. The electronic watch of claim 1, wherein the crown comprises:

- an opaque portion; and
- a light-transmissive portion defining a portion of the peripheral surface.

7. The electronic watch of claim 6, wherein the optical sensing element receives light through the light-transmissive portion of the crown.

8. A wearable electronic device comprising:

- a housing;
- a display positioned at least partially within the housing and configured to display a graphical output;
- a crown at least partially external to the housing and defining a light-transmissive window; and
- an optical sensing element within the housing and configured to receive an image of an object in contact with the light-transmissive window, wherein the wearable electronic device is configured to:

detect, using the optical sensing element, movement of the object along the light-transmissive window; and
modify the graphical output in accordance with the movement of the object along the light-transmissive window.

9. The wearable electronic device of claim 8, wherein the crown comprises a light-directing feature configured to direct, onto the optical sensing element, an image of an object in contact with the light-transmissive window.

10. The wearable electronic device of claim 9, wherein the light-directing feature defines an angled surface configured to direct light from the light-transmissive window to the optical sensing element.

11. The wearable electronic device of claim 10, further comprising a reflective material on the angled surface.

12. The wearable electronic device of claim 8, wherein the crown comprises:

- an opaque member; and
- a light-transmissive member positioned in the opaque member and defining the light-transmissive window.

13. The wearable electronic device of claim 8, further comprising a light source at least partially within the housing and configured to illuminate the object.

14. The wearable electronic device of claim 8, wherein the light-transmissive window includes a semi-transparent mirror coating.

15. An electronic watch comprising:

- a housing;
- a display positioned at least partially within the housing;
- an optical sensor at least partially within the housing and comprising an optical sensing element; and
- a crown comprising:
a head portion defining an optical sensing region along a peripheral surface of the head portion;
- a shaft portion extending at least partially into the housing; and
- a light-directing feature directing light from the optical sensing region towards the optical sensing element.

16. The electronic watch of claim 15, further comprising a contact sensor configured to detect contact between an object and the crown.

17. The electronic watch of claim 15, wherein the head portion comprises:

- a metal portion; and
- a light-transmissive window coupled to the metal portion and at least partially defining the optical sensing region.

18. The electronic watch of claim 15, wherein the crown comprises:

25

a transparent member defining the head portion and the shaft portion; and
an opaque coating positioned on the transparent member.

19. The electronic watch of claim **18**, wherein the optical sensing region is defined by an opening in the opaque coating.

20. The electronic watch of claim **18**, wherein the optical sensor includes an image-sensing element.

* * * * *

26