



US011921460B2

(12) **United States Patent**
Graemiger

(10) **Patent No.: US 11,921,460 B2**
(45) **Date of Patent: Mar. 5, 2024**

(54) **DEVICE FOR DISPLAYING AN INDICATION
OF TIME OR DERIVED FROM THE TIME
AND INDEXING DEVICE**

(71) Applicant: **ROLEX SA**, Geneva (CH)

(72) Inventor: **Pierre-Alain Graemiger**, Trélex (CH)

(73) Assignee: **ROLEX SA**, Geneva (CH)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 333 days.

(21) Appl. No.: **17/246,579**

(22) Filed: **Apr. 30, 2021**

(65) **Prior Publication Data**

US 2021/0341880 A1 Nov. 4, 2021

(30) **Foreign Application Priority Data**

May 1, 2020 (EP) 20172579

(51) **Int. Cl.**
G04B 13/02 (2006.01)
G04B 19/20 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G04B 13/027** (2013.01); **G04B 19/202**
(2013.01); **G04B 19/25333** (2013.01); **G04F**
7/089 (2013.01); **G04F 7/0876** (2013.01)

(58) **Field of Classification Search**
CPC G04B 19/25333; G04B 13/027; G04B
19/202; G04F 7/089; G04F 7/0876
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,688,490 A 9/1972 Oki
3,713,287 A 1/1973 Vogt et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CH 260353 A 3/1949
CH 310559 A 10/1955
(Continued)

OTHER PUBLICATIONS

European Search Report and Written Opinion dated Oct. 12, 2020
in priority application No. EP20172579; with X English machine
translation (total 8 pages).

(Continued)

Primary Examiner — Edwin A. Leon


Assistant Examiner — Sean R Brannon

(74) *Attorney, Agent, or Firm* — Seckel IP, PLLC

(57) **ABSTRACT**

A device (100) for display of an indication of the time or
derived from the time includes: a first display mobile unit
(10) including a first tothing (11b), a second tothing (11c)
and a first disk (12) carrying digits (13) intended to indicate
the units of indication of time or derived from time; a second
display mobile unit (20) including a third tothing (21b), a
fourth tothing (21c) and a second disk (22) carrying digits
(23) intended to indicate the tens of indication of time or
derived from time; and a mechanism (90) for driving the first
and second mobile that includes a command mobile unit
(30) including a fifth tothing (30a) adapted to cooperate by
obstacle, in particular by meshing, with the first and third
tothings, and a second command mobile unit (40) including
a sixth tothing (40a) adapted to cooperate by obstacle with
the second and fourth tothings.

20 Claims, 13 Drawing Sheets



(51) **Int. Cl.**

G04B 19/253 (2006.01)
G04F 7/08 (2006.01)

FOREIGN PATENT DOCUMENTS

CH	528767 A	6/1972
CH	986270 A4	6/1972
CH	712309 A2	10/2017
CH	713334 A2	6/2018
EP	2985660 A1	2/2016
FR	2120056 A1	8/1972
WO	9850829 A1	11/1998

(56) **References Cited**



U.S. PATENT DOCUMENTS

4,048,795 A	9/1977	Risi	
7,102,962 B2 *	9/2006	Suzuki	G04B 19/25366 368/37
7,110,326 B2 *	9/2006	Besse	G04B 19/25366 368/37
7,706,214 B2 *	4/2010	Scheufele	G04B 19/2536 368/37
8,750,080 B2 *	6/2014	Tran	G04B 27/005 368/220
9,367,039 B2 *	6/2016	Carreno	G04B 19/046
10,222,751 B2 *	3/2019	Robin	G04B 19/2536
2016/0048107 A1	2/2016	Carreno et al.	

OTHER PUBLICATIONS

European Search Report and Written Opinion dated Oct. 12, 2020 in priority application No. EP20172581 of co-pending U.S. Appl. No. 17/246,582; with English machine translation (total 9 pages).

* cited by examiner






Figure 3






Figure 4




III-III - (P1)



IV-IV - (P2)

Figure 5






Figure 7




Figure 8




Figure 9




Figure 10




Figure 11




Figure 12




Figure 13




Figure 14




Figure 15




Figure 16

1

DEVICE FOR DISPLAYING AN INDICATION OF TIME OR DERIVED FROM THE TIME AND INDEXING DEVICE

This application claims priority of European patent application No. EP20172579.3 filed May 1, 2020, the content of which is hereby incorporated by reference herein in its entirety.

The invention concerns a display for displaying an indication of the time or derived from the time. The invention also concerns a jumper or indexing device. The invention also concerns a timepiece movement including this kind of display device and/or this kind of jumper or indexing device. The invention further concerns a timepiece including this kind of display device and/or this kind of jumper or indexing device, or this kind of timepiece movement. The invention finally concerns a method of operating this kind of display device or this kind of timepiece movement or this kind of timepiece.

Prior art “grande date” mechanisms systematically employ a command wheel or a disk with 31 teeth, or a command wheel or a disk effecting a complete rotation in 31 steps, that are bulky and that consequently do not facilitate the incorporation of this kind of mechanism into a timepiece movement. Moreover, the sequencing of the command device for driving the tens and units disks is often complicated and offers little freedom of choice as to the positions of the mobile units in the plane.

All of the identified solutions employ either a command mobile unit or a disk with 31 teeth. By way of example, the documents CH310559 and WO9850829 describe the two main driving concepts known today for “grande date” mechanisms.

The document CH310559 describes the arrangement of a first command mobile unit driving a first display mobile unit for the units and a second display mobile unit for the tens. The two display mobile units are disposed side by side. The command mobile advances by one step every 24 hours and effects a complete rotation in 31 steps. The command mobile includes three toothings distributed on three distinct levels. A first tothing is provided to drive itself, a second tothing comprising 30 teeth is provided to drive the units display mobile unit, and a third tothing comprising 4 teeth is provided for driving the tens display mobile unit. The arrangement on three distinct levels and employing a command mobile unit sequencing the jumps over 31 steps render this solution particularly bulky and difficult to incorporate in a timepiece movement.

The second document WO9850829 describes the use of a command disk advancing one step every 24 hours and driving a first display mobile unit for the units and second display mobile unit for the tens. These two display mobiles units are disposed side by side. The command disk includes two toothings disposed at two distinct levels. The first tothing comprises 31 teeth, 30 of which are active for driving the units display mobile unit. The second tothing comprises 31 teeth, 4 of which are active for driving the tens display mobile unit. The overall size in the plane of this kind of disk is very large. It is similar to a date disk, which leaves virtually no freedom of choice as to the disposition of the two display mobile units in a timepiece movement. Moreover, employing a disk sequencing the jumps over 31 steps renders this solution particularly difficult for incorporating in a timepiece movement.

As described above, a “grande date” mechanism generally includes two display mobiles for displaying the date, a first for displaying the units and a second for displaying the tens.

2

Each of these two display mobiles necessitates an angular position indexing device respectively enabling indexing of the units and tens digits in the window. By “indexing” a mobile is preferably meant maintaining a mobile in a particular angular position from a finite number of angular positions of that mobile, the positions being separated from one another by angles, in particular separated from one another by a fixed angle.

The problem with this type of “grande date” mechanism is that, when changing the date, the energy consumption of the movement depends in particular on the date changed. In fact, according to the sequencing of the mechanism for displaying the date, it is necessary to drive one or more “grande date” display mobiles. With a conventional mobiles indexing device, the movement must overcome one or simultaneously two jumpers or levers each constituting an indexing device, which generates a consumption of energy liable to vary as a function of the date changed. When the movement has to overcome two jumpers or levers, there may be less energy available for the regulating unit which consequently may generate possible losses of amplitude at the level of that same regulating unit. These amplitude variations must be as small as possible in order to have the most optimum possible chronometric performance.

The various prior art documents identified describe mobiles indexing devices that employ two levers that are incompatible with a “grande date” mechanism and/or do not propose any solution for having an equivalent or substantially equivalent energy consumption whether there are one or several indexing levers to be actuated.

The document CH986270 describes a calendar including a date indicator and a day of the week indicator. These mobiles indexing devices include a lever with two beaks fastened to one another for positioning the two indicators, an elastic return element and an eccentric fixedly attached to the lever. The eccentric enables adjustment of the relative position of the two beaks and consequently adjustment of the angular indexing position of the two indicators. This solution cannot be employed for indexing a “grande date” mechanism because a degree of freedom between the two beaks is necessary for the latter to be able to function independently of one another.

The document U.S. Pat. No. 4,048,795 describes a calendar including a mobiles indexing device for positioning an indicator of the date and an indicator of the day of the week including a single lever with two beaks and two elastic return elements. In order to offer the indexing device an additional degree of freedom, the lever further includes a slot adapted to cooperate with a pin fixedly attached to the frame of the movement, thereby constituting a slide connection. Although the beaks are fixedly attached to only one lever, this additional degree of freedom allows the indicators to be able to function independently. In fact, thanks to this slide connection, when only one of the two indicators is actuated, for example during a first operation to adjust the calendar, the beak cooperating with the other indicator remains in the teeth of the latter and serves as a pivot for the lever. In this case, only one of the two elastic return elements is loaded. Operation is similar when it is the other indicator that is actuated, for example during a second operation to adjust the calendar. On the other hand, when the two indicators are actuated simultaneously during conventional operation of the calendar, the lever pivots around the pin and both the elastic return elements of the lever are loaded. This indexing device offers no solution enabling actuation of one and the same return element when the two indicators are actuated simultaneously. Moreover, it does not enable an

3

equivalent or substantially equivalent energy consumption to be obtained whatever the number of display mobiles actuated.

The document FR2120056 discloses a calendar including a mobiles indexing device including a lever with two beaks that can be actuated independently of one another. This mobiles indexing device is described as including at least one beak intended to index the date indicator or the day of the week indicator and elastic parts oriented in two directions allowing elastic return of the device. With this kind of device the arming of the elastic parts of the mobiles indexing device, and consequently the energy consumption, depend on the number of beaks actuated. This solution is therefore not the optimum solution.

In accordance with a first aspect, the aim of the invention is to provide a device for displaying an indication of the time or derived from the time making it possible to remedy the drawbacks mentioned above and to improve the known prior art devices. In particular, the invention proposes a device for displaying an indication of the time or derived from the time providing great suppleness or flexibility in the arrangement of a display mechanism and making it possible to obtain a structure with a very small overall size in the plane and offering very secure operation.

In accordance with a second aspect, the aim of the invention is to provide a jumper or position indexing device making it possible to remedy the drawbacks mentioned above and to improve the known prior art devices. In particular, the invention proposes a jumper or position indexing device having a simple structure enabling use of two levers functioning independently of one another and moreover an equivalent or substantially equivalent restitution force on an elastic return element to be obtained whatever the number of levers or of beaks to actuate.

In accordance with the first aspect of the invention, a display device is defined by the following propositions.

1. Device **100** for display of an indication of the time or derived from the time including:
 - a first display mobile unit **10** including a first tothing **11b**, a second tothing **11c** and a first disk **12** carrying digits **13** intended to indicate the units of the indication of the time or derived from the time,
 - a second display mobile unit **20** including a third tothing **21b**, a fourth tothing **21c** and a second disk **22** carrying digits **23** intended to indicate the tens of the indication of the time or derived from the time, and
 - a mechanism **90** for driving the first and second mobile units, the mechanism including:
 - a first command mobile unit **30** including a fifth tothing **30a** adapted to cooperate by obstacle, in particular by meshing, with the first tothing and the third tothing, and
 - a second command mobile unit **40** including a sixth tothing **40a** adapted to cooperate by obstacle, in particular by meshing, with the second tothing and the fourth tothing.
2. Display device according to proposition 1, characterized in that the first, third and fifth tothings have substantially the same first primitive diameter and/or in that the second, fourth and sixth tothings have substantially the same second primitive diameter.
3. Device according to proposition 2, characterized in that the first and second primitive diameters are equal or substantially equal.
4. Display device according to any one of propositions 1 to 3, characterized in that the first command mobile unit

4

30 and the second command mobile unit **40** are arranged coaxially on an axis **A3**.

5. Display device according to any one of propositions 1 to 4, characterized in that the drive mechanism **90** includes a drive wheel **60** including a seventh tothing **61** adapted to drive the first command mobile unit directly or indirectly.
6. Display device according to any one of propositions 1 to 5, characterized in that the second command mobile unit is adapted to be driven by the first display mobile unit and/or by the second display mobile unit.
7. Display device according to any one of propositions 1 to 6, characterized in that the drive mechanism **90** includes an intermediate mobile unit **50** cooperating by obstacle, in particular by meshing, with the seventh tothing of the drive wheel **60** and with the fifth tothing of the first command mobile unit **30** and/or in that the drive mechanism **90** includes a correction mobile unit **70** adapted to actuate the fifth tothing of the first mobile unit **30** directly or indirectly.
8. Display device according to any one of propositions 1 to 7, characterized in that the drive mechanism **90** is of the instantaneous jump type or of the semi-instantaneous jump type or of the trailing type.
9. Display device according to any one of propositions 1 to 8, characterized in that the first tothing **11b** comprises 9 teeth, the second tothing **11c** comprises 2 teeth, the third tothing **21b** comprises 4 teeth and the fourth tothing **21c** comprises 6 teeth.
10. Display device according to any one of propositions 1 to 8, characterized in that the first tothing **11b** comprises 9 teeth, the second tothing **11c** comprises 2 teeth, the third tothing **21b** comprises 7 teeth and the fourth tothing **21c** comprises 8 teeth.
11. Display device according to any one of propositions 1 to 10, characterized in that the first disk includes the following series of digits "0, 1, 2, 3, 4, 5, 6, 7, 8, 9" and/or in that the second disk includes the following series of digits "0, 0, 1, 1, 1, 2, 2, 2, 3, 3".
12. Display device according to any one of propositions 1 to 11, characterized in that the device for displaying an indication of the time or derived from the time is a date display device, in particular of "grande date" type, the first disk being a units disk and the second disk being a tens disk.

In accordance with the first aspect of the invention, a timepiece movement is defined by the following proposition.

13. Timepiece movement **110** including a device **100** according to any one of propositions 1 to 12.

In accordance with the first aspect of the invention, a timepiece is defined by the following proposition.

14. Timepiece **120**, in particular a watch, in particular a wristwatch, including a device **100** according to any one of propositions 1 to 12 and/or a timepiece movement **110** as claimed in proposition 13.

In accordance with the first aspect of the invention, a method of operating a display device is defined by the following proposition.

15. Method of operating a device **100** according to any one of propositions 1 to 12 or a timepiece movement **110** according to proposition 13 or a timepiece **120** according to proposition 14, characterized in that it includes:
 - a step of the first command mobile unit **30** driving the first display mobile unit **10**, and/or

5

simultaneously, a step of the first command mobile unit **30** driving the first display mobile unit **10** and a step of the first display mobile unit **10** driving the second display mobile unit **20** via the second command mobile unit **40**, and/or

a step of the first command mobile unit **30** driving the second display mobile unit **20**, and/or

simultaneously, a step of the first command mobile unit **30** driving the second display mobile unit **20** and a step of the second display mobile unit **20** driving the first display mobile unit **10** via the second command mobile unit **40**.

In accordance with the second aspect of the invention, a jumper device is defined by the following propositions.

16. Jumper device **80** for a timepiece device **100** including:

at least one first arm **81** including a first beak **81a** for positioning a first mobile unit **10**,

at least one second arm **82** including a second beak **82a** for positioning a second mobile unit **20**,

an elastic element **84** for returning the first arm and the second arm to configurations positioning the first and second mobile units, and

a lever **83; 83'** interfaced between:

on the one hand, the elastic return element, and
on the other hand, the first and second arms.

17. Device according to proposition 16, characterized in that the device is a device for indexing the angular position of a first mobile unit **10** mobile in rotation and of a second mobile unit **20** mobile in rotation.

18. Device according to proposition 16 or 17, characterized in that the device includes a frame **99**, in that the first arm is mounted to pivot relative to the frame **99** and in that the second arm is mounted to pivot relative to the frame **99**, the first and second arms being in particular mounted to pivot about the same axis **A5**.

19. Device according to any one of propositions 16 to 18, characterized in that the device includes a frame **99** and in that the lever **83; 83'** is mounted to be mobile relative to the frame with:

one degree of freedom in translation, and
one degree of freedom in rotation.

20. Device according to any one of propositions 16 to 19, characterized in that the greatest dimension of the lever is at least twice, or even three times, less than the greatest dimension of the first arm or the greatest dimension of the second arm.

21. Device according to any one of propositions 16 to 20, characterized in that the device includes a frame **99** and in that the device includes:

a groove **85** on the lever, respectively on the frame, and a pin **86** produced on or fixed to the frame, respectively to the lever, the groove and the pin cooperating with one another to constitute a mechanical connection having the degrees of freedom in translation and in rotation.

22. Device according to any one of propositions 16 to 21, characterized in that the elastic return element **84** comprises a spring leaf.

23. Device according to any one of propositions 16 to 22, characterized in that the lever **83'** or the elastic return element has a cam surface **89** adapted to arm the elastic return element **84** when the lever pivots in rotation.

In accordance with the second aspect of the invention, a display device is defined by the following propositions.

6

24. Date display device **100**, in particular "grande date" display device, including a jumper device according to any one of propositions 16 to 23.

25. Date display device **100** according to proposition 24, including a first mobile unit **10** for displaying units and a second mobile unit **20** for displaying tens.

In accordance with the second aspect of the invention, a timepiece movement is defined by the following proposition.

26. Timepiece movement **110** including a device according to any one of propositions 16 to 25.

In accordance with the second aspect of the invention, a timepiece is defined by the following proposition.

27. Timepiece **120**, in particular watch, in particular wristwatch, including a device according to any one of propositions 16 to 25 and/or a timepiece movement **110** according to proposition 26.

In accordance with the second aspect of the invention, a method of operating a device is defined by the following propositions.

28. Method of operating a device **80, 100** according to any one of propositions 16 to 25 or a timepiece movement **110** according to proposition 26 or a timepiece **120** according to proposition 27, characterized in that it includes:

a step of moving the first arm and/or the second arm by the effect of the movement of the first mobile unit **10** and/or of the second mobile unit **20** and a step of arming the elastic return element **84** by the effect of a movement of the lever **83; 83'**, and

a step of restituting of the elastic return element **84** causing driving in rotation of the first mobile unit **10** and/or the second mobile unit **20** by means of the lever **83; 83'** and the first arm and/or the second arm.

29. Method according to proposition 28, characterized in that the arming step has the same intensity in at least two of the following situations:

arming is brought about by a movement of the first mobile unit,
arming is brought about by a movement of the second mobile unit,
arming is brought about by movement of the first and second mobile units.

Failing technical or logical incompatibility, all combinations of features of the first and second aspects can be carried out.

The appended drawings represent two embodiments of a timepiece by way of example.

FIG. 1 represents a first embodiment of a timepiece.

FIG. 2 is a detail view of a first embodiment of a device for displaying an indication of the time or derived from the time.

FIG. 3 is a view in section (on the plane I-I in FIG. 2) of the first embodiment of the device for displaying an indication of the time or derived from the time.

FIG. 4 is a view in section (on the plane II-II in FIG. 2) of the first embodiment of the device for displaying an indication of the time or derived from the time.

FIG. 5 represents a first variant of the first embodiment of a device for displaying an indication of the time or derived from the time in a sectional view (in two sectional views on the planes III-III and IV-IV in FIGS. 3 and 4).

FIG. 6 represents a second variant of the first embodiment of a device for displaying an indication of the time or derived from the time in a sectional view (in two sectional views on the planes III-III and IV-IV in FIGS. 3 and 4).

FIG. 7 represents illustrations of the operation of the first variant of the first embodiment of a display device.

FIG. 8 represents illustrations of the operation of the second variant of the first embodiment of a display device.

FIG. 9 represents a second embodiment of a timepiece.

FIG. 10 represents a detail view of a first embodiment of an indexing device.

FIGS. 11 to 13 represent explanatory views of the operation of the first embodiment of the indexing device.

FIGS. 14 to 16 represent explanatory views of the operation of a second embodiment of the indexing device.

A first embodiment of a timepiece **120** is described hereinafter with reference to FIGS. 1 to 8.

The timepiece **120** is for example a watch, in particular a wristwatch.

The timepiece **120** includes a timepiece movement **110**. The timepiece movement is intended to be mounted in a timepiece case in order to protect it from the external environment.

The timepiece movement **110** may be an electronic movement or a mechanical movement, in particular an automatic movement.

The timepiece movement includes a device **100** for displaying an indication of the time or derived from the time. The indication of the time or derived from the time is preferably an indication of the date. However, the indication may be of any other kind, in particular a numerical indication of two digits or more such as an indication of the year or an indication of the month or an indication of the week or an indication of the hour or an indication of the minute or an indication of the second.

In this first embodiment the display device is for example a device for displaying dates of “grande date” type.

The device **100** for displaying an indication of the time or derived from the time includes:

- a first display mobile unit **10** including a first tothing **11b**, a second tothing **11c** and a first disk **12** carrying digits **13** intended to indicate the units of the indication of the time or derived from the time,
- a second display mobile unit **20** including a third tothing **21b**, a fourth tothing **21c** and a second disk **22** carrying digits **23** intended to indicate the tens of the indication of the time or derived from the time, and
- a mechanism **90** for driving the first and second mobile units.

The drive mechanism **90** includes:

- a first command mobile unit **30** including a fifth tothing **30a** adapted to cooperate by obstacle, in particular by meshing, with the first tothing and the third tothing, and
- a second command mobile unit **40** including a sixth tothing **40a** adapted to cooperate by obstacle, in particular by meshing, with the second tothing and the fourth tothing.

The first display mobile unit **10** pivots about a first axis **A1**. The second display mobile unit **20** pivots about a second axis **A2**. The first and second axes are preferably parallel or substantially parallel. The first and second mobile units are preferably disposed side by side so as to position in the vicinity of one another a units digit of the first mobile unit and a tens digit of the second mobile unit to indicate a value or information such as a monthly date value. The device may include a marker, such as a window produced in a dial or as a plate of a color contrasting with that of the numbers **13** and **23**, respectively the disks **12** and **22**, enabling an information reading zone to be indicated or defined.

The display device **100** further includes an indexing system **80** for the angular position of the first and second display mobile units. This system includes arms **81** and **82** respectively adapted to index angularly the first and second display mobile units, as described below.

The first display mobile unit **10** includes a first gear **11** including in particular the first tothing **11b** and the second tothing **11c**. The first tothing has nine teeth for example. The first tothing is for example a set of ten teeth equi-angularly distributed around the axis **A1**, one of the teeth of which has been removed or not formed. In other words, this is a set of ten teeth from which one tooth is missing. The second tothing **11c** for example has two teeth. The second tothing is for example a set of ten teeth equi-angularly distributed around the axis **A1**, eight teeth of which have been removed or not formed. In other words, it is a set of ten teeth of which eight teeth are missing. The two teeth of the second tothing are preferably juxtaposed, that is to say that there exists no space left free by a missing tooth between the two teeth of the second tothing. These configurations of toothings with teeth missing are adapted to allow a particular sequence in driving the first mobile unit but also the second mobile unit as will be described below. The first and second toothings may be seen as constituting a single tothing with no missing teeth, one tooth being located on the first tothing at an angular location where a tooth is missing on the second tothing and one tooth being located on the second tothing at an angular location where a tooth is missing in the first tothing. Moreover, at least one tooth of the first tothing may equally be juxtaposed to a tooth of the second tothing.

The first disk **12** includes 10 units digits 0 to 9. These digits are represented on the units display disk **12**.

The first tothing **11b** and the second tothing **11c** are juxtaposed on two distinct levels respectively disposed in the planes **P1** and **P2** as represented in FIG. 3. The planes **P1** and **P2** are parallel to one another and distinct from one another. They are preferably perpendicular to the axis **A1**. The plane **P1** therefore intersects the first tothing but does not intersect the second tothing. Likewise, the plane **P2** intersects the second tothing but does not intersect the first tothing.

The first and second toothings are fixedly attached to one another in rotation about the axis **A1**. Thus one of the toothings is not able to turn through a given angle about the axis **A1** without the other of the toothings also turning through that same given angle. For example, the first and second toothings are fixed to one another or connected by a built-in connection. Alternatively, the first and second toothings are in one piece or made as a single block or element.

The second display mobile unit **20** includes a second gear **21** including in particular the third tothing **21b** and the fourth tothing **21c**. The third tothing for example has four teeth. The third tothing for example consists of set of ten teeth equi-angularly distributed around the axis **A2**, of which six teeth have been removed or not formed. In other words, it is a set of ten teeth of which six teeth are missing. The four teeth of the third tothing are preferably distributed as follows: two juxtaposed teeth, a space left free by two missing teeth, one tooth, a space left free by two missing teeth, one tooth and a space left free by two missing teeth.

The fourth tothing **21c** for example includes six teeth. The fourth tothing for example consists of a set of ten teeth equi-angularly distributed about the axis **A2**, of which four teeth have been removed or not formed. In other words, it is a set of ten teeth of which four teeth are missing. The six teeth of the fourth tothing are preferably distributed as

follows: two juxtaposed teeth, a space left free by a missing tooth, two juxtaposed teeth, a space left free by a missing tooth, two juxtaposed teeth, a space left free by two missing teeth. The third and fourth toothings may be seen as constituting a single toothing with no missing teeth, one tooth being located on the third toothing at an angular location where a tooth is missing on the fourth toothing and one tooth being located on the fourth toothing at the angular location where a tooth is missing in the third toothing. Moreover, at least one tooth of the third toothing may equally be juxtaposed to at least one tooth of the fourth toothing.

These configurations of toothings with missing teeth are adapted to enable a particular sequencing in the driving of the second mobile unit but also of the first mobile unit, as will be explained below. In particular, the second command mobile unit is also adapted so as to be driven by the first display mobile unit and/or by the second display mobile unit.

The second disk **22** includes 10 tens digits 0 to 3. These digits are represented on the tens display disk **22**. The digits are represented in the following sequence: 0, 0, 1, 1, 1, 2, 2, 2, 3, 3.

The third toothing **21b** and the fourth toothing **21c** are juxtaposed on two distinct levels respectively disposed in the planes **P1** and **P2**, as represented in FIG. 3. The planes **P1** and **P2** are preferably perpendicular to the axis **A2**. Thus the plane **P1** intersects the third toothing but does not intersect the fourth toothing. Likewise, the plane **P2** intersects the fourth toothing but does not intersect the third toothing.

The third and fourth toothings are fixedly attached to one another in rotation about the axis **A2**. Thus one of the toothings is not able to turn through a given angle about the axis **A2** without the other of the toothings also turning through that given angle. For example, the third and fourth toothings are fixed to one another or connected by a built-in connection. Alternatively, the third and fourth toothings are in one piece or made as a single block or element.

In addition to the first command mobile unit and the second command mobile unit, the drive mechanism **90** includes a drive wheel **60** including a seventh toothing **61** adapted to drive the first command mobile unit directly or indirectly.

In particular, the drive mechanism **90** may include an intermediate mobile unit **50** cooperating by obstacle, in particular by meshing, with the seventh toothing **61** of the drive wheel **60** and with the fifth toothing of the first command mobile unit **30**. Thus the seventh toothing **61** is adapted to drive the first command mobile unit indirectly (via the intermediate mobile unit **50**).

The drive mechanism **90** may be of the instantaneous jump type or of the semi-instantaneous jump type or of the trailing type.

The driving mechanism **90** is configured and/or arranged so as to cause the first command mobile unit to advance by one step every twenty four hours, that is to say to cause the rotation through one tenth of a turn of the first display mobile unit every twenty four hours.

As stated above, the first command mobile unit **30**, via its fifth toothing **30a**, enables driving of the first display mobile unit **10** and/or of the second display mobile unit **20**, more particularly driving of the first toothing **11b** and/or the third toothing **21b**.

As stated above, the second command mobile unit **40**, via its sixth toothing **40a**, enables driving of the first display mobile unit **10** and/or of the second display mobile unit **20**, more particularly driving of the second toothing **11c** and/or

of the fourth toothing **21c**. Moreover, the second command mobile unit is driven by the first display mobile unit and/or by the second display mobile unit.

The first and second command mobile units **30** and **40** are for example coaxial relative to a third axis **A3**. The axis **A3** is preferably parallel to the axes **A1** and **A2**.

The fifth toothing **30a** and the sixth toothing **40a** are juxtaposed on two distinct levels respectively disposed in the planes **P1** and **P2** as represented in FIG. 4. The planes **P1** and **P2** are preferably perpendicular to the axis **A3**. Thus the plane **P1** intersects the fifth toothing but does not intersect the sixth toothing. Likewise, the plane **P2** intersects the sixth toothing but does not intersect the fifth toothing.

The first and second command mobile units **30** and **40** are mounted idly relative to one another. In other words, the first and second command mobile units are able to turn freely relative to one another.

The fifth and sixth toothings **30a** and **40a** each comprise 10 teeth for example. These toothings could have another number of teeth. However, the fifth and sixth toothings **30a** and **40a** advantageously have the same number of teeth.

The first and second toothings **11b** and **21b** disposed at the level of the first plane **P1** are each adapted to cooperate with the fifth toothing **30a** of the first command mobile unit **30**, which is also arranged at the level of the first plane **P1**. This first command mobile unit **30**, more particularly the fifth toothing **30a**, is driven by one step every 24 hours.

The two display mobile units **10** and **20** are also driven by means of the sixth toothing **40a** of the second command mobile unit **40**, which is arranged at the level of the second plane **P2**, and which is adapted to cooperate with the toothings **11c** and **21c**. As a function of the sequencing of the date jumps, this second command mobile unit **40** can drive and/or be driven by the toothings **11c** and **21c**.

More particularly, by way of its toothing **50a**, the drive mechanism **90** drives the fifth toothing **30a** of the first command mobile unit **30** by one step every day, which in turn, according to the date, drives the first display mobile unit **10** and/or the second display mobile unit **20** via the respective toothings **11b**, **21b**. Depending on the date, the toothing **40a** of the second command mobile unit **40** may be driven by the first display mobile unit **10**, more particularly by the toothing **11c**, and/or by the second display mobile unit **20**, more particularly by the toothing **21c**. When it is driven, the second command mobile unit **40** can in turn drive the first display mobile unit **10** via the toothing **11c** and/or the second display mobile unit **20** via the toothing **21c**.

In a second variant of the first embodiment illustrated in FIG. 6 only the conformation of the second display mobile unit **20** is modified. In this variant the second display mobile unit **20** includes a third toothing **21b** disposed in the plane **P1** having 7 teeth and a fourth toothing **21c** disposed in the plane **P2** having 8 teeth.

The third toothing consists for example of a set of ten teeth equi-angularly distributed about the axis **A2**, three of which teeth have been removed or not formed. In other words, it is a set of ten teeth of which three teeth are missing. The seven teeth of the third toothing are preferably distributed as follows: three juxtaposed teeth, a space left free by a missing tooth, two juxtaposed teeth, a space left free by a missing tooth, two juxtaposed teeth and a space left free by a missing tooth.

The fourth toothing consists for example of a set of ten teeth equi-angularly distributed about the axis **A2**, two of which teeth have been removed or not formed. In other words, it is a set of ten teeth of which two teeth are missing.

11

The eight teeth of the fourth toothing are preferably distributed as follows: eight juxtaposed teeth and a space left free by two missing teeth.

This variant has in particular the advantage of offering toothings **21b** and **21c** with few missing, removed or not formed teeth, which makes it possible to prevent skewing of the arms **81**, **82** and more particularly the arm **82** cooperating with the second mobile unit.

A second embodiment of a timepiece **120** is described hereinafter with reference to FIG. 9.

The timepiece **120** is for example a watch, in particular a wristwatch.

The timepiece **120** includes a timepiece movement **110**. The timepiece movement is intended to be mounted in a timepiece case in order to protect it from the external environment.

The timepiece movement **110** may be an electronic movement or a mechanical movement, in particular an automatic movement.

The timepiece movement includes a device **100** for displaying an indication of the time or derived from the time. The indication of the time or derived from the time is preferably an indication of the date. Nevertheless, the indication may be of any other kind, in particular a numerical indication on two digits or more such as an indication of the year or an indication of the month or an indication of the hour or an indication of the minute or an indication of the second.

In this second embodiment the display device is for example a “grande date” date display type.

In this second embodiment the display device further includes a correction mobile unit **70** acting on the intermediate mobile unit **50**, more particularly on the toothing **50a**. Alternatively, the correction could also be effected by driving directly the fifth toothing **30a** of the first command mobile unit **30**. The device could further include (substituted for the correction mobile unit **70**) an arm used to effect a correction by acting on the mobile unit **50** or on the first command mobile unit **30**.

Different design variants are possible for driving the two display disks **12** and **22**. All of the variants described here function in accordance with the same sequence of displaying the date, with the same number of teeth on the display mobile units **10** and **20** and on the command mobile units **30** and **40**. The only differences between the different variants described are the disposition and the number of teeth provided on the third and fourth toothings of the display mobile unit **20**.

Regardless of the embodiment or the variant, the first, third and fifth toothings preferably have substantially the same first primitive diameter.

Regardless of the embodiment or the variant, the second, fourth and sixth toothings preferably have substantially the same second primitive diameter.

Regardless of the embodiment or the variant, the first and second primitive diameters are preferably equal or substantially equal.

Regardless of the embodiment or the variant, the first and second command mobile units **30** and **40** are preferably arranged in a coaxial manner. Nevertheless, it is also possible to dispose them on two distinct axles whilst retaining the same operation of the kinematic chain of the display device.

Regardless of the embodiment or the variant, the first toothing **11b**, the second toothing **11c**, the third toothing **21b** and the fourth toothing **21c**, along with the fifth toothing **30a** and the sixth toothing **40a** of the first and second command

12

mobile units **30** and **40** preferably all have substantially identical profiles and moduli. These six toothings also have the same angular pitch with 10 teeth, missing or not, equi-angularly distributed about their respective axis. However, these features do not constitute a limitation on the functioning of the device. For example, it would be entirely conceivable to have different numbers of teeth on the two display mobile units **10** and **20** in order to follow different successions of digits on the other two display disks **12** and **22**. The numbers of digits on the two display mobile units **10** and **20** are not necessarily identical. Likewise, the numbers of teeth on the gears **11** and **21** do not need to be identical. The numbers of teeth on the two command mobile units **30** and **40** have no influence on the sequencing of the jumps of this device either. The number of teeth of the fifth toothing **30a** of the first command mobile unit **30** could be different from that of the sixth toothing **40a** of the second command mobile unit **40**.

Regardless of the embodiment or the variant, the number of locations available for arranging teeth on the toothings **11b**, **11c**, **21b** and **21c** of the two display mobile units **10** and **20** could also be a multiple of the number of digits indicated on the display disks **12** and **22**.

Regardless of the embodiment or the variant, the meshing of the toothings **11b**, **11c**, **21b** and **21c** of the two display mobile units **10** and **20** could equally be effected with different profiles and/or moduli on the toothings **30a** and **40a** of the two command mobile units **30** and **40**. For example, the toothings **30a** and **40a** could be substantially half the size of the toothings **11b**, **11c**, **21b**, **21c**.

In other design variants it is possible to have the two display disks **12** and **22** superposed or partly superposed. It is even possible to dispose the two display disks in a coaxial manner. In the case of a coaxial superposition of the display disks the construction of the kinematic chain would then have to be transposed onto four distinct planes instead of two, because the toothings **11b**, **11c**, **21b** and **21c** of the two display mobile units **10** and **20** must be coaxial. The kinematic chain would however remain unchanged, because it would still be possible to have a fifth toothing **30a** of a first command mobile unit **30** meshing with the first and third toothings **11b** and **21b** and a sixth toothing **40a** of a second command mobile unit **40** meshing with the second and fourth toothings **11c** and **21c**.

Regardless of the embodiment or the variant, a locking system, in particular a “Maltese cross”, could be added to one or more supplementary levels of the display mobile units **10** and **20** or of the command mobile units **30** and **40**.

Regardless of the embodiment or the variant, the first command mobile unit **30** may be driven directly by the intermediate mobile unit **50** via the respective toothings **30a** and **50a** or by a supplementary level of teeth not represented here.

Regardless of the embodiment or the variant, it is possible to drive the first and second mobile units directly with the first command mobile unit **30** (without recourse to mobile units **50** and **60**). To this end the first command mobile unit **30** could comprise a limited number n of teeth, for example one tooth or two teeth or three teeth (equi-angularly distributed), and configured so that a rotation of $1/n$ revolution occurs every 24 hours. The drive could be of the instantaneous jump type or of the semi-instantaneous jump type or of the trailing type. For example, the mobile unit **30** could include only two diametrically opposite teeth driving the first and second display mobile units **10** and **20** on the line of centers. The command mobile unit would then have to perform a half-turn every 24 hours.

13

Regardless of the embodiment or the variant, the display of the digit 0 on the tens display disk **22** may be replaced by a gap, that is to say a zone of the disk with no digit. Thus the sequence 0, 0, 1, 1, 1, 2, 2, 2, 3, 3 may be replaced by “gap”, “gap”, 1, 1, 1, 2, 2, 2, 3, 3.

Regardless of the embodiment or the variant, the time-piece, in particular the movement or the display device, may include a jumper or indexing device **80**, in particular a first embodiment of a jumper or indexing device **80** as described hereinafter with reference to FIGS. 9 to 13.

The jumper or indexing device **80** includes:

- at least one first arm **81** including a first beak **81a** for positioning a first mobile unit **10**,
- at least one second arm **82** including a second beak **82a** for positioning a second mobile unit **20**,
- an element **84** for elastically returning the first arm and the second arm to configurations positioning the first and second mobile units, and
- a lever **83** interfaced between:
 - on the one hand, the elastic return element, and
 - on the other hand, the first and second arms.

The jumper or indexing device **80** enables indexing of the angular position of each of the first and second mobile units, that is to say to definition of a particular angular position among a particular number of stable angular positions, for example 10 positions, for each of the first and second mobile units. Those positions are positions enabling the mobile units to indicate information.

As stated above, the first mobile unit **10** is mobile in rotation about the axis **A1** and the second mobile unit **20** is mobile in rotation about the axis **A2**. The device **80** preferably includes a frame **99** on which the first mobile unit **10** is mounted to be mobile in rotation about the axis **A1** and on which the second mobile unit **20** is mounted to be mobile in rotation about the axis **A2**. The frame may be in particular be a movement blank such as a plate or a calendar ring **99**.

The first arm or lever **81** is mounted to pivot relative to the frame **99** about a pivot axis **A5** of the first arm.

The second arm or lever **82** is mounted to pivot relative to the frame **99** about a pivot axis **A5** of the second arm.

The first arm or lever **81**, in particular the first beak **81a**, is intended to cooperate with the first toothing **11b** and second toothing **11c** of the first gear **11** of the first display mobile unit **10**. The second arm or lever **82**, in particular the second beak **82a**, is intended to cooperate with the third toothing **21b** and the fourth toothing **21c** of the second gear **21** of the second display mobile unit **20**. It is these two arms or levers **81**, **82**, in particular the beaks thereof, that by interaction with the teeth of the toothings enable angular indexing of the two display mobile units **10** and **20**, as represented in FIG. 2.

To be more precise, the indexing of the first display mobile unit **10** is handled by the beak or the head **81a** that is part of the arm **81**. The head **81a** has two flanks **81b** and **81c**. It is the arrangement of these two flanks cooperating by contact with the flanks of successive teeth of the first toothing **11b** and the second toothing **11c** that enables angular indexing of the first display mobile unit **10**, as illustrated in FIG. 10.

In an analogous manner, the second display mobile unit **20** is indexed by the beak or the head **82a** that is part of the arm **82**. The head **82a** has two flanks **82b** and **82c**. It is the arrangement of these two flanks cooperating by contact with the flanks of successive teeth of the third toothing **21b** and the fourth toothing **21c** that enables angular indexing of the second display mobile unit **20**, as illustrated in FIG. 10.

14

The elastic return element **84** enables elastic return of the arms or levers **81** and **82** by means of an interface means **83**, such as a lever, that enables transmission and distribution of the force of the elastic return element **84** between the two arms or levers **81** and **82**. The interface means is therefore interfaced or disposed between the arm or the levers **81** and **82** and the elastic return element **84**. The elastic return element **84** is mechanically connected to the frame **99**. For example, the elastic return element **84** is mechanically fixed to the frame **99** at one of its ends. The return element advantageously takes the form of a leaf spring.

The interface means **83** preferably includes a pin **86** that is guided in a groove **85** formed on the frame. Associated with the pin **86**, this groove **85** enables the interface means **83** to offer a first degree of freedom in rotation, in particular about an axis parallel to or substantially parallel to the axis **A5**, and a second degree of freedom in translation relative to the frame perpendicularly to the line of centers defined by the axes **A1** and **A2** or substantially perpendicularly to the line of centers defined by the axes **A1** and **A2**.

In a variant that is not illustrated the pin may be formed on or fixed to the frame and the groove may be formed in the interface means. In other words, in a variant the structure may be reversed.

The interface means **83** includes in particular a first contact zone **83a** or **83a'** cooperating with the elastic return element **84**, in particular with a second end of the leaf spring **84**, a second contact zone **83b** or **83b'** cooperating with the first arm or lever **81** and a third contact zone **83c** or **83c'** cooperating with the second arm or lever **82**, as represented in FIG. 10.

The spring **84** transmits its return force to the interface means **83** via the first contact zone **83a** or **83a'**. This return force is then transmitted to and distributed between the first and second arms **81** and **82** by means of the second and third contact zones **83b** or **83b'** and **83c** or **83c'** respectively.

A second embodiment of a jumper or indexing device **80** is described hereinafter with reference to FIGS. 14 to 16.

The second embodiment of the jumper or indexing device **80** differs from the first embodiment of the jumper or indexing device **80** mainly or only in the geometry of the interface means **83'**.

In the second embodiment of the jumper or indexing device **80** the interface means **83'** advantageously has a globally rectangular or trapezoidal section in the planes of FIGS. 14 to 16 perpendicular to the axes **A1**, **A2** and **A5**.

The interface means **83'** in particular includes a first contact zone **83a'** cooperating with the elastic return element **84**, in particular with the second end of the leaf spring **84**, a second contact zone **83b'** cooperating with the first arm or lever **81** and a third contact zone **83c'** cooperating with the second arm or lever **82**, as represented in FIGS. 14 to 16.

The first contact zone **83a'** may extend along a smaller base of the trapezoidal section. This contact zone advantageously constitutes a cam surface **89** adapted to arm the elastic return element **84** when the interface means pivots in rotation about an axis perpendicular to the plane of FIGS. 14 to 16, in particular about the axis of the pin **86**. In fact, relative to a rest or neutral position like that represented in FIG. 10 in which the surface **89** would be substantially parallel to the end of the leaf spring **84**, in the positions represented in FIGS. 14 and 16 the interface means **83'** has moved in translation downward, in the direction of the leaf spring **84**, perpendicularly to the axis **A5**, and has pivoted about the axis of the pin **86**. These movements cause a first movement or arming of the elastic return element **84** because of the movement in translation of the interface

15

means **83'** and a second movement or arming of the elastic return element **84** because of the rotation of the interface means **83'** via the cam surface **89**. The cam surface **89** is arranged or conformed so that, in the configurations of FIGS. **14** to **16**, the arming of the elastic return element **84** is the same or substantially the same as in the configuration from FIG. **15**, where the interface means has moved in translation downward, in the direction of the leaf spring **84**, perpendicularly to the axis **A5** and without or substantially without pivoting about the axis of the pin **86**.

The distribution of the force produced by the elastic return element **84** between the two arms **81**, **82** depends on the relative positions of the three contact zones **83a**, **83b** and **83c** or **83a'**, **83b'** and **83c'**, the geometries adopted for the arms **81**, **82** and the elastic return element **84** cooperating with these three contact zones **83a**, **83b** and **83c** or **83a'**, **83b'** and **83c'**, the geometry and the position of the guiding action of the means **83** or **83'** and the relative position between the arms **81** and **82**.

In one variant, the first arm and the second arm may consist of the same monobloc or monolithic assembly. In this kind of variant the monobloc or monolithic assembly may be conformed so as to allow a degree of freedom in rotation of the first and second arms about an axis parallel or substantially parallel to or coincident with the axis **A5**, for example by means of Rod Cluster Control type elastic pivots. The interface means **83** or **83'** may equally be part of the monobloc or monolithic assembly and offer a degree of freedom in rotation about an axis parallel to the rotation axis of the first and second arms and a second degree of freedom in translation relative to the frame perpendicularly to the line of centers defined by the axes **A1** and **A2** or substantially perpendicular to the line of centers defined by the axes **A1** and **A2**, via elastic connections formed to this end. The monobloc or monolithic assembly may include a sub-frame adapted to be fixed to the frame and positioned so that the interface means is able to be in contact with the end of the spring. The proposed mobile units indexing device could therefore be constructed in one or more flexible guidance parts able to combine a plurality of parts and/or functions described in the present document.

Regardless of the variant, the greatest dimension of the interface means **83** or **83'** is preferably at least twice or at least three times less than the greatest dimension of the first arm and/or the greatest dimension of the second arm.

In one variant, the geometries of the elastic return element **84**, the interface means **83** or **83'**, the arms **81**, **82** and consequently the contact zones **83a**, **83b** and **83c** or **83a'**, **83b'** and **83c'** could be modified so as to modify the distribution of the force transmitted to the two arms or levers **81**, **82** by the elastic return element **84** via the interface means **83** or **83'**. Employing the same logic, these geometric modifications would make it possible to modify the force and/or the variations of force produced by the elastic return element **84** as a function of the number of arms or levers actuated. It is therefore possible to modulate the return force at the level of the levers as a function of the requirements of the design.

In one variant the various degrees of freedom conferred on the interface means could be obtained with no pin or groove. To this end, the interface means **83** or **83'** would have to be, for example, guided directly by the arms or levers **81**, **82** and/or by the elastic return element **84**, the geometries of those components being adapted of course. With this type of design it would even be possible to add a

16

supplementary degree of freedom, for example a second degree of freedom in translation in a plane perpendicular to the axis **A5**.

In a variant, the pivoting of the arms or levers **81** and **82** could be other than coaxial.

In the variant illustrated in FIG. **10** in particular the two arms or levers **81** and **82** act oppositely to one another relative to the axis **A5**. However, in an alternative variant these two arm or levers **81** and **82** could be superposed, in particular in the situation where the two display mobile units are superposed or coaxial. In that case the interface means **83** or **83'** is advantageously mounted on a pivot connection about an axis parallel to the plane of FIGS. **11** to **13**.

In one variant the mobile units indexing device could equally be implemented with arms or levers **81** and **82** functioning in translation. In that case the interface means **83** or **83'** is advantageously disposed so as to bear against the ends of the arm or levers **81** and **82** functioning in translation.

In different variants the elastic return element **84** could in particular include one or more blades or be a coil spring, a flexible guide or any other device able to apply a return torque or force. The elastic return element could in particular comprise two leaf springs separated by a portion forming a cam adapted to cooperate with the interface means.

In one variant an intermediate part could be added between the interface means **83** or **83'** and the elastic return element **84**.

By extension, the indexing device **80** could equally function with more than two arms or levers.

Different situations of actuation of the arms or levers **81**, **82** as a function of the various possible sequences at the time of a date jump are explained below.

Thanks to the arrangement and to the conformation of the interface means **83** or **83'** the deformation of the elastic return element **84** when the two arms or levers **81**, **82** are actuated may here be advantageously equivalent or substantially equivalent to the deformation of the elastic return element **84** when only one of the two arms or levers **81**, **82** is actuated. This results in an equivalent or substantially equivalent consumption of energy regardless of the number of arms or levers actuated.

One embodiment of a first method for operating a device **100** described above or a timepiece movement **110** described above or a timepiece **120** described above is disclosed hereinafter with reference to FIGS. **7** and **8**.

The method includes:

- a step of the first command mobile unit **30** driving the first display mobile unit **10**, and/or
- simultaneously, a step of the first command mobile unit **30** driving the first display mobile unit **10** and a step of the first display mobile unit **10** driving the second display mobile unit **20** via the second command mobile unit **40**, and/or
- a step of the first command mobile unit **30** driving the second display mobile unit **20**, and/or
- simultaneously, a step of the first command mobile unit **30** driving the second display mobile unit **20** and a step of the second display mobile unit **20** driving the first display mobile unit **10** via the second command mobile unit **40**.

One embodiment of a second method of operating a device **80** described above or a device **100** described above or a timepiece movement **110** described above or a timepiece **120** described above is also disclosed hereinafter with reference FIGS. **11** to **16**.

17

The method includes:

a step of movement of the first arm and/or of the second arm because of the effect of the movement of the first mobile unit **10** and/or of the second mobile unit **20** and a step of arming the elastic return element **84** because of the effect of a movement of the lever **83**, **83'**, and a step of restituting of the elastic return element **84** (that is to say a step of restituting elastic potential energy) causing driving in rotation of the first mobile unit **10** and/or of the second mobile unit **20** via the lever **83**, **83'** and the first arm and/or the second arm, in particular until the first and/or the second mobile unit reaches its next stable or indexed position.

In the embodiment described with reference to FIGS. **14** to **16**, the arming step preferably has the same intensity in at least two of the following situations:

- the arming is brought about by a movement of the first mobile unit,
- the arming is brought about by a movement of the second mobile unit,
- the arming is brought about by a movement of the first and second mobile units.

The kinematic chain for driving the display mobile units **10** and **20** by the command mobile units **30** and **40** varies as a function of the date to jump. The various possible situations are explained below, in particular with reference to the first variant of the first embodiment. The diagrams in FIG. **7** enable these various situations to be illustrated.

Passage from “29” to “30”:

The display device indicates “29”. The toothing **50a** of the intermediate mobile unit **50** effects one step in the anticlockwise direction and drives the fifth toothing **30a** of the first command mobile unit **30** in the clockwise direction. The fifth toothing **30a** therefore drives the first toothing **11b** of the first display mobile unit **10** in the anticlockwise direction. The display of units on the first display disk **12** then passes from the unit “9” to “0”. The fifth toothing **30a** does not drive the third toothing **21b** of the second display mobile unit **20**. However, as it rotates, the toothing **11c** of the first display mobile unit **10** drives the sixth toothing **40a** of the second command mobile unit **40** in turn driving the toothing **21c** of the second display mobile unit **20**. The display of the tens on the second display disk **22** then passes from “2” to “3”.

This driving principle is identical for the passages from “09” to “10” and from “19” to “20”.

Passage from “30” to “31”:

The display device indicates “30”. The toothing **50a** of the intermediate mobile unit **50** effects one step in the anticlockwise direction and drives the fifth toothing **30a** of the first command mobile unit **30** in the clockwise direction. The fifth toothing **30a** therefore drives the toothing **11b** of the first display mobile unit **10** in the anticlockwise direction. The display of units on the first display disk **12** then passes from the unit “0” to “1”. The fifth toothing **30a** does not drive the third toothing **21b** of the second display mobile unit **20**. However, as it rotates, the toothing **11c** of the first display mobile unit **10** drives the sixth toothing **40a** of the second command mobile unit **40** in turn driving the toothing **21c** of the second display mobile unit **20**. The display of tens on the second display disk **22** then passes to the next digit, that is to say from “3” to “3”, the display “3” being duplicated on the disk **22**.

This driving principle is identical for the passages from “10” to “11” and from “20” to “21”, the displays of the “1” and the “2” being also duplicated.

18

Passage from “31” to “01”:

The display device indicates “31”. The fifth toothing **50a** of the intermediate mobile unit **50** effects one step in the anticlockwise direction and drives the fifth toothing **30a** of the first command mobile unit **30** in the clockwise direction. The fifth toothing **30a** is no longer able to drive the toothing **11b** of the first display mobile unit **10** because it is facing a missing, removed or not formed tooth. The fifth toothing **30a** drives the toothing **21b** of the second display mobile unit **20** in the anticlockwise direction. The tens display of the second display disk **22** then goes to the next tens digit, from “3” to “0”. As it rotates, the toothing **21c** of the second display mobile unit **20** is not able to drive the second command mobile unit **40** via the sixth toothing **40a** because here the toothing **21c** is missing, removed or not formed. The first, units display disk **12** of the first display mobile unit **10** then remains in place.

On the passage of the date from “31” to “01” as represented in FIGS. **11** and **14** only the second display mobile unit **20** is driven.

In a first phase of actuation of the second arm **82**, because of the effect of the rotation of the second display mobile unit **20**, the second arm **82** is actuated in a first rotation direction and rises up a tooth of the toothing **21b** or **21c**. As it rotates the second arm **82** arms the elastic return element **84** via the interface means **83** or **83'**. To be more precise, the second contact zone **83b** or **83b'** bearing on the first arm **81** that has remained in place, the interface means **83** or **83'** turns and moves in translation in the groove **85** in a first direction of movement because of the mobility where the second arm **82** bears on the third contact zone **83c** or **83c'**.

In a second phase of actuation of the second arm **82** that follows on after the summit of the tooth of the toothing **21b** or **21c** has been crossed, the second arm **82** is actuated in a second rotation direction and descends the tooth of the toothing **21b** or **21c** because of the effect of the re-arming of the elastic return element **84** via the interface means **83** or **83'**. The interface means **83** or **83'** turns and here moves in translation in a second direction of movement opposite the first direction of movement.

Passage from “01” to “02”:

The display device indicates “01”. The fifth toothing **50a** of the intermediate mobile unit **50** effects one step in the anticlockwise direction and drives the fifth toothing **30a** of the first command mobile unit **30** in the clockwise direction. The fifth toothing **30a** is no longer able to drive the toothing **11b** of the first display mobile unit **10** because it is facing a missing, removed or not formed tooth. On the other hand, this fifth toothing **30a** drives the toothing **21b** of the second display mobile unit **20** in the anticlockwise direction. The tens display of the second display disk **22** then passes to the next digit “0”, the display of the tens digit “0” being duplicated on the disk **22**. As it rotates the toothing **21c** of the second display mobile unit **20** drives the sixth toothing **40a** of the second command mobile unit **40** in turn driving the toothing **11c** of the first display mobile unit **10**. The units display of the first display disk **12** then passes from the units digit “1” to the units digit “2”.

Here the two display mobile units **10** and **20** are driven simultaneously, as illustrated in FIGS. **12** and **15**.

In a first phase of actuation of the two arms, because of the effect of the rotation of the first and second display mobile units **10** and **20**, the first and second arms **81** and **82** are actuated in a first rotation direction respectively rising on teeth of the toothings **11b** or **11c** and **21b** or **21c**. As they rotate the first and second arms **81** and **82** arm the elastic return element **84** via the interface means **83** or **83'**. To be more precise, the interface means **83** or **83'** moves in

19

translation in the groove **85** in a first direction of movement because of the combined effect of the first arm **81** bearing on the second contact zone **83b** or **83b'** and the second arm **82** bearing on the third contact zone **83c** or **83c'**, in such a manner as to arm the elastic return element **84** via the first bearing zone **83a** or **83a'**. Here the movement of the interface means **83** or **83'** corresponds to a movement in translation or substantially in translation. It is possible for the interface means **83** or **83'** to be able to pivot. Nevertheless, this potential movement in rotation is of small amplitude, or even very small amplitude, compared to its movement in translation.

In a second phase of actuation of the two arms that follows on after the summits of the teeth of the toothing **11b** or **11c** and **21b** or **21c** are crossed, the first and second arms **81** and **82** are actuated in a second rotation direction, descending the teeth because of the effect of the re-arming of the elastic return element **84** via the interface means **83** or **83'**. Here the latter moves in translation in a second direction of movement opposite the first direction of movement.

These drive principles are identical for the passage from "11" to "12" and from "21" to "22", the displays of "1" and "2" also being duplicated.

Passage from "02" to "03":

The display device indicates "02". The fifth toothing **50a** of the intermediate mobile unit **50** effects one step in the anticlockwise direction and drives the fifth toothing **30a** of the first command mobile unit **30** in the clockwise direction. The fifth toothing **30a** drives the toothing **11b** of the first display mobile unit **10** in the anticlockwise direction. The units display on the first display disk **12** then passes to the next unit. On the other hand, the tens are not driven. In fact, the fifth toothing **30a** is no longer able to drive the toothing **21b** of the second display mobile unit **20** because it is facing a tooth missing, removed or not formed. Nor is toothing **11c** of the first display mobile unit **10** able to drive the sixth toothing **40a** of the second command mobile unit **40** because a tooth of the toothing **11c** is also missing, removed or not formed here. Because of this, the second command mobile unit **40** and the second display mobile unit **20**, more particularly the second display disk **22**, remain in place.

In this instance, only the first display mobile unit **10** is driven, as represented in FIGS. **13** and **16**.

In a first phase of actuation of the first arm **81**, because of the effect of the rotation of the first display mobile unit **10**, the first arm **81** is actuated in a first rotation direction, rising up a tooth of the toothing **11b** or **11c**. As it rotates the first arm **81** arms the elastic return element **84** via the interface means **83** or **83'**. To be more precise, the third contact zone **83c** or **83c'** bearing on the second arm **82** that has remained in place, the interface means **83** turns and moves in translation in the groove **85** in a first direction of movement because of the mobility where the first arm **81** bears on the second contact zone **83b** or **83b'**.

In a second phase of actuation of the first arm **81**, which follows on after the tooth summit of the toothing **11b** or **11c** is crossed, the first arm **81** is actuated in a second rotation direction, descending the tooth of the toothing **11b** or **11c** because of the effect of the re-arming of the elastic return element **84** via the interface means **83** or **83'**. The interface means **83** or **83'** turns and here moves in translation in a second direction of movement opposite the first direction of movement.

These same principles are applicable to the other jumps from "03" to "09", and for the jumps from "12" to "13" and so on up to "19", and for the jumps "22" to "23" and up to "29".

20

As can be seen in FIGS. **5** and **6** and as explained hereinafter with reference to FIG. **8**, the teeth of the fifth toothing are preferably clipped. In fact, it is in particular necessary to truncate the end of the toothing **30a** so that the latter is able to cooperate with the toothings **11b** and **21b** only on the line of centers passing through the axes **A1** and **A2** and so that there is no risk of the latter interfering with the toothings **11b** and **21b** away from the line of centers.

Thanks to the solutions described above driving is effected by two distinct command mobile units having substantially the same size as the two gears **11** and **21** of the two display mobile units. The overall size in the plane is then advantageously reduced, whilst offering some flexibility for the arrangement of the display mobile units and for the sequencing of the display.

These solutions also allow greater freedom as to the disposition of the display of the date on the dial, but also in terms of the dimensions of the display disks and therefore in the quality of displaying the date.

These solutions do not involve one large command mobile unit, but rather two distinct command mobile units each taking the form of a small gear in a format equivalent or substantially equivalent to that of the gear fixedly attached to the tens disk and/or to that of the gear fixedly attached to the units disk.

The indexing device proposed here advantageously makes it possible to employ only one return element adapted to return two arms or levers able to function independently of one another or simultaneously. This kind of device is therefore cleverly able to solve the problematic of variations in the energy consumption of the movement linked to the simultaneous or non-simultaneous driving of the two "grande date" display mobile units.

Thanks to the solutions in accordance with the invention the energy consumption of the movement when driving the "grande date" is identical or substantially identical whether there is one or are two display mobile units to be driven. To achieve this, the interface means arranged between the elastic return element and the two arms indexing the two display mobile units may be conformed so as to impart to the end of the elastic return means substantially the same movement in a direction perpendicular to or substantially perpendicular to the line of centers that passes through the axes **A1** and **A2** in both situations. FIGS. **11** and **13** illustrates a means that moves by a first amount in a direction perpendicular or substantially perpendicular to the line of centers passing through the axes **A1** and **A2** because of the effect of the movement of the first or second arm. FIG. **12** illustrates a means that moves by a second amount in a direction perpendicular or substantially perpendicular to the line of centers passing through the axes **A1** and **A2** because of the effect of the simultaneous movement of the first and second arms. In the indexing device represented in FIGS. **11**, **12**, and **13** the first and second amplitudes are particularly small, so that the difference between these two amplitudes has no significant effect on the energy consumption of movement. Thus the energy necessary to drive the "grande date" mechanism remains identical or substantially identical whether there is one or there are two display mobile units to be driven and is preferably negligible compared to the energy consumed by the timepiece over 24 hours.

Of course, it is entirely possible to conform the first and/or the second arm and/or the interface means so that the second amplitude of movement of the means in a direction perpendicular or substantially perpendicular to the line of centers passing through the axes **A1** and **A2** to be equal to the first amplitude of movement of the interface means in a direction

21

perpendicular or substantially perpendicular to the line of centers passing through the axes A1 and A2. This kind of conformation is particularly favorable if the stiffness and/or the pre-arming of the spring are increased, in particular with the aim of making the functioning of the indexing device secure. In this case, the energy necessary to drive the “grande date” mechanism remains identical or substantially identical whether there is one or there are two display mobile units to be driven.

Of course, it is entirely possible to conform the first and/or the second arm and/or the interface means so that the amplitude of movements of the interface means in a direction perpendicular or substantially perpendicular to the line of centers passing through the axes A1 and A2 varies as a function of the arm or arms actuated and in particular as a function of the number of arms actuated. Thus the force transmitted to the arm(s) could in particular vary according to the number of arms actuated or according to which arm is actuated.

The timepiece mobiles indexing device solutions could be used in any other device employing a plurality of indexing arms such as, for example, a day-and-date calendar, an annual or semi-perpetual or perpetual date calendar, or a chronograph counting chain.

It could also be used in devices in which the arms would for example serve as a mobile unit brake, clutch clamp or play compensation clamp. Those devices could equally be equivalent to indexing systems.

None of the identified prior art documents discloses an indexing device employing two levers or lever beaks that can be actuated independently of one another or simultaneously cooperating with a single return element the arming level of which is substantially the same whatever the number of beaks actuated. More particularly, none of the identified documents discloses this kind of indexing device for a “grande date” mechanism.

Throughout the present document by “jumper” is preferably meant a position indexing device comprising a beak cooperating with a tothing, in particular with a hollow between two successive teeth of a tothing, to define at least one indexed position of a mobile unit, the beak being urged into the hollow by an elastic element.

Throughout the present document by “tothing” is preferably meant a set of one or more teeth.

Throughout the present document by “mobile unit” is preferably meant an element able to turn about an axis and to effect at least one complete rotation about the axis. The element may comprise a plurality of parts fixedly attached to one another in rotation about the axis. The mobile unit advantageously includes at least one tothing adapted to enable driving of the mobile unit in rotation about the axis, in particular by meshing with another tothing external to the mobile unit.

The invention claimed is:

1. A device for display of an indication of time or derived from the time comprising:

- a first display mobile unit including a first tothing, a second tothing and a first disk carrying digits intended to indicate units of the indication of the time or derived from the time,
- a second display mobile unit including a third tothing, a fourth tothing and a second disk carrying digits intended to indicate tens of the indication of the time or derived from the time, and
- a mechanism for driving the first and second mobile units, the mechanism including:

22

- a first command mobile unit including a fifth tothing adapted to cooperate by obstacle with the first tothing and the third tothing, and
- a second command mobile unit including a sixth tothing adapted to cooperate by obstacle with the second tothing and the fourth tothing.

2. The display device as claimed in claim 1, wherein at least one of the following:

- the first, third and fifth toothings have substantially a same first primitive diameter,
- the second, fourth and sixth toothings have substantially a same second primitive diameter.

3. The display device as claimed in claim 2, wherein the first and second primitive diameters are equal or substantially equal.

4. The display device as claimed in claim 2, wherein the first, third and fifth toothings have substantially a same first primitive diameter.

5. The display device as claimed in claim 2, wherein the second, fourth and sixth toothings have substantially a same second primitive diameter.

6. The display device as claimed in claim 2, wherein the first, third and fifth toothings have substantially a same first primitive diameter and the second, fourth and sixth toothings have substantially a same second primitive diameter.

7. The display device as claimed in claim 1, wherein the first command mobile unit and the second command mobile unit are arranged coaxially on an axis.

8. The display device as claimed in claim 1, wherein the drive mechanism includes a drive wheel including a seventh tothing adapted to drive the first command mobile unit directly or indirectly.

9. The display device as claimed in claim 1, wherein the second command mobile unit is adapted to be driven by at least one selected from the group consisting of the first display mobile unit and the second display mobile unit.

10. The display device as claimed in claim 1, wherein at least one of the following:

- the drive mechanism includes a drive wheel including a seventh tothing adapted to drive the first command mobile unit directly or indirectly, and the drive mechanism includes an intermediate mobile unit cooperating by obstacle with the seventh tothing of the drive wheel and with the fifth tothing of the first command mobile unit,
- the drive mechanism includes a correction mobile unit adapted to actuate the fifth tothing of the first mobile unit directly or indirectly.

11. The display device as claimed in claim 1, wherein the drive mechanism is of an instantaneous jump drive mechanism or a semi-instantaneous jump drive mechanism or a trailing drive mechanism.

12. The display device as claimed in claim 1, wherein the first tothing comprises nine teeth, the second tothing comprises two teeth, the third tothing comprises four teeth and the fourth tothing comprises six teeth.

13. The display device as claimed in claim 1, wherein the first tothing comprises nine teeth, the second tothing comprises two teeth, the third tothing comprises seven teeth and the fourth tothing comprises eight teeth.

14. The display device as claimed in claim 1, wherein at least one of the following:

- the first disk includes the following series of digits “0, 1, 2, 3, 4, 5, 6, 7, 8, 9”,
- the second disk includes the following series of digits “0, 0, 1, 1, 1, 2, 2, 2, 3, 3”.

15. The display device as claimed in claim 1, wherein the device for displaying an indication of the time or derived from the time is a date display device.
16. The display device as claimed in claim 15, wherein the device for displaying an indication of the time or derived 5 from the time is a “grande date” display device, the first disk being a units disk and the second disk being a tens disk.
17. A timepiece movement including a device as claimed in claim 1.
18. A timepiece including a timepiece movement as 10 claimed in claim 17.
19. A method of operating a device as claimed in as claimed in claim 1, the method comprising at least one of the following:
- by the first command mobile unit, driving the first display 15 mobile unit,
- simultaneously, by the first command mobile unit, driving the first display mobile unit, and by the first display mobile unit, driving the second display mobile unit via the second command mobile unit, 20
- by the first command mobile unit, driving the second display mobile unit,
- simultaneously, by the first command mobile unit, driving the second display mobile unit, and by the second display mobile unit, driving the first display mobile unit 25 via the second command mobile unit.
20. The display device as claimed in claim 1, wherein the fifth tothing is adapted to cooperate by meshing with the first tothing and the third tothing, and
- the sixth tothing is adapted to cooperate by meshing with 30 the second tothing and the fourth tothing.

* * * * *