

US 20220210152A1

(19) **United States**

(12) **Patent Application Publication**  
**Parry et al.**

(10) **Pub. No.: US 2022/0210152 A1**

(43) **Pub. Date: Jun. 30, 2022**

(54) **METHOD AND APPARATUS FOR  
AUTHENTICATION OF A USER TO A  
SERVER USING RELATIVE MOVEMENT**

(71) Applicant: **VNS Portfolio LLC**, Calabasas, CA  
(US)

(72) Inventors: **Beau Robertson Parry**, Cincinnati, OH  
(US); **Yasodekshna Boddeti**, Okemos,  
MI (US)

(73) Assignee: **VNS Portfolio LLC**, Calabasas, CA  
(US)

(21) Appl. No.: **17/571,358**

(22) Filed: **Jan. 7, 2022**

**Related U.S. Application Data**

(63) Continuation of application No. 16/748,373, filed on Jan. 21, 2020, now Pat. No. 11,245,693, which is a continuation of application No. 16/017,829, filed on Jun. 25, 2018, now Pat. No. 10,565,362, which is a continuation of application No. 15/675,357, filed on Aug. 11, 2017, now Pat. No. 10,049,203, which is a continuation of application No. 15/460,194, filed on Mar. 15, 2017, now Pat. No. 9,740,848, which is a continuation of application No. 14/827,134, filed on Aug. 14, 2015, now Pat. No. 9,600,649, which is a

continuation of application No. 13/829,180, filed on Mar. 14, 2013, now Pat. No. 9,137,246.

(60) Provisional application No. 61/621,728, filed on Apr. 9, 2012.

**Publication Classification**

(51) **Int. Cl.**

**H04L 9/40** (2006.01)

**H04L 9/08** (2006.01)

**H04W 12/06** (2006.01)

**G06V 40/70** (2006.01)

**G06F 21/36** (2006.01)

**G06F 21/31** (2006.01)

**H04N 7/18** (2006.01)


(52) **U.S. Cl.**

CPC ..... **H04L 63/0861** (2013.01); **H04L 9/0866**  
(2013.01); **H04W 12/068** (2021.01); **G06V**  
**40/70** (2022.01); **G06F 21/36** (2013.01);  
**H04W 12/65** (2021.01); **H04L 63/126**  
(2013.01); **G06F 21/316** (2013.01); **H04L**  
**63/0428** (2013.01); **H04L 63/107** (2013.01);  
**H04N 7/183** (2013.01); **H04L 63/10** (2013.01)


(57)

**ABSTRACT**

Method and apparatus for authentication of a user to a server that involves the user performing a requested act and that further involves relative movement between the user and a camera wherein fiducial marks are captured.










FIG. 2A

FIG. 2B

FIG. 2C

FIG. 2D




FIG. 2E

FIG. 2F

FIG. 2G

FIG. 2H






FIG. 2I




FIG. 2J




FIG. 2K




FIG. 2L




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D






FIG. 5A

FIG. 5B




FIG. 5D

540







FIG. 5C

500














FIG. 7C






FIG. 8A






FIG. 8B






FIG. 9




FIG. 10






FIG. 11




FIG. 12






FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17






FIG. 18A




FIG. 18B






FIG. 19A




FIG. 19B






FIG. 20A




FIG. 20B






FIG. 21





FIG. 22







# METHOD AND APPARATUS FOR AUTHENTICATION OF A USER TO A SERVER USING RELATIVE MOVEMENT

## CROSS-REFERENCE TO RELATED APPLICATION

**[0001]** This application is a continuation of co-pending U.S. application Ser. No. 16/748,373, filed on Jan. 21, 2020 by the same inventors, which is a continuation of U.S. application Ser. No. 16/017,829, filed Jun. 25, 2018 by the same inventors, which is a continuation of U.S. application Ser. No. 15/675,357, filed on Aug. 11, 2017 by the same inventors and entitled “METHOD AND APPARATUS FOR AUTHENTICATION OF A USER TO A SERVER USING RELATIVE MOVEMENT”, which is a continuation of prior U.S. application Ser. No. 15/460,194, filed Mar. 15, 2017 by the same inventors and entitled “AUTHENTICATION METHOD USING RELATIVE MOVEMENT”, which is a continuation of prior U.S. application Ser. No. 14/827,134, filed Aug. 14, 2015 by the same inventors and entitled “AUTHENTICATION METHOD USING LIVENESS VERIFICATION”, which is a continuation of U.S. application Ser. No. 13/829,180, filed on Mar. 14, 2013 by the same inventors and entitled “SYSTEMS, METHODS AND APPARATUS FOR MULTIVARIATE AUTHENTICATION”, which claims the benefit of U.S. provisional patent application Ser. No. 61/621,728, filed on Apr. 9, 2012, entitled “SYSTEMS AND METHODS FOR MULTIVARIATE AUTHENTICATION”, the disclosures of which are all hereby incorporated by reference herein in their respective entireties.

## BACKGROUND OF THE INVENTION

### Description of the Background Art

**[0002]** User authentication has become increasingly of interest as Internet and network-based computer usage have become more prevalent and capabilities of these media have grown. The significance of user authentication has also increased as businesses, government departments, medical organizations and individuals have become increasingly reliant on computer networks and on the security of proprietary information transmitted across networks to users of computing devices.

## SUMMARY

**[0003]** In accordance with one embodiment, a computer-based method of authenticating is provided. The method comprises receiving a request for authentication of a user. The request for authentication comprises biometric feature of the user collected by a user device and contextual data from the user device. The method also comprises comparing the biometric feature of the user to baseline biometric feature of the user, comparing the contextual data to an expected contextual data value, and determining whether to authenticate the user based on the comparison of the biometric feature of the user to the baseline biometric feature of the user and the comparison of the contextual data to the expected contextual data value.

**[0004]** In accordance with another embodiment a computer-based authentication system is provided. The system comprises a baseline image database, a contextual data database, and an authentication computing system. The

authentication system is configured to receive a request for authentication of a user from a user device. The request for authentication comprises an image of the user and contextual data. The authentication system is also configured to compare the image of the user to a baseline image of the user stored in the baseline image database, compare the contextual data to an expected contextual data value stored in the contextual data database, and determine whether to authenticate the user based on the comparison of the biometric feature of the user to the baseline image of the user and the comparison of the contextual data to the expected contextual data value.

**[0005]** In accordance with another embodiment a non-transitory computer readable medium having instructions stored thereon is provided. When the instructions are executed by a processor, they cause the processor to receive a request for authentication of a user. The request for authentication comprises an image of the user collected by a user device and contextual data from the user device. When the instructions are executed by a processor, they also cause the processor to compare the image of the user to a baseline image of the user, compare the contextual data to an expected contextual data value and determine whether to authenticate the user based on the comparison of the biometric feature of the user to the baseline image of the user and the comparison of the contextual data to the expected contextual data value.

**[0006]** In accordance with another embodiment a non-transitory computer readable medium having instructions stored thereon is provided. When the instructions are executed by a processor, they cause the processor to receive from a first user device via a network communication a network packet comprising an electronic data file and recipient biometrics and receive from a second user device via network communication biometric data obtained from a user of the second user device. When the biometric data obtained from the use of the second user device matches the recipient biometrics, the electronic data file is permitted to be accessed on the second user device.

**[0007]** In accordance with yet another embodiment a method of electronically sharing data is provided. The method comprises identifying an electronic file, providing biometrics associated with a recipient, providing contextual data associated with a recipient, causing the electronic file to be encrypted based on the provided biometrics and the provided contextual data and causing the transmission of the encrypted with another embodiment.

## BRIEF DESCRIPTION OF THE DRAWINGS

**[0008]** The present disclosure will be more readily understood from a detailed description of some example embodiments taken in conjunction with the following figures:

**[0009]** FIG. 1 illustrates an example authentication computing system that receives and process identity-based information for use authorization;

**[0010]** FIGS. 2A-2L schematically illustrate various forms of information that may be sent to an authentication computing system via an image in accordance with various non-limiting embodiments;

**[0011]** FIG. 3 illustrates a user device capturing an image of a user in accordance with one non-limiting embodiment;

**[0012]** FIGS. 4A-4D illustrate various image analysis techniques in accordance with non-limiting embodiments;



[0013] FIGS. 5A-5D show example images provided to an authentication computing system;

[0014] FIG. 6 shows a user authentication process in accordance with one non-limiting embodiment;

[0015] FIGS. 7A-7B depict example moving image scans;

[0016] FIG. 7C illustrate an example process flow associated with a moving image scan;

[0017] FIG. 8A illustrates an example moving image scan;

[0018] FIG. 8B illustrates an example process flow associated with a moving image scan utilizing multi-colored strobing;

[0019] FIGS. 9-10 illustrate example authentication processes utilizing multi-image acquisition processes;

[0020] FIG. 11 illustrates an authentication computing system that comprises a local authentication computing system and a remote authentication computing system;

[0021] FIG. 12 illustrates an example data transferring technique utilizing an authentication computing system;

[0022] FIG. 13 illustrates an authentication process for a computing device using a color signature in accordance with one non-limiting embodiment;

[0023] FIG. 14 illustrates an authentication process for an authentication computing system using a color signature in accordance with one non-limiting embodiment

[0024] FIG. 15 illustrates an authentication process for a computing device in accordance with one non-limiting embodiment;

[0025] FIG. 16 illustrates an authentication process of an authentication computing system in accordance with one non-limiting embodiment;

[0026] FIG. 17 illustrates an authentication process in accordance with one non-limiting embodiment;

[0027] FIG. 18A illustrates an example message flow diagram for a registration process;

[0028] FIG. 18B illustrates an example message flow diagram for an authentication process;

[0029] FIG. 19A illustrates an example simplified block diagram for a user registration process;

[0030] FIG. 19B illustrates an example simplified block diagram for a user authentication process;

[0031] FIG. 20A illustrates an example process for registering a user with an authentication computing system;

[0032] FIG. 20B illustrates an example process for authenticating a registered user of an authentication computing system;

[0033] FIG. 21 illustrates an example block diagram of a communication system;

[0034] FIG. 22 illustrates a system flow diagram for photo cloaking utilizing biometric key generation; and

[0035] FIG. 23 illustrates an example biometric encryption system flow diagram.

#### DETAILED DESCRIPTION

[0036] Various non-limiting embodiments of the present disclosure will now be described to provide an overall understanding of the principles of the structure, function, and use of the authentication systems and processes disclosed herein. One or more examples of these non-limiting embodiments are illustrated in the accompanying drawings. Those of ordinary skill in the art will understand that systems and methods specifically described herein and illustrated in the accompanying drawings are non-limiting embodiments. The features illustrated or described in connection with one non-limiting embodiment may be com-

bined with the features of other non-limiting embodiments. Such modifications and variations are intended to be included within the scope of the present disclosure.

[0037] The presently disclosed embodiments are generally directed to user identification and authorization. Such systems and methods may be implemented in a wide variety of contexts. In one example embodiment, the presently disclosed systems and methods allow the identity of a user of a computing device to be authenticated. The user may be authenticated through a multivariate platform, as described in more detail below. In some embodiments, the authentication process may process an image supplied by the computing device to the authentication computing system. The process may utilize a biometric attribute of the user along with one or more additional authentication variables in order to confirm an identity of the user. The image may, for example, include a user gesture, a flash burst, or other authentication variable. The gesture, the relative location of the gesture, and/or the relative location of the flash may be compared to a baseline image as part of the authentication process. In some implementations, contextual data associated with the image may be processed as part of the authentication process. Such contextual data (sometimes referred to as “meta-data”) may include, without limitation, a machine ID, device data, or geographical/location information. As described in more detail below, contextual data may also include data obtained from sensors onboard a user computer device. Example sensors include accelerometers, magnetometers, proximity sensors, and the like. Such sensors may provide contextual data such as movement data and user device orientation data, for example.

[0038] In some example embodiments, a computing device may display a particular color on its graphical display screen during an authentication process. The particular color may have been provided to the computing device by an authentication system. The image subsequently provided to the authentication computing system by the computing device may include an image of the user with the particular color reflected off of facial features of a user to form a color signature. Along with biometrical facial features of the user, the particular color present in the image and the color signature may be analyzed by an authentication computing system to provide user authentication.

[0039] In some example embodiments, at least some of the communication between a computing device and an authentication computing system is encrypted using any suitable encryption technique. In one example embodiment, chaos-based image encryption may be used, although this disclosure is not so limited. Additional details regarding chaos-based image encryption may be found in “Chaos-Based Image Encryption” by Yaobin Mao and Guaron Chen (available at <http://www.open-image.org/725publication/journal/CBIE.pdf>), which is incorporated herein by reference. In one example embodiment, images provided to the authentication computing system by a computing device are encrypted through a pixel-rotation technique, a codec watermarking technique, and/or other encrypting technique.

[0040] Generally, the presently disclosed systems and methods may authenticate a user before giving the user access to a mobile computer device, access to an application on a computer device, access to a building or other structure, access to a web portal, access to any other type of computing device, access to data, or access to any other secured virtual or physical destination. The authentication can be based on



a combination of biometric analysis and contextual data analysis, with the contextual data based on a user device of the user seeking authentication. Therefore, the presently disclosed systems and methods generally bind man and machine to effectuate the authentication paradigms described in more detail below.

**[0041]** Reference throughout the specification to “various embodiments,” “some embodiments,” “one embodiment,” “some example embodiments,” “one example embodiment,” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. Thus, appearances of the phrases “in various embodiments,” “in some embodiments,” “in one embodiment,” “some example embodiments,” “one example embodiment,” or “in an embodiment” in places throughout the specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures or characteristics may be combined in any suitable manner in one or more embodiments.

**[0042]** Referring now to FIG. 1, one example embodiment of the present disclosure may comprise an authentication computing system **100** that receives and processes identity-based information to execute user authorization. The authentication computing system **100** may be provided using any suitable processor-based device or system, such as a personal computer, laptop, server, mainframe, or a collection (e.g., network) of multiple computers, for example. The authentication computing system **100** may include one or more processors **116** and one or more computer memory units **118**. For convenience, only one processor **116** and only one memory unit **118** are shown in FIG. 1. The processor **116** may execute software instructions stored on the memory unit **118**. The processor **116** may be implemented as an integrated circuit (IC) having one or multiple cores. The memory unit **118** may include volatile and/or non-volatile memory units. Volatile memory units may include random access memory (RAM), for example. Non-volatile memory units may include read only memory (ROM), for example, as well as mechanical non-volatile memory systems, such as, for example, a hard disk drive, an optical disk drive, etc. The RAM and/or ROM memory units may be implemented as discrete memory ICs, for example.

**[0043]** The memory unit **118** may store executable software and data for authentication engine **120**. When the processor **116** of the authentication computing system **100** executes the software of the authentication engine **120**, the processor **116** may be caused to perform the various operations of the authentication computing system **100**, such as send information to remote computer devices, process information received from remote computer devices, and provide authentication information to the remote computer devices, as discussed in more detail below. Data used by the authentication engine **120** may be from various sources, such as a baseline image database **124**, which may be an electronic computer database, for example. The data stored in the baseline image database **124** may be stored in a non-volatile computer memory, such as a hard disk drive, a read only memory (e.g., a ROM IC), or other types of non-volatile memory. Also, the data of the database **124** may be stored on a remote electronic computer system, for example. Machine ID database **126**, which may be an electronic computer database, for example, may also provide used by the authentication engine **120**. The data stored in the machine ID

database **126** may be stored in a non-volatile computer memory, such as a hard disk drive, a read only memory (e.g., a ROM IC), or other types of non-volatile memory. Also, the data of the Machine ID database **126** may be stored on a remote electronic computer system, for example. In some embodiments, the Machine ID database comprises mobile equipment identification (MEID) numbers, Electronic Serial Numbers (ESN), and/or other suitable identifying indicia that may be used to identify electronic devices. While machine ID database **126** is illustrated as storing expected contextual data related to an identifier of a user device, it is to be appreciated that other embodiments may utilize other databases configured to store other forms of expected contextual data (expected movement data, expected geolocation data, expected magnetic data, and so forth) that may be compared to contextual data received from a user device during an authentication process.

**[0044]** The authentication computing system **100** may be in communication with user devices **102** via an electronic communications network (not shown). The communications network may include a number of computer and/or data networks, including the Internet, LANs, WANs, GPRS networks, etc., and may comprise wired and/or wireless communication links. In some example embodiments, an authentication system API is used to pass information between the user devices **102** and the authentication computing system **100**. The user devices **102** that communicate with the authentication computing system **100** may be any type of client device suitable for communication over the network, such as a personal computer, a laptop computer, or a netbook computer, for example. In some example embodiments, a user may communicate with the network via a user device **102** that is a combination handheld computer and mobile telephone, sometimes referred to as a smart phone. It can be appreciated that while certain embodiments may be described with users communication via a smart phone or laptop by way of example, the communication may be implemented using other types of user equipment (UE) or wireless computing devices such as a mobile telephone, personal digital assistant (PDA), combination mobile telephone/PDA, handheld device, mobile unit, subscriber station, game device, messaging device, media player, pager, or other suitable mobile communications devices. Further, in some example embodiments, the user device may be fixed to a building, vehicle, or other physical structure.

**[0045]** Some of the user devices **102** also may support wireless wide area network (WWAN) data communications services including Internet access. Examples of WWAN data communications services may include Evolution-Data Optimized or Evolution-Data only (EV-DO), Evolution For Data and Voice (EV-DV), CDMA/1×RTT, GSM with General Packet Radio Service systems (GSM/GPRS), Enhanced Data Rates for Global Evolution (EDGE), High Speed Downlink Packet Access (HSDPA), High Speed Uplink Packet Access (HSUPA), and others. The user device **102** may provide wireless local area network (WLAN) data communications functionality in accordance with the Institute of Electrical and Electronics Engineers (IEEE) 802.xx series of protocols, such as the IEEE 802.11a/b/g/n series of standard protocols and variants (also referred to as “Wi-Fi”), the IEEE 802.16 series of standard protocols and variants (also referred to as “WiMAX”), the IEEE 802.20 series of standard protocols and variants, and others.



[0046] In some example embodiments, the user device 102 also may be arranged to perform data communications functionality in accordance with shorter range wireless networks, such as a wireless personal area network (PAN) offering Bluetooth® data communications services in accordance with the Bluetooth®. Special Interest Group (SIG) series of protocols, specifications, profiles, and so forth. Other examples of shorter range wireless networks may employ infrared (IR) techniques or near-field communication techniques and protocols, such as electromagnetic induction (EMI) techniques including passive or active radio-frequency identification (RFID) protocols and devices.

[0047] The user device 102 may comprise various radio elements, including a radio processor, one or more transceivers, amplifiers, filters, switches, and so forth to provide voice and/or data communication functionality. It may be appreciated that the user device 102 may operate in accordance with different types of wireless network systems utilize different radio elements to implement different communication techniques. The user device 102 also may comprise various input/output (I/O) interfaces for supporting different types of connections such as a serial connection port, an IR port, a Bluetooth® interface, a network interface, a Wi-Fi interface, a WiMax interface, a cellular network interface, a wireless network interface card (WNIC), a transceiver, and so forth. The user device 102 may comprise one or more internal and/or external antennas to support operation in multiple frequency bands or sub-bands such as the 2.4

GHz range of the ISM frequency band for Wi-Fi and Bluetooth® communications, one or more of the 850 MHz, 900 MHz, 1800 MHz, and 1900 MHz frequency bands for GSM, CDMA, TDMA, NAMPS, cellular, and/or PCS communications, the 2100 MHz frequency band for CDMA2000/EV-DO and/or WCDMA/JMTS communications, the 1575 MHz frequency band for Global Positioning System (GPS) operations, and others.

[0048] The user device 102 may provide a variety of applications for allowing a user to accomplish one or more specific tasks using the authentication computing system 100. Applications may include, without limitation, a web browser application (e.g., INTERNET EXPLORER, MOZILLA, FIREFOX, SAFARI, OPERA, NETSCAPE NAVIGATOR) telephone application (e.g., cellular, VoIP, PTT), networking application, messaging application (e.g., e-mail, IM, SMS, MMS, BLACKBERRY Messenger), contacts application, calendar application and so forth. The user device 102 may comprise various software programs such as system programs and applications to provide computing capabilities in accordance with the described embodiments. System programs may include, without limitation, an operating system (OS), device drivers, programming tools, utility programs, software libraries, application programming interfaces (APIs), and so forth. Exemplary operating systems may include, for example, a PALM OS, MICROSOFT OS, APPLE OS, UNIX OS, LINUX OS, SYMBIAN OS, EMBEDIX OS, Binary Run-time Environment for Wireless (BREW) OS, JavaOS, a Wireless Application Protocol (WAP) OS, and others.

[0049] In general, an application may provide a user interface to communicate information between the authentication computing system 100 and the user via user devices 102. The user devices 102 may include various components

for interacting with the application such as a display for presenting the user interface and a keypad for inputting data and/or commands. The user devices 102 may include other components for use with one or more applications such as a stylus, a touch-sensitive screen, keys (e.g., input keys, preset and programmable hot keys), buttons (e.g., action buttons, a multidirectional navigation button, preset and programmable shortcut buttons), switches, a microphone, speakers, an audio headset, a camera, and so forth. Through the interface, the users may interact with the authentication computing system 100.

[0050] The applications may include or be implemented as executable computer program instructions stored on computer-readable storage media such as volatile or non-volatile memory capable of being retrieved and executed by a processor to provide operations for the user devices 102. The memory may also store various databases and/or other types of data structures (e.g., arrays, files, tables, records) for storing data for use by the processor and/or other elements of the user devices 102.

[0051] As shown in FIG. 1, the authentication computing system 100 may include several computer servers and databases. For example, the authentication computing system 100 may include one or more web servers 122 and application servers 128. For convenience, only one web server 122 and one application server 128 are shown in FIG. 1, although it should be recognized that this disclosure is not so limited. The web server 122 may provide a graphical web user interface through which users of the system may interact with the authentication computing system 100. The web server 122 may accept requests, such as HTTP requests, from clients (such as web browsers on the device 102), and serve the clients responses, such as HTTP responses, along with optional data content, such as web pages (e.g., HTML documents) and linked objects (such as images, etc.).

[0052] The application server 128 may provide a user interface for users who do not communicate with the authentication computing system 100 using a web browser. Such users may have special software installed on their user devices 102 that allows them to communicate with the application server 128 via the network. Such software may be downloaded, for example, from the authentication computing system 100, or other software application provider, over the network to such user devices 102. The software may also be installed on such user devices 102 by other means known in the art, such as CD-ROM, etc.

[0053] The servers 122, 128 may comprise processors (e.g., CPUs), memory units (e.g., RAM, ROM), non-volatile storage systems (e.g., hard disk drive systems), etc. The servers 122, 128 may utilize operating systems, such as Solaris, Linux, or Windows Server operating systems, for example.

[0054] Although FIG. 1 depicts a limited number of elements for purposes of illustration, it can be appreciated that the authentication computing system 100 may include more or less elements as well as other types of elements in accordance with the described embodiments. Elements of the authentication system 100 may include physical or logical entities for communicating information implemented as hardware components (e.g., computing devices, processors, logic devices), executable computer program instructions (e.g., firmware, software) to be executed by various hardware components, or combination thereof, as desired for a given set of design parameters or performance constraints.



**[0055]** In addition to the end user devices **102**, the authentication computing system **100** may be in communication with other entities, such as a biometric ID module **112**. In some example embodiments, biometric ID functionality may be supplied from one or more third party biometric services providers. One example provider of biometric services is available at <http://www.face.com> and accessible via an application programming interface (API). Other services may be provided by other third party providers, such as geolocation services, which may be provided by a geolocation module **114** through an API. An example geolocation service is the W3C Geolocation API provided by the World Wide Web Consortium (W3C). In some embodiments, biometric ID and/or geolocation services may be provided by the authentication computing system **100** without the aid of outside service providers. For example, biometric information of users of the system may be stored by the authentication computing system.

**[0056]** During an authentication event, the authentication computing system **100** may receive and process an encrypted network packet **106** from the user device **102**. The encrypted network packet **106** may be encrypted using chaos-based image encryption, for example. The network packet **106** may include an image **108** and may also include contextual data **110**. The image **108** may include, for example, an image of the user for biometric analysis. The image **108** may also include additional image data that may be analyzed and processed by the authentication computing system **100**. For example, the additional image data may include, without limitation, a source of light at a particular location in the image relative to the user, a particular gesture by the user, a particular facial expression by the user, a particular color reflected off a portion of the user, and so forth. The contextual data **110** may include, without limitation, a machine ID, locational information, device global positioning system (GPS) information, radio-frequency identification (RFID) information, near-field communication (NFC) information, MAC address information, and so forth. For user devices **102** supporting a position determination capability, examples of position determination capability may include one or more position determination techniques such as Global Positioning System (GPS) techniques, Assisted GPS (AGPS) techniques, hybrid techniques involving GPS or AGPS in conjunction with Cell Global Identity (CGI), Enhanced Forward Link Trilateration (EFLT), Advanced Forward Link Trilateration (AFTL), Time Difference of Arrival (TDOA), Angle of Arrival (AOA), Enhanced Observed Time Difference (EOTD), or Observed Time Difference of Arrival (OTDOA), and/or any other position determination techniques in accordance with the described embodiments. The image **108** and any other information associated with the image may be purged by the user device **102** subsequent to the transmission of the image **108** to the authentication computing system **100**.

**[0057]** The encrypted network packet **106** may be sent to the authentication computing system **100** in response to a user's interaction with the user device **102**. For example, a user may be seeking to log into a restricted website, access a restricted website, access a restricted file, access a restricted building, or access a restricted computing device. Upon receipt of the encrypted network packet **106** (which may be comprised of a plurality of individual network packets) the authentication computing system **100** may decrypt the information in order to process the image **108**

and any associated contextual data **110**. If a third party biometric ID module **112** is used, information may be provided to the service provider through an API. For example, the biometric ID module **112** may analyze facial features of the user to ascertain identity. The additional image data in the image **108** (such as relative flash placement, for example) may be compared to a baseline image stored in the baseline image database **124**. In some example embodiments, additional comparisons or analysis may be performed on the contextual data **110**, the image **108**, or other information contained in the encrypted network packet **106**.

**[0058]** In some embodiments, the encrypted network packet **106** may include an audio file **109** which includes a voice of the user, in addition to the contextual data **110**. The audio file **109** may be included, for example, in the place of the image **108** when an image of the user cannot be obtained. The audio file **109** may be processed by the authentication computing system **100** to compare the audio file **109** to a known voice signature of the user. The audio file **109** may be collected by the user device **102** and transmitted to the authentication computing system **100** when it is deemed, for example, that an onboard camera of the user device **102** is not functioning. In other embodiments, both the image **108** and the audio file **109** are required by the authentication computing system **100** for authentication.

**[0059]** Once the user has been authenticated, verification **130** indicating that the user has been properly authenticated may be provided to the user device **102** by the authentication computing system **100**. The verification **130** may be in any suitable form. For example, the verification **130** may indicate to an application running on the user device **102** that the user is an authorized user. Subsequent to receiving the verification, the user device **102** may allow the user to log into a restricted website, access a restricted website, access a restricted file, access a restricted building, or access a restricted computing device, for example.

**[0060]** FIGS. 2A-2L schematically illustrate various forms of information that may be sent to the authentication computing system **100** via an image in order to authenticate a particular user. As is to be appreciated, the illustrated images are merely examples of illustrative embodiments and are not intended to be limiting.

**[0061]** Referring first to FIG. 2A, in one example embodiment, an image **200** comprises a biometric feature and a flash location. The biometric feature may be, for example, a facial feature, a hand feature, a retinal feature, a biological sinusoidal rhythm, and so forth. The flash location, as described in more detail below, may be the relative position of a point of light relative to the biometric feature. Referring next to FIG. 2B, in one example embodiment, an image **210** comprises a biometric feature and a gesture. The gesture may be, for example, a hand gesture, a multi-hand gesture, a facial expression, an arm position, and so forth. Referring next to FIG. 2C, in one example embodiment, an image **212** comprises a biometric feature, a gesture, and a flash location. Referring next to FIG. 2D, in one example embodiment, an image **214** comprises a biometric feature, a gesture location, and a flash location.

**[0062]** Referring to FIG. 2E, in one example embodiment, an image **216** comprises a biometric feature and a color feature. As described in more detail below, in some example embodiments, prior to capturing the image, the computer device may output a particular color on its graphical display



such that can reflect off a biometric feature of the user as a color signature. The reflected color, along with the biometric features, may be analyzed by the authentication computing system 100 to confirm identity. Referring next to FIG. 2F, in one example embodiment, an image 218 comprises a biometric feature, a flash location, and a color feature. Referring next to FIG. 2G, in one example embodiment, an image 220 comprises a biometric feature, a color feature, and a gesture.

[0063] Referring to FIG. 2H, in one example embodiment, an image 224 comprises a biometric feature and a gesture. Machine ID may also be associated with the image 224 and provided to the authentication computing system 100. The machine ID may be contextual data, which may include any type of additional data, such as locational information, GPS information, RFID information, NFC information, MAC address information, device data, and so forth. The machine ID provided as contextual data may be compared to machine ID stored by the authentication computing system 100. For example, the authentication computing system 100 may compare the locational information provided with the image 224 to an expected location stored by the system. If the image 224 was not captured at a geographical location near the expected location, authentication will not be successful.

[0064] Referring to FIG. 2I, in one example embodiment, an image 226 comprises a biometric feature and a flash angle. The flash angle may be, for example, an angle of incidence of the flash. A non-limiting example of flash angle determination is described in more detail with regard to FIG. 4D. Referring now to FIG. 2J, an image 228 comprise a biometric feature and a user device angle. The value of the user device angle may be measured by an accelerometer on-board the user device, for example.

[0065] Referring now to FIG. 2K, an image 230 comprises a biometric feature and locational information. The locational information may be gathered by an on-board GPS, for example. In one embodiment, the location information can include longitude, latitude, and altitude. The image 230 may also comprise flash angle information.

[0066] Referring next to FIG. 2L, an image 232 may comprise a biometric feature, flash/shutter synchronicity information, and a gesture location. With regard to flash/shutter synchronicity, the authentication computing system 100 may communicate with the user device 102 during the image capture process to control the relative timing of the flash and the shutter. For example, the authentication computing system 100 may cause a slight flash delay or shutter delay to give the captured image a particular flash signature. A change in the flash delay or shutter delay may result in a different flash signature. The flash signature in the image may be analyzed by the authentication computing system 100 as an authentication variable.

[0067] It is noted that the informational components of the various images illustrated in FIGS. 2A-2L are merely for illustrative purposes. In fact, images provided to the authentication computing system 100 may include any number of authentication variables and/or any combination of authentication variables. The number or combination of authentication variables transmitted with the image may depend, at least in part, on a desired level of security. In some embodiments, the number authentication variables used and/or the priority of the authentication variables may be based on the available resources at the time of authentication. As described in more detail below, example resources that may

be considered included, without limitation, battery supply, data transmission rates, network signal strength, and so forth.

[0068] In some embodiments, the authentication computing system may require user authentication based on contextual operational information, such as the geographical location of the user device or the period of time since a previous successful authentication, for example. By way of example, a user of a user device may power down a user device during a plane flight. Upon arriving at the destination, the user device will be powered up. The distance between the particular geographic location of the user device upon power down and the particular geographic location of the user device upon power up can be assessed. If the distance is beyond a predetermined distance threshold, the user device may require user authentication before providing user access.

[0069] Furthermore, in some embodiments, the user device may include a plurality of data collection devices that each requires different levels of operational resources. For example, a smart phone may have two on-board cameras, a high-resolution camera and a low-resolution camera. Images captured using the low-resolution camera requires less data and, therefore, such camera may be useful during times of low data transmission rates. In such instances, the biometric data collected from the user may include periocular data, for example. If the user device is operating on a network connection having high data transmission rates, the high-resolution camera may be used. In any event, the systems and methods described herein may alter or shift the type of authentication variables considered, and the techniques for gathering such variables, based on operational or environmental factors existing at the time of the authentication request. The systems and methods described herein may use additional techniques or processes to compensate for operational conditions. For example, during low light conditions, a particular color may be displayed on a screen of the user device, such that the screen can be held proximate to the user to illuminate the user's face with that particular hue. The particular color may change over time (such as in a strobed fashion), with the shutter coordinated with the pulses of light. As such, as an additional layer of security, an image with a particular color reflected off of the user's face can be compared with an expected color.

[0070] FIG. 3 illustrates a user device 304 capturing an image of a user in accordance with the presently disclosed systems and methods. The user is positioned in front of a reflective surface 310, such as a mirror or reflective window, for example. Prior to capturing the image, a light source 306 (such as a flash on a smart phone) is activated. The user may then position the light source reflection 308 at a pre-defined position relative the user reflection 302. The pre-defined position may be based on a desired angle of incidence, a desired distance from the user, or other desired relative location. While not shown, in some embodiments, the user may additionally make a gesture for reflection by the reflective surface 310. Once in the proper position, a camera 312 associated with the user device 304 may capture an image of the reflective surface 310. The image, similar to image 108 in FIG. 1, for example, may be provided to an authentication computing system local to the user device 304 or to a remote authentication computing system via a networked connection. In some example embodiments, the reflective surface 310 may include a communication element 316. The com-



munication element **316** may utilize, for example, a BLUETOOTH® communication protocol or a near-field communication protocol. The communication element **316** may provide additional data (such as contextual data) that may be transmitted along with the image to the authentication computing system.

[0071] Various forms of assistance may be provided to the user by the authentication computing system **100** during the image capture process illustrated in FIG. 3. In one embodiment, for example, a visual cue is provided to the user on the screen of the user device **304**. The visual cue may provide an indication of the relative proper placement of the user device **304** in the image for a particular image capture session. The visual cue may be, without limitation, a solid dot on the screen, a flashing dot on the screen, a grid on the screen, graphical bars or lines on the screen, or any other suitable visual cue.

[0072] The particular location of the visual cue on the screen may be provided to the user device **304** by signaling from the authentication computing system **100**. In various embodiments, the particular location of the visual cue may change for each image capture process (similar to a rolling code, for example). As the user positions themselves in front of the reflective surface **310**, they may also position the user device **304** in the proper relative placement as noted by the visual cue. The user may also provide any additional authentication variables (such as a gesture, gesture location, user device angle, and so forth). Once the user device **304** is in the proper position the user device **304** may automatically capture the image without additional input from the user. For example, in one operational example, the screen of the user device **304** may have a visual indication flashing in the upper left quadrant of the screen. Once the user device **304** detects, through image analysis, that the user device **304** is positioned in the upper left quadrant of the image, an image may be automatically captured and transmitted to the authentication computing system **100**. While in some embodiments, the user device **304** may automatically capture an image, in other embodiments the user may initiate the image capture by pressing a button (physical or virtual) on the user device **304**.

[0073] It is noted that an audio cue may alternatively or additionally serve as a form of assistance. For example, when the user has positioned in the user device **304** in the proper relative position, an audible alert may be provided by the user device **304**. As is to be appreciated, other forms of assistance may be used, such as haptic feedback, for example.

[0074] The various image components of the image received from the user device **304** by an authentication computing system may be analyzed using any number of analytical techniques. FIG. 4A shows an analysis technique that divides the image **400** into a grid sixteen square segments. In one embodiment, the grid is keyed to a chin **404** of the user. As illustrated, the reflected light source **406** in the image **400** is located in segment **8**. As part of the authentication, the authentication computing system analyzing the image **400** could use a two part process. First, the identity of the user could be determined by a biometric analysis of the user image **402**. Second, the relative placement of the reflected light source **406** in the image could be used as an authentication variable. For example, a comparison could be made to a baseline image stored in a database in order to confirm the reflected light source **406** is in the

proper segment. In some embodiments, the proper segment may change over time. In such embodiments, a user of the system would know in which segment to place the reflected light source **406** based on a time of day, day of the week, or based on where the user was physically located, for example.

[0075] FIG. 4B shows an analysis technique that uses distances between various features of the image **420** to confirm identity and provide authorization. The illustrated embodiment shows a shoulder width distance **422**, a chin to shoulder vertical distance **424**, and a reflected light source to chin distance **426** as variables. In some example embodiments, a relative angle of the reflected light source may be calculated or measured and compared to a baseline angle.

[0076] FIG. 4C shows an analysis technique that divides the image **440** into a plurality of pie shaped segments. While the illustrated embodiment shows six pie segments, this disclosure is not so limited. For example, the image **440** may be divided up into 12 pie shaped segments to emulate the face of an analog clock. The pie shaped segments may converge on the nose **442** of the user image **402**, or may converge on another location (such as a gesture). As shown, the user is placing the reflected light source **406** in segment “B.” Similar to the embodiment illustrated in FIG. 4A, the segment in FIG. 4C providing proper authorization may change over time. With a rolling segment approach, the overall security offered by the system may be increased.

[0077] FIG. 4D shows an analysis technique for determining an angle of incidence (shown as “ $\theta$ ”) of the light source **306**. The angle  $\theta$  may be compared to a stored angular value as part of the authentication process. In FIG. 4D a top view of the user device **304** capturing a user image **402** and reflected light source **406** is provided. In the illustrated embodiment, angle  $\theta$  is function of a distance **450** (the distance between the reflected light source **406** and a center of the user image **402**) and the distance **458** (the distance between the user/light source **306** and the reflective surface **310**). The distance **450** may be orthogonal to distance **458**. It is noted that while the light source **306** and the user are illustrated as being co-planar with the reflected surface **310**, this disclosure is not so limited. In other words, in some implementations, the user may position the light source **306** either closer to the reflective surface **310** or further way from the reflected surface **310** relative to the user.

[0078] The distance **458** may be determined by the authentication computing system **100** based on an analysis of one or more facial dimensions (or ratios of dimensions) of the user image **402**. For example, a head width dimension **452**, an eye width dimension **456**, and/or a nose-to-ear dimension **454** may be determined by any suitable image processing technique. In one embodiment, the user image **402** may be vectorized by the authentication computing system **100** as part of the image analysis processing. Once the dimension(s) (and/or ratios) are determined, they can be compared to known biometric data stored by the authentication computing system **100** in order to extrapolate the distance **458**. The distance **450** can also be determined, for example, by image analysis of the image received by the authentication computing system **100**.

[0079] Once distances **450** and **458** are determined, in one embodiment, the angle  $\theta$  may be calculated based on Equations 1 and 2:



$$\tan\theta = \frac{\text{Distance } 450}{\text{Distance } 458} \quad \text{EQ. 1}$$

$$\theta = \text{ArcTan} \frac{\text{Distance } 450}{\text{Distance } 458} \quad \text{EQ. 2}$$

[0080] Once angle  $\theta$  has been determined, it can then be compared to an angular value stored by the authentication computing system 100 as an authentication variable.

[0081] By way of example, an angular value of  $30^\circ$  may be stored by the authentication computing system 100. If the determined angle  $\theta$  is in the range of  $27^\circ$  to  $33^\circ$ , for example, the flash angle may be deemed authenticated. It is to be appreciated that the acceptable range of angles may vary. In some embodiments, for example, the determined angle may be authenticated if it is within  $\pm 25\%$  of the stored angular value, while other embodiments may only permit authentication if the determined angle is within  $\pm 1\%$  of the stored angular value.

[0082] In some embodiments, real-time image analysis of the image feed from the camera 312 may be used during the image capture process. For example, the image feed may be analyzed to determine one or more facial dimensions (or ratios of dimensions) of the user image 402, such as the head width dimension 452 and the eye width dimension 456. When the dimensions are at a predetermined value (which may indicate the user is at a proper distance 458 from the reflective surface 310) the image may be automatically captured. As is to be appreciated, visual and/or audio cues can be provided to the user to assist with proper placement. Similar to above, the distance 450 may be determined by image analysis of the image received by the authentication computing system 100. Angle  $\theta$  may then be determined using Equations 1 and 2, for example.

[0083] FIGS. 5A-5D show example images provided to an authentication computing system. Image 500 in FIG. 5A shows a user 504 holding a light source 506 at one position and a gesture 502 at another position. Images 500, 520, 540, and 560 illustrate the user 504, the light source 506, and the gesture 502 at other relative positions. As it to be appreciated, the features 504, the relative placement of the light source 506, the gesture 502, and the relative placement of the gesture relative to the user 504 and/or the light source 506 may be analyzed in accordance with the systems and methods described herein. It is noted that FIG. 5D illustrates that the image 560 may also include contextual data for processing by the authentication computing system. The contextual data may include device information, geographical location data, or other information which may be compared to expected contextual data stored by the system.

[0084] In some example embodiments, in addition or alternatively to the various authentication techniques described above, various authentication systems may perform a color signature analysis on the incoming image as part of the authentication process. FIG. 6 shows a user authentication process in accordance with one non-limiting embodiment. As shown at an event 610, a user is interacting with a computer device 612. The computing device 612 may be similar to user device 102 (FIG. 1) and may include a camera 614 and a graphical display 616. The computer device 612 may send a request 692 to an authentication module 600 through a communications network 690. The request 692 may be dispatched by an application running on

the computing device 612. The request may include any information needed by the authentication module 600. The request may include, for example, a device ID or a user ID. Upon receipt of the request 692, the authentication computing system 600 may transmit a color key 694. The color key 694 may be stored in a color database 602. In various embodiments, the color key 694 may be in the form of a hex code or a decimal code, as shown in Table 1.

TABLE 1

COLOR CHART		
HTML name	Hex code R G B	Decimal code R G B
IndianRed	CD 5C 5C	205 92 92
LightCoral	F0 80 80	240 128 128
Salmon	FA 80 72	250 128 114
DarkSalmon	E9 96 7A	233 150 122
LightSalmon	FF A0 7A	255 160 122
Red	FF 00 00	255 0 0
Crimson	DC 14 3C	220 20 60
FireBrick	B2 22 22	178 34 34
DarkRed	8B 00 00	139 0 0
Pink	FF C0 CB	255 192 203
LightPink	FF B6 C1	255 182 193
HotPink	FF 69 B4	255 105 180
DeepPink	FF 14 93	255 20 147
MediumVioletRed	C7 15 85	199 21 133
PaleVioletRed	DB 70 93	219 112 147
LightSalmon	FF A0 7A	255 160 122
Coral	FF 7F 50	255 127 80
Tomato	FF 63 47	255 99 71
OrangeRed	FF 45 00	255 69 0
DarkOrange	FF 8C 00	255 140 0
Orange	FF A5 00	255 165 0
Gold	FF D7 00	255 215 0
Yellow	FF FF 00	255 255 0
LightYellow	FF FF E0	255 255 224
LemonChiffon	FF FA CD	255 250 205
LightGoldenrodYellow	FA FA D2	250 250 210
PapayaWhip	FF EF D5	255 239 213
Moccasin	FF E4 B5	255 228 181
PeachPuff	FF DA B9	255 218 185
PaleGoldenrod	EE E8 AA	238 232 170
Khaki	F0 E6 8C	240 230 140
DarkKhaki	BD B7 6B	189 183 107
Lavender	E6 E6 FA	230 230 250
Thistle	D8 BF D8	216 191 216
Plum	DD A0 DD	221 160 221
Violet	EE 82 EE	238 130 238
Orchid	DA 70 D6	218 112 214
Fuchsia	FF 00 FF	255 0 255
Magenta	FF 00 FF	255 0 255
MediumOrchid	BA 55 D3	186 85 211
MediumPurple	93 70 DB	147 112 219
BlueViolet	8A 2B E2	138 43 226
DarkViolet	94 00 D3	148 0 211
DarkOrchid	99 32 CC	153 50 204
DarkMagenta	8B 00 8B	139 0 139
Purple	80 00 80	128 0 128
Indigo	4B 00 82	75 0 130
DarkSlateBlue	48 3D 8B	72 61 139
SlateBlue	6A 5A CD	106 90 205
MediumSlateBlue	7B 68 EE	123 104 238
GreenYellow	AD FF 2F	173 255 47
Chartreuse	7F FF 00	127 255 0
LawnGreen	7C FC 00	124 252 0
Lime	00 FF 00	0 255 0
LimeGreen	32 CD 32	50 205 50
PaleGreen	98 FB 98	152 251 152
LightGreen	90 EE 90	144 238 144
MediumSpringGreen	00 FA 9A	0 250 154
SpringGreen	00 FF 7F	0 255 127
MediumSeaGreen	3C B3 71	60 179 113
SeaGreen	2E 8B 57	46 139 87



TABLE 1-continued

COLOR CHART		
HTML name	Hex code R G B	Decimal code R G B
ForestGreen	22 8B 22	34 139 34
Green	00 80 00	0 128 0
DarkGreen	00 64 00	0 100 0
YellowGreen	9A CD 32	154 205 50
OliveDrab	6B 8E 23	107 142 35
Olive	80 80 00	128 128 0
DarkOliveGreen	55 6B 2F	85 107 47
MediumAquamarine	66 CD AA	102 205 170
DarkSeaGreen	8F BC 8F	143 188 143
LightSeaGreen	20 B2 AA	32 178 170
DarkCyan	00 8B 8B	0 139 139
Teal	00 80 80	0 128 128
Aqua	00 FF FF	0 255 255
Cyan	00 FF FF	0 255 255
LightCyan	E0 FF FF	224 255 255
PaleTurquoise	AF EE EE	175 238 238
Aquamarine	7F FF D4	127 255 212
Turquoise	40 E0 D0	64 224 208
MediumTurquoise	48 D1 CC	72 209 204
DarkTurquoise	00 CE D1	0 206 209
CadetBlue	5F 9E A0	95 158 160
SteelBlue	46 82 B4	70 130 180
LightSteelBlue	B0 C4 DE	176 196 222
PowderBlue	B0 E0 E6	176 224 230
LightBlue	AD D8 E6	173 216 230
SkyBlue	87 CE EB	135 206 235
LightSkyBlue	87 CE FA	135 206 250
Deep SkyBlue	00 BF FF	0 191 255
DodgerBlue	1E 90 FF	30 144 255
CornflowerBlue	64 95 ED	100 149 237
RoyalBlue	41 69 E1	65 105 225
Blue	00 00 FF	0 0 255
MediumBlue	00 00 CD	0 0 205
DarkBlue	00 00 8B	0 0 139
Navy	00 00 80	0 0 128
MidnightBlue	19 19 70	25 25 112
Cornsilk	FF F8 DC	255 248 220
BlanchedAlmond	FF EB CD	255 235 205
Bisque	FF E4 C4	255 228 196
NavajoWhite	FF DE AD	255 222 173
Wheat	F5 DE B3	245 222 179
BurlyWood	DE B8 87	222 184 135
Tan	D2 B4 8C	210 180 140
RosyBrown	BC 8F 8F	188 143 143
SandyBrown	F4 A4 60	244 164 96
Goldenrod	DA A5 20	218 165 32
DarkGoldenrod	B8 86 0B	184 134 11
Peru	CD 85 3F	205 133 63
Chocolate	D2 69 1E	210 105 30
SaddleBrown	8B 45 13	139 69 19
Sienna	A0 52 2D	160 82 45
Brown	A5 2A 2A	165 42 42
Maroon	80 00 00	128 0 0
White	FF FF FF	255 255 255
Snow	FF FA FA	255 250 250
Honeydew	F0 FF F0	240 255 240
MintCream	F5 FF FA	245 255 250
Azure	F0 FF FF	240 255 255
AliceBlue	F0 F8 FF	240 248 255
GhostWhite	F8 F8 FF	248 248 255
WhiteSmoke	F5 F5 F5	245 245 245
Seashell	FF F5 EE	255 245 238
Beige	F5 F5 DC	245 245 220
OldLace	FD F5 E6	253 245 230
FloralWhite	FF FA F0	255 250 240
Ivory	FF FF F0	255 255 240
AntiqueWhite	FA EB D7	250 235 215
Linen	FA F0 E6	250 240 230
LavenderBlush	FF F0 F5	255 240 245
MistyRose	FF E4 E1	255 228 225
Gainsboro	DC DC DC	220 220 220
LightGrey	D3 D3 D3	211 211 211

TABLE 1-continued

COLOR CHART		
HTML name	Hex code R G B	Decimal code R G B
Silver	C0 C0 C0	192 192 192
DarkGray	A9 A9 A9	169 169 169
Gray	80 80 80	128 128 128
DimGray	69 69 69	105 105 105
LightSlateGray	77 88 99	119 136 153
SlateGray	70 80 90	112 128 144
DarkSlateGray	2F 4F 4F	47 79 79
Black	00 00 00	0 0 0

[0085] At event 630, the computing device 612 may output the color on the graphical display 616. The user can then position themselves proximate the graphical display 616 so that the color 618 is reflected off the user's feature as a color signature 620. In some embodiments, the user positions themselves within about 12 inches of the graphical display 616. The computer device 612 may then capture an image 622 of the user with accompanying color signature 620 using the camera 614. As is to be appreciated, while not illustrated in FIG. 6, the user may also make a gesture that could be captured by the camera 614. Furthermore, the graphical display 616 may be caused to sequentially display a plurality of different colors, such as to provide a color-keyed strobe affect, as described herein.

[0086] At event 650, the image 622 is sent to the authentication computing system 600, as illustrated by image upload 696. The image 622 may be encrypted using any suitable encryption scheme. Upon receipt, the authentication computing system 600 may perform various analytic processes on the image. For example, the authentication computing system 600 may perform a color analysis on the color signature 620 to confirm the proper color is present in the image and that it is properly reflected off the user. Furthermore, biometric analysis techniques may also be performed to the image received to confirm the identity of the user. Biometric information may be stored in a biometric database 604. As is to be appreciated, a gesture present in the image could also be analyzed by the authentication computing system as part of the authentication process. As is to be appreciated, the authentication computing system 600 may comprise a variety of databases 606 relevant to the authentication process. For example, in some embodiments, one or more databases 606 may store gesture-related information. Database 606 may also store various device specific variables, such as machine IDs. Database 606 (or other associated databases) may also various authentication variables, such as flash angle variables, user device angle variables, shutter/flash synchronicity variables, and so forth.

[0087] At event 670, an authentication confirmation 698 is sent to the computing device 612. Upon receipt of the authentication confirmation, an application, or other gate-keeper on the computing device, could allow the user access to the desired destination.

[0088] In some embodiments, a moving image scan may be utilized for authentication purposes. The moving image scan (sometimes referred to herein as a rotary scan) can generate image data that is recorded as a video file or can generate image data that is a series of still images. The image data may be obtained as a user moves a user device in a particular path in space proximate to the user's body. The



particular path may be chosen so that image data regarding a user's body is collected from many different angles so that it may be analyzed as part of the authentication process. In one embodiment, the particular path is generally arc-shaped and circumnavigates at least a portion of a user's head or upper torso. In some embodiments, instead of moving the user device, the user may move in a predetermined path while the camera on the user device remains relatively still. For example, the user may slowly sweep or swivel their head side to side as image data is collected by a relatively stationary camera. The camera (such as a camera on a user device), may be held in the hand of a user or positioned on a stationary object, for example.

[0089] In addition to image data, additional contextual data may be collected during the moving image scan and provided to the authentication computing system as part of authentication processes utilizing "man and machine" binding. The contextual data may be collected by sensors that are onboard the user device, such as gyroscopes, accelerometers, and electromagnetic field meters, for example. This contextual data may be used by the authentication computing system to determine whether parameters associated with the predetermined path are within a particular range. For example, for proper authentication, a user may need to move the user device at a speed of about 2 ft/sec in a counter-clockwise direction, while the user device held at about a 45 degree angle. Information that may be used to determine if these requirements are satisfied may be provided as contextual data that is sent with image data to the authentication computing system. Furthermore, measurements related to electromagnetic fields may be included with the contextual data and be used to confirm that the user started and ended the path at the proper positions.

[0090] FIG. 7A depicts an example moving image scan in accordance with one non-limiting embodiment. A user device 702 includes an onboard camera 708 that may collect video and/or still images. As part of an authentication process the user 704 sweeps the user device 702 in a path 706 while the camera 708 collects image data. While the path 706 is shown as an arc, a variety of paths may be used, such as saw-tooth paths, v-shaped paths, linear paths, and so forth. FIG. 7B depicts an example moving image scan where the user 704 sweeps their head side to side in a path 706 while the camera 708 collects the image data. In other embodiments, the user may be required to nod their head up and down, move their head in a circular pattern, or otherwise execute a particular head and/or body movement. In any event, during or subsequent to the sweep, images 710 may be provided to an authentication computing system, such as the authentication computing system 100 shown in FIG. 1. The images 710 may include contextual data 712, which may include speed data, orientation data, machine ID, GPS data, and so forth. The images 710 and the contextual data 712 may be transmitted to the authentication computing system in an encrypted network packet, similar to the encrypted network packet 106 shown in FIG. 1. The authentication computing system can analyze the images 710 and the contextual data 712 to determine if the user 704 should be authenticated. For example, the images 710 may be compared to images in a baseline image database 124 (FIG. 1).

[0091] FIG. 7C depicts an example process flow 740 associated with a moving image scan. At 742, a camera is activated on a user device, such as a mobile computing

device. At 744, sensor data from the mobile computing device is gathered. While a wide variety of sensor data can be gathered from the mobile computing device, example sensors 764 include, without limitation, a gyroscope 766, an accelerometer 768, a magnetometer 770, a camera 772, a GPS 774, among others. As described herein, in some embodiments the particular sensor data that is utilized by the process flow 740 may be based, at least in part, on the availability of resources, such as network bandwidth and battery power, for example. In any event, at 746 a face is moved in front of the camera, such as by sweeping the camera in front of the face (similar to the moving image scan described in FIG. 7A, for example). During the moving image scan, at time periods "Ts", the mobile computing device can find the face in the image and detect various fiducial points, as shown at 748. Time period Ts can be any suitable period of time, such as 0.03125 seconds (i.e., 32 frames/second), 0.1 seconds, 0.5 seconds, and so forth. As is to be appreciated, as the interval Ts is shortened, the needed bandwidth may increase. Example fiducial points include eye locations, nose location, ear locations, facial measurements, and the like. At 750, camera movement is detected, by way of the sensor data gathered by the mobile computing device. Camera movement may be detected at intervals Ts. By way of the determined camera movement, it is can determined if the camera was moved by the user in the expected path. At 760, liveness of the user is detected. In one embodiment, liveness is confirmed based on changes of the face in the image matching the angular movements as detected by the sensors. Basing the determination off of angular movements can mitigate attempted spoofing by using a 2-dimensional image of a user. At 762, it is determined whether to authenticate user. Such determination may be made, for example, after a sufficient number of intervals Ts have elapsed, such as 5 intervals, 10 intervals, 20 intervals, 100 intervals, or 160 intervals, for example.

[0092] FIG. 8A depicts another example of an authentication process utilizing a moving image scan. The illustrated authentication process includes the use of a color signature, which is described above with regard to FIG. 6A user device 802 includes a graphical display 816 and an onboard camera 808 that may collect video and/or still images. As part of an authentication process, the graphical display 816 projects a particular color 818, which may be reflected off the facial features of the user 804 as a color signature 820, as described above. The user 804 sweeps the user device 802 in a path 806 while the camera 808 collects image data, which includes the color signature 820. During or subsequent to the sweep, images 810 may be provided to an authentication computing system, such as the authentication computing system 100 shown in FIG. 1. The images 810 may include contextual data 812, as described above with regard to contextual data 712. The authentication computing system may analyze the images 810 and the contextual data 812 to determine if the user 804 should be authenticated.

[0093] FIG. 8B illustrates an example process flow 840 associated with a moving image scan utilizing multi-colored strobing. At 842, a scan is started. The scan may be generally similar to the moving image scan described with regard to FIG. 8A. At 844, an ambient light condition is sensed. Such condition may be sensed using an ambient light sensor onboard the user device 802 (FIG. 8A). If there is adequate ambient lighting to collect biometric data, the process can continued to execute authentication under normal light con-



ditions, as shown at **860**. If a low light condition exists (i.e., under a threshold lux level), the authentication process may utilize a multi-colored strobe technique to gather biometric data from the user. At **848**, a multi-color strobe is activated by successively displaying different colors on a display of the user device **801**. In one embodiment, one of seven colors is blinked twice on the screen. The color may be displayed on the display for a particular time period, such as  $T_s$ , described above. The periodic color strobe and the periodic collection of the image data may be coordinated so that image data is collected at times when the display is illuminated with a particular color. At **850**, the camera is moved relative to a face. At **852**, the camera is rotated with respect to the face such that images of the face at a plurality of different angular vantages can be collected. At **854**, an image is received **854**. As the color changes after  $T_s$ , additional images can be collected at **854**. At **856**, the illumination on the face with respect to both the angular position (as determined by sensor data) and the color data is determined. At **858**, authentication is determined using biometric data, illumination data, and any other contextual data, such as geolocational information, machine ID, and so forth.

**[0094]** The data collected from the image scan using the strobing colors may not be sufficient to satisfy an authentication threshold. In some embodiments, a communication feedback loop between the authentication computing system and the user may be used to obtain the user's observations during the scan. For example, if the facial recognition data is not sufficient to authenticate the user, the authentication computing system can send an electronic communication to the user device. The electronic communication can be in any suitable format, such as a SMS text message, an email message, an "in-application" message, a messenger message, and so forth. The electronic communication can ask the user to identify the color or colors they saw on the screen during the attempted authentication. The user can reply with the color using any suitable messaging technique, such as a reply SMS message, for example. If the user's observation of the color data matches the color that was, in fact, blinked on the screen on the user device, the authentication computing system can use that observation to qualify the user. Accordingly, using this techniques, there generally two observers in the authentication process. The authentication computing system observes the illumination data reflected off the skin of a user by way of the image gathering process and the user observes the color that is displayed on the display of the user device.

**[0095]** In some embodiments, the authentication may include acquisition of images from a plurality of devices in either a sequential or concurrent image collection process. For example, for proper authentication, a handheld mobile device may need to collect a first image of a user and a laptop computer (or other computing device), collects a second image of the user. In other embodiments, a different collection of computing devices may be used to collect the images, such as a mobile device and a wall-mounted unit, for example. FIG. 9 illustrates an authentication process utilizing a multi-image acquisition process in accordance with one non-limiting embodiment. A user is positioned proximate to a first user device (shown as a smart phone) having a camera **904**. The user is also positioned proximate to a second user device **906** (shown as a laptop) having a camera **908**. While two user devices are illustrated in FIG. 9, some embodiments may utilize three more or more user devices.

In any event, the first user device **902** collects first image **910** and the second user device collects second image **914**. The first image **910** and the second image **914** may be collected at generally the same time or they may be collected sequentially. Each image **910**, **914** may include associated contextual data **912**, **916**. The images **910**, **914** may be provided to the authentication computing system **100** for processing. As shown, verification **130** may be provided to the first user device **902** if the authentication computing system **100** to indicate a successful authentication of the user. It is noted that while the verification **130** is shown being delivered to the first user device **902**, the verification **130** may additionally or alternatively be delivered to the second user device **906**.

**[0096]** FIG. 10 illustrates an authentication process utilizes multi-image acquisition process in accordance with another one non-limiting embodiment. The authentication process is generally similar to the process shown in FIG. 9. In FIG. 10, however, user movement **920** is required as part of the authentication process. Such movement may be used to aid in thwarting spoofing techniques. In some embodiments, the particular movement required of the user may be identified during the authentication process. For example, the first image **910** may be collected with the user at a first position. The user may then be instructed by one of the first and second user devices **904**, **906** to perform a certain movement, such as raise an arm. The second image **914** may then be collected and analyzed by the authentication computing system **100** to confirm the user successfully completed the requested movement.

**[0097]** Various systems and methods described herein may generally provide resource aware mobile computing. Examples of resources that can be considered include, without limitation, network bandwidth, batter power, application settings, and the like. Based on the particular availability of the resources at the time of authentication, the system may change the type of biometric data collected and transmitted, the type of contextual data collected and transmitted, or change other authentication parameters. During periods of relatively high resource availability, the system can use authentication techniques that utilize large amount of resources, such as bandwidth, battery power, and the like. During periods of relatively low resource availability, the system can use authentication techniques that do not necessarily utilize large amount of resources. In some embodiments, authentication procedures, or at least some of the authentication procedures, may be performed local to the computing device by a local authentication computing system. The amount or portion of the authentication process performed local to the computing device compared to the amount or portion of the authentication process performed remotely (such as by authentication computing system **100**), may be based on available resources, including environmental and/or operational factors.

**[0098]** Example factors may include, without limitation, power source strength, available data transmission rates, available image processing ability, type of network connections available (i.e., cellular vs. WiFi), and so forth. Thus, resource-aware decision making may be used to determine which part of the authentication process is performed locally and which part of the authentication process is performed remotely. In some embodiments, the system attempts to perform the entire authentication process local to the user device. Such approach may be aimed to conserve bandwidth



and/or to minimize communications over a network. If the user cannot be properly authenticated, communications with a remote authentication computing system may be utilized in an attempt to complete the authentication request. In some embodiments, if the battery supply of the client device is beneath a certain threshold, a majority of the authentication process is offloaded to the remote authentication computing system. Moreover, the number of authentication variables considered, or the types of authentication variables considered during the authentication process may be dependent on the environmental and/or operational factors. For example, during periods of high data connectivity and/or high-battery strength, the authentication computing system may require the user device to supply a relatively high number of authentication variables and/or resource intensive variables. During periods of low data connectivity and/or low battery strength, the authentication computing system may determine that a subset of authentication variables are suitable for authentication based on the operational conditions and request a limited number of authentication variables from the user device. In some embodiments, when the user device resumes high data connectivity and/or high battery strength, the authentication computing system may require the user to re-authenticate using additional authentication variables.

[0099] FIG. 11 illustrates an authentication computing system that comprises a local authentication computing system 1101 and a remote authentication computing system 1100. In the illustrated embodiment the remote authentication computing system 1100 comprises the elements of the authentication computing system 100 described above with regard to FIG. 1. The local authentication computing system 1101 is executed on a user device 102. The local authentication computing system 1100 may include a variety of modules or components for authenticating a user of the user device 102. For example, the local authentication computing system 1100 may comprise one or more processors 1116 and one or more computer memory units 1118. For convenience, only one processor 1116 and only one memory unit 1118 are shown in FIG. 11. In some embodiments, for example, the user device 102 includes a graphics processing unit (GPU). The processor 1116 may execute software instructions stored on the memory unit 1118. The processor 1116 may be implemented as an integrated circuit (IC) having one or multiple cores. The memory unit 1118 may include volatile and/or non-volatile memory units. Volatile memory units may include random access memory (RAM), for example. Non-volatile memory units may include read only memory (ROM), for example, as well as mechanical non-volatile memory systems, such as, for example, a hard disk drive, an optical disk drive, etc. The RAM and/or ROM memory units may be implemented as discrete memory ICs, for example.

[0100] The memory unit 1118 may store executable software and data for authentication engine 1120. When the processor 1116 of the local authentication computing system 1101 executes the software of the authentication engine 1120, the processor 1116 may be caused to perform the various operations of the local authentication computing system 1101, such as send information to remote computer devices, process information received from remote computer devices, and provide verification information regarding user authentication to applications executing on the user device 102. Data used by the authentication engine 1120 may be from various sources, either local or remote, such as a baseline image database 1124 and/or baseline image

database 124. The data stored in the baseline image database 1124 may be stored in a non-volatile computer memory, such as a hard disk drive, a read only memory (e.g., a ROM IC), or other types of non-volatile memory.

[0101] The user device 102 in the illustrated embodiment also comprises various components, such as a camera 1130, a microphone 1132, an input device 1134, a display screen 1136, a speaker 1138, and a power supply 1140. As is to be readily appreciated, other types of user device may have different components as those illustrated in FIG. 11. In any event, the user may interact with various components during an authentication process. Depending on the available resources, the authentication engine 1120 may determine whether to perform some or all of the authentication process, or to offload some of all of the authentication process to the remote authentication computing system 1100. For example, if the available power in the power supply 1140 is relatively low, the user device 1101 may offload much of the authentication processing to the remote authentication computing system 1100. In another example, if the data connection to the remote authentication computing system 1100 is unstable, of low quality, or non-existent, the user device 1101 may perform much of the authentication processing using the local authentication computing system 1101.

[0102] FIG. 12 illustrates an example data transferring technique utilizing an authentication computing system. In the illustrated embodiment, the authentication computer system 100 illustrated in FIG. 1 is utilized. A first user (illustrated at User 1) determines which file 1212 to transmit using a user device 1210. The file 1212 may be any suitable type of electronic data file, such as a document file, an image file, a video file, or any other type of computer storable data. The first user may send an encrypted packet 1204 through a communications network 1202, such as a public network (i.e., the Internet), to the authentication computing system 100. The encrypted packet 1204 may include the file 1212 and recipient biometrics 1208. In one embodiment, the recipient biometrics 1208 includes an image of the recipient.

[0103] In other embodiments, the recipient biometrics 1208 includes a recipient fingerprint, a recipient retina scan, or other recipient biometric identifier. In the illustrated embodiment, the second user (illustrated as User 2) is the intended recipient of the file 1212. Prior to being given access to the file 1212, the second user provides the user 2 biometrics 1214 to the authentication computing system 100. Such user 2 biometrics 1214 may include, for example, an image of the second user obtained using a camera (not shown) of the user device 1220. When the user 2 biometrics 1214 are deemed to match the recipient biometrics 1208, or at least satisfy a confidence threshold, that were originally provided by the first user, an encrypted packet 1216 may be delivered to the user device 1220 of the second user. The encrypted packet 1216 may include the file 1212.

[0104] While FIG. 12 illustrates a one-to-one file sharing scenario, other sharing scenarios may be facilitated by the authentication computing system 100, such as a one-to-many file sharing scenario. In such scenarios, user 1 may provide recipient biometrics 1208 for each of a plurality of recipients, such as a group of N recipients. When the file 1212 is encrypted, as described above, biometrics from all of the plurality of recipients may be used. Subsequently, when a user seeks access to the encrypted file 1212, the authentication computing system 100 may determine if the biometrics of the user seeking access to the file matches any



one of the recipient biometrics **1208** provided by user 1. The authentication computing system **100** may also utilize contextual data received from the user seeking access to the file, as described herein.

[0105] In yet another embodiment one-to-many sharing scenario, such as for high security type implementations, a certain number of recipients must concurrently access the encrypted file **1212** at the same time, or at least nearly at the same time, in order for the collective group to gain access to the encrypted file. Such techniques may seek to ensure that certain files are accessed only in presence of other people. By way of example, user 1 may identify the biometrics of  $N$  recipients that may access the file **1212**, where  $N > 1$ . User 1 may also identify a threshold number  $k$ , where  $k = 1 \dots N$ . Here,  $k$  is the number of recipients that must each provide individual biometrics before the file is decrypted so that the file may be accessed by the group of  $k$  recipients. The value for  $k$  can be any suitable number, and may vary based on implementation, the desired level of security, or any other factors. In some embodiment,  $k$  is set by the authentication computing system **100** based on the number  $N$  of recipients such that  $k$  is a majority of  $N$ , for example. In some embodiments,  $k$  is 20% of  $N$ , rounded to the nearest integer, and so forth. Furthermore, in addition to having the requisite number of recipients providing biometrics, the authentication computing system **100** may also process contextual data associated with each recipient for an additional layer of security.

[0106] FIG. 13 illustrates an authentication process **1300** for a computing device using a color signature in accordance with one non-limiting embodiment. At block **1302**, an application is executed. The application may be executed on a user device **102** (FIG. 1), for example. At block **1304**, the application sends a call requesting a color key. The call may include various identification data. At block **1306**, the color key is received. The color key may be in the form of a hex color code. At block **1308**, the color is displayed on the display screen of the user device. At block **1310**, a camera is activated. The camera may be integral or may be a standalone camera (such as a web cam, for example). At block **1312**, an image is captured. The image may be of the face of the user with the color reflecting off the face as a color signature. At block **1314**, the image may be cryptographically sent to an authentication computing system. At block **1316**, an authentication confirmation is received when the face and the color signature is authenticated.

[0107] FIG. 14 illustrates an authentication process **1400** for an authentication computing system using a color signature in accordance with one non-limiting embodiment. At block **1402**, a color key is requested from a mobile device. In some example embodiments, the request may be received from other types of devices, such as building access devices or desktop computers, for example. At block **1404**, a particular color key is sent to the mobile device. At block **1406**, an image is received from the mobile device. At block **1408**, the biometric components of the image are analyzed. In some example embodiments, this analysis is performed by a third party biometric analytics service. At block **1410**, color analysis is performed on a color signature of the image. In particular, the color signature can be analyzed to confirm it matches the signature for a particular user and that it is the same color as the color key originally sent to the mobile

device. At block **1412**, an authentication confirmation is sent to the mobile device when the face and the color signature is authenticated.

[0108] FIG. 15 illustrates an authentication process **1500** for a computing device in accordance with one non-limiting embodiment. At block **1502**, an application is executed. At block **1504**, a flash on the computing device is activated. At block **1506**, the camera is activated. At block **1508**, an image is captured by the camera. At block **1510**, the image is sent to an authentication computing system. The image may be encrypted prior to transmission. In some embodiments, the computing device purges the image subsequent to the transmission so that there is no local copy of the image stored on the device. At block **1512**, when the face and flash location have been authenticated by the authentication computing system, an authentication confirmation is received.

[0109] FIG. 16 illustrates an authentication process **1600** of an authentication computing system in accordance with one non-limiting embodiment. At block **1602**, a baseline image is received from a mobile device. The baseline image may be stored in a baseline image database. The baseline image may contain various features, such as a gesture by a user and a relative location of a source of light. At block **1604**, an image is received from the mobile device for the purposes of authentication. At block **1606**, biometric analysis may be performed on the user's features (such as facial features, hand features, fingerprint features, or retinal features, for example). At block **1608**, the location of the flash in the received image is compared to the location of the flash in the baseline image. In some embodiments, the baseline image must be updated (changed) periodically. In any event, at block **1610**, when the face and flash location are authenticated, an authentication confirmation is sent to the mobile device. As discussed herein, additional layers of authentication may also be performed, such as analysis of locational data or device data, for example.

[0110] FIG. 17 illustrates a user's authentication process **1700** in accordance with one non-limiting embodiment. At block **1702**, a user holds a mobile device with its flash activated. At block **1704**, the user faces a reflective surface. At block **1706**, the user makes a gesture and positions the gesture relative to their body, the mobile device, or other object. At block **1708**, the user positions the active flash in a particular position. At block **1710**, a photograph of the reflective surface is taken by a camera of the mobile device. At block **1712**, the photograph is uploaded for authentication. As is to be appreciated, any number of authentication variables may be provided with the uploaded image at block **1712**. For example, uploaded authentication variables may include, without limitation, the mobile device angle, the shutter/flash synchronicity information, location information and so forth.

[0111] FIG. 18A illustrates an example message flow diagram **1800** for a registration process in accordance with one embodiment. The message flow diagram **1800** generally depicts messages utilized by a user device **1802** and an authentication computing system **1806**, some of which may be sent through a communications network **1804**, during user registration. The user device **1802** comprises a biometric collection tool **1808** and a contextual data collection tool **1810**. The biometric collection tool **1808** may be, for example, a digital camera, a retina scanner, a fingerprint scanner or any other suitable device. The contextual data collection tool **1810** may include software and/or hardware



components for acquiring data, such as geolocational data, user device movement data, machine identification data, and so forth. The biometric collection tool **1808** and a contextual data collection tool **1810** may respectively provide, via messages **1822** and **1824**, data to the processor **1812**. The messages **1822** and **1824** may generally provide various types of data unique to the user and the user device **1802**. The processor **1812** may perform pre-transmission processing of the data, such as crop an image collected by the biometric collection tool **1808**, convert an image to grey scale, convert a file type of the image (i.e., convert to .BMP), create array of images, normalize the data to a particular format, encrypt the data, and so forth.

[0112] Subsequent to any pre-transmission processing, the processor **1812** may cause a message **1826** to be sent through the communications network **1804** to the authentication computing system **1806**. The message **1826** may be received by a listener **1814**. The listener **1814** may be “listening,” for example, to messages transmitted using HTTP or HTTPS protocols for an authentication request or a registration request. Here, the message **1826** is an authentication request so the listener **1814** provides a message **1828** which includes registration data to a processor **1816**. The processor **1816** may process the information received and then provide a message **1830** to a user database **1818**, a message **1832** to a biometric database **1820**, and a message **1834** to a contextual database **1822**. The message **1830** may identify provide user identification data (such as social security number, patient ID number, account number, etc.), the message **1832** may include, for example, image data, and the message **1834** may include, for example, geolocational data and/or machine identification data. Generally, the messages **1830**, **1832**, and **1834** register a user of the user device **1802** with the authentication computing system **1806**. The database **1818**, **1820**, and **1822** may be implemented using any suitable type of database hardware or software. For example, in some embodiments, cloud-based storage systems are utilized.

[0113] FIG. 18B depicts an example message flow diagram **1840** for an authentication process in accordance with one embodiment. The message flow diagram **1840** generally depicts messages utilized by the user device **1802** and the authentication computing system **1806**, some of which may be sent through the communications network **1804**, during user authentication. As part of the authentication process, the biometric collection tool **1808** and the contextual data collection tool **1810** may respectively provide, via messages **1850** and **1852**, data to the processor **1812**. The messages **1850** and **1852** may generally provide various types of data unique to the user and the user device **1802**. Similar to the processing described in FIG. 18A, the processor **1812** may perform pre-transmission processing of the data. It is noted that the contextual data delivered using message **1852** may vary. For example, the type of user device **1802** (including the type of on-board sensors) or the operational conditions (such data transmission rates, for example), may at least partially determine which type of contextual data may be transmitted to authentication purposes.

[0114] Subsequent to any pre-transmission processing, the processor **1812** may cause a message **1854** to be sent through the communications network **1804** to the authentication computing system **1806**. The message **1854** may be received by a listener **1814**, as described above. Here, the message **1854** is a registration request so the listener **1814**

provides a message **1856**, which includes authentication data, to the processor **1816**. The processor **1816** may execute an authentication process utilizing various database calls. A message **1858** to the user database **1818** may seek confirmation of a user’s personal data included in the message **1854**, such as SSN, patient number, user name, account number, and so forth. A message **1860** may indicate whether a positive match was found.

[0115] A message **1862** to the biometric database **1818** may seek confirmation of a user’s biometric data included in the message **1854**, such as facial data, fingerprint data, and so forth. In some embodiments, the biometric data is a streamed collection of facial images. A message **1864** may indicate whether a positive match was found. As is to be appreciated, a positive match of the biometric data may be based on a threshold confidence level or other metric. A message **1866** to the contextual database **1822** may seek authentication of various types of additional data received from the user device **1802**, such as geolocational data and/or machine identification data. A message **1868** indicates if a positive match for contextual data was found. In some embodiments, the confidence level threshold for biometric data, along with the confidence level thresholds for other types of contextual data that are analyzed may be selectively increased or decreased to adjust the overall usability of function of the authentication system.

[0116] Upon receiving and processing the information from the various databases, the processor **1816** may provide an authentication request response message **1870** to the listener **1814**. In turn, the listener **1814** may transmit a message **1872** through the network **1804** to the user device **1802** indicating a positive or negative authentication.

[0117] Authentication processes in accordance with the present systems and methods may be triggered using any suitable techniques. For example, when a user seeks to access a protection computing device, application, electronic document, and so forth, the authentication process may be triggered. In some embodiments, a transponder (such as an RFID device) may be positioned proximate to a restricted access device, such as a lockable door. Upon a user approaching the restricted access device, the transponder may trigger an authentication process to activate on a user device of the user. The user device may gather and provide information, such as biometric data and contextual data, to an authentication computing system associated with door. When authentication is successfully performed, an unlock command may be transmitted to the restricted access device.

[0118] FIG. 19A illustrates an example simplified block diagram for a user registration process. In some embodiments, the authentication computing system **1900** is implemented as a DLL access server. The authentication computing system **1900** may be positioned behind a firewall **1904**, which may generally serve protect enterprise data stored by the authentication computing system, for example. A user device **1916** may be in communication with the authentication computing system **1900** through a communications network **1904**. The user device **1916** may be provided using any suitable processor-based device or system, such as a personal computer, laptop, server, mainframe, or a collection (e.g., network) of multiple computers, for example. The user device **1916** may include one or more processors **1918** and one or more computer memory units **1920**. For convenience, only one processor **1918** and only one memory unit **1920** are shown in FIG. 19A. The processor **1918** may execute



software instructions stored on the memory unit **1924**, such as a web browsing application **1924**. The processor **1918** may be implemented as an integrated circuit (IC) having one or multiple cores. The memory unit **1920** may include volatile and/or non-volatile memory units. Volatile memory units may include random access memory (RAM), for example. Non-volatile memory units may include read only memory (ROM), for example, as well as mechanical non-volatile memory systems, such as, for example, a hard disk drive, an optical disk drive, etc. The RAM and/or ROM memory units may be implemented as discrete memory ICs, for example.

[0119] The memory unit **1920** may store executable software and data. When the processor **1918** of the user device **1916** executes the software, the processor **1918** may be caused to perform the various operations used for registration and authentication of a use of the user device **1916**, such as send information to the authentication computing system **1900** and process information received from the authentication computing system **1900**.

[0120] The user device **1916** may comprise a wide variety of components, some example of which are illustrated in FIG. **19A**. For example, the user device **1916** may comprise a biometric collection unit **1922** for collecting biometric information from a user of the user device **1916**. In certain embodiments, the biometric collection unit **1922** is a digital camera. The user device **1916** may also include, without limitation, an accelerometer **1926**, a magnetometer **1928**, or any other type of sensor **1930**, device, or component (such as an ambient light sensor, gyroscopic sensor, microphone, proximity sensor, and so forth) that may be used for collecting data or information that may be provided to the authentication computing system **1900** during a registration or authentication process.

[0121] During a registration process, the user device **1916** may transmit a communication **1906** to the authentication computing system **1900**. The communication **1906**, or at least components of the communication, may be encrypted. In the illustrated embodiment, the communication **1906** comprises base image data **1908** and contextual data **1910**. The base image data **1908** may be, for example, a series of streamed images of a user. The contextual data **1910** may comprise information gathered from one or more sensors, such as magnetometer **1928**, information regarding the user device **1916**, such as a machine ID or ESN, for example. Upon processing by the authentication computing system **1900**, an output **1912** may be provided to the user device **1916**. The output **1912** may include, for example, an indication **1914** that registration is complete.

[0122] Subsequent to registration with the authentication computing system, a use may seek an authorization request. FIG. **19B** illustrates an example simplified block diagram for a user authentication process. In the illustrated embodiment, an authorization request **1950** comprises image data **1952** and contextual data **1954**. The image data **1952** may be, for example, streamed image data of a user's face. The contextual data **1954** may include, for example, machine ID or ESN information, acceleration or movement data, magnetic field data, and so forth. In any event, based on the image data **1952** and the contextual data **1954**, the authentication computing system **1900** may determine whether the user of the user device **1916** is an authenticated user. An output **1956** may be transmitted to the user device **1916** to

convey the results of the authentication request, which may include an indication of authentication **1958** or an indication of non-authentication **1960**.

[0123] FIG. **20A** illustrates an example process for registering a user with an authentication computing system. At **2000**, a camera on a user device is activated. The user device may be a component of, for example, a mobile computing device, a laptop computer, a desktop computer, a table computer, a wall-mounted device, and so forth. At **2002**, the liveness of a user is detected using any suitable technique or combination of suitable techniques. The particular technique or techniques used may vary on operational conditions, such as ambient lighting conditions, available data transfer rates, battery life, and so forth. A rotary facial scan **2004** may be employed in suitable conditions, such as high ambient lighting conditions. Image collection during a color keyed strobe **2006** may be used, such as during low ambient conditions. During a color keyed strobe, a screen on a user device may be sequentially changed colors, which images of the user's face positioned close to the screen sequentially collected. Other techniques **2008** may be used to detect liveness, such as instructing a user to make certain movements, say certain words, and so forth. At **2010**, a plurality of facial images are collected by the camera. In some embodiments, each facial image is a non-compressed file that is 100 pixels by 100 pixels, although other formats may be used. At **2012**, an array of the images is streamed to an authentication computing system. In some embodiments, five facial images are combined into a 100 pixel by 500 pixel array. At **2014**, contextual data is streamed. As provided herein, the contextual data may include, for example, machine identification data, geolocational data, movement data, and so forth. At **2016**, upon satisfaction of the registration requirements, the user is registered with the authentication computing system.

[0124] FIG. **20B** illustrates an example process for authenticating a registered user of an authentication computing system. At **2050**, a camera on a user device is activated. As described above with regard to FIG. **20A**, the user device may be a component of, for example, a mobile computing device, a laptop computer, a desktop computer, a table computer, a wall-mounted device, and so forth. At **2052**, the liveness of the user seeking authentication is detected. Example techniques for detecting liveness during the authentication process include a rotary scan **2054**, a color keyed strobe **2056**, or other technique **2058**, such as requiring certain movements or audio responses by a user. At **2060**, one or more facial images are gathered and at **2062**, the one or more facial images are streamed to an authentication computing system. At **2064**, contextual data associated with the user device is streamed to the authentication computing system. At **2066**, the user is authenticated based on processing of the facial images and the contextual data.

[0125] In some embodiments, an authentication computing system in accordance with the systems and methods described herein may be used by a certain relying parties, such as using an OpenID-type authentication. FIG. **21** illustrates an example communication block diagram. A protected application **2106** may be accessible via a use device **2108**. The protected application **2106** may be, without limitation, a website, a local application, a remote application, and so forth. A user operating the user device may either be a registered user of the OpenID platform **2104** or need to become a registered user in order to access the



protected application **2106**. As illustrated, during a “new user” registration process credentials may be logged with an authentication computing system **2100**. In some embodiments, the credentials include both a user ID and biometric data, such as an image. Once the user is registered with the OpenID platform **2104**, the user’s credentials may be provided to the authentication computing system **2100** (which may include biometric data) so that a user may be authenticated. It is noted that communications between the protected application **2106** and the authentication computing system **2100** may be facilitated through one or more application programming interfaces **2102**. Accordingly, in some embodiments, the authentication computing system **2100** may generally function as a third party, biometric authentication tool for a variety of websites, applications, and the like.

[0126] FIG. 22 illustrates a system flow diagram **2200** for photo cloaking utilizing biometric key generation. In the illustrated embodiment, secret image/text **2204A** may be any type of data that a user wishes to transmit in an encrypted format. The system flow also utilizes a cover image **2202A**. At **2206**, encryption is performed such that the secret image/text **2204A** is hidden within the cover image **2202A** utilizing a biometric/contextual data encryption technique. An example biometric/contextual data encryption technique is described in more detail below with regard to FIG. 23. A stego object **2208** is created that generally comprises the cover image **2202A** with the secret image/text **2204A** embedded in it. The stego object **2208** can then be transmitted through a communications network **2210**, which can include, for example, a public network. At **2212**, the stego object **2208** can be decrypted using the biometric/contextual data key **2210**. As a result, a cover image **2204B** and secret text **2204B** are extracted from the stego object **2208**, with the cover image **2204B** and secret text **2204B** being similar, or identical to, the cover image **2202A** and the secret image/text **2204A**.

[0127] FIG. 23 illustrates an example biometric encryption system flow diagram **2300**. The system flow diagram generally includes three aspects, namely an input-side **2302**, a network **2304**, and a target-side **2306**. A variety of operational environments can utilize the system flow diagram **2300**, such as a first user operating a first smart phone on the input-side **2302** and communicating with a second user operating a second smart phone on the target-side **2306**. The first and second user may be, for example, chatting using a real-time chatting application utilizing communications over the network **2304**. Using the systems and methods described herein, the first user can share a document, image, or other type of data file utilizing the described encryption process. The data file may be shared in generally real-time using the network **2304**. In the illustrated embodiment, the document desired to be shared is shown as a sensitive document **2308A**. The sensitive document **2308A** may be any type of data capable of being transmitted over a network. Prior to transmitting the sensitive document **2308A**, it may be encrypted using an encryption key **2310**. Generally, the encryption key **2310** enables the sensitive document **2308A** to be securely shared over a public network and requiring the target recipient to provide biometric and contextual data to access the sensitive document **2308A**. In the illustrated embodiment, a plurality of variants are provided at the input-side **2302** to form the encryption key **2310**, including a target user location **2312**, target biometrics **2314**, and a

time duration of validity **2316**. The target user location **2312** provided may vary based on implementation. In some cases, a city or address of the target is provided. In some cases, latitude and longitude coordinates are provided. Other implementations may use other techniques for identifying a geographic location of a target. The target biometrics **2314** can include, for example, an image of the target user stored within a target biometrics database **2318**. The target biometrics database **2318** can be local to the input side **2302**, or hosted by a third party, such as a social networking website, or example. In some embodiments, the target biometrics **2314** is an image selected from a digital photo album stored on a user device.

[0128] In some embodiments, target biometrics **2314** may include the biometrics for N recipients, as described above with regard to FIG. 12. In any event, the encryption key **2310** may then be created based on the biometric data of the target along with various forms of contextual information. Once the encryption key **2310** key is generated, an encrypted document **2320** may then be transmitted via the network **2304** to a user device of the target. In order to retrieve the sensitive document, target biometrics are retrieved **2322** (i.e., using a camera associated with a user device of the target), target location is retrieved **2324** (i.e., based on GPS data), and a time of access **2326** is determined (i.e., based on network time). When the target satisfies the confidence thresholds associated with all of the various variables, the document is decrypted at **2328** and a copy of the sensitive document **2308B** may be provided to the target. As is to be readily appreciated, the authentication process at the target-side **2306** can include any of various authentication techniques described herein, such as color strobing, liveness detection, moving image scans, and so forth. Furthermore, when biometric encryption system flow diagram **2300** is used with one-to-many file sharing scenarios, similar to those described above, the document may be decrypted at **2328** only after a sufficient number of recipients, such as k recipients, provide their biometrics to an authentication engine.

[0129] In general, it will be apparent to one of ordinary skill in the art that at least some of the embodiments described herein may be implemented in many different embodiments of software, firmware, and/or hardware. The software and firmware code may be executed by a processor or any other similar computing device. The software code or specialized control hardware that may be used to implement embodiments is not limiting. For example, embodiments described herein may be implemented in computer software using any suitable computer software language type, using, for example, conventional or object-oriented techniques. Such software may be stored on any type of suitable computer-readable medium or media, such as, for example, a magnetic or optical storage medium. The operation and behavior of the embodiments may be described without specific reference to specific software code or specialized hardware components. The absence of such specific references is feasible, because it is clearly understood that artisans of ordinary skill would be able to design software and control hardware to implement the embodiments based on the present description with no more than reasonable effort and without undue experimentation.

[0130] Moreover, the processes associated with the present embodiments may be executed by programmable equipment, such as computers or computer systems and/or pro-



processors. Software that may cause programmable equipment to execute processes may be stored in any storage device, such as, for example, a computer system (nonvolatile) memory, an optical disk, magnetic tape, or magnetic disk. Furthermore, at least some of the processes may be programmed when the computer system is manufactured or stored on various types of computer-readable media.

**[0131]** It can also be appreciated that certain process aspects described herein may be performed using instructions stored on a computer-readable medium or media that direct a computer system to perform the process steps. A computer-readable medium may include, for example, memory devices such as diskettes, compact discs (CDs), digital versatile discs (DVDs), optical disk drives, or hard disk drives. A computer-readable medium may also include memory storage that is physical, virtual, permanent, temporary, semipermanent, and/or semitemporary.

**[0132]** A “computer,” “computer system,” “host,” “server,” or “processor” may be, for example and without limitation, a processor, microcomputer, minicomputer, server, mainframe, laptop, personal data assistant (PDA), wireless e-mail device, cellular phone, pager, processor, fax machine, scanner, or any other programmable device configured to transmit and/or receive data over a network. Computer systems and computer-based devices disclosed herein may include memory for storing certain software modules used in obtaining, processing, and communicating information. It can be appreciated that such memory may be internal or external with respect to operation of the disclosed embodiments. The memory may also include any means for storing software, including a hard disk, an optical disk, floppy disk, ROM (read only memory), RAM (random access memory), PROM (programmable ROM), EEPROM (electrically erasable PROM) and/or other computer-readable media.

**[0133]** In various embodiments disclosed herein, a single component may be replaced by multiple components and multiple components may be replaced by a single component to perform a given function or functions. Except where such substitution would not be operative, such substitution is within the intended scope of the embodiments. Any servers described herein, for example, may be replaced by a “server farm” or other grouping of networked servers (such as server blades) that are located and configured for cooperative functions. It can be appreciated that a server farm may serve to distribute workload between/among individual components of the farm and may expedite computing processes by harnessing the collective and cooperative power of multiple servers. Such server farms may employ load-balancing software that accomplishes tasks such as, for example, tracking demand for processing power from different machines, prioritizing and scheduling tasks based on network demand and/or providing backup contingency in the event of component failure or reduction in operability.

**[0134]** The computer systems may comprise one or more processors in communication with memory (e.g., RAM or ROM) via one or more data buses. The data buses may carry electrical signals between the processor(s) and the memory. The processor and the memory may comprise electrical circuits that conduct electrical current. Charge states of various components of the circuits, such as solid state transistors of the processor(s) and/or memory circuit(s), may change during operation of the circuits.

**[0135]** While various embodiments have been described herein, it should be apparent that various modifications, alterations, and adaptations to those embodiments may occur to persons skilled in the art with attainment of at least some of the advantages. The disclosed embodiments are therefore intended to include all such modifications, alterations, and adaptations without departing from the scope of the embodiments as set forth herein.

We claim:

1. A method, comprising:

providing an authentication request to a user, said authentication request requiring said user to record an act that involves relative movement between said user and a camera;

receiving a recording from said user of said user performing said act;

determining whether said recording indicates a live performance of said act by said user, based at least in part on said recording;

authenticating said user, based at least in part on said recording; and

providing access to a resource to said user based on said authentication of said user and said determination of whether said recording indicates a live performance of said act by said user.

2. The method of claim 1, wherein said authentication request requires said user to illuminate a color while said camera records said act.

3. The method of claim 1, wherein said authentication request requires said user to generate a flash at a location while said camera records said flash.

4. The method of claim 1, wherein said authentication request requires said user to perform a gesture while said camera records said user performing said gesture.

5. The method of claim 1, wherein said authentication request requires said user to cause a flash at an angle relative to said camera while said camera records said flash at said angle relative to said camera.

6. The method of claim 1, wherein said authentication request requires said user to perform a gesture and at the same time cause a flash while said camera observes said gesture.

7. The method of claim 1, further comprising determining that authentication is required based at least in part on conditions.

8. The method of claim 7, wherein said conditions include contextual operational information comprising a geographical location of said user, a time period since a previous successful authentication, or a distance between a current location of said user and a location of said user during said previous authentication.

9. The method of claim 1, further comprising receiving a request to access said resource from said user.

10. The method of claim 1, wherein said recording is encrypted.

11. The method of claim 10, wherein said recording is encrypted utilizing a chaos-based encryption method.

12. The method of claim 1, wherein said resource includes data stored in a blockchain.



**13.** A server providing access to a resource, said server comprising:

a processor configured to execute code; and  
 memory storing data and said code, said data including software that, when executed by said processor, causes said server to  
 provide an authentication request to a user, said authentication request requiring said user to record an act that involves relative movement between said user and a camera,  
 receive a recording from said user of said user performing said act,  
 determine whether said recording indicates a live performance of said act by said user, based at least in part on said recording,  
 authenticate said user, based at least in part on said recording, and  
 provide access to a resource to said user based on said authentication of said user and said determination of whether said recording indicates a live performance of said act by said user.

**14.** A method for authenticating a user to allow said user to access functionality of a restricted access device, said method comprising:

detecting a user approaching said device, thereby causing said restricted access device to trigger an authentication process on a user device separate from said restricted access device;  
 providing contextual data to an authentication computing system associated with said restricted access device, said contextual data being indicative of an identity of said user;

authenticating said identity of said user with said authentication computing system using at least said contextual data; and

providing an unlock command to said restricted access device, when said identity of said user is successfully authenticated.

**15.** The method of claim **14**, wherein:

said restricted access device is a door lock; and  
 said unlock command causes said door lock to unlock.

**16.** The method of claim **14**, further comprising placing a transponder proximate to said restricted access device, wherein:

said transponder is configured to determine if said user has approached said restricted access device; and  
 said transponder is configured to trigger said authentication process on said user device.

**17.** The method of claim **14**, wherein said contextual data includes data indicative of a location of said user device.

**18.** The method of claim **14**, further comprising providing biometric data indicative of said identity of said user to said authentication computing system.

**19.** The method of claim **14**, wherein:

said restricted access device is a computing device; and  
 said unlock command allows said functionality of said computing device to be accessible by said user.

**20.** The method of claim **14**, wherein:

said contextual data includes a recording captured by said user subsequent to said detection of said user approaching said device; and  
 the liveness of said recording can be determined based at least in part on content of said recording.

\* \* \* \* \*