



US007814180B2

(12) **United States Patent**
Pulleyn et al.

(10) **Patent No.:** **US 7,814,180 B2**
(45) **Date of Patent:** **Oct. 12, 2010**

(54) **DOMAIN NAME SERVICE SERVER**

(75) Inventors: **Ivan W. Pulleyn**, Chicago, IL (US);
Stuart M. Bailey, Evanston, IL (US)

(73) Assignee: **Infoblox, Inc.**, Santa Clara, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/799,033**

(22) Filed: **Mar. 12, 2004**

(65) **Prior Publication Data**

US 2004/0210672 A1 Oct. 21, 2004

Related U.S. Application Data

(63) Continuation of application No. 09/615,271, filed on Jul. 13, 2000, now abandoned.

(51) **Int. Cl.**
G06F 15/177 (2006.01)

(52) **U.S. Cl.** **709/220**; 709/221; 709/222;
709/245

(58) **Field of Classification Search** 709/208,
709/219, 249, 226, 227, 220, 221, 222, 245;
713/201; 707/10; 700/65

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,909,545 A * 6/1999 Frese, II et al. 709/208
6,131,095 A * 10/2000 Low et al. 707/10
6,262,726 B1 * 7/2001 Stedman et al. 715/745
6,427,170 B1 * 7/2002 Sitaraman et al. 709/226

6,564,216 B2 * 5/2003 Waters 707/10
6,718,385 B1 * 4/2004 Baker et al. 709/225
6,801,952 B2 * 10/2004 Belzile 709/249
6,832,120 B1 * 12/2004 Frank et al. 700/65
6,832,322 B1 * 12/2004 Boden et al. 713/201
7,047,301 B2 * 5/2006 Skene et al. 709/226
7,127,471 B1 * 10/2006 Wilson 707/103 R
2002/0004796 A1 * 1/2002 Vange et al. 707/10

FOREIGN PATENT DOCUMENTS

WO WO 99/27680 * 6/1999

OTHER PUBLICATIONS

Stephen Shankland, Firms flock to growing server appliance market, Oct. 27, 1999, <http://news.cnet.com/news/0-1003-200-1420358.html>.

Gail R. James and Paul Anderson, The name game, Mar. 15, 1999, http://www.nwfusion.com/archive/1999/59940_03-15-1999.html.

* cited by examiner


Primary Examiner—Kenny S Lin

(74) *Attorney, Agent, or Firm*—Van Pelt, Yi & James LLP

(57) **ABSTRACT**

A DNS server system provides IP addresses for a host in a computer network. Upon receiving a request from a client for an IP address associated with a domain name, the requested IP address is retrieved from an object oriented database and transmitted to the client. The DNS server system provides configuration access from a client in a computer network. Communicative coupling is established between a client web browser and a DNS server system web server. A user interface adapted to provide configuration access to a DNS server system is requested. The user interface is downloaded from the DNS server system over the computer network.

69 Claims, 8 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6



InfoBlox OODatabase Network Move Operation
Relink Hosts to the 192.168.20.0 Network

FIG. 7




FIG. 8

1

DOMAIN NAME SERVICE SERVER**FIELD OF THE INVENTION**

The present invention relates generally to server appliances, and more particularly to domain name service server appliances.

BACKGROUND OF THE INVENTION

A domain name service (DNS) is generally a directory service for translating user friendly alphanumeric names for specific computers or hosts within a computer network into computer recognizable numerical addresses. While DNS was originally developed to facilitate communications between computers via the Internet, the use of DNS is becoming increasingly common in intranet environments, especially those which employ Internet Protocol (IP) to send data from one computer to another within a network.

Intranet and Internet-connected computers utilize a numeric addressing system to locate and route communications to other computers within a network. The numeric addressing system requires that each computer connected to the Internet have its own unique numeric IP address. IP addresses are typically 32 bit addresses that are represented by a string of numbers separated by periods, such as for example, "192.168.10.100." Since numeric addresses are difficult to remember, DNS was created to enable the pairing of domain names to specific numeric IP addresses. For example, when an Internet user types in the domain name "www.support.infoblox.com," DNS is the intermediary system that translates the domain name to the corresponding numeric IP address, "192.168.10.100."

There are generally two different entities which interact with the DNS server: clients and administrators. Clients are generally other computers which request IP addresses associated with specific domain names from the DNS server. Administrators are the individuals responsible for managing the DNS data stored in the DNS server.

Many large organizations, such as for example corporate intranets, commercial Internet Service Providers (ISPs), Internet content providers and educational and government institutions maintain IP based computer networks. Such organizations typically develop and maintain their own DNS servers for Internet and intranet applications. For prior art systems, establishing a DNS server usually requires the expertise of an information technology (IT) specialist and involves the selection and integration of multiple hardware and software components.

The software components in a prior art system typically include an operating system and a DNS server software package. The DNS server hardware generally consists of typical computer hardware including a processor, a hard drive, and memory. The DNS server software typically includes a DNS server engine, a database for storing DNS data and a graphical user interface (GUI) which permits the administrator to access the database. The DNS server engine responds to client requests for DNS data by retrieving the requested data from the DNS database and forwarding the retrieved data to the client.

The DNS server software can be selected from a number of prior art DNS server software packages available for purchase or a DNS software package, Berkeley Internet Domain Name (BIND), can be downloaded free of charge from the Internet Software Consortium. Since the DNS server hardware and the operating system are acquired separately from the DNS server software, DNS server software developers

2

may be unable to create software to optimize the performance of the DNS server for particular hardware and software systems. The specifications of the DNS server hardware, such as the specific hard drive model, the processor speed, the memory size and hardware component redundancies as well as operating system parameters, such as Transmission Control Protocol/Internet Protocol (TCP/IP) stack parameters and kernel memory allocation sizes are generally unknown to the DNS server software developers at the time they are developing such software.

Selecting appropriate hardware and an appropriate operating system for the DNS server requires research into the minimum operating system requirements and the minimum hardware requirements necessary to support the DNS server software. In addition, standard operating systems typically include a multitude of drivers that are unnecessary for the operation of a DNS server, such as for example drivers for sound cards, video cards and all available disk drives. The presence of extra drivers within the operating system creates a potential for conflicts with other DNS server software components thereby increasing the likelihood of error or malfunctions. The larger kernel size of an operating system with unnecessary drivers often results in decreased DNS server performance, such as reduced input/output throughput to the computer network and hard drive.

Following the selection of the appropriate DNS server hardware, the DNS server software requires tuning to the selected hardware to optimize the performance of the DNS server. For example, kernel buffer sizes have to be set to match the specific input/output hardware including a disk controller and network adapters.

Prior art DNS server software packages typically include a relational database for storing DNS data. DNS data generally consists of numerous data items with often complex interconnections between those items. Relational databases do not easily support complex mapping between data items and as a result multiple complex relational queries in a relational query language, such as Structured Query Language (SQL), may be required to perform simple modifications to data relationships within the database.

Prior art DNS server software packages also includes graphical user interfaces (GUIs) which permit the administrator to access the relational database. GUIs are typically installed on a single computer and accessible only on that computer by the administrator. Typically, DNS server software does not permit access to the GUIs from any networked computer within a computer network. The selection and integration of network software, such as PC Anywhere, with the DNS server system may be used to permit the administrator to access the GUI over a computer network. However, such software does not work with World Wide Web (WWW) protocols and requires special installation on every computer used to access the DNS server computer. Also, prior art DNS servers typically do not include a web based interface to access GUIs.

Prior art DNS servers may also have multiple unnecessary hardware and software access points. For example, the DNS server hardware can be accessed via a monitor, a keyboard, a mouse, a parallel port, serial ports, a network interface and a universal serial bus (USB) interface. The availability of multiple access points render the DNS server susceptible to access by unauthorized personnel. In addition, standard operating systems also include multiple access points, such as a console terminal and numerous network ports. The availability of such unnecessary access ports render the DNS server vulnerable to potential attacks from computer hackers and may also cause the DNS server to run inefficiently.

3

SUMMARY OF THE INVENTION

A method of providing configuration access to a DNS server system from a client in a computer network includes establishing communicative coupling between a client web browser and a DNS server system web server. A user interface adapted to provide configuration access to a DNS server system is requested. The user interface is downloaded from the DNS server system over the computer network.

The user interface may comprise a GUI.

The user interface may comprise a JGUI.

The user interface may be adapted to provide configuration access to a DNS database.

The user interface may be adapted to provide configuration access to a DNS object oriented database.

The user interface may be adapted to provide access to an object oriented database.

Communicative coupling may be established between the client web browser and a DNS configuration server.

The computer network may comprise the Internet.

The computer network may comprise an IP based computer network.

The computer network may comprise an intranet.

Communicative coupling may be established between the user interface and a configuration server.

The DNS server system may comprise a DNS server appliance.

In accordance with another aspect of the present invention, a method of providing an IP address for a host in a computer network includes receiving a request for an IP address associated with a domain name from a client in a computer network. The requested IP address is retrieved from an object oriented database. The retrieved address is transmitted to the client.

Communicative coupling may be established between a client web browser and a DNS server.

The computer network may comprise the Internet.

The computer network may comprise an IP based computer network.

The computer network may comprise an intranet.

The DNS server system may comprise a DNS server appliance.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram representation of the DNS server appliance within a computer network in accordance with the principles of the present invention.

FIG. 2 is a block diagram representation of the hardware components of the DNS server appliance of FIG. 1.

FIG. 3 is a block diagram representation of the software components of the DNS server appliance of FIG. 1.

FIG. 4 is a representation of a hierarchical structure of zones and sub-zones in the DNS system.

FIG. 5 is a block diagram representation of data routes from a client to a host via sub-networks.

FIG. 6 is a block diagram representation of objects typically stored in a DNS object oriented database.

FIG. 7 is a block diagram representation illustrating the rerouting of host objects within the DNS object oriented database.

FIG. 8 is an example of a GUI for accessing the DNS server appliance.

DETAILED DESCRIPTION OF THE INVENTION

Referring to FIG. 1, a domain name service (DNS) server appliance 10 in accordance with a preferred embodiment of

4

the present invention is shown in a computer network 16. Matched hardware and pre-installed software components are integrated into a fully functional package to facilitate the installation and operation of the DNS server appliance 10. The DNS server appliance 10 includes a power button 12 and a status light 14 which is turned on when power is supplied to the DNS server appliance 10.

The DNS server appliance 10 is adapted for use in Internet Protocol (IP) based computer networks, such as the Internet and intranet applications employing IP to convey data from one networked device to another networked device. The computer network 16 including a plurality of hosts 18, a plurality of clients 20 and the DNS server appliance 10 is shown. Each host 18 is identifiable by at least one domain name 22 and a unique IP address 24. For example, the host computer 18 may be identified by its domain name "www.support.infoblox.com" 26 or by its IP address as "192.168.10.100." 28.

The DNS server appliance 10 is limited to enable interaction with clients 20 and administrators. When a client 20 wishes to establish a network connection with the host computer 18 for "www.support.infoblox.com," 26, the client 20 contacts the DNS server appliance 10 and requests the IP address 24 associated with the domain name "www.support.infoblox.com" 26. The DNS server appliance 10 supplies the client 20 with the corresponding IP address "192.168.10.100." 28. The client 20 then uses the received IP address 24 to send data packets to the host 18. The DNS server appliance 10 is designed to enable the administrator to access the DNS server appliance 10 via the computer network 16 using any client 18. This permits an administrator to perform routine administrative functions, such as updating the IP address 24 for a domain name 22, via a remote networked computer.

Referring now to FIG. 2, the DNS server appliance hardware 30, the platform for running and storing DNS server appliance software, storing DNS data and providing an interface to the computer network 16, is shown. The DNS server appliance hardware 30 generally includes a computer motherboard 32 including a central processing unit (CPU) 34 coupled to a random access memory (RAM) 36. A disk 38 (e.g., a computer readable medium), such as for example a multigigabyte hard drive, is used to store DNS server appliance software and DNS data and is coupled to the motherboard 32. A power supply 39 is adapted to be coupled to an alternating current (AC) power source (not shown), such as for example a 110 Volt AC power source, via a power input 41. The power supply 39 is also coupled to the motherboard 32 and converts the AC power supplied by the power source into a direct current (DC) voltage, such as for example ± 5 DC volts, to power the motherboard 32. The power button 12 is coupled to the power supply 39 and controls the application of power to the motherboard 32. The status light 14, such as for example a light emitting diode (LED), is coupled to the motherboard 32 and provides an indication of when power is supplied to the motherboard 32 and the DNS server appliance 10 is powered on. A network interface 43 to the motherboard 32 is provided to permit a client 20 to access the DNS server appliance 10 to request an IP address 24 for a specific domain name 22. A serial interface 40 to the motherboard 32 provides the administrator with access to the motherboard 32 to assign an IP address 24 to the DNS server appliance 10. The DNS server appliance 10 hardware configuration limits the number of hardware access ports to minimize the risk of unauthorized access to the DNS server appliance software and DNS data. Limiting the number of hardware access ports also reduces

5

the number of software drivers necessary to operate the DNS server appliance **10** thereby reducing inefficiencies in the system.

In an alternative embodiment, multiple disks may be used to provide redundancy and increase system reliability. In another embodiment, a wireless access port, such as an infrared port, may be added to the system or may be substituted for the serial interface **40**. Such a port would enable an administrator to assign an IP address **24** to the DNS server with the use of a personal assistant device, such as a Palm Pilot. While the preferred embodiment of the DNS server appliance **10** includes the disclosed hardware configuration, alternative configurations of hardware adapted to optimize DNS server appliance performance and provide limited access to DNS server appliance software are considered to be within the scope of the invention.

Turning now to FIG. 3, the DNS server appliance software components **42** including DNS server **44**, a web server **46** and a configuration server **48** all run on an operating system **52**. Network ports **54** provide communication links between each server and the computer network **16**. An object oriented database **56** is generally used to store domain name data and IP address data. A graphical user interface (GUI) **58** is provided to enable the administrator to access the object oriented database **56** to perform configuration changes, such as modifications and updates. In an alternative embodiment, a dynamic host configuration protocol (DHCP) server may also be included as a component of the DNS server appliance **10**.

The DNS server **42** is coupled to the computer network **16** via a network port **54** and to the object oriented database **56**. When a client **20** issues a request for an IP address **24** associated with a specific domain name **22**, the DNS server responds to the request by accessing the object oriented database **56** to retrieve the requested IP address **24** and conveying the retrieved IP address **24** to the client **20** via the network port **54**.

The web server **46** is adapted to perform the single function of responding to a request from the administrator to retrieve and deliver the GUI **58** to the administrator. The administrator uses a networked client **20**, to convey a request to the web server **46** to download the GUI **58**. The web server **46** responds to the request by retrieving the GUI **58** from the disk and conveying it via the computer network **16** to the administrator's networked client **20**. The downloaded GUI **58** runs on a standard web browser, such as Netscape or Internet Explorer and establishes an interface between the client **20**, being used by the administrator, and the configuration server **48**. The configuration server **48** responds to commands issued by the administrator via the GUI **58** to perform configuration changes to the object oriented database **56**.

The DNS server appliance software components **42** and the operating system **52** are specifically matched and tuned to accommodate the specifications of the DNS server appliance hardware components **30** to optimize the overall performance of the DNS server appliance **10**.

In the preferred embodiment, the operating system **52** is derived from an operating system kernel, as is included in a standard Linux distribution. The necessary device drivers are added to the operating system kernel. The device drivers used are specifically matched to the DNS server appliance hardware **30** and updated with the most recent patches to achieve the higher levels of system stability and performance. For example, unnecessary drivers or other utilities are present in the kernel operating system are removed or disabled. The lack of extra drivers reduces the possibility of conflicts occurring between the operating system software and other DNS server appliance software components. The reduced kernel size of

6

the operating system **52** increases DNS server appliance performance. For example, input/output throughput to the computer network **16** and hard drive is increased. The operating system **52** is also streamlined to eliminate unnecessary software access points, such as unnecessary network ports **54**. This reduces the vulnerability of the DNS server appliance **10** to potential attacks by hackers. In addition, the DNS server software components **42** are pre-installed and pre-configured for operation so as to reduce the time and expertise necessary to install and operate the DNS server appliance **10**.

An alternative embodiment of the DNS server appliance includes a microkernel operating system which may be embedded in a read only memory (ROM) boot image. In another embodiment, a solid state storage device is used to store the object oriented database. The use of a microkernel operating system, ROM boot image, and solid state storage eliminates the need for a mechanical storage disk in the DNS server appliance thereby reducing the amount of DNS server appliance hardware which in turn reduces the possibility of potential hardware malfunctions.

Referring now to FIG. 4, DNS uses a logical hierarchical structure **60** consisting of zones and sub-zones to facilitate the organization of domain names within the DNS system. Such a structure is comparable to an inverted tree with the root "dot" **62** at top of the hierarchy. The root "dot" **62** branches down to the top level of zones **64**. Examples of top level zones **64** include "com," "edu," "org," "net," "gov," and "mil," as well as abbreviations for numerous countries. Each top level zone **64** may branch further into a number of sub-zones or second level zones **66**. For example the top level zone "com" may include a number of second level sub-zones such as "infoblox.com" and "yahoo.com." The second level sub-zones **66** may branch into further third level sub-zones **68**. For example, the second level sub-zone "infoblox.com" includes further third level sub-zones "support.infoblox.com" and "sales.infoblox.com." The lowest level sub-zone **70** includes one or more hosts **18**. For example, the sub-zone "support.infoblox.com" includes three hosts: "www.support.infoblox.com," "mail.support.infoblox.com" and "server.support.infoblox.com." The sub-zone "sales.infoblox.com" includes a single host, "mail.sales.infoblox.com." FIG. 4 is merely illustrative of an example of an hierarchy within the DNS system. Different DNS hierarchies may include a greater or fewer number of sub-zones. In addition, it is possible for a member of a sub-zone to be linked to more than one upper level zones.

Referring now to FIG. 5, a block diagram representation of an example of a network configuration **72** is shown, where a client **20** sends a data packet to a host **18** having an IP address "192.168.10.100." IP addresses **24** for hosts **18** generally consist of four numbers separated by periods, such as for example 192.168.10.100. When a client **20** sends data packets to a given host **18**, the IP address designates the route that the data packets must take to reach the host associated with the IP address **24**. The route consists of a number of sub-networks within the computer network **16**. Each sub-network is associated with a router. Routers are responsible for interpreting IP addresses **24** and channeling appropriate packets into appropriate sub-networks. The client **20** routes the data packet with the IP address **24** to the routers. The router recognizing "192.000.00.000" as the designation **74** for its associated sub-network accepts and routes the data packet to additional routers associated with further sub-networks. The router recognizing "192.168.00.000" as the designation **76** for its associated sub network accepts and further routes the data packet to routers associated with further sub networks. The router recognizing "192.168.10.000" **78** as the designa-

tion for its associated sub network accepts the data packet and routes the data packet to the hosts **18** within the sub network. The host **80** having the IP address of “192.168.10.100” accepts the data packet.

As shown in FIG. 6, the hierarchical zone information associated with domain names **22** and the sub-network designations are used by the DNS server appliance **10** to store domain name data and IP address data in the object oriented database **56**. The DNS server appliance **10** stores the hierarchical zone information as zone objects **82**, network designations as network objects **84** and the host data as host objects **86**. For example, the zone “com” is represented in the objected oriented database as a zone object **88** having an attribute “com”. Similarly, the zone “infoblox.com” is represented as a zone object **90** having an attribute “infoblox” and an association to the zone object **88** having the attribute “com”. The zone “support.infoblox.com” is represented as zone object **92** having the attribute “support” and the zone “sales.infoblox.com” is represented as zone object **94** respectively, with each zone object having an association to the zone object **90** having the attribute “infoblox”.

The network designations are stored in a similar manner. For example, the network designation “192.000.00.000” is stored as a network object **96** having an attribute “192”. The network designation “192.168.00.000” is stored as a network object **98** having an attribute “168” and an association to the network object **96** having the attribute “192”. Network designation “192.168.10.000” is stored as network object **100** having the attribute of “10” and network designation “192.168.20.000” is stored as network object **102** having the attribute of “20” respectively, with each network object having an association to the network object **98** having the attribute “168”.

The hosts **18** are also stored as host objects **86** where each host object **86** has two attributes. For example, the host “www.support.infoblox.com” is stored as a host object **104** having attributes “www” and “100” and associations to the zone object **92** having the attribute “support” and the network object **100** having the attribute “10”. The other hosts **18** are stored in a similar manner as host objects **86** with two attributes and an association to a zone object **82** and a network object **84**. While the preferred embodiment discloses the use of the described object oriented database model, alternative object models are also within the scope of the invention.

The process of requesting and retrieving an IP address **24** associated with a specific domain name **22** from the DNS server appliance **10** begins with the client **20** providing a domain name, such as “www.support.infoblox.com,” to the web browser. The web browser establishes a connection with the DNS server **44** and issues a request for the IP address **24** associated with the provided domain name, “www.support.infoblox.com.”

The DNS server **44** first identifies the top level zone **64** in the domain name “www.support.infoblox.com.” as “com.” The DNS server **44** uses this information to access the object oriented database **56** and retrieve the zone object **88** having the attribute “com”. The DNS server **44** then identifies the next sub-zone **66** in the hierarchy as “infoblox.com.” The DNS server **44** then accesses the object oriented database **56** and retrieves the zone object **90** having the attribute “infoblox” and an association to the zone object **88** having the attribute “com”. The DNS server **44** then identifies the next sub-zone **68** in the hierarchy as “support.infoblox.com.” The DNS server **44** uses this information to access the object oriented database **56** and retrieves the zone object **92** having the attribute “support” and an association to the zone object **90** having the attribute “infoblox”.

The DNS server **44** realizes that it has reached the last term in the domain name **22** and that “www.support.infoblox.com” identifies the host **18**. The DNS server **44** returns to the object oriented-database **56** and identifies the host object **104** having the attribute “www” and an association with the zone object **92** having the attribute “support.” The identified host object **104** also has a second attribute “100.” The DNS server **44** recognizes that the host object **104** has an association to the network object **100** having the attribute “10” which in turn has an association to the network object **98** having the attribute “168” which in turn has an association to the network object **96** having the attribute “192”. As a result, the DNS server **44** is able to retrieve the entire IP address of “192.168.10.100” in a single access. The DNS server **44** forwards the requested IP address **24** to the client **20**. The client **20** then uses the supplied IP address **24** to establish a connection with the host **20**.

In the previous example, the DNS server **44** accessed the object oriented database **56** a total of four times to perform the IP address retrieve operation, as opposed to a relational database which would have required the DNS server to access the relational database seven times. Storing the zones, network designations and hosts **18** as objects in an object oriented database **56** permits the mapping of complex interrelationships between data items in such a manner as to enable the DNS server **44** to retrieve IP addresses **24** using a fewer number of database accesses. Given the large number of IP addresses **24** retrieved by the DNS server appliance **10** on a routine basis, the use of an object oriented database **56** increases the efficiency of the operation of the DNS server appliance **10** by reducing the number of database accesses required per IP address **24** retrieval.

Referring now to FIG. 7, networks are often reconfigured resulting in changes to the IP address **24** associated with a host **18**. This requires that the DNS server appliance **10** be updated to reflect the new IP address **24** so that data packets addressed to affected hosts **18** are rerouted appropriately through other available sub-networks. Suppose for example, that the sub-network **106** designated as “192.168.10.000” was removed from the computer network **16**. The DNS server appliance **10** would have to be updated with a new IP addresses **24** for the host **108** “www.support.infoblox.com,” the host **110** “mail.support.infoblox.com” and the host **112** “server.support.infoblox.com.” To update the DNS server appliance **10**, the affected hosts **108**, **110**, **112** are first unlinked from the unavailable sub-network **106**. This is achieved by first removing the network object **106** having the attribute “10” from the object oriented database **56**. The deletion of the network object **106** automatically removes the associations between the affected host objects **108**, **110**, **112** and the network object **106**. Next the affected hosts **108**, **110**, **112** must be relinked to the available sub-network “192.168.10.000.” Associations between the network object **116** having the attribute “20” and the affected host objects **108**, **110**, **112** are created. The DNS server appliance **10** automatically updates the IP addresses **24** for the hosts “www.support.infoblox.com,” “mail.support.infoblox.com” and “server.support.infoblox.com” to “192.168.20.100,” “192.168.20.101” and “192.168.20.102,” respectively. Storing the sub-network designations as objects facilitates the reassignment of hosts to different sub networks by minimizing the number of modifications an administrator is required to make to implement a successful reassignment.

Referring now to FIG. 8, the administrator makes configuration changes to the object oriented database **56** via the GUI **58**, an example of which is shown. The GUI **58** includes an upper header section **200** including a plurality of icons with a text label below each icon. Upon clicking on an icon, a dia-

logue box is provided requesting the data necessary to implement the configuration operation associated with that icon. Selecting the first icon **202** enables the administrator to add network objects to the object oriented database **56**. The second icon **204** provides a mechanism for adding zone object. Similarly, clicking on the third icon **206** provides for the addition of a network object. Clicking on the fourth icon **208** permits the user to add additional domain names associated for IP addresses already present in the database. Clicking on the fifth **210** and sixth **212** icons permits the administrator to modify an existing object and remove objects, respectively, from the object oriented database. The remainder of the GUI is divided into a first section **214** and a second section **216**. The first section **214** displays network and zone information in a tree format. The second section **216** displays a listing of hosts associated with user selected zones or networks.

In the preferred embodiment, a Java applet is used as the GUI **58**. An applet is a type of Java application that is adapted to be downloaded from a web server by a web browser via the computer network **16** and executed as a web browser application. Such web browser applications include Netscape and Internet Explorer. In the preferred embodiment the GUI **58** is developed using a customized GUI library, such as Java Graphical User Interface (JGUI). A GUI library is a collection of GUI widgets, such as buttons, scroll bars and windows. A JGUI based interface provides the same GUI screenshot regardless of the underlying operating system. For example, a client would have a GUI screenshot with the same look and feel whether the GUI was downloaded to a Windows system, Xwindows, Macintosh windowing system. The JGUI based interface reduces the GUI **58** response time, for example bringing up a dialogue box following the selection of an associated button typically takes less time than on other types of GUIs.

While in the preferred embodiment, the use of JGUI is disclosed, other types of GUIs such as those based on Java Abstract Windows Toolkit (AWT), Hypertext Markup Language (HTML), JavaScript, Visual Basic Script (VBScript) and web browser plugins, such as Macromedia's Flash, are also considered to be within the scope of the invention. In addition, the preferred embodiment discloses the use of a web browser in conjunction with a web server **46** to deliver the GUI **58** to the administrator, other comparable methods of retrieving the GUI **58** from the DNS server appliance **10** over the computer network **16** are also considered to be within the spirit of the invention.

In the preferred embodiment, the DNS server appliance **10** is adapted to enable a one click auto software upgrade of all of the DNS server appliance software, including the operating system **52**, simultaneously. This minimizes the risk of software incompatibilities which can often lead to system failures. The administrator initiates the auto software upgrade by clicking on a single button provided on the GUI **58**.

In an alternative embodiment, the DNS server appliance **10** is provided with a server to server auto failover feature. This enables an administrator to run a set of redundant DNS server appliances **10**, a primary and a secondary DNS server. Both DNS server appliances **10** receive simultaneous updates to their object oriented databases **56**, so that they both contain identical DNS data. In the event the DNS server appliance **10** fails, a scheme is automatically implemented to hand over control to the secondary DNS server appliance **10** without any action required on the part of the administrator. In an alternative embodiment, the DNS server appliance includes a self-upgrade feature where the DNS server can automatically update its software without any action from an administrator.

In another embodiment, the DNS server appliance **10** maintains a journaled file system to increase the reliability of the system.

In an alternative embodiment, specialized hardware, such as EZ chip, may be used to resolve domain name to IP address maps or IP address to domain name maps as wire speed.

While the invention has been described with specific embodiments, other alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, it is intended to include all such alternatives, modifications and variations set forth with the spirit and scope of the appended claims.

The invention claimed is:

1. A method of providing an IP address for a host in a computer network, the method comprising the steps of:
 - receiving, from a client in a computer network, at an appliance a request for an IP address associated with a domain name associated with a zone;
 - retrieving the requested IP address from an object oriented database associated with the appliance; and
 - transmitting the retrieved IP address to the client;
 wherein:
 - the object oriented database comprises a zone object tree that includes a plurality of zone objects, including a first zone object associated with the zone, wherein the first zone object is linked to a second zone object associated with a sub-zone of the zone;
 - the zone and sub-zone are associated with a logically hierarchical set of zone information;
 - the object oriented database comprises a network object tree that includes a logically hierarchical set of network objects each associated with a numerical sub-network designation, wherein the logically hierarchical set of network objects corresponds to the IP address associated with a host object; and
 - the zone object tree and the network object tree are linked via the host object that is associated with the domain name and the IP address, wherein the host object is stored with a first attribute corresponding to a first sub-zone of the domain name and a second attribute corresponding to a first numerical sub-network designation of the IP address.
2. The method of claim 1, further comprising the step of establishing communicative coupling between a client web browser and the appliance.
3. The method of claim 1, wherein the computer network comprises the Internet.
4. The method of claim 1, wherein the computer network comprises an IP based computer network.
5. The method of claim 1, wherein the computer network comprises an intranet.
6. The method of claim 1, wherein the appliance receives the request.
7. The method of claim 1, further including linking a host object with a network object and a zone object.
8. The method of claim 7, wherein the zone object is linked to another zone object.
9. The method of claim 7, wherein the network object is linked to another network object.
10. The method of claim 1, further including:
 - unlinking an old network object from a host object;
 - deleting the old network object; and
 - linking the host object to a new network object.
11. The method of claim 10, further including automatically updating the host object to reflect an association with the new network object.

11

12. The method of claim 1, wherein the operating system is derived from a full operating system that includes the at least one software component.

13. The method of claim 1, wherein the at least one software component includes one of the following: a driver or a utility software.

14. The method of claim 1, wherein the appliance excludes a hardware component that typically is included in a host computing system but that is not required to provide the network name-related functionality.

15. The method of claim 1, wherein the appliance excludes a communication port that typically is included in a host computing system but that is not required to provide network name-related functionality.

16. The method of claim 1, wherein the network name-related functionality comprises the Domain Name Service (DNS) and the IP address comprises a requested IP address associated with a host identified in a DNS request received at the appliance.

17. The method of claim 1, further including providing an interface for configuring the appliance.

18. The method of claim 1, further including providing a web interface for configuring the appliance from a client web browser.

19. The method of claim 1, wherein the appliance includes a DNS server, a configuration server, a web server, a database, and/or a GUI.

20. The method of claim 1, wherein the database comprises an object oriented database.

21. The method of claim 1, wherein retrieving includes identifying a top level zone in the domain name and accessing a zone object associated with the top level zone.

22. The method of claim 21, wherein retrieving includes identifying a sub-zone in the domain name and accessing a zone object associated with the sub-zone.

23. The method of claim 22, wherein retrieving includes realizing that a last term in a domain name has been reached and accessing a host object associated with the domain name.

24. A computer program product for providing an IP address for a host in a computer network, the computer program product being embodied in a computer readable medium and comprising computer instructions for:

receiving, from a client in a computer network, at an appliance a request for an IP address associated with a domain name associated with a zone;

retrieving the requested IP address from an object oriented database associated with the appliance; and

transmitting the retrieved IP address to the client;

wherein:

the object oriented database comprises a zone object tree that includes a plurality of zone objects, including a first zone object associated with the zone, wherein the first zone object is linked to a second zone object associated with a sub-zone of the zone;

the zone and sub-zone are associated with a logically hierarchical set of zone information;

a logically hierarchical set of network objects each associated with a numerical sub-network designation, wherein the logically hierarchical set of network objects corresponds to the IP address associated with a host object; and

the zone object tree and the network object tree are linked via the host object that is associated with the domain name and the IP address, wherein the host object is stored with a first attribute corresponding to a first sub-zone of the domain name and a second

12

attribute corresponding to a first numerical sub-network designation of the IP address.

25. A computer program product as recited in claim 24, the computer program product further comprising computer instructions for establishing communicative coupling between a client web browser and the appliance.

26. A computer program product as recited in claim 24, wherein the computer network comprises the Internet.

27. A computer program product as recited in claim 24, wherein the computer network comprises an IP based computer network.

28. A computer program product as recited in claim 24, wherein the computer network comprises an intranet.

29. A computer program product as recited in claim 24, wherein the appliance receives the request.

30. A computer program product as recited in claim 24, the computer program product further comprising computer instructions for linking a host object with a network object and a zone object.

31. A computer program product as recited in claim 30, wherein the zone object is linked to another zone object.

32. A computer program product as recited in claim 30, wherein the network object is linked to another network object.

33. A computer program product as recited in claim 24, the computer program product further comprising computer instructions for:

unlinking an old network object from a host object;

deleting the old network object; and

linking the host object to a new network object.

34. A computer program product as recited in claim 33, the computer program product further comprising computer instructions for automatically updating the host object to reflect an association with the new network object.

35. The computer program product of claim 24, wherein the operating system is derived from a full operating system that includes the at least one software component.

36. The computer program product of claim 24, wherein the at least one software component includes one of the following: a driver or a utility software.

37. The computer program product of claim 24, wherein the appliance excludes a hardware component that typically is included in a host computing system but that is not required to provide the network name-related functionality.

38. The computer program product of claim 24, wherein the appliance excludes a communication port that typically is included in a host computing system but that is not required to provide network name-related functionality.

39. The computer program product of claim 24, wherein the network name-related functionality comprises the Domain Name Service (DNS) and the IP address comprises a requested IP address associated with a host identified in a DNS request received at the appliance.

40. The computer program product of claim 24, the computer program product further comprising computer instructions for providing an interface for configuring the appliance.

41. The computer program product of claim 24, the computer program product further comprising computer instructions for providing a web interface for configuring the appliance from a client web browser.

42. The computer program product of claim 24, wherein the appliance includes a DNS server, a configuration server, a web server, a database, and/or a GUI.

43. The computer program product of claim 24, wherein the database comprises an object oriented database.

13

44. The computer program product of claim 24, wherein retrieving includes identifying a top level zone in the domain name and accessing a zone object associated with the top level zone.

45. The computer program product of claim 44, wherein retrieving includes identifying a sub-zone in the domain name and accessing a zone object associated with the sub-zone.

46. The computer program product of claim 45, wherein retrieving includes realizing that a last term in a domain name has been reached and accessing a host object associated with the domain name.

47. A system for providing an IP address for a host in a computer network, including:

a processor configured to:

receive, from a client in a computer network, at an appliance a request for an IP address associated with a domain name associated with a zone;

retrieve the requested IP address from an object oriented database associated with the appliance;

transmit the retrieved IP address to the client;

wherein:

the object oriented database comprises a zone object tree that includes a plurality of zone objects, including a first zone object associated with the zone, wherein the first zone object is linked to a second zone object associated with a sub-zone of the zone;

the zone and sub-zone are associated with a logically hierarchical set of zone information;

a logically hierarchical set of network objects each associated with a numerical network sub-designation, wherein the logically hierarchical set of network objects corresponds to the IP address associated with a host object; and

the zone object tree and the network object tree are linked via the host object that is associated with the domain name and the IP address, wherein the host object is stored with a first attribute corresponding to a first sub-zone of the domain name and a second attribute corresponding to a first numerical sub-network designation of the IP address; and

a memory coupled with the processor, wherein the memory provides the processor with instructions.

48. The system of claim 47, wherein the processor is further configured to establish communicative coupling between a client web browser and the appliance.

49. The system of claim 47, wherein the computer network comprises the Internet.

50. The system of claim 47, wherein the computer network comprises an IP based computer network.

51. The system of claim 47, wherein the computer network comprises an intranet.

52. The system of claim 47, wherein the appliance receives the request.

14

53. The system of claim 47, wherein the processor is further configured to link a host object with a network object and a zone object.

54. The system of claim 53, wherein the zone object is linked to another zone object.

55. The system of claim 53, wherein the network object is linked to another network object.

56. The system of claim 47, wherein the processor is further configured to:

unlink an old network object from a host object;

delete the old network object; and

link the host object to a new network object.

57. The system of claim 56, wherein the processor is further configured to automatically update the host object to reflect an association with the new network object.

58. The system of claim 47, wherein the operating system is derived from a full operating system that includes the at least one software component.

59. The system of claim 47, wherein the at least one software component includes one of the following: a driver or a utility software.

60. The system of claim 47, wherein the appliance excludes a hardware component that typically is included in a host computing system but that is not required to provide the network name-related functionality.

61. The system of claim 47, wherein the appliance excludes a communication port that typically is included in a host computing system but that is not required to provide network name-related functionality.

62. The system of claim 47, wherein the network name-related functionality comprises the Domain Name Service (DNS) and the IP address comprises a requested IP address associated with a host identified in a DNS request received at the appliance.

63. The system of claim 47, wherein the processor is further configured to provide an interface for configuring the appliance.

64. The system of claim 47, wherein the processor is further configured to provide a web interface for configuring the appliance from a client web browser.

65. The system of claim 47, wherein the appliance includes a DNS server, a configuration server, a web server, a database, and/or a GUI.

66. The system of claim 47, wherein the database comprises an object oriented database.

67. The system of claim 47, wherein retrieving includes identifying a top level zone in the domain name and accessing a zone object associated with the top level zone.

68. The system of claim 67, wherein retrieving includes identifying a sub-zone in the domain name and accessing a zone object associated with the sub-zone.

69. The system of claim 68, wherein retrieving includes realizing that a last term in a domain name has been reached and accessing a host object associated with the domain name.

* * * *