



US007870686B2

(12) **United States Patent**  
**Hines**

(10) **Patent No.:** **US 7,870,686 B2**  
(45) **Date of Patent:** **Jan. 18, 2011**

(54) **LIGHTED SUBWAY SIGNAGE**

(76) Inventor: **Stephen P. Hines**, 1540 Wabasso Way,  
Glendale, CA (US) 91208

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 239 days.

(21) Appl. No.: **12/290,937**

(22) Filed: **Nov. 5, 2008**

(65) **Prior Publication Data**

US 2009/0071050 A1 Mar. 19, 2009

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 12/150,534,  
filed on Apr. 29, 2008, which is a continuation-in-part  
of application No. 11/801,891, filed on May 11, 2007,  
now abandoned.

(51) **Int. Cl.**  
**G09F 19/14** (2006.01)

(52) **U.S. Cl.** ..... **40/453; 40/442; 40/564;**  
352/100

(58) **Field of Classification Search** ..... **40/453,**  
**40/454, 442, 564; 352/100**  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

742,632 A \* 10/1903 Hadden ..... 352/100

917,587 A *	4/1909	Good	.....	352/100
978,854 A *	12/1910	Czerniewski	.....	352/100
2,026,753 A *	1/1936	Rosenthal et al.	.....	352/100
4,179,198 A *	12/1979	Brachet et al.	.....	352/100
4,383,742 A *	5/1983	Brachet et al.	.....	352/100
6,353,468 B1 *	3/2002	Howard et al.	.....	352/100
2005/0174539 A1 *	8/2005	Walker et al.	.....	352/100

\* cited by examiner


*Primary Examiner*—Gary C Hoge

(74) *Attorney, Agent, or Firm*—Wagner, Anderson & Bright,  
P.C.; Roy L. Anderson

(57) **ABSTRACT**

A subway tunnel light box for displaying a back-lighted image to a viewer inside of a subway car traveling in the subway tunnel in which a transparent video display for displaying a number of images, such as an LCD, is mounted in the light box and a narrow light source, preferably having a width of one pixel, is positioned in the box behind each of the images at a distance less than a typical viewing distance so that each image is illuminated by an associated narrow light source with an associated narrow light source horizontal illumination angle substantially the same as a preselected perceived horizontal viewing angle calculated for the typical viewing distance based upon a physical height of the transparent video display and a desired aspect ratio of a perceived image.

**25 Claims, 33 Drawing Sheets**






Fig. 1





Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12






Fig. 13






Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 23




Fig. 22




Fig. 24a




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29




Fig. 30




Fig. 31




Fig. 32




Fig. 33




Fig. 34




Fig. 35




Fig. 36




Fig. 37




Fig. 38a




Fig. 38b




Fig. 39




Fig. 40b

Fig. 40a

**LIGHTED SUBWAY SIGNAGE****CROSS REFERENCE TO RELATED APPLICATIONS**

This application is a continuation-in-part application of U.S. patent application Ser. No. 12/150,534 filed Apr. 29, 2008 which itself was a continuation-in-part application of U.S. patent application Ser. No. 11/801,891 filed May 11, 2007, now abandoned, the disclosures of both of which are specifically incorporated herein by reference.

**FIELD OF THE INVENTION**

The present invention is in the field of graphic displays viewed by persons rapidly moving past them, such as passengers in a subway car or a train.

**BACKGROUND OF THE INVENTION**

Advertising is pervasive in today's world. It seems as if it appears everywhere and advertisers are always looking for new ways to get their message across and attract the attention of target audiences. Indeed, industries have grown up around advertising in various media, including new, specialized media, as well as around new ways of advertising, product placement, and so on.

It has long been known that subways and trains present an advertising opportunity. A subway or train is filled with passengers and they often go through tunnels not visible to the outside world. This means that signage in such tunnels presents a rather unique advertising opportunity. A sign in such a location will have a captive audience as riders pass by it. Locating signage in such tunnels will not generate the same types of concerns that often arise in connection with billboards and other signage in open, public places, which often is subject to regulation. However, there are some difficulties with such signage, such as access for changing the signs and lamps, size and the need to catch the attention of riders, especially when they are passing through a tunnel at a relatively high rate of speed.

One idea that has been around for quite some time overcomes the smearing effect of a speeding subway train to create the appearance of a stationary picture, which can be a still image or animated, by use of a series of fixed still frames. This can be analogized to motion pictures in the pre-digital age when motion pictures relied upon a series of still photographs on film projected in rapid succession onto a screen by a movie projector, which, with persistence of vision, produced the effect of moving images. However, unlike motion pictures, the screen in a subway tunnel is not fixed. It is, instead the movement of the train past a series of pictures fixed on the subway wall that is roughly analogous to the movie projector by providing the rapid succession of images to the viewer. This means that the series of pictures must be correctly positioned on the subway wall, and lighted, and if animated, the pictures must be created to take into account the speed of the train relative to the fixed images to display the animated commercial at the correct speed. This, in turn, has created many challenges, and a great many inventors have sought to address such challenges for a long time.

For example, in U.S. Pat. No. 2,299,731, issued in 1942, a display system for moving vehicles is described which provides for illumination of a series of displays by successive brilliant flashes of light of extremely short duration. Roughly thirty years later, stroboscopic systems for display were disclosed in U.S. Pat. Nos. 3,694,062 and 3,951,529 while U.S.

Pat. No. 3,704,064 disclosed a flash tube for use in a subway signage animation system. One of the problems with such systems was high cost, and U.S. Pat. No. 4,393,742, issued in 1983, sought to reduce such cost by using a sensor to measure the velocity of a train and then initiate the flash cycle based upon the results of the sensor. Another problem with such systems was the triggering mechanism for illuminating the series of displays, and one invention directed to this problem is U.S. Pat. No. 5,108,171, issued in 1992.

With the dawning of the new millennium, a number of new patents have issued in the art of subway signage. U.S. Pat. No. 6,169,368 discloses the use of a sensor to activate a controller upon the approach of a train to trigger an electronic display mechanism controlled by a computer. U.S. Pat. No. 6,353,468 discloses use of flat screen LED monitors in the display. U.S. Pat. No. 6,466,183 discloses a video display apparatus. U.S. Pat. No. 6,870,596 discloses a subway movie/entertainment medium and news reports indicate that the company which owns this patent, Sidetrack Technologies Inc., has installed its system in a number of subways throughout the world.

Thus, it is clear that there is a need and demand for subway signage systems and this is a medium of advertising that has drawn considerable attention, including commercial attention, over the years.

In U.S. Pat. No. 6,564,486, issued in 2003 to Spodek et al. ("Spodek"), an approach to subway signage is disclosed which is analogous to a zoetrope for use in subway signage systems in an attempt to overcome problems associated with stroboscopic displays, such as timing. Spodek uses a display in which a series of still pictures are viewed through a slit-board mounted between the images and the viewers in a train. The details and math associated with such a display are discussed in rather great detail in Spodek and will not be repeated herein, but simply incorporated herein by reference for use as part of the background to the present invention. The technology of Spodek has been licensed to a company named Submedia that has advertising systems that are now located in some of the world's top media markets, including New York, Washington, D.C., Chicago, Atlanta, Boston, Hong Kong, Tokyo and Mexico City.

The present invention seeks to advance the art of subway signage by advancing the teachings of Spodek through use of novel apparatus and methods that greatly increases the efficiency and ease of use of subway signage systems according to the teachings of the present invention.

**SUMMARY OF THE INVENTION**

The present invention is generally directed to a subway tunnel light box and a method of installing it in a subway tunnel for displaying a back-lighted image to a viewer inside of a subway car traveling in the subway tunnel in which a transparent video display for displaying a number of images is mounted in the light box and a narrow light source is positioned in the box behind each of the images so that each image is illuminated by an associated narrow light source with an associated light source horizontal illumination angle substantially the same as a preselected perceived horizontal viewing angle calculated for a typical viewing distance based upon a physical height of the transparent video display and a desired aspect ratio of a perceived image.

In a first, separate group of aspects of the present invention, the transparent video display is a liquid crystal display ("LCD") while the narrow light source has a width substantially equivalent to a pixel width of one pixel of the LCD which can be created by a slit (which preferably has a substantially uniform width and can be formed by depositing an

opaque material on a clear surface to form masks on either side of the slit) with the physical light source located behind the slit relative to the liquid crystal display or by a curved reflector about a vertical axis in a convex shape (such as a cylindrical shape) and a physical light source. The narrow light source preferably has a height substantially the same as a perceived height of the back-lighted image and is located at distance from the transparent video display that is substantially less than the typical viewing distance (such as 25% or less).

In a second, separate group of aspects of the present invention, the aspect ratio of a perceived image is chosen and calculated and the number of images that is displayed by the transparent video display in the light box is determined by use of an acceptable horizontal image resolution for each of said perceived images within the transparent video display.

Accordingly, it is a primary object of the present invention to provide improved back-lighted images for viewers moving rapidly past such back-lighted images that rely upon a single vertical light source to provide multiple reflected line scans of transparent images located between the light source reflections and viewers.

This and further objects and advantages will be apparent to those skilled in the art in connection with the drawings and the detailed description of the preferred embodiment set forth below.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 depicts a series of viewing boxes according to the present invention arranged in series in a subway tunnel.

FIG. 2 is a top view depiction of a viewing box simplified with only one light source according to the present invention showing the horizontal field of illumination of a single vertical light source.

FIG. 3 is a frontal view illustrating the viewing box of FIG. 2.

FIG. 4 is a top view depiction of a series of viewing boxes according to the present invention, each of the viewing boxes having multiple vertical light sources and transparent images (not shown) which can be separated by an optional baffle.

FIG. 5 is a frontal view illustrating the series of viewing boxes of FIG. 4 without baffles.

FIG. 6 is an illustrative drawing of a viewing box according to the present invention illustrating the viewing box being opened so as to install a film image.

FIG. 7 is illustrative of a viewing box according to the present invention using either a film image of FIG. 6 or a video screen, without its typical backlight and omni-directional diffuser.

FIG. 8 is an illustrative cross-sectional top view depiction of a viewing box according to the present invention using a neon tube as a substantially vertical light source illuminating image I on film F with the field of illumination illustrated by light rays LR at the outer boundaries.

FIG. 9 is an illustrative cross-sectional side view taken along line 9-9 of FIG. 8 that also illustrates, in phantom, opening of hinged frame HF.

FIGS. 10 and 11 are similar to FIGS. 8 and 9 except that the substantially vertical light source is a miniature fluorescent lamp and hinged frame HF is not illustrated as opening in phantom lines.

FIGS. 12 and 13 illustrate an alternative embodiment to the embodiment depicted in FIGS. 10 and 11 in which a conventional fluorescent lamp is located behind a wall having a slit S so as to create a substantially vertical light source of narrow width relative to the transparent image I on film F.

FIG. 14 is similar to FIG. 10 except that the substantially vertical light source is a column of light emitting diodes (LEDs) with a vertical diffuser D.

FIG. 15 is similar to FIG. 11, based upon the embodiment shown in FIG. 14, except that portions of the structure illustrated in FIG. 16 have been removed.

FIG. 16 is a partial side depiction of a column of LEDs shown in FIG. 14.

FIG. 17 is the image perceived by a viewer as a train moves rapidly past multiple back lighted images according to the present invention. The vertical sides appear smeared due to the motion of the train past the light boxes.

FIG. 18 is a top view showing two light sources, each reflecting off of two tubular reflectors. Further, FIG. 18 shows that the reflected-light pitch RLP is uniform between two tubular reflectors associated with one light source, and also between tubular reflectors associated with adjacent light sources.

FIG. 19 is a partial cut away front view of a light box showing two light sources LS, each covered with a light-source baffle LSB, and reflective tubes RT showing the light-source reflection LSR.

FIG. 20 is a perspective cut away of the light box showing one light source LS, its light-source baffle LSB, internal-reflection barrier IRB, reflective tubes RT with light-source reflections LSR, and front glass G image panel with images I1, I2 and I3.

FIG. 21 shows a detailed ray trace from the fluorescent lamp light source LS with incident light IL onto reflective tube RT, with reflected light RL directed toward the film or video image I.

FIGS. 22 and 23 show the location of the reflection on the reflective tube RT for the extreme right and left positions, respectively.

FIG. 24 is an enlarged section through a light box showing at left a magnified view of the adhesive-backed velvet VEL attached to the back wall.

FIG. 24a shows an alternate technique to simplify assembly is shown by attaching black velvet VEL to a strip of velvet-backing material VBM which has been fitted with snap fasteners SF, used to attach that strip to the back metal wall of the light box LB.

FIG. 25 is a perspective view of the cut away light box showing the light source LS and light-source baffle LSB illuminating cylindrical stamped indentations SI on the back wall of the light box, and black velvet VEL to absorb unwanted stray light.

FIGS. 26 and 27 show an alternate light box LB made with small tabs TAB stamped into the back of the metal light box LB to which reflective film RF is attached.

FIGS. 28-30 show extruded reflector supports ERS, made preferably of black plastic, or aluminum with black anodized finish or painted with flat black paint.

FIGS. 29 & 30 show the inner walls IW of the extrusions which serve the same function as the internal-reflection barrier IRB in FIGS. 18 and 20-23.

FIG. 31 shows an alternate construction in which reflective film RF is "wall papered" or attached to the interior wall of the box.

FIG. 32 is a perspective view showing the assembly of the reflective film RF being trapped by black-velvet covered backing material which forces the reflective film to wrap around, and therefore conform to, the curvature of the stamped indentations SI.

FIG. 33 is a flow chart for a method for designing a subway tunnel light box in a subway tunnel in accordance with the present invention.

## 5

FIGS. 34 and 35 illustrate vertical and horizontal viewing angles  $\alpha$  and  $\beta$ , respectively, of a perceived image by a viewer in a subway car.

FIG. 36 illustrates an image width and a slit width of an LCD with multiple images.

FIG. 37 illustrates a potential problem with forming a narrow slit from solid materials.

FIG. 38a is a top plan section of a fluorescent lamp and light shining through a narrow slit between plates where the angle of illumination is restricted by the relatively thick masking plates to the slit width.

FIG. 38b is a top plan section of a fluorescent lamp and light shining through a beveled slit so that the illumination angle is not restricted by the inner edges of the slit.

FIG. 39 is an isometric view of a slit mask which has been printed onto a clear substrate material.

FIG. 40a is an isometric exploded view of opaque material for separate right and left sides of a slit mask printed on separate pieces of clear substrate.

FIG. 40b is an isometric view of the elements of FIG. 40a after having been brought into contact leaving the desired amount of slit width and having been mounted to the mounting surface.

## DESCRIPTION OF THE INVENTION

As this is a continuation-in-part application which is an improvement over the inventions that I disclosed in my earlier applications, I will first describe the original invention and my first improvements thereto for context, and then describe my present invention. However, to aid the reader in understanding my disclosures, the following is a glossary of the elements identified in the Figures:

$\alpha$  Vertical Viewing Angle, FIG. 34  
 A Antenna, FIG. 1  
 $\beta$  Horizontal Viewing or Illumination angle, FIG. 35  
 B Baffle, FIGS. 4, 6, 7  
 BVL Bevel, FIG. 39b  
 C Channel, FIGS. 28-30  
 CS Clear Substrate, FIG. 39  
 CS-B Clear Substrate Back, FIGS. 40a, 40b  
 CS-F Clear Substrate Front, FIGS. 40a, 40b  
 D Diffuser, FIGS. 14, 15, 16  
 DR Door, FIGS. 18, 20, 24-30, 32  
 ERS Extruded Reflector Support, FIGS. 28-30  
 F Film, FIGS. 6, 8, 9, 10, 11, 12, 13, 14, 15  
 FL Fluorescent Lamp, FIGS. 12, 13  
 G Glass, FIGS. 18-20, 24-30, 32  
 H Hinge, FIGS. 8-15  
 HF Hinged Frame, FIGS. 3, 5, 6, 8-15  
 I Image, FIGS. 3, 5, 8, 10, 12, 14, 18-20, 22-28  
 I-HT Image Height, FIG. 34  
 IL Incident Light, FIG. 21-23  
 IP Image Pitch, FIG. 4,  
 IR Internal-Reflection, FIGS. 18, 22-24  
 IRB Internal-Reflection Barrier (or "Baffle"), FIGS. 18 & 20-27  
 IMW Image Width, FIGS. 35, 36  
 IW Inner Wall, FIGS. 28-30  
 L Latch, FIGS. 18, 19, 24, 26, 28 & 30-31  
 LB Light Box, FIGS. 1, 2, 4, 6-16, 18-20, 26-32  
 LCD Liquid Crystal Display, FIGS. 34, 35  
 LED Light Emitting Diode, FIGS. 14, 15, 16  
 LR Light Ray, FIGS. 2, 4, 8, 10, 12, 14, 39a, 39b  
 LS Light Source, FIGS. 1, 2, 4, 6, 7, 18-30  
 LSB Light-Source Baffle, FIGS. 18-32  
 LSR Light-Source Reflection, FIGS. 19-21, 25, 27, 29 and 32

## 6

LSW Light-Source Width, FIGS. 21-23  
 M Mask, FIGS. 36, 37, 38, 39a, 39b  
 MB Mounting Board, FIGS. 39a, 39b  
 MFL Miniature Fluorescent Lamp, FIGS. 10, 11  
 5 N Neon tube, FIGS. 8, 9  
 OW Outer Wall, FIGS. 28-30  
 PCB Printed Circuit Board, FIGS. 14, 15, 16  
 PIW Perceived Image Width, FIG. 35  
 PM Printed Mask, FIGS. 39, 40a, 40b  
 10 PS Proximity Sensor, FIG. 1  
 PW Pixel Width, FIG. 36  
 RF Reflective Film (aluminized Mylar™), FIGS. 26-32  
 RLB Reflective Light Box, FIGS. 24 & 25  
 RL Reflected Light, FIG. 21-23  
 15 RLP Reflected Light Pitch, FIGS. 18 & 30  
 RP Registration Pins, FIGS. 6, 8, 15  
 RS Reflective Surface, FIGS. 24 & 25  
 RT Reflective Tubes 18-23  
 S Slit, FIGS. 12, 13, 34, 35  
 20 SB Side Baffle, FIG. 30  
 SF Snap Fastener, FIGS. 7a, 28-32  
 SH Screw Hole, FIG. 40a  
 S-HT Slit Height, FIG. 34  
 SI Stamped Indentation, FIGS. 24-25, 31 & 32  
 25 SL Slot, FIG. 40a  
 SW Slit Width, FIGS. 36, 37, 38a, 38b, 39, 40b  
 T Train, FIGS. 1, 34, 35  
 TAB Tab, FIGS. 26 & 27  
 30 TC Transparent Cover, FIGS. 6, 8-15  
 TW Tunnel Wall, FIGS. 1, 34, 35  
 V Video Display, FIG. 7  
 VD Viewing Distance, FIG. 34  
 VEL Velvet, FIGS. 18, 20, 24, 24a, 25, 31 & 32  
 35 VBM Velvet-Backing Material, FIGS. 24a, 31 & 32  
 My original invention provides a lighted subway system that is much more energy efficient, and thus less costly, than prior lighted subway systems. The display of my invention simulates the visual experience of a train rider who is viewing  
 40 the scene out of the train window, passing distant landscapes, mountains, landscapes, trees, buildings etc. In this setting, the scene looks real and natural, as is the case. Even when the train might pass a tall fence or pass through a wooden covered bridge with sides of vertical slats with narrow slits between  
 45 the boards, the train rider still sees the scene as the train rushes past the slits between the boards, although a darker image because the slits occupy a small portion of the pitch distance from board to board. Example: if the boards are turned vertically and placed on 6 inch centers however have a 0.06-inch  
 50 wide gap, the brightness is reduced to  $0.06/6=1\%$ . If the train is traveling at an adequate speed, the passing slits (or boards) will blur and will not appear to be in motion; however, the distant scene will appear normally but attenuated to 1% brightness.  
 55 Using the principle of a Zoetrope, viewing an image through a rapidly passing slit, it is possible to simulate the experience of the train rider in the covered bridge by providing slits in the foreground through which lighted images are displayed behind the slit. In accordance with simple geometry  
 60 and proportions, when the distance of the image behind the slit is reduced, the width of the image must be reduced in proportion. The width of the image behind the slit is such that from the train rider's viewing distance, the image width must be compressed so that the width of the perceived image is in  
 65 proportion to the height of the image, for example when displaying a TV commercial. Depending on the slit-to-image distance, in order to provide the appropriate width (so that a

circle looks like a circle), the actual image must be horizontally compressed approximately 6:1 to 10:1.

When the subway train is traveling fast enough, these slits blur and, due to the persistence of vision, multiple images from the series of lighted images appear to superimpose one over the other. By displaying images with slight changes, an animated effect is created from these passive displays. This explains the conventional thinking on passive lighted subway signage by viewing the image through a slit as in Spodek.

The subject of this invention however switches the foreground/background relationship of the slit and image so that the image is in the foreground and the slit or the equivalent of a slit, or a narrow vertical light source, is in the background. The bare light source is viewed through the foreground image as the viewer passes the light box.

My earlier invention will now be described in connection with several embodiments with references, where appropriate, to the Figures.

As already noted in the background of the invention, my original invention is especially well suited to use in subway tunnels where there is no natural light, where viewers are riding in a subway car at a relatively rapid speed (as compared, for example, to walking or running), and where signage has the ability to be viewed by a great many viewers as they travel through such tunnels.

A viewing box, or light box LB, according to my original invention may have one or more transparent images, I, and it is especially preferred that any such image(s) be protected by a transparent cover, TC. FIG. 3 illustrates a viewing box with one image, I, while FIG. 5 illustrates a viewing box with multiple images. When multiple images are aligned in parallel along a path of travel the images can be made to appear animated as a viewer moves past the images.

Each transparent image I in a viewing box according to my original invention is illuminated by its own substantially vertical light source, LS, of narrow width relative to the transparent image, the light source being located in the viewing box behind the transparent image, relative to the viewer. The vertical light source provides a line scan of the image as a viewer moves past the image, in much the same way as a slit provides a similar line scan when the slit is located between the viewer and the lighted image in a device such as is disclosed in U.S. Pat. No. 6,564,486 to Spodek et al. In contrast to Spodek in which the illumination is greatly attenuated by either being (1) reflected off of a front-lighted opaque print, or (2) transmitted through a back-lighted diffuser and image, both about 39% efficient, the present invention provides that the viewer is looking through the image directly at the bare light source LS. To further illustrate the point, consider the difference in brightness of light that falls on a book from a reading lamp to looking at the bare hot tungsten filament of a clear light bulb in the reading lamp. This approximate 10:1 increase in brightness allows the subway signage of this invention to be illuminated, to the same level as Spodek, with a light source LS of approximately 10% of the energy requirements.

The vertical light source LS used in my original invention can take many forms, examples of which are illustrated in FIGS. 8-15. FIGS. 8 and 9 illustrate use of a narrow neon tube N. FIGS. 10 and 11 illustrate use of miniature fluorescent lamp MFL. FIGS. 12 and 13 illustrate use of a conventional fluorescent lamp FL which, although not used efficiently, is advantageous due to the low cost and ready availability, and whose output is limited by use of a slit S to create a substantially vertical light source of narrow width relative to the image I. This same concept, of limiting the width of the light source through use of a slit, can be used with other light

sources as well, and it is an especially preferred way to achieve a desired narrow width vertical light source when its the cost is less than what might be required by using a very narrow vertical light source without a slit. FIGS. 14 and 15 illustrate use of a column of light emitting diodes, LEDs, mounted to a printed circuit board, PCB, while FIG. 16 illustrates such a column of LEDs in an especially preferred embodiment with the addition of a linear diffuser D which diffuses or spreads transmitted light exclusively in a vertical direction so as to fill in the gaps between individual LEDs to create the impression of a continuous unbroken vertical line of light. This linear diffuser can be lenticular plastic with lenticles oriented horizontally, of the type used oriented vertically over three-dimensional photographs, or holographic light-shaping diffuser. In each of these light sources, the width of the transmitted light source is narrow relative to the image so that the vertical line of light will horizontally scan the image as a viewer moves laterally past the light box.

The transparent image(s) can take many forms. For example, the transparent image may be a photographic film such as Agfa Cibachrome®, Kodak Duraclear® or Endura® film, or a transparency that might be printed on a computer color printer or planar sheet of material such as transparent vinyl or Mylar® that may be obtained from rolls. To insure proper alignment of such a transparency within a viewing box the transparency can include one or more markings or registration holes for alignment with one or more registration pins RP (see, e.g., FIGS. 6 and 8-15) and, as is depicted in FIGS. 6 and 9, the viewing box can have a hinged frame HF connected by a hinge H to allow the transparent cover to be opened for ease of replacement of any transparency it holds.

As an alternative to a physical transparent image that must be replaced when the image is changed, the image can be formed by a transparent video display, V, such as an LCD video display with its typical backlight and omni-directional diffuser removed, or any other form of image display equivalent to such a display in the context of my invention in which the display is lit from within the display box but can be changed (or altered) without physically changing the actual display.

One advantage of a video display over a film image is that it can be updated remotely by an update signal. Such a signal can be delivered via a wired connection or via a wireless connection (see antennae FIG. 1, A) and the update signal can be based on any number of preselected criteria, such as, for example, a time interval. In an especially preferred embodiment, the update signal can be based upon detection of movement of the train past a box. Thus, for example, as shown in FIG. 1, a proximity sensor, PS, might be mounted on a viewing box attached to a tunnel wall, TW, for detecting movement of a train, T.

In an embodiment using a video display that can be updated remotely from the light box, the video display can be programmed so that passengers in different train or subway cars moving past it might actually see different images; in other words, passengers in the first car in a train might see a first image (such as an advertisement) while passengers in a second car of the train might see a second image or advertisement, and so on. As a result of such flexibility, an advertiser using such a system might be charged different rates for times of peak travel or the advertiser might be charged based upon the number of cars that pass by the viewing box(s) of a particular location, all of which create far more flexibility than can be obtained by use of film image, especially since the number of potential images that can be displayed, and their sequence and timing of display, can all be controlled electronically, instead of manually.

Another advantage of a video display over a physical transparent image is that its image can be individually adjusted remotely vertically and horizontally to make images register, image to image, when multiple display boxes are being used together to create a still or animated image. This is very important because if images in a series of boxes are not properly aligned the image or images that are being viewed appear to jump around. Also, the pace of the animated commercial can be adjusted to compensate for train speed, something that obviously cannot be done with a physical transparent image.

In connection with my original invention, it will usually be the case that multiple viewing boxes will be mounted along a path of travel past the boxes, even if the image to be displayed is only a still image. However, multiple images can be displayed in a single viewing box, as is illustrated in FIGS. 1 and 5, and this is especially preferred when the image is being displayed on a video display so as to maximize the use of such display. When multiple images are displayed in a single viewing box, each of the images must be lighted by its own substantially vertical light source. In such an embodiment, as shown in FIG. 4, it may be desirable to include a baffle, B, between individual light sources. The purpose of such a baffle is to eliminate possibly distracting side images created by a light source illuminating a neighboring or adjacent image. When the vertical light source is a series of LEDs, a separate baffle is usually not required because the support structure which supports the printed circuit board PCB, LED's and vertical diffuser D serves the purpose of a baffle that might be used otherwise with a miniature fluorescent lamp or neon tube.

Persistence of vision is such that the images will need to be pass the viewer frequently to prevent the perception of flicker. The minimum flicker frequency is approximately 18 Hz. A horizontal spacing, or image pitch IP, of 2.2 feet provides 20 images per second for a train traveling 30 miles per hour. By placing images closer than 2.2 feet, a higher frame rate is achieved and the illumination appears continuous. Particularly with the more expensive LCD video displays, it is important to use them efficiently and to maximize image resolution. By carefully choosing the image pitch IP and spacing between light boxes LB the image pitch IP can be made uniform between multiple images within one light box, and from light box to adjacent light box as shown in FIGS. 4 and 5. This assures a uniform and sufficiently high refresh rate so as to not see a vertical dark band sweep horizontally through the image as the train moves, and in general makes the image more comfortable and pleasant to view.

I will now turn to the first improvement over my original invention that is disclosed in my first continuation-in-part application.

So far this application has disclosed the subway-tunnel signage system I described in my original patent application U.S. Ser. No. 11/801,891 which requires tall, narrow light sources to back light the images. The images are visible to the commuters in the train because of the combination of motion parallax, persistence of vision and the horizontal line scanning of the images by the vertical light sources behind the front images.

My original patent application describes several directly viewed vertical light sources, each with various advantages; however, one light source was required per image, and several increased the depth of the light box.

Subway regulations limit the maximum thickness of any such signage that reduces the clearance between the train and the tunnel wall. Thus, my first continuation-in-part application proposed a compact, simple and economical lighting

technique that alleviates several of the mentioned problems by reflecting light, from vertical light sources off vertical reflectors in the back of the light box. The vertical light source, typically a fluorescent lamp, is placed just behind the front image plane but also behind an opaque black baffle so that light is directed toward the reflectors at the back of the light box, and not directly into the viewers' eyes. The reflected light off each curved reflector becomes the light source for each image.

FIG. 21 shows a detailed ray trace from the fluorescent lamp light source LS with incident light IL onto reflective tube RT, with reflected light RL directed toward the film or video image I. Light is reflected off the reflective tube RT at a sufficient angle to fully illuminate the width of the image. Any and all diffusers traditionally associated with LCD video displays are removed from the LCD, making it a transparent image trapped between two sheets of glass G. The image is viewed by the train rider at a relatively large distance, therefore essentially only a vertical line of the image is back lighted and made visible to the train rider. Because the fluorescent lamp has a physical width, its reflection also has a physical width, although reduced. FIGS. 22 and 23 show the location of the reflection on the reflective tube RT for the extreme right and left positions, respectively. By combining the ray traces of FIGS. 22 and 23 in FIG. 21, the equivalent position of the light-source reflection LSR can be determined. This light-source reflection LSR must be centered with respect to and behind each front image.

Further, the width of the light-source reflection LSR, the light-source width LSW, affects the horizontal image resolution. The wider the LSW, the lower the horizontal image resolution but the brighter the image. The narrower the LSW, the sharper the horizontal image resolution, but the dimmer the image. In the case of displaying a video image, using a liquid-crystal display LCD, the light-source width LSW can be as wide as one column of pixels of the LCD without compromising the image resolution. To have the light-source width narrower than a single column of pixels would unnecessarily dim the image.

The light box LB is assembled with modules comprised of one light source and multiple reflective rods, and their associated baffles as in FIGS. 18-20, 24-30 and 32. Each module is designed so that each light-source reflection LSR is centered with its corresponding film or video image. The lateral spacing of images determines the lateral spacing of the reflective tubes RT, reflective surfaces RS or strips of reflective film RF. Because the light-source reflections LSR occur at different portions of alternate rods (approximately the 5 o'clock or 7 o'clock positions), the modules are spaced so that the light-source reflections LSR between reflective rods of adjacent modules are maintained uniformly across the width of the light box LB.

Because each light source can reflect off multiple reflectors, only a fraction as many light sources are required, reducing lamp replacement cost, electricity, heat and the need for cooling fans.

The reflectors at the back of the box could be solid rods, not shown, or hollow tubes as in FIGS. 18-23 or rounded shapes stamped in the back of a reflective sheet metal light box as in FIGS. 24 and 25, or bent reflective film RF as in FIGS. 26-30. Hollow tubes are preferred to solid rods due to their reduced weight and cost, non-directional mechanical stability, and ease of mounting by their top and bottom ends. The tubes could be any reflective material, i.e. polished stainless steel, mirrored glass, chrome-plated steel tubes, etc.

The curvature of all reflectors discussed here narrows the width of the light-source reflection LSR without affecting the

vertical length, the height, of the reflection. The width of the light-source reflection LSR is easily established during the design stage by (a) using a different curvature reflector, (b) different diameter fluorescent lamp, or (c) altering the distance between the lamp and reflector.

FIGS. 24 and 25 show a light box RLB made of a reflective material such as Alzak aluminum, polished stainless steel, or chrome-plated steel which has had its back wall stamped with vertical, rounded stamped indentions SI's which replace the chrome-plated tubes and provide vertical reflectors to reflect the light sources. For light control, the majority of the inner walls of the reflective light box RLB are blackened with flat black paint, or by attaching adhesive backed black velvet, to the back wall, with cutouts to reveal the reflective stamped indentation SI. An alternate way to paint the back wall is by a shallow dipping into flat-black paint to coat the flat areas but reveal the linear reflectors.

It is important that only one bright reflection appear behind each film or video image. Therefore, light control within the light box LB is important, which is why a "V" shaped light-source baffle LSB shown in FIGS. 18-30 is placed between the light source and the viewer.

An internal reflection barrier IRB shown in FIGS. 18 and 20-27 is placed behind the lamps with enough gap between it and the "V"-shaped light-source baffle LSB to allow light to illuminate the reflectors RT, RS or RF.

Further, an additional baffle, the internal-reflection barrier IRB is placed between the pairs of reflectors to prevent secondary reflections, first off one reflector, then onto an adjacent reflector, creating an undesirable "false" reflected light source, and thereby a ghost image to the train rider. As shown in FIGS. 18, 20, 24-27 because of the relatively large light source LS, reflective surface RS and confined space, some spill light is inevitable on the back wall of the light box. All interior surfaces not needed for reflection should be as black and light absorbing as possible. Various approaches include making the light boxes and baffles from black plastic, black-anodized aluminum, or using flat-black paint and/or covering surfaces with black velvet.

FIGS. 24 and 25 show adhesive-backed black velvet VEL attached to the interior back and side wall of a reflective light box RLB, leaving reveals in the areas of the vertical stamped indentations SI which serve as the reflectors for the light sources. FIG. 24a is an enlarged section through a light box showing at left a magnified view of the adhesive-backed velvet VEL attached to the back wall. In the central portion of FIG. 24a, an alternate technique to simplify assembly is shown by attaching black velvet VEL to a strip of velvet-backing material VBM which has been fitted with snap fasteners SF, used to attach that strip to the back metal wall of the light box LB. The widths of the strips of vertical backing material VBM are dimensioned such that they self align between the stamped indentations SI so that only the crowns of the stamped indentations are revealed.

FIGS. 26 and 27 show an alternate light box LB made with small tabs TAB stamped into the back of the metal light box LB to which reflective film RF is attached. The strips are reflective plastic film, made by aluminizing rolls of Mylar or other plastic of the appropriate width so that when cut to the required length, can be curved and snapped between the tabs to form an approximate cylindrical shape. The edges of the plastic strips may bow out slightly between securing tabs TAB; however, the front crown is straight and provides a very accurate linear reflector. The geometry of the reflective strip, although not completely straight on the sides, is straight in the middle for two reasons: (1) the averaging effect of equal and opposite lateral deformations at the tabs TAB on opposite

sides, and (2) flat materials when bent can curve exclusively around one axis, in this example generally cylindrically. This technique makes it very easy to change the width of the light-source reflection LSR shown in FIGS. 19-21, 25, 27 and 29, and as light-source width LSW in FIGS. 21-23 by changing the width of the reflective film RF, shown in FIGS. 26-30, or the lateral space between tabs TAB shown in FIGS. 26 and 27.

FIGS. 28-30 show extruded reflector supports ERS, made preferably of black plastic, or aluminum with black anodized finish or painted with flat black paint. The extruded-reflector supports ERS are shown attached to the back wall of the light box LB with snap fasteners SF. Each extruded reflector support ERS has vertical channels C into which flexible-reflective strips, typically aluminized Mylar plastic, are bent into a curve and inserted to form linear reflective surfaces RS. As in FIGS. 26-30, the width of the reflective film RF, or the width of the channels C, will determine the curvature of the reflective strips and therefore the width of the light-source reflection LSR.

FIGS. 28-30 show the inner walls IW of the extrusions which serve the same function as the internal-reflection barrier IRB in FIGS. 18 and 20-23 by blocking the internal reflection that would reflect off one reflector, then onto the adjacent reflector and then out through the image, creating a false ghost image in addition to the brighter primary image.

In FIGS. 27-30, on the extrusion ERS, the space between the walls, adjacent to any strip of reflective film RF, is sufficient to allow incident from the light source LS and reflected light from the reflective strip to the image, but as narrow as possible to trap and minimize scatter light within the light box LB.

FIG. 31 is similar to FIG. 24 in that the light box LB is stamped with indentations SI from the back. FIG. 31 is to show an alternate construction to achieve the reflective surfaces RS and black light control velvet VEL. In this case, the light box LB material itself need not be reflective and, in fact, is preferably black. Instead, reflective film RF for example aluminized Mylar™ is "wall papered" or attached to the interior wall of the box by fitting strips of stiff flat velvet covered backing material VBM to the back wall so that it traps the reflective film RF and forces the film to conform to the curvature of the protrusions (made by the stamped indentations SI). In advance, the Mylar is die cut with holes that align with holes in the light box and the snap fasteners SF in the velvet backing material. The backing material is cut in vertical strips approximately the interior height of the box but the width is such that it forces the Mylar tightly against the protrusions. This approach speeds up the assembly and leaves the interior extremely black with excellent light control, revealing the reflective Mylar only in the areas that are needed to reflect the light source LS.

FIG. 32 is a perspective view of FIG. 31, which shows the assembly of the reflective film RF being trapped by black-velvet covered backing material which forces the reflective film to wrap around, and therefore conform to, the curvature of the stamped indentations SI. This assembly technique is quick and accurate and provides excellent light control and reveals the reflective film RF only in areas that are needed to reflect the light sources LS. Typically, the light box LB would have many light sources LS, strips of velvet-backing material VBM, and exposed columns of reflective film RF; however only a portion of the interior of the light box LB is shown.

When the fluorescent lamp light sources LS need to be replaced, the front door DR of the light box LB hinges open, carrying the LCD video display (or film image), hinged on a

hinge typically horizontal and at the bottom, carrying with it the "V"-shaped baffles LSB and SB, leaving the lamps accessible for replacement.

In theory, numerous reflected-light sources RLS can be generated by reflecting light from a single light source off multiple reflectors. FIG. 30 shows an expanded module in which one lamp illuminates four reflective flexible strips, requiring one fourth the number of lamps compared to the lamps being viewed directly. As suggested by FIG. 30, when generating multiple light-source reflections LSR, while not essential, it is more practical to have a symmetrical layout where there are equal numbers of reflective surfaces RS on both sides of the light source LS. When the layout is symmetrical, the light source LS "hides" between the inner two reflective surfaces RS in an out-of-the-way position behind the light source baffle LSB.

It is important that the light-source width LSW, in FIGS. 21-23, be equal, and that the reflected light pitch RLP, in FIGS. 18 & 30, be equal. As in FIG. 30, the geometry of the light source LS and the inner two strips of reflective film RF2 and RF3 in are identical in width LSW to those of strips of reflective film RF1 and RF4. However, in FIG. 30, the outer strips of reflective film RF1 and RF4 are farther from the light source, therefore the radius of curvature of RF1 and RF4 is increased to compensate and preserve the width of the light-source reflection LSR, FIG. 21.

In FIG. 30, the edges of the light source baffle LSB, side baffles SB, and inner and outer walls, IW and OW, respectively, of the extruded reflector support ERS are dimensioned so as to allow light from the light source to illuminate the strips of reflective film; however, minimize stray light and internal reflections.

Thus far I have described my original invention and the improvements to it that I described in my first continuation-in-part application. However, I have realized that actually designing and installing a subway tunnel light box that is useful and effective while still economically viable requires careful consideration and understanding of a number of critical factors when a transparent video display is chosen for use in the light box. Accordingly, I will now disclose a methodology for actually creating such light boxes (see FIG. 33) and, to better demonstrate this methodology, I will go through a hypothetical example of designing such a box. As an initial matter, since a subway tunnel light box will be installed in a subway tunnel, one should obtain tunnel and train dimensions for where the box will be installed. Each subway authority has regulations about what can be used in the subway tunnel, relating to how far from the wall any object can protrude, the electrical load, and the time of day access to service any equipment. The width of train tunnels varies primarily based on the number of tracks. For purposes of an example, I will assume a one-track tunnel is approximately 12 feet wide, a train is approximately 8 feet wide and a typical viewing distance VD (see FIG. 34) is approximately 40 inches. The actual viewing distance will depend upon true dimensions and the location from within the train that a viewer is located relative to the display, but a typical viewing distance can be established based upon known parameters.

The next step in designing a subway tunnel light box, especially if it will use a liquid crystal display ("LCD"), is to choose an LCD. An LCD will be chosen for a variety of properties, the image resolution, physical size to be appropriate for the viewing distance and train window size and cost and availability. The signage technique of the present invention looks best when the display has high resolution, therefore, a high-definition display (HDTV) is the clear choice over a standard-definition display. Also the price is important

since a hundred or more LCD's (one per light box) will typically be required for an animated commercial. Because the public now demands larger video displays for home TV, typically 42" diagonal or larger, there remains a supply of relatively inexpensive 37" LCD's on the market which I will use throughout the following design process.

After an LCD is chosen, a vertical viewing angle  $\alpha$  is calculated (see FIG. 34). Continuing with the example of using a 37"-diagonal LCD HDTV with a 16:9 (width-to-height) aspect ratio, the image area measures 32.24x18.14 inches. The vertical viewing angle  $\alpha$  of the image, from the point of view of the train passenger at 40 inches, is  $2 [\arctan((18.14/2)/40)]=25.55^\circ$ .

Next, a desired aspect ratio of the perceived image needs to be chosen. This is chosen aesthetically and somewhat arbitrarily and is independent of the aspect ratio of the physical LCD. To fit the sometimes small train windows and close viewing distance, I have chosen a 4:3 (width-to-height) aspect ratio for the perceived image.

My next step is to calculate a horizontal viewing angle  $\beta$  of the perceived image (see FIG. 35). Knowing that the physical height of the image will be 18.14", and having chosen a 4:3 aspect ratio, yields a perceived image width of  $4/3 \times 18.14" = 24.18$  inches wide. The perceived image will appear to the train passenger to be 24.18 inches wide. At a 40-inch viewing distance, the horizontal viewing angle is  $2 [\arctan((24.18/2)/40)]=33.64^\circ$ .

Now that I have calculated the horizontal viewing angle of the perceived image, I must choose minimum acceptable horizontal image resolution. The horizontal resolution of the perceived image will be a trade off with the depth of the light box, the number of images per light box, and the number of light boxes required to display a 30-second commercial, and therefore the cost of the system. Somewhat arbitrarily, I choose each image to have a horizontal resolution of 242, or to use 242 columns of pixels on the HDTV LCD per image. In comparison to the perceived 24.2-inch wide image, each pixel column will be  $1/10$  inch wide, a minimum acceptable image resolution, in my opinion.

The next step is to calculate the physical width on the HDTV LCD allocated to one image. The screen width on the HDTV has 1920 columns of pixels across its 32.24" width. The width of 242 columns of pixels is  $242/1920 \times 32.24" = 4.06"$ .

I can now determine the number of images per LCD. Full resolution high-definition displays (HDTV's) have a horizontal resolution of 1920 pixels.  $1920/242=7.93$ , therefore there will be seven images, each 242 pixels wide, using a total of 1694 columns of pixels across the width of the LCD with six vertical black guard bands occupying the remaining 226 columns of pixels, of 37.6 pixels each. The black guard bands between images isolate the central image from the train rider, so that wing images do not create distractions.

Now that I know how many images can be viewed on my chosen LCD, I must position a light source, in the engineering layout, behind each image at a distance so that its horizontal illumination angle matches the horizontal viewing angle  $\beta$  (see FIG. 35).

By definition, the horizontal viewing angle of the perceived image ( $33.64^\circ$  in this example) is determined by the relationship of the distance of the light source behind the image to the width of the image in the LCD. Therefore, the light source should be positioned, in the engineering layout, behind the image on the LCD to match or slightly exceed this  $33.64^\circ$  angle. The width of the physical image on the LCD, calculated above, is 4.06". The distance of the light source behind image plane =  $[(4.06"/2)/\tan(33.64^\circ/2)]=2.03/0.302=6.715"$ .

If the horizontal illumination angle slightly exceeds  $33.64^\circ$  the LCD can mask the excess by using black vertical guard bands between images.

I next calculate the width of the narrow light source that is to be used behind each image. Because it is not really practical to design a light source to such a precise measurement without unduly increasing cost, unless a light source might fortuitously have the desired width, the light source can be created by two different alternatives to a direct line-of-sight light source having the desired width. First, a larger physical light source can be used located behind a slit that will create a desired narrow light source at the slit of an appropriate width. Second, light from a physical light source of greater width can be reflected off concave surfaces, preferably reflective cylinders, so that no physical slit is necessary. This will lead to only a slight loss in brightness of the light (to approximately 94%). If the first alternative is chosen, the distance of the slit from the perceived image will be used as the distance of the light source behind the image plane (6.715" in my example). If the second alternative is chosen, the distance of the reflected light source LSR in FIG. 21 will be used as the distance of the light source behind the image plane. Whichever of these two alternatives is chosen, the correct distance of the narrow light source can be carefully controlled, and use of a slit allows for precision location of the light source by location of the slit.

The width of the narrow light source should match the pixel width PW of the LCD (see FIG. 36). If the width of the narrow light source is wider than one column of pixels, the horizontal resolution of the perceived image will be compromised whereas if the width is narrower than a column of pixels the brightness of the display will be compromised. The width of the narrow light source is calculated by dividing the physical width of the overall LCD by the number of columns of pixels,  $32.24"/1920 \text{ pixels} = 0.0168"$ .

In order to obtain a narrow light source with sufficient height behind each image, the narrow light source should have a height that is substantially the same or slightly greater than the height of the perceived back-lighted image. However, to avoid unduly increasing the depth of the light box, the light source height should be located at a light source distance from the transparent video display so that its horizontal illumination angle matches the horizontal viewing angle, and when this distance is less than 25% of the typical viewing distance, the location of the light source should not unduly increase the viewing box depth and it should minimize the need for requiring the physical light box to be larger than it needs to be, thus minimizing costs associated with its operation.

When the narrow light source is created by use of a physical slit, one might create a slit by cutting a narrow slot in a flat opaque masking material for example metal to create an approximately 20 inch long slot or slit, or one could form a slit by placing two pieces of flat material of similar length near each other, leaving the desired gap or slit. However, there are potential problems with creating a slit by such methods. The gap should be the width of only one column of LCD pixels, approximately 0.017 inches (about the thickness of a business card). When the gap is this narrow, the thickness of the slit-forming masking material must be taken into consideration, see FIG. 38a. In concept, ideally, one would like the masks to be zero thickness, and perfectly flat and parallel and in a common plane. If thin metal is used for example for masks, considering that nothing is perfect, the metal on each side of the slit will likely buckle slightly as shown in FIG. 37, creating the appearance of a wider or narrower gap when viewed from a side angle. Even if the two flat masks were perfectly aligned, for practical mechanical-stability considerations, the

mask material must have adequate thickness to be mounted to the mounting surface MS. The thickness of these masks, in combination with the narrow slit width SW, restricts the angle of light which can pass through the slit S, as shown in FIG. 38a. One solution for working with masks of a practical thickness, without restricting the illumination angle is to bevel the inner edges of the masks at an angle greater than the illumination angle, shown as  $33.64^\circ$ , in FIG. 38b.

To overcome the foregoing problems in creating a suitable slit for use with my invention, a slit of width SW can be created by essentially printing a black opaque material (ink or paint) on a clear substrate (plastic or glass), leaving a narrow gap. The opaquing material can be lithographically printed with great precision (see FIG. 39). Another version that will allow adjustment of the slit width is to print each side of the slit on a separate plastic or glass panel and to clamp those panels together, printed side to printed side, after having set the gap to the desired opening (see FIG. 40a). The printed opaque areas would then be protected on both sides from damage from someone replacing the fluorescent tubes. (Even if a slit is printed on only one substrate, a second substrate can be used, as shown in FIG. 40b, to protect the printed substrate in a like fashion.) Another technique is to create the slit photographically with film that creates an opaque black, or clear image, without any gray scale, such as Kodak Kodalith® reprographic film or its equivalent.

While the invention has been described herein with reference to certain preferred embodiments, those embodiments have been presented by way of example only, and not to limit the scope of the invention. Additional embodiments thereof will be obvious to those skilled in the art having the benefit of this detailed description. Further, modifications are also possible in alternative embodiments without departing from the inventive concept.

Accordingly, it will be apparent to those skilled in the art that still further changes and modifications in the actual concepts described herein can readily be made without departing from the spirit and scope of the disclosed inventions as defined by the following claims.

What is claimed is:

1. A method of installing a subway tunnel light box in a subway tunnel for displaying a back-lighted image to a viewer inside of a subway car traveling in the subway tunnel, comprising the steps of:

- choosing a transparent video display that is mounted in the light box;
- calculating a perceived horizontal viewing angle for a typical viewing distance of the subway tunnel light box installed at a preselected location in the subway tunnel by a viewer in the subway car based upon a physical height of the transparent video display and a desired aspect ratio of a perceived image for the transparent video display;
- determining a number of images to be displayed on the transparent video display with an acceptable horizontal image resolution for each of said perceived images;
- positioning a narrow light source in the subway tunnel light box behind each of the displayed images so that each of the displayed images is illuminated by an associated narrow light source with an associated narrow light source horizontal illumination angle substantially the same as the perceived horizontal viewing angle; and
- installing the subway tunnel light box at the preselected location.

2. The method of claim 1, wherein the transparent video display is a liquid crystal display ("LCD").

## 17

3. The method of claim 2, wherein the narrow light source has a light source width substantially equivalent to a pixel width of one pixel of the LCD.

4. The method of claim 3, wherein the narrow light source is comprised of a slit with the light source width and a physical light source located behind the slit relative to the liquid crystal display.

5. The method of claim 4, wherein the slit has a substantially uniform width.

6. The method of claim 5, wherein the slit is formed by depositing an opaque material on a clear surface to form masks on either side of the slit.

7. The method of claim 3, wherein the narrow light source is comprised of a curved reflector about a vertical axis in a convex shape and a physical light source.

8. The method of claim 7, wherein the convex shape is a cylindrical shape

9. The method of claim 3, wherein the narrow light source has a light source height that is substantially the same as a perceived height of the back-lighted image.

10. The method of claim 9, wherein the light source is located at a light source distance from the transparent video display that is substantially less than the typical viewing distance.

11. The method of claim 10, wherein the light source distance is less than 25% of the typical viewing distance.

12. The method of claim 1, comprising the additional step of:

choosing the desired aspect ratio.

13. The method of claim 1, wherein a vertical guard band in the LCD between displayed images masks illumination substantially exceeding the associated narrow light source horizontal illumination angle of said images.

14. A subway tunnel light box for use in a subway tunnel for displaying a back-lighted image to a viewer inside of a subway car traveling in the subway tunnel, comprising:

a transparent video display for displaying a number of images that is mounted in the light box; and

a narrow light source positioned in the subway tunnel light box behind each of the number of images so that each of said number of images is illuminated by an associated narrow light source with an associated narrow light

## 18

source horizontal illumination angle substantially the same as a preselected perceived horizontal viewing angle;

wherein the preselected perceived horizontal viewing angle is calculated for a typical viewing distance based upon a physical height of the transparent video display and a desired aspect ratio of a perceived image.

15. The subway tunnel light box of claim 14, wherein the number of images that is displayed by the transparent video display in the light box is determined by use of an acceptable horizontal image resolution for each of said perceived images within the transparent video display.

16. The subway tunnel light box of claim 15, wherein the transparent video display is a liquid crystal display ("LCD").

17. The subway tunnel light box of claim 16, wherein the narrow light source has a light source width substantially equivalent to a pixel width of one pixel of the LCD.

18. The subway tunnel light box of claim 17, wherein the narrow light source is comprised of a slit with the light source width and a physical light source located behind the slit relative to the liquid crystal display.

19. The subway tunnel light box of claim 18, wherein the slit has a substantially uniform width.

20. The subway tunnel light box of claim 19, wherein the slit is formed by depositing an opaque material on a clear surface to form masks on either side of the slit.

21. The subway tunnel light box of claim 14, wherein the narrow light source is comprised of a curved reflector about a vertical axis in a convex shape and a physical light source.

22. The subway tunnel light box of claim 21, wherein the convex shape is a cylindrical shape.

23. The method of claim 14, wherein the narrow light source is located at a light source distance from the transparent video display that is substantially less than the typical viewing distance.

24. The method of claim 23, wherein the light source distance is less than 25% of the typical viewing distance.

25. The subway tunnel light box of claim 14, wherein the narrow light source has a light source height that is substantially the same as a perceived height of the back-lighted image.

\* \* \* \* \*