

(12) **United States Patent**
Doggett et al.

(10) **Patent No.:** **US 9,168,659 B2**
(45) **Date of Patent:** **Oct. 27, 2015**

(54) **TENSION STIFFENED AND TENDON ACTUATED MANIPULATOR**

(71) Applicant: **The United States of America, as represented by the Administrator of the National Aeronautics and Space Administration**, Washington, DC (US)

(72) Inventors: **William R. Doggett**, Poquoson, VA (US); **John T. Dorsey**, Hampton, VA (US); **George G. Ganoe**, Yorktown, VA (US); **Bruce D. King**, Yorktown, VA (US); **Thomas C. Jones**, Newport News, VA (US); **Charles D. Mercer**, Chesapeake, VA (US); **Cole K. Corbin**, Williamsburg, VA (US)

(73) Assignee: **The United States of America as represented by the Administrator of the National Aeronautics and Space Administration**, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 248 days.

(21) Appl. No.: **13/864,396**

(22) Filed: **Apr. 17, 2013**

(65) **Prior Publication Data**

US 2013/0305867 A1 Nov. 21, 2013

Related U.S. Application Data

(63) Continuation of application No. PCT/US2013/024321, filed on Feb. 1, 2013.

(60) Provisional application No. 61/594,115, filed on Feb. 2, 2012.

(51) **Int. Cl.**
B25J 9/06 (2006.01)
B25J 17/00 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC .. **B25J 18/00** (2013.01); **B25J 9/06** (2013.01);
B25J 9/1045 (2013.01); **B25J 17/00** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC B25J 1/02; B25J 9/0009; B25J 9/1075;
B25J 9/126; B25J 17/00; B25J 18/00; B25J
9/06; B25J 9/1045; B64G 2004/005; Y10T
74/20323; Y10T 4/20329; B66C 23/62;
B66C 23/64; B66C 23/66; B66C 23/68
USPC 74/490.04, 490.05, 490.07, 490.08,
74/89.2-89.22, 490.13; 901/19, 21;
244/159.4, 158.9, 173.1, 173.3,
244/172.4-172.6

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS
1,108,029 A 8/1914 Tull
3,045,837 A 7/1962 Liebherr et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 7425234 U * 9/1976 B66C 23/16
DE 3223169 12/1983

(Continued)

OTHER PUBLICATIONS

PCT International Search Report and written opinion, PCT/US13/24321, Mailed Apr. 22, 2013.

Primary Examiner — William Kelleher


Assistant Examiner — Bobby Rushing, Jr.

(74) *Attorney, Agent, or Firm* — Andrea Z. Warmbier

(57) **ABSTRACT**



A tension stiffened and tendon actuated manipulator is provided performing robotic-like movements when acquiring a payload. The manipulator design can be adapted for use in-space, lunar or other planetary installations as it is readily configurable for acquiring and precisely manipulating a payload in both a zero-g environment and in an environment with a gravity field. The manipulator includes a plurality of link arms, a hinge connecting adjacent link arms together to allow the adjacent link arms to rotate relative to each other and a cable actuation and tensioning system provided between adjacent link arms. The cable actuation and tensioning system includes a spreader arm and a plurality of driven and non-driven elements attached to the link arms and the spreader arm. At least one cable is routed around the driven and non-driven elements for actuating the hinge.

15 Claims, 9 Drawing Sheets



[illegible]

* cited by examiner






FIG. 4




FIG. 6




FIG. 3




FIG. 5




FIG. 9A




FIG. 9B




FIG. 7







FIG. 8





Q




ॐ







216





576








FIG. 20




FIG. 21




FIG. 22

TENSION STIFFENED AND TENDON ACTUATED MANIPULATOR

CROSS-REFERENCE TO RELATED APPLICATION

This patent application is a continuation of Patent Cooperation Treaty patent application number PCT/US13/24321, filed Feb. 1, 2013, which claims the benefit of and priority to U.S. Provisional Application Ser. No. 61/594,115, filed Feb. 2, 2012. The contents of each of the foregoing are hereby incorporated by reference in their entireties.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH AND DEVELOPMENT

The invention described herein was made in the performance of work under NASA contracts and by employees of the United States Government and is subject to the provisions of 51 U.S.C. §20135 and 35 U.S.C. §202, and may be manufactured and used by or for the Government of the United States of America for governmental purposes without the payment of any royalties thereon or therefor. In accordance with 35 U.S.C. §202, the contractor elected not to retain title.

FIELD OF THE INVENTION

The present invention relates to tension stiffened and tendon actuated manipulators.

BACKGROUND OF THE INVENTION

Space-based manipulators are known in the art. Advanced long-reach high-performance manipulators are needed to support in-space operations such as Near Earth Object berthing, telescope assembly and satellite servicing. Manipulators that can lift, translate and precisely position payloads, equipment and infrastructure on planetary surfaces are necessary to execute most space exploration missions. The requirements for these planetary surface devices include having long reach (to unload landers for example), package efficiently for launch, be able to exert large tip forces and have low mass.

It has been concluded that conventional (Earth-based) robotic manipulator configurations would have extreme difficulty meeting planetary surface requirements because their mass increases rapidly with increases in reach and payload handling mass. In Earth-bound applications, cranes are mass efficient devices that have long reach and high payload capability, but cranes lack the dexterity and versatility found in robotic manipulators.

In order to meet planetary surface requirements, a hybrid crane/manipulator, the Lightweight Surface Manipulation System (LSMS), was created. The LSMS is a cable-actuated manipulator that achieves high structural efficiency by using an architecture that reacts payload handling load through members acting in either pure tension or compression (as opposed to bending in conventional robotic manipulators). Further mass efficiency, achieved by using the tension structure (cables) to also articulate the LSMS arm hinges, is enabled by the mechanical advantage inherent in the tension/compression LSMS architecture. Lightweight hoists are used to reel cable in and out (thus articulating the hinge), replacing the massive high-torque motor gear-boxes used in a conventional boom manipulator.

In-space applications, just as in a ground-based application, for a desired applied tip force, the structural efficiency of

a traditional boom/rotary-hinge manipulator architecture rapidly degrades as the manipulator reach is increased. The LSMS uses the tension/compression member architecture with tendon-controlled articulation architecture to achieve high structural efficiency. Similarly, a manipulator that is based on an architecture of tension-stayed booms and tendon-controlled articulating hinges has the potential to achieve the high structural efficiency necessary to make long-reach manipulators practical. The LSMS takes advantage of gravity and LSMS self-weight, plus the weight of the payload, to maintain tension forces in the cables during articulation. Cable stiffened structures have also been developed for many space applications and structures, but have never been considered as components in a space robotic manipulator.

There are many critical features that must be present in a manipulator if it is to be viable for space missions. The manipulator must be lightweight, stiff, package efficiently, reliably deploy and operate reliably. It is also desirable for the manipulator to have the ability to restow. For the case of a hyper dexterous manipulator (HDM), it must also have a large range of motion, allowing it to avoid obstacles away from the wrist/tip while reaching into difficult to access locations. A high level of dexterity can be achieved by using the traditional approach of using a large number of link-actuator pairs (with manipulator complexity increasing as the number of link/hinge pairs increases).

A major capability for a manipulator, defined as its stiffness, is the ability to apply a force at its tip/wrist without exceeding a specified level of deflection. High stiffness can be desirable to provide the tools/end effectors a stable platform off of which to work, to provide a high degree of stability and precision and/or prevent large deflections that might cause the arm to collide with surrounding objects. For a given tip force, as stiffness is increased, the deflection decreases. For a selected material construction, the stiffness of a tubular link, as found in most conventional manipulators, is increased by increasing the tube diameters. At some point, increasing tube diameter becomes impractical because of either packaging limitations, or the size of the tube impedes operations, or the ability to reach into tight spaces.

The articulating hinges in a manipulator are designed to apply a moment such that a force of a specified magnitude is generated at the manipulator tip/wrist. In a conventional manipulator, the hinges are typically actuated by motor-driven gearboxes that incorporate brakes on the motors and which generate a moment about their drive axis. Compared to the structural links, these conventional manipulator hinge designs provide the dominant contribution to the manipulator mass as well as its compliance.

A more recent focus on in-space missions has identified a need for long-reach, low-mass manipulators that can support operations for missions to Near Earth Objects, orbital debris removal, satellite and propellant depot servicing, rapid International Space Station resupply, and large telescope assembly. As with ground-based applications, the current state of the art for manipulators, the Shuttle and Space Station Remote Manipulator Systems (SRMS and SSRMS), represent conventional embodiments consisting of long lightweight tubular booms, connected by massive rotary torque hinge, gearbox and motor system. The SRMS and SSRMS have proven the benefit of long reach manipulators in the 15-18 meter class. The SRMS has a maximum reach of approximately 50 feet and can exert a maximum tip force of 12 pounds and has a design goal of 10 lbf/inch stiffness measured as deflection at the tip for the fully extended (straight) arm. The total weight (on Earth) of the SRMS is 905 lbf, with the hinges (shoulder, elbow and wrist) weighing 561

3

lbf and the links (upper and lower arm) having a combined weight of 108 lbf. The hinges dominate, at 84%, the combined mass of the hinges and links in the manipulator. In addition, the compliance of the hinges in rotation dominates the stiffness of the manipulator as measured at the tip. As the required reach for a manipulator increases, a conventional configuration suffers from the same rapid increase in mass as a ground-based manipulator.

While the SRMS and SSRMS have proven the benefit of long reach manipulators with the reach of both manipulators in the 15-18 meter class, manipulators with an even greater reach would provide many benefits. The SRMS's limited reach required an additional boom to augment its reach during inspection of the belly of the Shuttle Orbiter in support of return to flight following the Columbia disaster. Berthing operations benefit from longer reach because visiting space craft are intercepted at a greater separation allowing more time to accomplish the berthing maneuver. This additional separation allows capture at higher delta V's, reduction in the interface forces as well as additional time to execute contingency options. If the SSRMS had a longer reach, fewer power data grapple fixtures would be required along the space station truss and the SSRMS could reach a larger percentage of the space station. Future large space structures, such as large telescopes, space solar power and fuel depots would benefit from a longer reach manipulator during construction, repair and upgrade operations.

The manipulator architecture of the SRMS and SSRMS has limited scalability. Longer manipulators require large diameter booms and massive motor gearbox combinations to actuate the hinges, driving up weight and reducing packaging efficiency. In addition, the architecture does not lend itself to on-orbit repair, requiring the entire device to be returned to Earth for routine maintenance or repair. Further, the primary flexibility occurs at the hinges of these manipulators due to the collocation of the hinge drive gear system.

The structural efficiency of several column embodiments have been compared for space applications. Truss columns have been shown to be much more efficient than tubes as length and stiffness requirements increase, with tubular longeron trusses generally having higher efficiency than solid longeron trusses. Based on this, truss structures were used to develop long-reach manipulators such as the Space Crane. The Space Crane achieved a higher structural efficiency over the conventional boom/high-torque rotary hinge configuration by using trusses instead of cylindrical tubes for the links, and an offset linear-actuator/revolute hinge instead of a high-torque revolute hinge.

A manipulator is provided herein which provides improvements to existing structures and which overcomes the disadvantages presented by the prior art. Other features and advantages will become apparent upon a reading of the attached specification, in combination with a study of the drawings.

BRIEF SUMMARY OF THE INVENTION

A tension stiffened and tendon actuated manipulator is provided performing robotic-like movements when acquiring a payload. The manipulator design can be adapted for use in-space, lunar or other planetary installations as it is readily configurable for acquiring and precisely manipulating a payload in both a zero-g environment and in an environment with a gravity field. The manipulator includes a plurality of link arms, a hinge connecting adjacent link arms together to allow the adjacent link arms to rotate relative to each other and a cable actuation and tensioning system provided between adjacent link arms. The cable actuation and tensioning system

4

includes a spreader arm and a plurality of driven and non-driven elements attached to the link arms and the spreader arm. At least one cable is routed around the driven and non-driven elements for actuating the hinge.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

The organization and manner of the structure and operation of the invention, together with further objects and advantages thereof may best be understood by reference to the following description, taken in connection with the accompanying drawings, wherein like reference numerals identify like elements in which:

FIG. 1 is a perspective view of a first embodiment of a manipulator which incorporates features of the present invention;

FIG. 2 is a side elevation view of the manipulator of FIG. 1;

FIG. 3 is a perspective view of a second embodiment of two links and a joint of a manipulator which incorporates features of the present invention;

FIG. 4 is a perspective view of a third embodiment of two links and a joint of a manipulator which incorporates features of the present invention;

FIG. 5 is a side elevation view of the manipulator of FIG. 4;

FIG. 6 is a side elevation view of a fourth embodiment of a manipulator which incorporates features of the present invention;

FIG. 7 is a side elevation view of a fifth embodiment of a manipulator which incorporates features of the present invention;

FIG. 8 is a perspective view of a sixth embodiment of a manipulator which incorporates features of the present invention;

FIG. 9A is a side elevation view of the manipulator of FIG. 8 in an articulated position;

FIG. 9B is side elevation view of a portion of the manipulator showing a constrained lift-off configuration;

FIG. 10 is a perspective view of an seventh embodiment of a manipulator which incorporates features of the present invention;

FIG. 11 is a side elevation view of the manipulator of FIG. 10;

FIG. 12 is a second side elevation view of the manipulator of FIG. 10 in an articulated position;

FIG. 13 is a perspective view of a eighth embodiment of a manipulator which incorporates features of the present invention;

FIG. 14 is a perspective view of the manipulator of FIG. 13 in an articulated position;

FIG. 15 is a perspective view of a ninth embodiment of a manipulator which incorporates features of the present invention;

FIG. 16 is a perspective view of a hinge that can be used as the hinge in any of the embodiments of the manipulator;

FIG. 17 is an end-on view of the hinge of FIG. 16 in the packaged state;

FIG. 18 is an end-on view of the hinge of FIG. 16 in the deployed state;

FIG. 19 is an alternate plan of view of the hinge of FIG. 16;

FIG. 20 is an elevation view of the hinge of FIG. 16 in a first position;

FIG. 21 is an elevation view of the hinge of FIG. 16 in an exaggerated position; and

FIG. 22 contains sequence of elevation views of the hinge of FIG. 16 showing various positions as it articulates.

DETAILED DESCRIPTION OF THE INVENTION

While the invention may be susceptible to embodiment in different forms, there is shown in the drawings, and herein will be described in detail, a specific embodiment with the understanding that the present disclosure is to be considered an exemplification of the principles of the invention, and is not intended to limit the invention to that as illustrated and described herein. Therefore, unless otherwise noted, features disclosed herein may be combined together to form additional combinations that were not otherwise shown for purposes of brevity.

A manipulator **20** has a plurality of link arms **22a**, **22b**, **22c** which are connected together by hinges **24**. The manipulator **20** has a cable actuation and tensioning system **26** which actuates the hinges **24** and stiffen the structure of the manipulator **20** in a modular fashion. The manipulator **20** achieves both high structural performance, as well as high dexterity by combining a number of tendon-actuated hinges **24** with extendable-length link arms **22a**, **22b**, **22c** to form the manipulator **20**. Each hinge **24** provides for relative motion between the link arms **22a**, **22b** and **22b**, **22c** attached thereto.

The manipulator **20** has long reach, high payload mass/tip force capability, high stiffness, precise positioning, system simplicity, and high reliability while also being lightweight and packaging efficiently. The cable actuation and tensioning system **26** increases the stiffness of the manipulator **20**, without increasing tube diameter of the link arms **22a**, **22b**, **22c**, thus still allowing for efficient packaging.

The manipulator **20** is, in general, a component assembly for use in a variety of larger assemblies that can perform robotic-like movements when acquiring and/or manipulating a payload. These larger assemblies utilizing manipulator **20** are ideally suited for in-space use or planetary installations as they are readily configurable for acquiring and precisely manipulating a payload. However, the present invention is not limited to these applications as it could also be used for Earth-based operations.

The manipulator **20** has at least two link arms **22a**, **22b**, **22c**, with adjacent arms **22a**, **22b/22b**, **22c** being joined together by hinge **24**, the cable actuation and tensioning system **26** provided at each hinge **24**. The adjacent link arms **22a**, **22b/22b**, **22c** are coupled to the respective hinge **24**, as described herein. As many link arms/hinges as desired can be used; as a result, the manipulator **20** is modular. Each hinge **24** provides a degree-of-freedom, such that as many degrees of freedom as required can be provided.

Each link arm **22a**, **22b**, **22c** is an elongated, stiff member that is coupled to the respective hinge **24** as described herein. Each link arm **22a**, **22b**, **22c** can be solid, hollow, constructed as a truss, fixed or variable length, deployed, etc., without departing from the scope of the present invention. As shown, each link arm **22a**, **22b**, **22c** is rectangular-shaped and has first and second outboard ends **28**, **30**, however, other shapes may be provided. A centerline extends between the first and second outboard ends **28**, **30** of each link arm **22a**, **22b**, **22c**. The first outboard end **28** (see FIG. 15) of the first arm **22a** is rigidly coupled to a base end **29** that is attached to a stationary structure **31**, for example a spacecraft, a space station (stationary relative between the arms and the structure; the spacecraft or space station is not stationary relative to the planetary surface), planetary station, etc.; the second outboard end **30** at the outermost arm (the arm furthest away from the stationary structure) has a tip which is free and serves as the mounting location for a payload holding device **33** (e.g., effector end, hook, grabber arm, bucket, scoop, platform, electromagnet, etc.) coupled thereto or incorporated therewith. For adjacent

link arms **22a**, **22b**, the second outboard end **30** of link arm **22a** and the first outboard end **28** of link arm **22b** are attached to the hinge **24** between arms **22a**, **22b**; for adjacent link arms **22b**, **22c**, the second outboard end **30** of link arm **22b** and the first outboard end **28** of link arm **22c** are attached to the hinge **24** between arms **22b**, **22c**.

Each cable actuation and tensioning system **26** includes at least one spreader arm **32** extending from the respective hinge **24**, at least one driven element, such as a capstan **34** or a hoist **36**, at least one non-driven elements, such as pulleys **38**, **40**, **42** or wheel **37**, at least one cable routed around the driven and non-driven elements as described herein, and at least one motor **46** which drives the driven element. The driven and non-driven elements are attached to the link arms **22a**, **22b/22b**, **22c** and spreader arm(s) **32**. The ends of the spreader arm(s) **32** can be configured to engage the cables to allow the cables to slide therealong, without the use of pulleys.

Each cable is a fixed-length member which has its length fixed prior to operation of the manipulator **20**. If desired, each cable can incorporate a length adjustment feature (e.g., removable section, turnbuckle, etc.) that allows the lengths to be adjusted after installation with the link arms **22a**, **22b**, **22c**.

A pair of tensioning members **50a**, **50b**, which are preferably springs, may also be provided in each cable actuation and tensioning system **26**. The driven element and the non-driven elements are attached to (or provided as part of if the non-driven elements are the ends of the spreader arms **32**) the link arms **22a**, **22b**, **22c** and the spreader arms **32** as discussed herein to effect movement of the one link arm relative to the adjacent link arm. Illustrative examples of possible arrangements of the cable actuation and tensioning systems **26** are shown, however, it is to be understood that these shown arrangements are illustrative only, and that there are many additional varieties of arrangements that can be used. The critical aspect is that the cable actuation and tensioning system **26** provides a driven element on one or more of the arms (link arm or spreader arm) which is remote from the hinge **24**, with non-driven elements coupled to (or provided as part of) the other arms which are remote from the hinge **24**, and that the driven member is used to circulate the cables using the non-driven members. When the cable actuation and tensioning system **26** is used to control the hinge **24**, the cables and tensioning members must be arranged in an antagonistic manner to provide bi-directional hinge motion.

Each spreader arm **32** is a stiff member that is coupled to the hinge **24**. Each spreader arm **32** can be solid, hollow, constructed as a truss, fixed or variable length, deployed, etc. without departing from the scope of the present invention. As shown, the spreader arms **32** can take a variety of shapes, e.g. elongated rectangular-shaped, a pair of triangles forming an elongated member, a wheel **37**. Each spreader arm **32** has a pair of outboard ends **52**, **54** upon which either the driven or non-driven members are mounted or provided, and a centerline extends between the outboard ends **52**, **54**. The spreader arms **32** provide mechanical advantage about the hinge **24**. A single spreader arm **32** above and below the hinge **24** can be used, or multiple spreader arms can be used depending on design requirements.

Attention is invited the embodiment of the manipulator **20** shown in FIGS. 1 and 2. Two hinges **24** and three link arms **22a**, **22b**, **22c** are shown, however, any number and size of hinges **24** and link arms **22a**, **22b**, **22c** can be combined based on the requirements of a particular application. The base end **29** and tip which serves as the mounting location for a payload holding device **33** are not shown in these Figures.

A pair of first spaced apart ears **56**, **58** are provided at the first outboard end **28** of each link arm **22a**, **22b**, **22c**. The first

ears **56, 58** are enlarged and extend from a first surface **60** of the link arms **22a, 22b, 22c**. Each first ear **56, 58** has an aperture there which are aligned with each other. The apertures through the ears **56, 58** are offset from the centerlines of the link arms **22a, 22b, 22c**. A pair of second spaced apart ears **62, 64** are provided at the second outboard end **30** of each link arm **22a, 22b, 22c**. The second ears **62, 64** are enlarged and extend from a second surface **66** of the link arms **22a, 22b, 22c**. Each second ear **62, 64** has an aperture therethrough which are aligned with each other. The apertures through the ears **62, 64** are offset from the centerlines of the link arms **22a, 22b, 22c**.

To couple the link arms **22a, 22b, 22c** together, the link arms **22a, 22b, 22c** are aligned such that the second end **30** of link arm **22a** is proximate to the first end **28** of link arm **22b**, and the second end **30** of link arm **22b** is proximate to the first end **28** of link arm **22c**. When placed end-to-end, the first surface **60** of link arm **22a**, the second surface **66** of link arm **22b**, and the first surface **60** of link arm **22c** are flush, or substantially flush, with each other; the second surface **66** of link arm **22a**, the first surface **60** of link arm **22b**, and the second surface **66** of link arm **22c** are flush, or substantially flush, with each other. As a result, the centerlines of the link arms **22a, 22b, 22c** are aligned with each other (additional link arms would also alternate in this manner). The ears **62, 64** at the second end **30** of link arm **22a** interengage with the ears **62, 64** at the first end **28** of link arm **22b** such that the apertures align with each other. A pivot pin **68** is mounted through these aligned apertures to allow the link arms **22a, 22b** to rotate relative to each other to form a hinge. Accordingly, the pivot pin **68** is offset from the centerlines of the link arms **22a, 22b, 22c**. The ears **62, 64** at the second end **30** of link arm **22b** interengage with the ears **56, 58** at the first end **28** of link arm **22c** such that the apertures align with each other. A pivot pin **68** is mounted through these aligned apertures to allow the link arms **22b, 22c** to rotate relative to each other to form a hinge. Accordingly, the pivot pin **68** is offset from the centerlines of the link arms **22a, 22b, 22c**. Each pivot pin **68** defines an axis of rotation for the adjacent link arms **22a, 22b** and **22b, 22c**. It is to be understood that other hinge structures can be provided in each of the embodiments to allow the articulation of the hinge **24**.

The innermost ears **58, 64** are spaced apart from each other such that a spreader aperture **70** is formed therebetween in which the spreader arm **32** is mounted. The spreader arm **32** has a passageway at its center through which the pivot pin **68** extends.

The hinge **24** between link arms **22a, 22b** is described with the understanding that the other hinges **24** provided in the manipulator **20** are identical in structure (of course, each hinge **24** can vary in size).

The spreader arm **32** has a rotatable pulley **38, 40** mounted at each of its ends **52, 54**. Apertures are provided in the spreader arm **32** to reduce weight, to provide a mounting location for a spring **50a** mounted on one side of the spreader arm **32**, and to allow continuous internal wire paths. A first end of the spring **50a** is affixed to the spreader arm **32** proximate to the end of the aperture **72** which is proximate to the center of the spreader arm **32**, and the spring **50a** extends along the centerline of the spreader arm **32**.

A rotatable pulley **42** is mounted in an aperture in the link arm **22a** proximate to, but spaced from, the second outboard end **30**. A driven capstan **34** is mounted in an aperture in the link arm **22b** proximate to, but spaced from, the first end **28**. A motor **48** is mounted on the link arm **22b** proximate to, but spaced from, the first end **28**, and drives the capstan **34** as discussed herein.

A spring **50b** has an end attached to the link arm **22a** proximate to the hinge **24** and extends along the centerline of the link arm **22a**. (The apertures shown in FIG. 1 above the spring **50b** can be provided, or can be eliminated).

In this embodiment, the capstan **34** and the pulleys **38, 40, 42** are located equidistant from the hinge axis defined by the pivot pin **68** and a single capstan **34** is located along one of the link arms **22b** to actuate the hinge **24** (the capstan **34** and the pulleys **38, 40, 42** do not need to be located equidistant from the hinge axis). The capstan **34** has two warping end profiles at different diameters for actuation. The springs **50a, 50b** are used to accommodate changes in the total cable path as the hinge **24** articulates. In this embodiment, the cables **44, 46** are used as the primary tension element, however, a variety of approaches may be taken such as fixed rods, telescoping members or tapes, etc.

FIG. 2 provides a side elevation view of the hinge **24** described in FIG. 1. In this embodiment, the springs **50a, 50b** are used to provide the antagonistic force. The two tension cables **44, 46** form two loops; one cable **44** pulls the **54** of the spreader arm **32** at B toward the capstan **34** at C, and the second cable **46** pulls the link arm **22a**, via a connection at A, toward the capstan **34** at C on link arm **22b**. Cable **44** is anchored on the spreader arm **32** at B, proceeds clockwise around the capstan **34** at C on the inner radius of the capstan **34**, proceeds over pulley **38** at D, proceeds over pulley **42** at A, proceeds over pulley **40** at B, and proceeds down to the spring **50a** and is attached thereto. Cable **46** is anchored at to the link arm **22a** at A, proceeds clockwise over pulley **40** at B, proceeds around capstan **34** at C, proceeds over pulley **38** at D, proceeds over pulley **42** at A, and is attached to the spring **50b** on link arm **22a**.

The hinge articulation, i.e. control of the angle AOC, is accomplished by rotating the capstan **34**. The angle AOC can range from 0 degrees to 315 degrees, in this example. When the capstan **34** is rotated clockwise, the angle AOC decreases as point B is drawn toward point C via cable **44** and point A is drawn toward point C via cable **46**. To balance motion of each link arm **22a, 22b**, relative to the spreader arm **32**, the capstan **34** for cable **46** has twice the diameter of the capstan **34** for the cable **44**. When the capstan **34** is rotated counter-clockwise, the spreader **32** at B moves away from the capstan **34** at C due to the action of the tensioning springs **50a, 50b** which apply a restoring force, thus causing the angle AOC to increase.

The geometry of the link arms **22a, 22b** and the spreader arm **32** are such that the thickness of the link arm **22a, 22b** is accommodated to enable to the angle AOC to be 0 degrees to 315 degrees, in this example.

In this configuration, extra pulleys are used to balance the loads were the cables **44, 46** react on the springs **50a, 50b**. For example, cable **44** could be arranged so that it is anchored at B goes around the capstan **34** at C, over pulley **38** at D and then terminates on a spring (not shown) between D and O. This cable routing eliminates pulley **42** at A and the additional cable from D to A, but results in unbalanced load at D and A.

FIG. 1 also provides a tension network from of a pair of fixed spreader arms **133, 133'** which provide a mounting locating for a pair of tensioning cables **143, 145**. As shown, the fixed spreader arms **133, 133'** extend from the center of the link arm **22b**. Spreader arm **133** extends from first surface **60**, and spreader arm **133'** extends from second surface **66**. The ends of cable **143** are attached proximate to the outboard ends **28, 30** of the link arm **22b** and extend over the end of the spreader arm **133**. The ends of cable **145** are attached proximate to the outboard ends **28, 30** of the link arm **22b** and extend over the end of the spreader arm **133**. This tension network aids in stiffening the link arm **22b**. This stiffening

complements the stiffening provided by the tension network provided by the cable actuation and tensioning systems 26. Depending upon requirements, either tension network or a combination of these tension networks may be used.

FIG. 3 shows the hinge 24 of FIGS. 1 and 2, but with the pulley 42 at the first end 28 of link arm 22a and the capstan 34 at the second end 30 of link arm 22b. As a result, the distance from A to O and the distance from B to O does not need to be equal as is provided in FIGS. 1 and 2. This embodiment also shows that a portion of cable 44 is formed by a solid, non-bending tension rod 74. Solid tension rods 74 provide advantages in weight and packaging in some applications. A tension rod(s) 74 can be used in any of the embodiments disclosed herein.

FIG. 4 shows the hinge 24, with the capstan 34 and associated motor 48 mounted on the end 54 of spreader arm 32, and with the pulley 40 and its associated spring 50a mounted on link arm 22b. The dual capstan 34 warping end profiles may be the same diameter, or have different diameters.

FIG. 5 provides a side elevation view of the hinge 24 shown in FIG. 4. The dual capstan 34 provided at the end 54 of the spreader arm 32 articulates the hinge 24. Two tension cables 44, 46 are provided. The first cable 44 is anchored on link arm 22a at A, proceeds clockwise around the capstan 34 at B, proceeds around pulley 40 at C, proceeds around pulley 38 at D, proceeds around pulley 42 at A, and terminates on the tensioning spring 50b on link arm 22a which is located between A and O. The second cable 46 is anchored on link arm 22b at C, proceeds clockwise around the capstan 34 at B, proceeds around pulley 42 at A, proceeds around pulley 38 at D, proceeds around pulley 40 at C, and terminates on the tensioning spring 50a on link arm 22b which is located between C and O.

Like the first embodiment, the hinge articulation, i.e. control of the angle AOC, is accomplished by rotating the capstan 34. The angle AOC can range from 0 degrees to 315 degrees, in this example. Clockwise rotation of the capstan 34 at B causes the angle AOC to decrease, while counterclockwise rotation of the capstan 34 at B causes the angle AOC to increase.

FIG. 6 provides four hoists 36 and associated motors which actuate the hinge 24 by operating in an antagonistic manner, much like the muscles in a human arm. The hoists 36 are motorized and pay out/retrieves the cables 44, 45, 46, 47 between B and A, B and C, A and D, C and D, respectively.

In FIG. 7, the capstan 34 is provided on link arm 22b and the spreader arm and pulleys have been combined into a wheel 37 which has a plurality of spreader arms 32 extending from a central hub 41 to an outer ring 43 which acts like a pulley around which the cable 44 circulates. The hinge 24 connects to the central hub 41 by a pivot pin 68. The wheel 37 is connected to link arm 22a such that link arm 22a rotates with the wheel 37. The cable 44 routes around the outer surface of the ring 43 and around the capstan 34. As the capstan 34 is driven, the wheel 37 rotates and moves link arm 22a toward link arm 22b.

FIGS. 8 and 9 show the hinge 24 of FIG. 3, but without the tension rod 74. In FIGS. 3, 8 and 9, the cables 44, 46 have been extended to span the entire length of the link arms 22a, 22b and link arms 22b, 22c, moving the pulley 42 and capstan 34 of each hinge 24 toward the outboard ends 28, 30 of the respective link arms 22a, 22b, 22c. Thus, the cables 44, 46 serve the dual purpose of hinge articulation and link stiffening. As shown in FIG. 9A, as the hinge 24 articulates, the mechanical advantage provided by the spreader arm 32 is reduced. As the hinge 24 continues to articulate clockwise, the angle BOC decreases, decreasing the mechanical advantage

the cables 44, 46 can exert about the hinge axis O. On one side of the hinge 24, this effect can be alleviated by allowing the lift-off of the spreader arm 32. In this embodiment, the cables 44, 46 which were originally in contact with the pulley 38 at D lift-off of the spreader arm 32 which results in significant mechanical advantage of the cables 44, 46 between AC about hinge O. Lift-off occurs just after the points ADC become co-linear as the hinge 24 articulates. Lift-off causes the cables 44, 46 to sweep through a larger portion of the workspace, which may be undesirable. This can be remedied by constraining the degree of lift-off, for example a limited travel telescoping spreader between O and D. FIG. 9B shows a possible containment arrangement with additional pulley 38 placed to constrain the cables 44, 46 after the lift-off. The pulley 38 re-engages with the cables 44, 46 when the hinge 24 is articulated in the reverse direction. This distance at which the cable 44, 46 is constrained is shown by the arrow in FIG. 9B. This distance can vary depending upon the desired application.

In order to maintain the mechanical advantage along the top side of the hinge 24 in FIG. 9, i.e. along tension path ABC, additional spreader arms 32 can be used as is shown in FIG. 10. The additional spreader arm 32a supports the cables 44, 46 at B1 and B2 as the hinge 24 articulates. Operational requirements determine how many spreader arms are needed and if it is sufficient to only add the additional spreaders above the hinge 24 as shown in FIGS. 10-12. Spreader arms, correctly located, are one approach to minimizing changes in the cable 44, 46 length as the hinge 24 articulates which reduces the stroke required for the springs 50a, 50b.

FIGS. 13 and 14 show a hinge 24 which has the link arms 22a, 22b and the spreader arm 32 provided therebetween. A pair of hoists 36 are mounted in each link arm 22a, 22b. In this embodiment, four cables 44, 45, 46, 47 are provided. Cable 44 extends from one of the hoists 36 in link arm 22a to the end 52 of the spreader arm 32 and is affixed to the end 52 of the spreader arm 32. Cable 45 extends from the other of the hoists 36 in link arm 22a to the end 54 of the spreader arm 32 and is affixed to the end 54 of the spreader arm 32. Cable 46 extends from one of the hoists 36 in link arm 22b to the end 54 of the spreader arm 32 and is affixed to the end 54 of the spreader arm 32. Cable 47 extends from the other of the hoists 36 in link arm 22b to the end 52 of the spreader arm 32 and is affixed to the end 52 of the spreader arm 32.

The hinge 24 is articulated by engaging the motors driving the hoists 36 to increase the length of, or decrease the length of the appropriate cables 44, 45, 46, 47 to articulate the hinge 24 as shown in FIG. 14. The motors driving the hoists 36 are arranged in an antagonistic relationship.

FIG. 15 shows a manipulator 20 which has a pair of orthogonal cable actuation and tensioning systems 26, 26' provided for each hinge 24. In this embodiment, a first spreader arm extends from the adjacent link arms (for example, link arms 22a, 22b) at the hinge 24 in a direction which is perpendicular to the axis of rotation of the hinge 24 defined by pivot pin 68, and a second spreader arm extends from the adjacent link arms (for example, link arms 22a, 22b) perpendicular to the first spreader arm and extends from the axis of rotation of the hinge 24. In this embodiment, preferably, only one cable actuation and tensioning systems 26, 26' is driven; however, both cable actuation and tensioning systems 26, 26' can be driven, for example, if the single degree of freedom hinge 24 is replaced by a two degree of freedom hinge. In addition, cable actuation and tensioning system 26' can be driven to adjust pretension. The hinges 24 and the cable actuation and tensioning systems 26, 26' are provided such that the link arms 22a, 22b, 22c, 22d fold on each other

11

(alternating folding), that is along parallel axes; or the cable actuation and tensioning systems **26**, **26'** are provided such that the link arms **22a**, **22b**, **22c**, **22d** fold on each other (alternating folding), that is along perpendicular axes. That is to say, the pivot axes of the hinges **24** can be either perpendicular or alternating perpendicular to each other along the length of the manipulator **20** to accomplish the desired folding. While a perpendicular folding arrangement is described, other angular geometries can be provided for the folding arrangement.

FIGS. **16-22** show a novel hinge **80** that can be used for the hinge **24** between adjacent link arms (shown as link arms **22a**, **22b** in these Figures for illustration purposes only) in any of the embodiments of the manipulator **20**. While the hinge **80** is described for use in the manipulator **20**, hinge **80** is not limited to such use; hinge **80** can be used in a variety of structures to connect two components together. The hinge **80** is formed of a pair of frames **82a**, **82b** which are attached to the ends of the respective link arms **22a**, **22b**, a torque reaction tube **100a** attached between the frame **82a** and a central member **102**, and a torque reaction tube **100b** attached between the frame **82b** and the central member **102**. While the frames **82a**, **82b** are shown as separate members from the link arms **22a**, **22b**, the frames **82a**, **82b** can be formed as an integral part of link arms **22a**, **22b**.

Link arm **22a** is hollow and, as shown, has a rectangular cross-section (this is illustrative, other shapes can be provided). The frame **82a** is attached to the end of the link arm **22a** and can mirror the shape of the link arm **22a**, or can take a different shape than the link arm **22a** (an adaptor (not shown) may be provided to attach the frame **82a** to the link arm **22a**). As shown in these figures, the link arm **22a** and the frame **82a** are rectangular, and, as such, the frame **82a** has a first portion **84a**, a second portion **86a** which is parallel to the first portion **84a**, a third portion **88a** which connects a first end of the first and second portions **84a**, **86a** together, and a fourth portion **90a** which connects the opposite ends of the first and second portions **84a**, **86a** together. As such, a central passageway **91a** is formed therein. The first portion **84a** has a pair of retaining guides **92a** which extend therefrom toward the centerline of the link arm **22a**. The retaining guides **92a** are formed as a pair of spaced apart flanges, which are proximate to but spaced from, the third portion **88a**. The first portion **84a** further has a retaining guide **94a** which extends therefrom toward the centerline of the link arm **22a**. The retaining guide **94a** is formed as a flange which is proximate to, but spaced from, the fourth portion **90a**. The second portion **82a** has a first ear **96a** which extends at an angle relative to the centerline of the link arm **22a** and is proximate to the third portion **88a**. The ear **96a** has an aperture therethrough. The second portion **82a** further has a pair of spaced-apart ears **98a** which extend at an angle relative to the centerline of the link arm **22a** and are proximate to the fourth portion **90a**. Each ear **98a** has an aperture therethrough. The apertures through the ears **96a**, **98a** are aligned with each other. As the ears **96a**, **98a** are angled relative to the centerline of the link arm **22a**, the apertures are offset from the centerline of the link arm **22b**.

Like link arm **22a**, link arm **22b** is hollow and, as shown, has a rectangular cross-section (this is illustrative, other shapes can be provided). The frame **82b** is attached to the end of the link arm **22b** and can mirror the shape of the link arm **22b**, or can take a different shape than the link arm **22b** (an adaptor (not shown) may be provided to attach the frame **82b** to the link arm **22b**). As shown in these figures, the link arm **22b** and the frame **82b** are rectangular, and, the frame **82b** is the mirror image of frame **82a** attached to link arm **22a** and

12

therefore, the same reference numerals with the suffix "b" are provided thereon, and the specifics are not repeated herein.

The torque reaction tube **100a** has a rectangular frame **104a** having a first portion **106a**, a second portion **108a** which is parallel to the first portion **106a**, a third portion **110a** which connects a first end of the first and second portions **104a**, **106a** together, and a fourth portion **112a** which connects the opposite ends of the first and second portions **104a**, **106a** together. As such, a central passageway **113a** is formed therein. Each of the third and fourth portions **110a**, **112a** has a retaining tab **114a**, **116a** extending therefrom. Each retaining tab **114a**, **116a** is proximate to the first portion **106a**. The first portion **106a** has a pair of ears **118a**, **120a** which extends at an angle relative to the frame **104a**. Ear **118a** aligns with the third portion **110a**; ear **120a** aligns with the fourth portion **112a**. Each ear **118a**, **120a** has an aperture therethrough which are aligned with each other. The second portion **108a** has a pair of spaced-apart ears **122a** which extend at an angle relative to the frame **104a** in the same direction as ears **118a**, **120a**. Ears **122a** are proximate to the third portion **110a**. The second portion **108a** further has an ear **124a** which extends at an angle relative to the frame **104a** in the same direction as ears **118a**, **120a**. Ear **124a** is proximate to the fourth portion **112a**. Each ear **122a**, **124a** has an aperture therethrough which are aligned with each other.

The torque reaction tube **100a** is attached to the frame **82a** by ear **124a** engaging between ears **98a** with a pivot pin **126** inserted through the aligned apertures, and ear **96a** engaging between ears **122a** with a pivot pin **126** inserted through the aligned apertures. The torque reaction tube **100a** is rotatable relative to the frame **82a**.

Torque reaction tube **100b** is attached to the frame **82b**. Torque reaction tube **100b** is the mirror image of torque reaction tube **100a** and therefore, the same reference numerals with the suffix "b" are provided thereon, and the specifics are not repeated herein.

The torque reaction tube **100b** is attached to the frame **82b** by ear **124b** engaging between ears **98b** with a pivot pin **128** inserted through the aligned apertures, and ear **96b** engaging between ears **122b** with a pivot pin **128** inserted through the aligned apertures. The torque reaction tube **100b** is rotatable relative to the frame **82b**.

The central member **102** is formed of a rectangular frame **130** having a first portion **132**, a second portion **134** which is parallel to the first portion **132**, a third portion **136** which connects a first end of the first and second portions **132**, **134** together, and a fourth portion **138** which connects the opposite ends of the first and second portions **132**, **134** together. A pair of spaced-apart support bars **140**, **142** extend between the first and second portions **132**, **134** and are parallel to the third and fourth portions **136**, **138**. As such, a central passageway **139** is formed between the first and second portions **132**, **134** and the support bars **140**, **142**; a first side passageway **144** is formed between support bar **140** and first, second and third portions **132**, **134**, **136**; and a second side passageway **146** is formed between support bar **142** and first, second and fourth portions **132**, **134**, **138**. The spreader arm **32** extends through a passageway formed through the first portion **132**, the support bars **140**, **142** and the second portion **134**. The spreader arm **32** has central passageway **141** therethrough which aligns with the central passageways **113a**, **139**, **113b**. The first portion **132** has a first ear **140** extending into side passageway **144**, and a second ear **142** extending into side passageway **146**. Each ear **140**, **142** has an aperture therethrough which are aligned with each other.

The torque reaction tubes **100a**, **100b** are attached to the central member **102** by ear **140** engaging with ear **118a** and

13

with ear **120b** with a pivot pin **148** inserted through the aligned apertures, and by ear **142** engaging with ear **118b** and with ear **120a** with a pivot pin **150** inserted through the aligned apertures. The torque reaction tubes **100a**, **100b** are rotatable relative to the central member **102**.

The link arms **22a**, **22b** can rotate 360 degrees relative to each other as shown in FIG. **22**. As shown in FIG. **20**, the link arms **22a**, **22b** are aligned with each other. As the link arms **22a**, **22b** are rotated by the cable actuation and tensioning system **26**, the link arms **22a**, **22b** rotate via hinge **80**. The torque reaction tubes **100a**, **100b** pivot relative to the central member **102** and the frames **82a**, **82b** to enable the hinge **80** to be anywhere from 0 degrees to 360 degrees as shown in FIG. **22**. When the hinge **80** is in the 0 degree position, the link arms **22a**, **22b** are side-by-side, the torque reaction tubes **100a**, **100b** are engaged with the frames **82a**, **82b** (the tabs **114a**, **116a** engage with the retaining guides **92a**, **94a**; the tabs **114b**, **116b** engage with the retaining guides **92b**, **94b**), and the spreader arm guide **102** is perpendicular to the torque reaction tubes **100a**, **100b**. When the hinge **80** is in the 180 degree position, the link arms **22a**, **22b** are aligned with each other, the torque reaction tubes **100a**, **100b** are engaged with the frames **82a**, **82b** (the tabs **114a**, **116a** engage with the retaining guides **92a**, **94a**; the tabs **114b**, **116b** engage with the retaining guides **92b**, **94b**), and the spreader arm guide **102** is sandwiched between the torque reaction tubes **100a**, **100b**. When the hinge **80** is in the 360 degree position, the link arms **22a**, **22b** are side-by-side, the torque reaction tubes **100a**, **100b** are disengaged from the frames **82a**, **82b**, and the spreader arm guide **102** is sandwiched between the torque reaction tubes **100a**, **100b**.

The hinge **80** prevents loads from the spreader arm **32** from causing hinge **24** to separate (i.e. a vertical positive or negative force acting through pivot pins **126**, **128**, **146**, **148**). This is accomplished by the location of the pins **126**, **128** over the centerline of the hinge **80** as shown in FIG. **20**, and the location of pins **146**, **148** on the centerline. The symmetric design of the hinge **80** reduces number of unique parts.

The central passageways **113a**, **139**, **113b** provides a large pass through for wires: which remains unobstructed during deployment and operation of the manipulator **20**. The size of the central passageways **113a**, **139**, **113b** may be adjusted due to requirements on the spreader arm geometry. The hinge **80** is scalable for different dimensioned cross-sections as well as directly applicable to other cross-sectional geometries, such as circular, triangular, hexagonal, etc.

The central member **102** can be synchronized to bi-sect angle (or follow many other relations) involving the location of link arm **22a** relative to link arm **22b**. The hinge **80** can be augmented to have a preload across the hinge **80** to prevent pulling-apart of the hinge **80** under tension. The preload force is provided by the cable tension in a cable articulated hinge. The over center hinge lines prevent spreader compression from spreading the hinge **24**.

The hinge **80** supports a deployable central link (i.e. the spreader arm **32** in this embodiment) which is restowable. The central member **102** can be modified to accommodate any spreader arm **32** cross-section geometry.

The tabs **114a**, **116b** and ears **92a**, **92b**, **94a** react to torques on the hinge **80** and improve the stiffness of the hinge **80**.

As shown in FIG. **22**, when the link arms **22a**, **22b** are side-by-side, two different folding patterns are provided. This allows for multiple packaging options during stowage.

In addition, this hinge **80** reduces the internal wiring bundle length to accommodate the full 360 degree rotation compared to a traditional hinge joint, because the rotation effectively occurs around the cross-section center line instead

14

of the hinge axis as a result of the joint geometry. This requires less slack in the wire bundle during articulation than a conventional hinge.

In each embodiment, while tensioning by cables are shown and described herein, it is to be understood that the tensioning can be accomplished in a variety of ways, including, but not limited to cables, metallic tapes, rigid bar, springs, etc. or some combination of these approaches.

In each embodiment, actuating the hinges **24** of the manipulator **20** through the cable actuation and tensioning system **26** provides a large mechanical advantage for the motor **48** that actuates the hinge **24**, enabling use of smaller, lighter-weight motors, thus requiring less power. Low precision motors can be used because the cable actuation and tensioning system **26** can be designed to damp out irregularities in the motor torque, further reducing motor complexity and costs. A single motor **48** is preferably used per hinge **24**, however, multiple motors **48** per hinge **24** operating in an antagonistic manner can be provided, depending on the performance or redundancy required. In addition, since the motors **48** are located away from the mechanical hinge formed by pivot pin **68** forming the hinge **24**, this simplifies the mechanical design and enables straight forward on-orbit repair because removal of the motor does not affect the hinge angle. Further, the cable actuation and tensioning system **26** increases the stiffness of the link arms **22a**, **22b**, **22c**, providing for a smaller, lighter-weight system.

In each embodiment, the hinge **24** achieves as high torque efficiency by using mechanical advantage to generate the required hinge torque. The mechanical advantage is defined as the perpendicular distance from the cable actuation and tensioning system **26** to the rotation axis defined by pivot pin **68**. This distance is a design variable that can be adjusted based upon requirements. The tendon-actuated hinges **24** have high structural efficiency, and significantly reduce the total mass of the manipulator **20** while also achieving higher stiffness of the hinge **24**. Because of the lack of gravity, the manipulator **20** uses the opposing (antagonistic) tension loops of cables **44**, **46** or cables **44**, **45**, **46**, **47** to maintain structural integrity and exert force on payloads during articulation of the hinge **24**.

In each embodiment, it is to be understood that the pulleys on the spreader arm(s) **32** can be eliminated, and instead, the cables **44**, **46** can interengage with the ends **52**, **54** of the spreader arm(s) **32** and slide along the ends of the spreader arm(s) **32** such that the ends **52**, **54** of the spreader arm(s) **32** provide the non-driven elements. The spreader arm(s) **32** can disengage from the cables **44**, **46** and re-engage as necessary during articulation of the hinge **24**. In this configuration, the ends **52**, **54** of the spreader arm(s) **32** provide the non-driven elements of the cable actuation and tensioning system **26**.

The tension stiffening provides a versatile approach that is integrated with variable length link arms **22a**, **22b**, **22c** or spreaders **32**, and can be selectively applied to only a subset of the link arms **22a**, **22b**, **22c** (only near the root for example) or spreaders **32** as needed to meet performance and operational requirements.

The link arms **22a**, **22b**, **22c** and spreader arm(s) **32** can be deployable members (STEMS for example) to allow for more efficient packaging. The very long versions (many link arms) of the manipulator **20** can be deployable structures, erectable structures, manufactured on-orbit, or some combination of those methods.

The cable actuation and tensioning system **26** reduces the costs of manufacture of the manipulator **20** and reduces cross-sectional size and weight of the link arms **22a**, **22b**, **22c**.

15

Because of the passive antagonistic control about the hinge **24**, a significant mechanical advantage is achieved. Since the motors are non-co-located (the motor drive axis is not on the same axis or substantially the same axis as the hinge axis **68** where the link arms **22a**, **22b**, **22c** rotate) and since the motor (s) **48** are remote from hinge axis **68**, a significant amount of mechanical advantage is provided by the cable actuation and tensioning system **26**.

If desired, multiple mounting locations can be provided on the link arms **22a**, **22b**, **22c** and the spreader arm(s) **32** to allow the location of the pulleys, hoists or capstans to be adjusted. Preferably, this is accomplished before the manipulator **20** is put into service, but this is not required. The length of the cabling can be adjusted in service to allow dynamic adjustment of the pulley, hoists or capstan with the springs **50a**, **50b** (or other devices) taking up the slack in the cables **44**, **46** or cables **44**, **45**, **46**, **47**.

If desired, other arrangements of cables **44**, **46** employing single or multiple cables, incorporating additional pulleys, pulley systems, capstans and motors can be used. For example, the additional pulleys can be mounted anywhere on the link arms **22a**, **22b**, **22c** and/or spreader arm(s) **32**.

While preferred embodiments of the present invention are shown and described, it is envisioned that those skilled in the art may devise various modifications of the present invention without departing from the spirit and scope of the appended claims.

What is claimed is:

1. A manipulator comprising:
 - a plurality of link arms;
 - a hinge connecting adjacent link arms of the plurality of link arms together to allow said adjacent link arms to rotate relative to each other; and
 - a cable actuation and tensioning system provided between adjacent link arms, said cable actuation and tensioning system comprising:
 - at least one spreader arm;
 - a plurality of driven elements each attached to a respective one of said adjacent link arms remote from said hinge;
 - a non-driven element provided on each of the others of said adjacent link arms and at a respective end of said at least one spreader arm, wherein each non-driven element is remote from said hinge;
 - at least one cable routed around the driven and non-driven elements;
 - a pair of tensioning members each connected to a respective one of the at least one spreader arm and one of the plurality of link arms for accommodating changes in a length of the at least one cable; and
 - a motor for driving said driven element to circulate the cable around the driven and non-driven elements;
- wherein the at least one cable and the pair of tensioning members are arranged in an antagonistic manner to provide bi-directional motion of the adjacent link arms with respect to the hinge.
2. The manipulator of claim 1, wherein said at least one driven element is a capstan.
3. The manipulator of claim 1, wherein the plurality of driven elements includes a hoist.
4. The manipulator of claim 1, wherein each said non-driven element is a pulley.
5. The manipulator of claim 1, wherein one of said non-driven elements is an end of said spreader arm.

16

6. The manipulator of claim 1, wherein each said non-driven element is a pulley mounted on each end of said spreader arm, said cable being detachable from at least one of said pulleys.

7. The manipulator of claim 1, wherein the at least one spreader arm includes a plurality of spreader arms and said non-driven element is a ring connected to each of said spreader arms and to one of said link arms.

8. The manipulator of claim 1, wherein the tensioning members are springs.

9. The manipulator of claim 1, wherein a portion of said at least one cable is formed by at least one non-bending tension member.

10. The manipulator of claim 1, wherein at least one of said non-driven elements can disengage from said cable during actuation of the cable actuation and tensioning system.

11. The manipulator of claim 1, wherein the plurality of link arms includes at least three link arms and the hinge includes a plurality of hinges, and wherein some of said hinges rotate about a first axis and others of said hinges rotate about other axes which are angled relative to said first axis.

12. The manipulator of claim 1, wherein between first and second ones of said link arms, said hinge comprises

- a central member for holding said spreader arm;
- a first torque reaction tube rotatably attached to said first link arm, said first torque reaction tube rotatably attached to said central member; and
- a second torque reaction tube rotatably attached to said second link arm, said second torque reaction tube rotatably attached to said central member.

13. The manipulator of claim 12, wherein said hinge further comprises a frame connected to each of said link arms, each said frame having at least one retaining guide thereon, each said torque reaction tube having at least one tab thereon which is capable of engaging with said at least one retaining guide.

14. The manipulator of claim 12, wherein each of said central member, said first torque reaction tube and said second torque reaction tube have a central passageway therethrough which allow for the passage of wires therethrough.

15. A cable actuation and tensioning system for a manipulator having adjacent first and second link arms joined by a hinge that allows the adjacent first and second link arms to move relative to each other, the system comprising:

- a spreader arm coupled to the adjacent first and second link arms via the hinge;
- a first pulley disposed at an end of the spreader arm remote from the hinge;
- a second pulley positioned on the first link arm remote from the hinge;
- a capstan and a motor attached to the second link arm remote from the hinge;
- at least one tensioning element, each of which is positioned on one or more of the first link arm and the spreader arm; and
- a cable routed around the first pulley, the second pulley, and the capstan, wherein the capstan is driven via the motor to circulate the cable via the first pulley, the second pulley, and the at least one tensioning element and thereby provide bi-directional motion of the adjacent link arms respect to the hinge, and wherein the capstan and the at least one tensioning element are arranged in an antagonistic manner with respect to the hinge such that tension is maintained on the cable during the bi-directional motion.